
**Road vehicles — Compressed natural
gas (CNG) fuel systems —**

**Part 1:
Safety requirements**

*Véhicules routiers — Systèmes d'alimentation en gaz naturel
comprimé (GNC) —*

iTeh STANDARD PREVIEW
Partie 1: Exigences de sécurité
(standards.iteh.ai)

[ISO 15501-1:2016](https://standards.iteh.ai/catalog/standards/sist/d37a337a-844f-4d67-8d64-88e62969eced/iso-15501-1-2016)

<https://standards.iteh.ai/catalog/standards/sist/d37a337a-844f-4d67-8d64-88e62969eced/iso-15501-1-2016>



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 15501-1:2016

<https://standards.iteh.ai/catalog/standards/sist/d37a337a-844f-4d67-8d64-88e62969eced/iso-15501-1-2016>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Requirements	3
4.1 Design	3
4.1.1 General	3
4.1.2 Components	4
4.2 Refuelling connection	5
4.2.1 General	5
4.2.2 Receptacle location	5
4.2.3 Receptacle mounting	5
4.2.4 Minimum receptacle clearance	6
4.3 Leakage control	6
4.4 Mounting of the cylinders	7
4.5 Heat protection	8
4.6 Minimizing risk of gas ignition	8
4.7 Venting system	8
5 Instruction for use	9
6 Marking	9
Annex A (informative) Technical solutions to functional requirements	10
Annex B (informative) Compressed natural gas (CNG) on-board fuel systems	11
Bibliography	13

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 22, *Road vehicles*, Subcommittee SC 41, *Specific aspects for gaseous fuels*.

This third edition cancels and replaces the second edition (ISO 15501-1:2012), which has been technically revised.

A list of all parts in the ISO 15501 series can be found on the ISO website.

Introduction

For the purposes of this document, all fuel system components in contact with natural gas have been considered suitable for natural gas as defined in ISO 15403.

When applying this document, it is to be understood that a safety device to prevent overfilling the vehicle's fuel system is part of the refuelling station. The pressure gauge has not been considered as a safety component.

When necessary, technical solutions regarding functional requirements are given in [Annex A](#).

This document refers to a service pressure of 20 MPa (200 bar).

NOTE 1 1 bar = 0,1 MPa = 10^5 Pa. 1 MPa = 1 N/mm².

NOTE 2 This document is based upon a service pressure for natural gas as fuel of 20 MPa (200 bar) settled at 15 °C. Other service pressures can be accommodated by adjusting the pressure by the appropriate factor (ratio). For example, a 25 MPa (250 bar) service pressure system will require pressures to be multiplied by 1,25.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 15501-1:2016](#)

<https://standards.iteh.ai/catalog/standards/sist/d37a337a-844f-4d67-8d64-88e62969eced/iso-15501-1-2016>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 15501-1:2016

<https://standards.iteh.ai/catalog/standards/sist/d37a337a-844f-4d67-8d64-88e62969eced/iso-15501-1-2016>

Road vehicles — Compressed natural gas (CNG) fuel systems —

Part 1: Safety requirements

1 Scope

This document specifies the minimum safety requirements applicable for the functionality of CNG on-board fuel systems intended for use on the types of motor vehicles defined in ISO 3833. This document is applicable to vehicles using compressed natural gas in accordance with ISO 15403, including mono-fuel, bi-fuel or dual-fuel applications, original-production and converted vehicles.

All matters relating to the skills of installers and converters have been excluded from this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 11439, *Gas cylinders — High pressure cylinders for the on-board storage of natural gas as a fuel for automotive vehicles*

ISO 15501-1:2016

ISO 14469 (all parts), *Road vehicles — Compressed natural gas (CNG) refuelling connector*

ISO 15500 (all parts), *Road vehicles — Compressed natural gas (CNG) fuel system components*

ISO 15501-2, *Road vehicles — Compressed natural gas (CNG) fuel systems — Part 2: Test methods*

IEC 60079-10-1, *Explosive atmospheres — Part 10-1: Classification of areas — Explosive gas atmospheres*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 1176, ISO 15500-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

service pressure

settled pressure of 20 MPa (200 bar) at a uniform gas temperature of 15 °C

3.2

CNG on-board fuel system

compressed natural gas fuel system comprising cylinder, or cylinders according to ISO 11439, mounting, one or more refuelling receptacles according to ISO 14469 (all parts), and the components described in ISO 15500-3 to ISO 15500-20

3.3

main shut-off valve

automatic valve designed to isolate a high-pressure source

3.4

mono-fuel NGV

vehicle which operates on natural gas only

Note 1 to entry: Also known as “Dedicated Natural Gas Vehicle”.

Note 2 to entry: In Europe and in India the term Mono-Fuel also applies to a light duty NGV with max 15 l gasoline tank.

3.5

bi-fuel NGV

vehicle that has two independent fuel systems (one of them for natural gas) and can run alternatively on either fuel, but only on one at a time

Note 1 to entry: The term bi-fuel also applies to vehicles that run on both fuels simultaneously in limited amount or duration.

3.6

dual-fuel NGV

vehicle that has two independent fuel systems (one of them for natural gas) and can run on both fuels simultaneously

Note 1 to entry: Vehicle also may run on one fuel alone.

STANDARD PREVIEW
(standards.iteh.ai)

3.7 Vehicle mass

3.7.1

kerb mass

complete shipping mass of a vehicle fitted with all equipment necessary for normal operation plus the mass of the following elements for M1, N1 and M2 having a maximum authorized mass not exceeding 3 500 kg:

- lubricants, coolant (if needed), washer fluid;
- fuel (tank filled to at least 90 % of the capacity specified by the manufacturer);
- other equipment if included as basic parts for the vehicle, such as spare wheels, wheel chocks, fire extinguishers, spare parts and tool kit

Note 1 to entry: The definition of kerb mass may vary from country to country, but in this document it refers to the definition contained in ISO 1176.

3.7.2

maximum authorized mass

kerb mass plus the maximum allowable payload

3.8 Vehicle categories

3.8.1

category M

power-driven vehicles having at least four wheels and used for the carriage of passengers

3.8.1.1

category M1

vehicles used for the carriage of passengers and comprising no more than eight seats in addition to the driver's seat

3.8.1.2**category M2**

vehicles used for the carriage of passengers and comprising more than eight seats in addition to the driver's seat and having a maximum authorized mass not exceeding 5 000 kg

3.8.1.3**category M3**

vehicles used for the carriage of passengers and comprising more than eight seats in addition to the driver's seat and having a maximum authorized mass exceeding 5 000 kg

3.8.2**category N**

power-driven vehicles having at least four wheels and used for the carriage of goods

3.8.2.1**category N1**

vehicles used for the carriage of goods and having a maximum authorized mass not exceeding 3 500 kg

3.8.2.2**category N2**

vehicles used for the carriage of goods and having a maximum authorized mass exceeding 3 500 kg but not exceeding 12 000 kg

3.8.2.3**category N3**

vehicles used for the carriage of goods and having a maximum authorized mass exceeding 12 000 kg

ITeC STANDARD PREVIEW
(standards.iteh.ai)

4 Requirements**4.1 Design**

<https://standards.iteh.ai/catalog/standards/sist/d37a337a-844f-4d67-8d64-88e62969eced/iso-15501-1-2016>

4.1.1 General

The CNG on-board fuel system components shall comply with ISO 11439, ISO 14469 (all parts) and ISO 15500 (all parts), as applicable.

For bi-fuel vehicles, provision shall be made to avoid accelerated deterioration of the non-CNG fuel system as a result of sustained operation on natural gas. Such measures shall be as recommended by the original vehicle manufacturer (e.g. fuel hoses).

All fuel system components shall fulfill the following conditions.

- a) They shall withstand the environmental temperatures and other environmental conditions safely during their operational life.
- b) They shall be located with full regard for anticipated damage while the vehicle is being used safely. Such damage may be caused by the vehicle itself, by extraneous factors such as heat, road debris, automotive fluids (brake liquid, oil, petrol, cooling liquid, etc.), or by rust, etc.
- c) They shall be fitted so that they are not the outermost, highest or lowest parts of the vehicles; otherwise they shall be protected.
- d) They shall be fitted so as not to affect ground clearance, approach angle, ramp (break-over) angle or departure angles as defined by the vehicle manufacturer.
- e) They shall be located so that they will not suffer corrosion damage by accumulation of water or cargo chemicals.
- f) They shall ensure the proper electrical conductivity throughout the fuel system in order to avoid the electrostatic charges. This provision does not apply to gas-tight housing and ventilation hose.

g) All connections shall be made in locations where access is possible for inspection.

The CNG system shall be installed in such a way that it has suitable protection against damage, such as damage due to moving vehicle components, collision, grit or due to the loading or unloading of the vehicle or the shifting of those loads.

The CNG system shall include automatic valves designed to close when the engine is not running on CNG, and shall be able to be manually opened or closed in case of failure of the automatism (see [Annex B](#)).

The CNG on-board fuel system shall include the following:

- an automatic valve to be installed directly on every CNG cylinder with a manual valve rigidly fixed to the CNG cylinder, which may be integrated into the automatic valve. The manual valve shall be able to isolate the cylinder content from the automatic valve;
- a PRD installed on each cylinder, functionally independent from any other component;
- one or more additional PRD as applicable to the approval of the cylinder according to ISO 11439; and
- an excess flow valve inside every cylinder or a functionally equivalent system to control the gas leakage in the event of an abnormal flow (see informative [Annex A](#)).

The automatic valve shall be closed when

- the vehicle is not operating on CNG, and
- the engine is not running;

The valve may remain open when the engine stops during the stop phase in start-stop systems where the valve shall remain open by design.

Only automatic valves that are normally closed when deactivated shall be used in the CNG on-board fuel system.

<https://standards.iteh.ai/catalog/standards/sist/d37a337a-844f-4d67-8d64-88e62969eced/iso-15501-1-2016>

4.1.2 Components

4.1.2.1 Receptacle

The receptacle shall comply with ISO 14469 (all parts).

The receptacle shall be provided with a protective cap, to prevent the entry of dust, fluid or other foreign matter. The protective cap shall be attached in such a way that will prevent loss of the cap.

The following data shall be displayed near the receptacle (marking shall be permanent):

- type of fuel (i.e. “CNG” for compressed natural gas);
- periodic inspection date for gas cylinders according to ISO 11439 or applicable regulations; and
- service pressure for the vehicle.

4.1.2.2 Gas cylinder

Gas cylinders shall be provided with cylinder valves, automatic valves, excess flow valves (or a functionally equivalent system) and pressure-relief devices, and shall be mounted in accordance with [4.4](#).

To prevent heat damage, gas cylinders and appurtenances shall either use a heat shield or be located in relation to the exhaust system such that their skin temperature does not exceed the value specified by the vehicle, valves (including PRD) or cylinder manufacturers and in accordance to ISO 11439 and ISO 15500. If no shielding is provided, there shall be a clearance of at least 100 mm between the fuel container and the exhaust system.

All fibre-reinforced gas cylinders (types 2, 3, and 4 according to ISO 11439) shall be protected from ultraviolet radiation and automotive fluids.

4.1.2.3 Pressure regulator

Components located downstream of the pressure regulator shall be protected from over pressurization due to regulator failure. This protection may be provided by components inside the pressure regulator (i.e. pressure relief valve) as specified in ISO 15500-9.

4.1.2.4 PRD and PRV

The suggested configuration for PRDs is parallel combination or thermal relief device for every type of cylinder. Series PRDs may only be used in type 1 steel cylinders and shall not be used in type 2, type 3 and type 4 cylinders.

The PRD shall be protected from dirt and water ingress and shall be located as far away as possible from sources of ignition and heat in the vehicle.

The PRD shall comply with ISO 15500-13, venting gas to protect cylinder rupture.

The PRV shall be used to prevent over pressurization of the system downstream of the first stage of the pressure regulator or regulators. If multiple regulators are used it may be necessary to provide additional PRVs.

PRVs may be used upstream of the first stage of the pressure regulator.

PRVs shall be protected from dirt and water ingress.

4.1.2.5 Pipework

Pipework shall be laid, if possible on the chassis, in such a way that no damage from intrinsic vibrations occurs (e.g. resonance with engine vibration) and there are no friction points. The intervals between two attachment points shall not exceed 0,60 m, and pipework installation and bending shall be in accordance with the pipe and fitting manufacturer's specification. Adequate provision shall be made to allow adequate essential flexibility.

4.2 Refuelling connection

4.2.1 General

The piping, receptacle and all valves and fittings installed on-board the natural gas vehicle should be selected to minimize the pressure drop along the lines, and hence minimize the filling time of, and maximize the fill volume into, the CNG on-board fuel system.

4.2.2 Receptacle location

The receptacle should be installed in a suitable on-board location that is easy to reach, allowing safe operation. The preferred location is on the side of the vehicle.

Receptacles installed inside the engine compartment shall be attached to the vehicle chassis or body. They shall not be fixed near the battery or the ignition high-tension circuit or possible ignition sources.

The receptacle shall not be installed in a wheel arch, or close to a heat source such as the exhaust.

4.2.3 Receptacle mounting

The vehicle's CNG on-board fuel system shall be able to withstand the values of force and torque specified in ISO 15501-2 of loading on the receptacle in any direction without its gas tightness being affected (in the case of a refueling hose breakaway).