

---

---

**Assembly, adjustment and inspection  
of an alpine ski/binding/boot  
(S-B-B) system**

*Montage, réglage et contrôle d'un ensemble ski/fixation/chaussure  
(SFC) pour skis alpins*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[oSIST ISO 11088:2018](https://standards.iteh.ai/catalog/standards/sist/ae1d84c5-22c9-4b20-8fb8-fbc8c7c98af5/osist-iso-11088-2018)

<https://standards.iteh.ai/catalog/standards/sist/ae1d84c5-22c9-4b20-8fb8-fbc8c7c98af5/osist-iso-11088-2018>



## iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST ISO 11088:2018](https://standards.iteh.ai/catalog/standards/sist/ae1d84c5-22c9-4b20-8fb8-fbc8c7c98af5/osist-iso-11088-2018)

<https://standards.iteh.ai/catalog/standards/sist/ae1d84c5-22c9-4b20-8fb8-fbc8c7c98af5/osist-iso-11088-2018>



### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
[copyright@iso.org](mailto:copyright@iso.org)  
[www.iso.org](http://www.iso.org)

# Contents

	Page
Foreword.....	iv
Introduction.....	v
<b>1 Scope.....</b>	<b>1</b>
<b>2 Normative references.....</b>	<b>1</b>
<b>3 Terms and definitions.....</b>	<b>1</b>
<b>4 Skier's parameters.....</b>	<b>3</b>
4.1 General.....	3
4.2 Weight method.....	3
<b>5 Equipment parameters.....</b>	<b>3</b>
5.1 Choice of new equipment.....	3
5.2 Visual inspection and preparation of used equipment.....	3
5.3 Assembly.....	4
5.4 Binding-to-boot fitting adjustments.....	4
5.5 Initial indicator adjustment.....	4
5.6 Functional check (inspection of functions).....	4
5.7 Measurement of release moment.....	4
5.8 Report.....	5
<b>Annex A (normative) Definition of skier type.....</b>	<b>6</b>
<b>Annex B (normative) Method of setting.....</b>	<b>8</b>
<b>Annex C (normative) Flow chart.....</b>	<b>10</b>
<b>Annex D (normative) Clean versus lubricated diagnostic test for boot/binding compatibility.....</b>	<b>11</b>
<b>Annex E (normative) Drill.....</b>	<b>12</b>
<b>Bibliography.....</b>	<b>13</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 83, *Sports and other recreational facilities and equipment*, Subcommittee SC 4, *Snowsports equipment*.

This fifth edition cancels and replaces the fourth edition (ISO 11088:2006), which has been technically revised where Annex F (informative) has been removed.

## Introduction

International Standards exist for the components of the alpine ski/binding/boot (S-B-B) system, mainly intended for the component manufacturers. An International Standard (ISO 8061) also exists for the selection of release moments. The present International Standard is intended primarily for retailers. However, its aim is to include in one text the different phases of the choice of components, their assembly, adjustment and inspection in the form of practical procedures, and to provide tolerances for inspection and adjustment.

The inspection procedures and tolerances described in this International Standard apply to the condition of the S-B-B system before it leaves the ski shop and are not intended to be used to judge the condition of the equipment once it is put into use.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST ISO 11088:2018](https://standards.iteh.ai/catalog/standards/sist/ae1d84c5-22c9-4b20-8fb8-fbc8c7c98af5/osist-iso-11088-2018)

<https://standards.iteh.ai/catalog/standards/sist/ae1d84c5-22c9-4b20-8fb8-fbc8c7c98af5/osist-iso-11088-2018>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[oSIST ISO 11088:2018](#)

<https://standards.iteh.ai/catalog/standards/sist/ae1d84c5-22c9-4b20-8fb8-fbc8c7c98af5/osist-iso-11088-2018>

# Assembly, adjustment and inspection of an alpine ski/binding/boot (S-B-B) system

## 1 Scope

This International Standard specifies assembly, adjustment and inspection procedures for the binding mechanisms of skis, integrating in a practical way, the requirements of those International Standards which are related to skis, bindings and boots.

It is intended for all individuals and institutions concerned with those procedures, and especially for sports retailers.

It is applicable to a ski/binding/boot system (S-B-B) for alpine skiing, of which at least one component is owned by the user.

**NOTE** In the case where the two components (SB and B) are rented, ISO 13993 gives a method of measurement by sampling as an alternative to systematic measurement, before delivery to the end-user.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5355, *Alpine ski-boots — Requirements and test methods*

ISO 8061:2015, *Alpine ski-bindings — Selection of release torque values*

ISO 8364, *Alpine skis and bindings — Binding mounting area — Requirements and test methods*

ISO 9462, *Alpine ski-bindings — Requirements and test methods*

ISO 9523, *Touring ski-boots for adults — Interface with touring ski-bindings — Requirements and test methods*

ISO 11087, *Alpine ski-bindings — Retention devices — Requirements and test methods*

ISO 11110, *Winter-sports equipment — Test devices for the setting of the functional unit ski/boot/binding — Requirements and tests*

ISO 13992, *Alpine touring ski-bindings — Requirements and test methods*

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1

#### **fitting adjustment**

procedure required to obtain geometric compatibility and correct functioning of different components

### 3.2

#### **indicator value**

##### **Z-mark**

release indicator value marked on the binding in accordance with ISO 9462

**3.3 skier type**

release adjustment criteria pertaining to the type of skiing to be undertaken, as assessed by the skier in accordance with [Table A.1](#)

Note 1 to entry: The designations L, A, S, which were used in ISO 8061:1984, have been replaced by types 1, 2 and 3, respectively, in ISO 8061:1991 and in ISO 8061:2004.

Note 2 to entry: If the skier desires a setting outside the tolerances of this International Standard, he or she can select such a setting at his or her own discretion. Ski-binding manufacturers should provide guidelines to shops and skiers regarding the recommended magnitude of such changes. Skiers should be clearly informed when these changes result in release values above the upper limit or below the lower limit defined in ISO 8061.

**3.4 initial indicator position**

release indicator position of the binding corresponding with the instructions given in [Table B.1](#)

**3.5 Release moment (values)  $M_Z$  and  $M_Y$**

**3.5.1 selected individual release moment reference moment**

(for a given skier) release moment determined in accordance with ISO 8061

**3.5.2 measured release moment**

(for a given S-B-B system) average or middle quantitative value of three consecutive release measurements in the same direction on the same unit

Note 1 to entry: It is expressed in newton metres.

**3.6 deviation accepted for the setting inspection tolerance**

maximum difference between the *measured release moment* ([3.5.2](#)) and the *selected individual release moment* ([3.5.1](#))

Note 1 to entry: This difference, which may be reduced by the setting, is limited for  $M_Z$  to  $\pm 15\%$  or 3 N·m (whichever is greater), and for  $M_Y$  to  $\pm 15\%$  or 10 N·m (whichever is greater).

**3.7 release adjustment**

procedure for making the measured  $M_Z$  and  $M_Y$  values coincide with the selected individual  $M_Z$  and  $M_Y$  values within the limits stated in [Table B.1](#)

**3.8 trouble-shooting procedures**

additional procedures recommended by the equipment manufacturer

**3.9 deviation accepted for the re-adjustment re-adjustment tolerance**

maximum difference between the *measured release moment* ([3.5.2](#)) at the *initial indicator position* ([3.4](#)) and the *selected individual release moment* ([3.5.1](#))

Note 1 to entry: This difference, which may be reduced by re-adjustment, is limited for  $M_Z$  to  $\pm 30\%$  or 6 N·m (whichever is greater), and for  $M_Y$  to  $\pm 30\%$  or 10 N·m (whichever is greater).



## 4 Skier's parameters

### 4.1 General

The individual release moment values are given in ISO 8061. The following procedure using discrete values may be considered as an acceptable approximation of the basic functions of ISO 8061.

### 4.2 Weight method

4.2.1 Determine the skier's parameters with the following:

- mass (weight);
- height;
- type (according to [Annex A](#));
- age;
- sole length if necessary.

4.2.2 Using [Table B.1](#), choose the individual release values of  $M_Z$  and  $M_Y$ .

## 5 Equipment parameters

### 5.1 Choice of new equipment

The components shall be in conformance with the following International Standards:

- a) ISO 8364 for skis; <https://standards.iteh.ai/catalog/standards/sist/ae1d84c5-22c9-4b20-8fb8-fbc8c7c98af5/osist-iso-11088-2018>
- b) ISO 5355 and ISO 9523 for boots;
- c) ISO 9462 and ISO 13992 for bindings;
- d) ISO 11087 for brakes.

The skier should receive specific recommendations concerning the selection of boot, binding and ski, if they are provided by the manufacturer.

### 5.2 Visual inspection and preparation of used equipment

If any of the components of the S-B-B system have been used, the installer shall carry out a visual check according to the following criteria. In addition to this, older equipment may require special attention as defined by the manufacturer.

- a) The edges and sole of the ski shall be properly prepared according to the recommendations of the ski manufacturer. Unused mounting holes, if any, shall be carefully filled in, according to the manufacturer's specifications.
- b) The condition of the boot sole shall meet the binding manufacturer's requirements. All buckles, fasteners and support areas shall be in good condition.

In cases where release is independent of the boot (e.g. some plate bindings), the inspection of the sole may be less exacting.

- c) The condition of the binding components shall meet the binding manufacturer's requirements (i.e. no broken, deformed, missing or worn-out parts).

Component guides or rotation points shall be free-moving, free of obvious rust, corrosion and dirt, etc. The manufacturer's inspection and maintenance instructions shall be observed (including lubrication). The brake shall not be deformed. Suspect components shall be repaired or exchanged.

### 5.3 Assembly

When assembling the system, comply with the instructions of the binding and ski manufacturers and use the proper tools.

The use of a drill according to [Annex E](#) is recommended. Once they are drilled, it is recommended that the holes be tapped and glue applied if this is required by the ski manufacturer. New holes shall not be drilled less than 10 mm from old holes (measured from centre of hole to centre of hole), even when they are filled in, unless otherwise specified by the ski or binding manufacturer.

When inserting the screws, take care not to damage the threads. A maximum tightening moment of 4 N·m shall fulfil this requirement, unless otherwise specified by the ski manufacturer.

### 5.4 Binding-to-boot fitting adjustments

Follow the binding manufacturer's instructions.

### 5.5 Initial indicator adjustment

The binding manufacturer shall provide a table similar to [Table B.1](#) for his products.

Using [Table B.1](#), adjust the bindings to the appropriate initial indicator position.

### 5.6 Functional check (inspection of functions)

Check visually that everything conforms to the binding manufacturer's instructions and operates correctly.

Check if the boot returns quickly to its initial position within less than 2 mm after a sideward displacement of approximately 10 mm.

### 5.7 Measurement of release moment

Precondition the binding by releasing each unit as required by the binding manufacturer.

Using a test device in accordance with ISO 11110, proceed as follows.

- a) Follow the test device manufacturer's instructions and check the calibration of the test device according to the manufacturer's procedures.
- b) Check that the measured  $+M_Z$ ,  $-M_Z$  and  $+M_Y$  values are within the limits stated in [Table B.1](#) and, if required, correct the release adjustment. If the first two successive release measurements in the same direction fall within the  $\pm 15\%$  inspection tolerance range, it is not necessary to make a third release measurement.
- c) If the measured  $+M_Z$ ,  $-M_Z$  and  $+M_Y$  values fall near opposite limits of the inspection tolerance range, the manufacturer's procedure for evaluation of non-symmetrical release shall be implemented.
- d) If the release values are out of the limit for re-adjustment (see [3.9](#)), check the binding manufacturer's most recent instructions before proceeding. If no instructions are provided, the person mounting the bindings should conduct a clean versus lubricated diagnostic test in accordance with [Annex D](#).
- e) If the measured  $+M_Z$ ,  $-M_Z$  and  $+M_Y$  values are outside the  $\pm 15\%$  inspection tolerance, consult the manufacturer's trouble-shooting instructions. After completing the trouble-shooting procedures,

if the measured values fall within the  $\pm 30\%$  limit for re-adjustment tolerance, re-adjustment of the binding may be undertaken. These re-adjustments shall achieve measured values as close as practical to the selected individual release moment, within the  $\pm 15\%$  tolerance.

## 5.8 Report

An adjustment report is established by the ski shop and delivered to the user. It shall contain at least the following information:

- skier's parameters;
- indicator value;
- measured values of  $M_Z$  and  $M_Y$ , or pass/fail result of the system test.

NOTE The exact content of the report and its delivery conditions are defined by the national standard organizations.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST ISO 11088:2018](https://standards.iteh.ai/catalog/standards/sist/ae1d84c5-22c9-4b20-8fb8-fbc8c7c98af5/osist-iso-11088-2018)

<https://standards.iteh.ai/catalog/standards/sist/ae1d84c5-22c9-4b20-8fb8-fbc8c7c98af5/osist-iso-11088-2018>