

ETSI EN 303 978 v2.2.1 (2024-12)



**Satellite Earth Stations and Systems (SES);
Earth Stations on Mobile Platforms (ESOMP)
communicating with satellites in geostationary orbit,
operating in the 27,5 GHz to 30,0 GHz and
17,3 GHz to 20,2 GHz frequency bands;
Harmonised Standard for access to radio spectrum**

ETSI EN 303 978 v2.2.1 (2024-12)

<https://standards.iteh.ai/catalog/standards/etsi/160515ef-c2f6-4727-bd74-3a410c0d102a/etsi-en-303-978-v2-2-1-2024-12>

Reference
REN/SES-00468

Keywords
antenna, earth station, GSO, mobile, regulation,
satellite

ETSI
650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

<https://standards.iteh.ai/catalog/standards/cti/160515cf-c2f6-4737-b174-3a410c04102a/etsi-en-303-978-v2-2-1-2024-12>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Contents

| | |
|---|----|
| Intellectual Property Rights | 8 |
| Foreword..... | 8 |
| Modal verbs terminology..... | 9 |
| Introduction | 9 |
| 1 Scope | 11 |
| 2 References | 11 |
| 2.1 Normative references | 11 |
| 2.2 Informative references..... | 12 |
| 3 Definitions of terms, symbols and abbreviations | 13 |
| 3.1 Terms..... | 13 |
| 3.2 Symbols | 14 |
| 3.3 Abbreviations | 15 |
| 4 Technical requirements specifications | 16 |
| 4.1 General | 16 |
| 4.1.1 Environmental profile | 16 |
| 4.1.2 Operational configurations | 16 |
| 4.1.3 Determination of geographical location of the ESOMP | 16 |
| 4.1.4 EIRP _{Aggregate} for networks of ESOMPs..... | 16 |
| 4.1.5 Presentation of equipment for testing purposes | 16 |
| 4.1.6 Choice of model for testing | 17 |
| 4.2 Conformance requirements | 17 |
| 4.2.1 Off-axis spurious radiation | 17 |
| 4.2.1.1 Justification | 17 |
| 4.2.1.2 Specification..... | 17 |
| 4.2.1.3 Conformance tests..... | 18 |
| 4.2.2 On-axis spurious radiation | 18 |
| 4.2.2.1 Justification | 18 |
| 4.2.2.2 Specification..... | 18 |
| 4.2.2.2.1 "Carrier-on" radio state..... | 18 |
| 4.2.2.2.2 "Carrier-off" and "Emissions disabled" radio states | 19 |
| 4.2.2.3 Conformance tests..... | 19 |
| 4.2.3 Off-axis EIRP emission density within the band | 19 |
| 4.2.3.0 General | 19 |
| 4.2.3.1 Justification | 19 |
| 4.2.3.2 Total EIRP density specification..... | 19 |
| 4.2.3.3 Void..... | 20 |
| 4.2.3.4 Void..... | 20 |
| 4.2.3.5 Burst Transmission Specification..... | 20 |
| 4.2.3.6 Off-axis Geometry Specification | 20 |
| 4.2.3.7 Conformance tests..... | 21 |
| 4.2.4 Uplink Power Control Specification | 21 |
| 4.2.5 Carrier suppression | 21 |
| 4.2.5.1 Justification | 21 |
| 4.2.5.2 Specification..... | 21 |
| 4.2.5.3 Conformance tests..... | 21 |
| 4.2.6 Antenna pointing and polarization alignment | 21 |
| 4.2.6.1 Antenna pointing accuracy..... | 21 |
| 4.2.6.1.1 Justification | 21 |
| 4.2.6.1.2 Pointing accuracy specification | 21 |
| 4.2.6.1.3 On-axis cross polarization isolation specification | 22 |
| 4.2.6.1.4 Conformance tests | 22 |
| 4.2.6.2 Antenna Pointing Error Detection..... | 22 |
| 4.2.6.2.0 General | 22 |
| 4.2.6.2.1 Pointing error detection specification | 22 |

| | | |
|-----------|---|----|
| 4.2.6.2.2 | Polarization angle alignment specification | 22 |
| 4.2.6.2.3 | Conformance tests | 23 |
| 4.2.7 | Cessation of emissions..... | 23 |
| 4.2.7.1 | Justification | 23 |
| 4.2.7.2 | Specification..... | 23 |
| 4.2.7.2.1 | Specification 1: Mode of cessation of emissions..... | 23 |
| 4.2.7.2.2 | Specification 2: Conditions under which the ESOMP shall cease emissions | 23 |
| 4.2.7.2.3 | Specification 3: Cessation of emissions | 24 |
| 4.2.7.2.4 | Specification 4: Fault conditions | 24 |
| 4.2.7.3 | Conformance tests..... | 24 |
| 4.2.8 | Identification of the ESOMP | 24 |
| 4.2.8.1 | Justification | 24 |
| 4.2.8.2 | Specification..... | 24 |
| 4.2.8.3 | Conformance tests..... | 24 |
| 4.2.9 | Control and Monitoring Functions (CMFs)..... | 25 |
| 4.2.9.1 | ESOMP States..... | 25 |
| 4.2.9.1.0 | General | 25 |
| 4.2.9.1.1 | CMF state diagram | 26 |
| 4.2.9.2 | Processor monitoring | 27 |
| 4.2.9.2.1 | Justification | 27 |
| 4.2.9.2.2 | Specification..... | 27 |
| 4.2.9.2.3 | Conformance tests | 28 |
| 4.2.9.3 | Transmit subsystem monitoring..... | 28 |
| 4.2.9.3.1 | Justification | 28 |
| 4.2.9.3.2 | Specification..... | 28 |
| 4.2.9.3.3 | Conformance tests | 28 |
| 4.2.9.4 | Power-on/Reset | 28 |
| 4.2.9.4.1 | Justification | 28 |
| 4.2.9.4.2 | Specification..... | 28 |
| 4.2.9.4.3 | Conformance tests | 28 |
| 4.2.9.5 | Control Channel (CC) and Response Channel (RC)..... | 28 |
| 4.2.9.5.1 | Justification | 28 |
| 4.2.9.5.2 | Specification..... | 29 |
| 4.2.9.5.3 | Conformance tests | 29 |
| 4.2.9.6 | Network control commands | 29 |
| 4.2.9.6.1 | Justification | 29 |
| 4.2.9.6.2 | Specification..... | 29 |
| 4.2.9.6.3 | Conformance tests | 30 |
| 4.2.9.7 | Initial burst transmission..... | 30 |
| 4.2.9.7.1 | Justification | 30 |
| 4.2.9.7.2 | Specification..... | 30 |
| 4.2.9.7.3 | Conformance tests | 30 |
| 4.2.9.8 | Inhibition of transmissions | 30 |
| 4.2.9.8.1 | Justification | 30 |
| 4.2.9.8.2 | Specification..... | 31 |
| 4.2.9.8.3 | Conformance tests | 31 |
| 4.2.10 | Receive antenna off-axis gain pattern..... | 31 |
| 4.2.10.1 | Justification | 31 |
| 4.2.10.2 | Specification..... | 31 |
| 4.2.10.3 | Conformance tests | 31 |
| 4.2.11 | Blocking performance..... | 31 |
| 4.2.11.1 | Justification | 31 |
| 4.2.11.2 | Specification..... | 32 |
| 4.2.11.3 | Conformance tests | 32 |
| 4.2.12 | Adjacent Signal Selectivity..... | 32 |
| 4.2.12.1 | Justification | 32 |
| 4.2.12.2 | Specification..... | 32 |
| 4.2.12.3 | Conformance tests | 32 |
| 5 | Testing for compliance with technical requirements..... | 33 |
| 5.1 | Environmental conditions for testing | 33 |
| 5.2 | Radio test suites..... | 33 |

| | | |
|-----------|--|----|
| 6 | Test methods for all aspects of the ESOMP | 33 |
| 6.1 | General | 33 |
| 6.1.0 | Introduction..... | 33 |
| 6.1.1 | Uplink power control | 33 |
| 6.1.1.1 | General | 33 |
| 6.1.1.2 | Test method..... | 34 |
| 6.1.2 | Measuring receiver | 34 |
| 6.2 | Off-axis spurious radiation | 35 |
| 6.2.0 | Introduction..... | 35 |
| 6.2.1 | Test method | 35 |
| 6.2.1.0 | Void..... | 35 |
| 6.2.1.1 | General | 35 |
| 6.2.1.2 | Multi-carrier operation | 35 |
| 6.2.2 | Measurements up to 1 000 MHz | 36 |
| 6.2.2.1 | Test site | 36 |
| 6.2.2.2 | Measuring receivers | 36 |
| 6.2.2.3 | Procedure | 36 |
| 6.2.3 | Measurements above 1 000 MHz | 36 |
| 6.2.3.0 | General | 36 |
| 6.2.3.1 | Identification of the significant frequencies of spurious radiation | 37 |
| 6.2.3.1.1 | Test site..... | 37 |
| 6.2.3.1.2 | Procedure | 37 |
| 6.2.3.2 | Measurement of radiated power levels of identified spurious radiation..... | 37 |
| 6.2.3.2.1 | Test site..... | 37 |
| 6.2.3.2.2 | Procedure | 37 |
| 6.2.3.3 | Measurement of conducted spurious radiation at the antenna flange | 38 |
| 6.2.3.3.1 | Test site..... | 38 |
| 6.2.3.3.2 | Procedure | 39 |
| 6.3 | On-axis spurious radiation | 39 |
| 6.3.1 | Test method | 39 |
| 6.3.1.0 | General | 39 |
| 6.3.1.1 | Test site | 39 |
| 6.3.1.2 | Method of measurement..... | 39 |
| 6.3.1.2.1 | General | 39 |
| 6.3.1.2.2 | Method of measurement at the antenna flange | 39 |
| 6.3.1.2.3 | Method of measurement for an EUT with antenna | 40 |
| 6.4 | Off-axis EIRP emission density within the band | 41 |
| 6.4.1 | Test method | 41 |
| 6.4.1.0 | Introduction | 41 |
| 6.4.1.1 | Transmit output power density | 42 |
| 6.4.1.1.1 | General | 42 |
| 6.4.1.1.2 | Test site..... | 42 |
| 6.4.1.1.3 | Method of measurement | 42 |
| 6.4.1.2 | Antenna transmit gain | 43 |
| 6.4.1.2.1 | General | 43 |
| 6.4.1.2.2 | Test site..... | 43 |
| 6.4.1.2.3 | Method of measurement | 43 |
| 6.4.1.3 | Antenna transmit radiation patterns | 44 |
| 6.4.1.3.1 | General | 44 |
| 6.4.1.3.2 | Test site | 44 |
| 6.4.1.3.3 | Test arrangement | 45 |
| 6.4.1.3.4 | Co-polar radiation pattern - azimuth | 45 |
| 6.4.1.3.5 | Co-polar radiation pattern - elevation | 45 |
| 6.4.1.3.6 | Cross-polar radiation pattern - azimuth | 46 |
| 6.4.1.3.7 | Cross-polar radiation pattern - elevation | 46 |
| 6.4.2 | Computation of results | 47 |
| 6.5 | Carrier suppression | 47 |
| 6.5.1 | Test method | 47 |
| 6.6 | Antenna pointing | 47 |
| 6.6.1 | General..... | 47 |
| 6.6.2 | Test method | 48 |
| 6.7 | Polarization angle alignment capability | 48 |

| | | |
|-----------|--|----|
| 6.7.1 | General..... | 48 |
| 6.7.2 | Test site..... | 48 |
| 6.7.3 | Test method | 48 |
| 6.8 | Cessation of emissions of the ESOMP | 49 |
| 6.8.0 | General..... | 49 |
| 6.8.1 | Test Method..... | 49 |
| 6.8.1.1 | Required documentation | 49 |
| 6.8.1.2 | Cessation of emissions from the "Transmission enabled" state | 49 |
| 6.8.1.3 | Cessation of emission from the "Transmission disabled" state | 49 |
| 6.8.1.4 | Cessation of emission from the "Initial Phase" state | 50 |
| 6.8.1.4.1 | EUTs transmitting initial bursts..... | 50 |
| 6.8.1.4.2 | EUTs not transmitting initial bursts..... | 50 |
| 6.8.1.5 | "Single action" means of cessation of emissions..... | 51 |
| 6.8.1.6 | Fault conditions | 51 |
| 6.9 | Identification of ESOMP | 52 |
| 6.9.1 | Test arrangement | 52 |
| 6.9.2 | Test method | 52 |
| 6.10 | Control and monitoring functions | 52 |
| 6.10.0 | General..... | 52 |
| 6.10.1 | Test arrangement | 52 |
| 6.10.2 | Processor monitoring- Test method | 52 |
| 6.10.3 | Transmit subsystem monitoring-Test method..... | 53 |
| 6.10.4 | Power-on/Reset-Test method..... | 53 |
| 6.10.5 | Control Channel (CC) and Response Channel (RC) - Test method..... | 53 |
| 6.10.6 | Network Control commands-Test method..... | 54 |
| 6.10.7 | Initial burst transmission-Test method..... | 55 |
| 6.10.8 | Inhibition of transmission-Test method | 55 |
| 6.11 | Receive antenna off-axis gain pattern | 56 |
| 6.11.1 | Test method | 56 |
| 6.11.1.1 | Test site | 56 |
| 6.11.1.2 | Method of measurement..... | 56 |
| 6.11.1.3 | Computation..... | 57 |
| 6.12 | Blocking performance | 57 |
| 6.12.1 | Test method | 57 |
| 6.13 | Adjacent Signal Selectivity | 58 |
| 6.13.1 | Test method | 58 |
| 6.14 | Test for determination of geographical location of the ESOMP | 58 |
| 6.14.1 | Test arrangement | 58 |
| 6.14.2 | Test method | 58 |

| | | |
|-------------------------------|---|-----------|
| Annex A (informative): | Relationship between the present document and the essential requirements of Directive 2014/53/EU | 59 |
|-------------------------------|---|-----------|

| | | |
|-----------------|-------------------|-----------|
| Annex B: | Void | 61 |
|-----------------|-------------------|-----------|

| | | |
|-----------------------------|----------------------------------|-----------|
| Annex C (normative): | Radiated measurement..... | 62 |
|-----------------------------|----------------------------------|-----------|

| | | |
|-------|---|----|
| C.1 | Test sites and general arrangements for measurements involving the use of radiated fields | 62 |
| C.1.0 | General | 62 |
| C.1.1 | Anechoic Chamber | 62 |
| C.1.2 | Anechoic Chamber with a conductive ground plane | 63 |
| C.1.3 | Open Area Test Site (OATS) | 64 |
| C.1.4 | Minimum requirements for test sites for measurements above 18 GHz..... | 65 |
| C.1.5 | Test antenna..... | 65 |
| C.1.6 | Substitution antenna | 66 |
| C.1.7 | Measuring antenna | 66 |
| C.2 | Guidance on the use of radiation test sites | 66 |
| C.2.0 | General | 66 |
| C.2.1 | Verification of the test site | 66 |
| C.2.2 | Preparation of the EUT..... | 66 |
| C.2.3 | Power supplies to the EUT | 66 |
| C.2.4 | Range length..... | 67 |

| | | |
|-------------------------------|---|-----------|
| C.2.5 | Site preparation | 67 |
| C.3 | Coupling of signals..... | 68 |
| C.3.1 | General | 68 |
| C.4 | Standard test methods..... | 68 |
| C.4.0 | General | 68 |
| C.4.1 | Calibrated setup..... | 68 |
| C.4.2 | Substitution method..... | 69 |
| Annex D (normative): | Conducted measurements | 70 |
| Annex E (informative): | General Requirements for RF Cables..... | 71 |
| Annex F (informative): | RF Waveguides | 72 |
| Annex G (informative): | Applicability of parameters given in ETSI EG 203 336 | 74 |
| Annex H (informative): | Maximum measurement uncertainty..... | 76 |
| Annex I (informative): | Bibliography..... | 77 |
| Annex J (informative): | Change history | 78 |
| History | 79 | |

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 303 978 V2.2.1 \(2024-12\)](#)

<https://standards.iteh.ai/catalog/standards/etsi/160515ef-c2f6-4727-bd74-3a410c0d102a/etsi-en-303-978-v2-2-1-2024-12>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™, LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the **GSM** logo are trademarks registered and owned by the GSM Association.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The present document is a revision of ETSI EN 303 978 (V2.1.2). Major changes concern the off-axis eirp density.

Editorial clarifications have also been introduced.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.9] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.11].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

| National transposition dates | |
|--|-------------------|
| Date of adoption of this EN: | 19 December 2024 |
| Date of latest announcement of this EN (doa): | 31 March 2025 |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 30 September 2025 |
| Date of withdrawal of any conflicting National Standard (dow): | 30 September 2026 |

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Introduction

The Earth Stations on Mobile Platforms (ESOMPs) system overview is given in figure 1 and has the following characteristics:

- The ESOMP operates as part of a satellite network (e.g. star, mesh or point-to-point) used for the distribution and/or exchange of information.
- The ESOMP is comprised of all the equipment, electrical and mechanical, from the antenna itself to the interface with other communications equipment on a mobile platform (usually referred to as the terrestrial interface).
- The ESOMP transmits in the frequency range from 27,50 GHz to 30,00 GHz, and receives in one or more frequencies within the range from 17,30 GHz to 20,20 GHz (FSS) which are bands allocated to the Fixed Satellite Services (FSS) (Earth-to-space) among other services.
- The ESOMP uses linear or circular polarization.
- The ESOMP is designed for unattended operation.
- The ESOMP is controlled and monitored by a Network Control Facility (NCF). This function may be performed centrally (e.g. for a network of ESOMPs with a central hub) or it could be performed within the ESOMP for autonomous control. The NCF is outside the scope of the present document.
- The ESOMP operates through a geostationary satellite (or a cluster of co-located geostationary satellites) that is at least 2° away from any other geostationary satellite operating in the same frequencies and over the same coverage area.
- The geostationary satellite network with which the ESOMP communicates is assumed to have completed coordination per ITU requirements with the neighbouring geostationary satellite networks.
- The coordination agreement or agreements above would allow the ESOMP to operate with the coordinated parameters, such as off-axis EIRP density and other parameters.

NOTE: ESOMPs may operate with satellites that are more closely spaced than 2° with additional operational constraints that are beyond the scope of the present document.

Enclosure / Radome




Figure 1: ESOMP System Overview

The present document may also be applicable to the frequency bands 30,0 GHz to 31,0 GHz (Earth-to-space) and 20,2 GHz to 21,2 GHz (space-to-Earth) subject to national regulation.

Annex A (informative) provides HS Requirements specifications.

Annex B is void.

Annex C (normative) provides specifications concerning radiated measurements.

Annex D (normative) provides specifications concerning conducted measurements.

Annex E (informative) provides general information concerning RF cables.

Annex F (informative) provides information concerning RF waveguides.

Annex G (informative) covers selection of receiver conformance parameters.

Annex H (informative) covers maximum measurement uncertainty.

Annex I (informative) provides bibliographical references.

Annex J (informative) change history.

iTeh Standards (<https://standards.iteh.ai>) Document Preview

[ETSI EN 303 978 V2.2.1 \(2024-12\)](#)

<https://standards.iteh.ai/catalog/standards/etsi/160515ef-c2f6-4727-bd74-3a410c0d102a/etsi-en-303-978-v2-2-1-2024-12>

1 Scope

The present document specifies technical characteristics and methods of measurements for Earth Stations on Mobile Platforms (ESOMP) equipment with the following characteristics:

- The ESOMP is designed for both mobile and stationary operation.
- The ESOMP operates on various mobile platforms such as trains, maritime vessels, aircraft and other vehicles.
- The ESOMP is controlled and monitored by a Network Control Facility (NCF). This function may be performed centrally (e.g. for a network of ESOMPs with a central hub) or it could be performed within the ESOMP for autonomous control. The NCF is outside the scope of the present document.
- The ESOMP transmit and receive frequencies are shown in table 1.

Table 1: Frequency bands

| Frequency Bands/frequencies (GHz) | |
|--------------------------------------|----------------|
| Transmit (Earth-to-space) | 27,50 to 30,00 |
| Receive (space-to-Earth) | 17,30 to 20,20 |

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.11] is given in annex A.

2 References

ITEH Standards
(<https://standards.iteh.ai>)

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the [ETSI docbox](#).

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] Void.
- [3] Void.
- [4] [CISPR 16-1-1 \(2019\)](#): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus".
- [5] [CISPR 16-1-4:2019+AMD1:2020+AMD2:2023 CSV Consolidated version](#): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements".
- [6] [ANSI C63.5-2006](#): "American National Standard for Calibration of Antennas Used for Radiated Emission Measurements in Electro Magnetic Interference".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Void.
- [i.2] Void.
- [i.3] Void.
- [i.4] ETSI TR 102 375: "Satellite Earth Stations and Systems (SES); Guidelines for determining the parts of satellite earth station antenna radiation patterns concerned by the geostationary satellite orbit protection".
- [i.5] Void.
- [i.6] Void.
- [i.7] Void.
- [i.8] Void.
- [i.9] [Commission Implementing Decision C\(2015\) 5376 final of 4.8.2015](#) on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.10] IEC 153 (all parts): "Hollow metallic waveguides".
- [i.11] [Directive 2014/53/EU](#) of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC (RE Directive).
- [i.12] ETSI TR 103 896: "Satellite Earth Stations and Systems (SES); Considerations on off-axis EIRP density mask applicability for Ka band GSO ESOMPs in relation to potential revision to ETSI EN 303 978 (V2.1.2)".
- [i.13] ETSI EG 203 336 (V1.2.1) (05-2020): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.14] ETSI TR 103 581 (V1.1.1) (11-2019): "Use of measurement detectors in radio measurement methods".
- [i.15] ETSI TR 102 273 (all parts) (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [i.16] ETSI TR 100 028: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".

3 Definitions of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in Directive 2014/53/EU [i.11] and the following apply:

ancillary equipment: equipment used in connection with an ESOMP, where:

- the equipment is intended for use in conjunction with the ESOMP to provide additional operational and/or control features (e.g. to extend control to another position or location); and
- the equipment cannot be used on a stand alone basis, to provide user functions independently of the ESOMP; and
- the absence of the equipment does not inhibit the operation of the ESOMP.

antenna controller: equipment used to maintain antenna stabilization and tracking accuracy based on inputs from the Control and Monitoring Functions (CMF)

applicant: manufacturer or his authorized representative within the European Community or the person responsible for placing the apparatus on the market

carrier-off radio state: radio state in which the ESOMP may transmit and does not transmit any carrier

NOTE 1: The phrase "the ESOMP may transmit" means that all the conditions for transmission are satisfied (e.g. in a state where transmissions are permitted, no failure detected, and the ESOMP is correctly pointed towards the satellite).

NOTE 2: The existence of a "Carrier-off" radio state depends on the system of transmission used. For ESOMPs designed for continuous transmission mode there may be no "Carrier-off" state.

carrier-on radio state: radio state in which the ESOMP may transmit and transmits a carrier

Control Channel (CC): channel or channels by which ESOMPs receive control information from the NCF

EIRP_{Aggregate}: sum of the EIRP (watts) within the nominated bandwidth of the ESOMP network

EIRP_{cs}: clear sky EIRP of the ESOMP

EIRP_{max}: maximum EIRP capability of the ESOMP provided with the equipment for the intended use

emissions disabled radio state: radio state in which the ESOMP is not emitting

NOTE: Examples of cases where the ESOMP is in this radio state: before system monitoring pass, before the control channel is received, when a failure is detected, when an ESOMP is commanded to disable, and when the ESOMP is in a location requiring cessation of emissions.

external control channel: control channel which is either:

- i) carried by the ESOMP network via the same or another satellite, but not within the internal protocol of the ESOMP system; or
- ii) carried by any other radio communication system.

external response channel: response channel which is either:

- i) carried by the ESOMP network via the same or another satellite, but not within the internal protocol of the ESOMP system; or
- ii) carried by any other radio communication system.

integral antenna: antenna which may not be removed during the tests

internal control channel: control channel which is carried by the ESOMP network via the same satellite as used for transmission of user data and within the internal protocol structure of the ESOMP system

internal response channel: response channel which is carried by the ESOMP network via the same satellite as used for transmission of user data and within the internal protocol structure of the ESOMP system

mobile platform: any platform such as a train, a vessel, an aircraft or other vehicles capable of moving.

Network Control Facility (NCF): set of functional entities that, at system level, monitor and control the correct operation of the ESOMP and, if appropriate, all of the ESOMPs in a network

nominal antenna diameter: antenna diameter in meters for the intended use. For non circular antennas the nominal diameter is that of the widest dimension

NOTE : Network operators might request antennas of a certain diameter. Then an antenna that is compliant with the requirement for nominal antenna diameter equal to the requested antenna diameter can be used. Equipment can be marked with antenna diameters used in the requirements during compliance test.

nominated bandwidth: bandwidth of the ESOMP radio frequency transmission provided with the equipment for the intended use

NOTE 1: The nominated bandwidth is centred on the transmit frequency and does not exceed 5 times the occupied bandwidth.

NOTE 2: The nominated bandwidth is wide enough to encompass all spectral elements of the transmission which have a level greater than the specified spurious radiation limits. The nominated bandwidth is wide enough to take account of the transmit carrier frequency stability. The nominated bandwidth allows identification of adjacent channel interference levels which will be taken into account by operational procedures depending on the exact transponder carrier assignment situation.

occupied bandwidth: for a digital modulation scheme the width of the signal spectrum 10 dB below the maximum in-band density

off-axis angle: angle between the direction of the axis of the antenna main beam and the considered direction

removable antenna: antenna which may be removed during the tests according to the intended use

Response Channel (RC): channel by which ESOMP transmit monitoring information to the ACF

Special Test Equipment (STE): specific equipment needed for a test

EXAMPLE: NCF, downlink beacon frequencies, etc.

spurious radiation: any radiation outside the nominated bandwidth

transmission disabled state: ESOMP is in this state when it is not authorized by the NCF to transmit

transmission enabled state: ESOMP is in this state when it is authorized by the NCF to transmit

wanted signal occupied Bandwidth (BW):

- for a digital modulation scheme: the width of the signal spectrum 10 dB below the maximum in-band density;
- for an analogue modulation scheme: the width of a frequency band such that, below the lower and above the upper frequency limits, the mean power emitted is equal to 0,5 % of the total mean power of the emission.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

| | |
|--------------|--|
| dBc | ratio expressed in decibels relative to the EIRP of the unmodulated carrier |
| dBi | ratio of an antenna gain to the gain of an isotropic antenna, expressed in decibels |
| dBm | radio of a power to 1 milliwatt, expressed in decibels |
| dBpW | ratio of a power to 1 picowatt, expressed in decibels |
| dBsd | ratio expressed in decibels relative to the spectral density |
| dBW | ratio of a power to 1 watt, expressed in decibels |
| dB μ V/m | ratio of an electric field to 1 μ V/m, expressed in decibels (20 log(electric field /1 μ V/m)) |