



SLOVENSKI STANDARD SIST ISO 13778:2020

01-maj-2020

Drсни ležaji - Zagotavljanje kakovosti tankostenih ležajnih blazinic - Selektivni izbor blazinic za ozek tolerančni razpon

Plain bearings - Quality assurance of thin-walled half bearings - Selective assembly of bearings to achieve a narrow clearance range

iTeh STANDARD PREVIEW

Paliers lisses - Assurances qualité des demi-coussinets minces - Assemblage sélectif des paliers pour obtenir un jeu faible

[SIST ISO 13778:2020](https://standards.itih.si/sist-iso-13778-2020)

Ta slovenski standard je istoveten z: [SIST ISO 13778:2020](https://standards.itih.si/sist-iso-13778-2020) [ISO 13778:2017](https://standards.itih.si/sist-iso-13778-2020)

ICS:

21.100.10 Drsni ležaji Plain bearings

SIST ISO 13778:2020

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 13778:2020](#)

<https://standards.iteh.ai/catalog/standards/sist/315446f9-653f-43b5-9100-784dd553450b/sist-iso-13778-2020>

**Plain bearings — Quality assurance of
thin-walled half bearings — Selective
assembly of bearings to achieve a
narrow clearance range**

*Paliers lisses — Assurances qualité des demi-coussinets minces —
Assemblage sélectif des paliers pour obtenir un jeu faible*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 13778:2020](https://standards.iteh.ai/catalog/standards/sist/315446f9-653f-43b5-9100-784dd553450b/sist-iso-13778-2020)

<https://standards.iteh.ai/catalog/standards/sist/315446f9-653f-43b5-9100-784dd553450b/sist-iso-13778-2020>



iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 13778:2020

<https://standards.iteh.ai/catalog/standards/sist/315446f9-653f-43b5-9100-784dd553450b/sist-iso-13778-2020>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword.....	iv
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Housing swell and thermal expansion.....	2
5 Measurement and identification.....	2
5.1 Housings and journals.....	2
5.2 Bearings.....	2
6 Suggested schemes for fitting.....	3
6.1 General.....	3
6.2 Scheme 1: Standard application, without grading.....	3
6.3 Scheme 2: Grading of bearings.....	4
6.4 Scheme 3: Grading of bearings and journals or housings.....	4
6.5 Scheme 4: Unmixed bearings (Matrix scheme).....	5
6.6 Scheme 5: Mixed bearings (Matrix scheme).....	6
6.7 Scheme 6: Mixed bearings (fine matrix).....	6

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 13778:2020](https://standards.iteh.ai/catalog/standards/sist/315446f9-653f-43b5-9100-784dd553450b/sist-iso-13778-2020)

<https://standards.iteh.ai/catalog/standards/sist/315446f9-653f-43b5-9100-784dd553450b/sist-iso-13778-2020>

ISO 13778:2017(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html. (standards.iteh.ai)

This document was prepared by Technical Committee ISO/TC 123, *Plain bearings*, Subcommittee SC 5, *Quality analysis and assurance*.
SIST ISO 13778:2020

<https://standards.iteh.ai/catalog/standards/sist/315446f9-653f-43b5-9100->

This second edition cancels and replaces the first edition (ISO 13778:1999), which has been technically revised.
The following table gives the technical changes from ISO 13778:1999.

Plain bearings — Quality assurance of thin-walled half bearings — Selective assembly of bearings to achieve a narrow clearance range

1 Scope

This document specifies the selective assembly of bearings (in accordance with ISO 3548-1).

The bearing diametral clearance is determined by the housing diameter, journal diameter and the wall thickness of the two half bearings. Typically, these components will have a total tolerance “stack up” of 50 µm to 60 µm. Current engine development and in particular, the desire for improved engine refinement, has provided a need to decrease the clearance range due to the tolerance “stack up”. This document suggests various schemes of selective assembly to achieve such ranges.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3548-1, *Plain bearings — Thin-walled half bearings with or without flange — Part 1: Tolerances, design features and methods of test*

ISO 4378-1, *Plain bearings — Terms, definitions, classification and symbols — Part 1: Design, bearing materials and their properties*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4378-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

theoretical bearing diametral clearance

C

difference between the housing diameter, D_H , less twice the half bearing wall thickness (3.3), s_3 , and the journal diameter (3.4), D_J

$$C = D_H - (2s_3 + D_J)$$

3.2

housing diameter

D_H

diameter of the housing with no bearing fitted measured perpendicular to the split line

ISO 13778:2017(E)**3.3
bearing wall thickness**

s_3
wall thickness measured at 90° from the split line (at the “crown”)

Note 1 to entry: If two measurements are made, the larger of the two is used.

**3.4
journal diameter**

D_j
diameter of the finished shaft measured at a position to give maximum diameter

**3.5
tolerance**

range between the upper and lower limits specified on the drawing

**3.6
housing swell**

expansion of a housing bore caused by the interference fit of the bearings

4 Housing swell and thermal expansion

Housing swell is defined as the “expansion of a housing bore, caused by the interference fit of the bearings”. When two half bearings are assembled into a housing and the housing is bolted up, the assembled bore will be slightly greater than the arithmetical subtraction of the two bearing wall thicknesses from the housing diameter as measured before the bearing is fitted. Housing swell is generally of the order of a few micrometres. Maximum housing swell will occur with a combination of maximum bearing overstand (nip) and minimum housing diameter. It is prudent to measure actual housing swell by carrying out fitting tests. Actual housing deformation may also be affected by the degree of control of bolt tension.

With light alloy housings, the housing swell may be larger, due not only to the lower modulus of elasticity but also to thermal expansion.

Allowance for housing swell and thermal expansion has to be made when setting the bearing diametral clearance.

5 Measurement and identification**5.1 Housings and journals**

Specific measurement of each housing and journal may be necessary in more complex grading schemes. While bearings will be graded according to only the crown wall thickness, journals in particular may have to be measured in several places, both axially and circumferentially, to ascertain the mean journal diameter. The crown housing diameter may be the only housing measurement necessary. With grade tolerances of a few micrometres, accurate measurement with minimal dirt and constant temperature is necessary.

Traditionally, crankshaft journals of different grades have been identified with a dab of paint or ink adjacent to the journal. Housings have been similarly identified. Such a method relies upon the visual discrimination of the operator and this may on occasions be unreliable. One alternative is to bar or dot code the housing and/or journal with either adhesive labels or by etching. Another is to store the data on computer for retrieval at assembly stage.

5.2 Bearings

If bearing grades with wall thickness tolerances of less than the normal process capability are required, then consideration shall be given as to how the bearings are graded and identified. The part number is

stamped upon the bearing prior to final wall thickness machining. Additional stamping after bearing grading is not feasible as this will create high spots of wall thickness. The usual practice is to mark the bearing side face after grading with a permanent colour code or with other suitable methods.

6 Suggested schemes for fitting

6.1 General

The selective assembly of bearings shall be in accordance with ISO 3548-1.

Before choosing the scheme for selectively fitting bearings, it is first necessary to set the desired clearance range. As a general rule, the narrower the clearance range, the more complex the grading scheme will be and the tighter the tolerance on each component. As an example, if a clearance range of 24 μm is required, this could entail grade tolerances of 6 μm , while with a clearance range of 32 μm , grade tolerances of 8 μm would be acceptable.

While it may be desirable from the design viewpoint to achieve a very narrow clearance range, there may come a point at which perceived performance gains from working very close to the desired mean clearance become offset by the cost and complexity of the selective fitting scheme.

While such schemes are feasible for OE engine assembly, they are not practical for replacement bearings where the bearings are packed in sets of similar sizes.

Other points to consider are as follows.

- a) Due to the normal distribution of journal and housing sizes, the required quantity of each bearing grade will not necessarily be equal. Carefully controlled scheduling will be necessary in order to minimize bearing stocks and prevent shortages of particular bearing grades.
- b) Intermediate grades can be formed by fitting together half bearings from adjacent grades. This can significantly increase the flexibility of the system.
- c) If it is necessary to grade bearings by measurement after final wall thickness machining, then overlapping bearing grades are permissible and in fact allow the bearing supplier flexibility in achieving correct quantities of each bearing grade.
- d) When choosing a grading scheme, the difference in process capability for wall thickness between bimetallic and multi-layer should be taken into account.

The schemes described in [6.2](#) to [6.7](#) are examples only.

6.2 Scheme 1: Standard application, without grading

The clearance shall be determined by the limitations of normal process capability (see [Table 1](#)).

Housing diameter, D_H : not graded

Journal diameter, D_J : not graded

Bearing wall thickness, s_3 : not graded