



Designation: D 5785 – 95 (Reapproved 2000)

Standard Test Method for (Analytical Procedure) for Determining Transmissivity of Confined Nonleaky Aquifers by Underdamped Well Response to Instantaneous Change in Head (Slug Test)¹

This standard is issued under the fixed designation D 5785; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers determination of transmissivity from the measurement of the damped oscillation about the equilibrium water level of a well-aquifer system to a sudden change of water level in a well. Underdamped response of water level in a well to a sudden change in water level is characterized by oscillatory fluctuation about the static water level with a decrease in the magnitude of fluctuation and recovery to initial water level. Underdamped response may occur in wells tapping highly transmissive confined aquifers and in deep wells having long water columns.

1.2 This analytical procedure is used in conjunction with the field procedure Test Method D 4044 for collection of test data.

1.3 *Limitations*—Slug tests are considered to provide an estimate of transmissivity of a confined aquifer. This test method requires that the storage coefficient be known. Assumptions of this test method prescribe a fully penetrating well (a well open through the full thickness of the aquifer), but the slug test method is commonly conducted using a partially penetrating well. Such a practice may be acceptable for application under conditions in which the aquifer is stratified and horizontal hydraulic conductivity is much greater than vertical hydraulic conductivity. In such a case the test would be considered to be representative of the average hydraulic conductivity of the portion of the aquifer adjacent to the open interval of the well. The method assumes laminar flow and is applicable for a slug test in which the initial water-level displacement is less than 0.1 or 0.2 of the length of the static water column.

1.4 This test method of analysis presented here is derived by van der Kamp (1)² based on an approximation of the underdamped response to that of an exponentially damped sinusoid. A more rigorous analysis of the response of wells to a sudden change in water level by Kipp (2) indicates that the method presented by van der Kamp (1) matches the solution of Kipp

(2) when the damping parameter values are less than about 0.2 and time greater than that of the first peak of the oscillation (2).

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

D 653 Terminology Relating to Soil, Rock, and Contained Fluids³

D 4043 Guide for Selection of Aquifer-Test Method in Determining of Hydraulic Properties by Well-Techniques³

D 4044 Test Method for (Field Procedure for) Instantaneous Change in Head (Slug Test) for Determining Hydraulic Properties of Aquifers³

D 4750 Test Method for Determining Subsurface Liquid Levels in a Borehole or Monitoring Well (Observation Well)³

3. Terminology

3.1 Definitions:

3.1.1 *aquifer, confined*—an aquifer bounded above and below by confining beds and in which the static head is above the top of the aquifer.

3.1.2 *confining bed*—a hydrogeologic unit of less permeable material bounding one or more aquifers.

3.1.3 *control well*—well by which the aquifer is stressed, for example, by pumping, injection, or change in head.

3.1.4 *head, static*—the height above a standard datum of the surface of a column of water (or other liquid) that can be supported by the static pressure at a given point.

3.1.5 *observation well*—a well open to all or part of an aquifer.

3.1.6 *overdamped well response*—characterized by the water level returning to the static level in an approximately exponential manner following a sudden change in water level. (See for comparison *underdamped well response*.)

¹ This test method is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.21 on Ground Water and Vadose Zone Investigations.

Current edition approved Sept. 10, 1995. Published November 1995.

² The boldface numbers given in parentheses refer to a list of references at the end of the text.

³ *Annual Book of ASTM Standards*, Vol 04.08.

3.1.7 *slug*—a volume of water or solid object used to induce a sudden change of head in a well.

3.1.8 *storage coefficient*—the volume of water an aquifer releases from or takes into storage per unit surface area of the aquifer per unit change in head. For a confined aquifer, the storage coefficient is equal to the product of specific storage and aquifer thickness. For an unconfined aquifer, the storage coefficient is approximately equal to the specific yield.

3.1.9 *transmissivity*—the volume of water at the existing kinematic viscosity that will move in a unit time under a unit hydraulic gradient through a unit width of the aquifer.

3.1.10 *underdamped well response*—response characterized by the water level oscillating about the static water level following a sudden change in water level (See for comparison *overdamped well response*.)

3.1.11 For definitions of other terms used in this test method, see Terminology D 653.

3.2 Symbols: Symbols and Dimensions:

3.2.1 T —transmissivity [$L^2 T^{-1}$].

3.2.2 S —storage coefficient [nd].

3.2.3 L —effective length of water column, equal to $L_c + (r_c^2/r_s^2)$ (m/2).

3.2.3.1 *Discussion*—This expression for the effective length is given by Kipp (2). The expression for the effective length of the water column from Cooper et al (3) is given as $L_c + 3/8L_s$ and assumes that the well screen and well casing have the same diameter.

3.2.4 L_c —length of water column within casing [L].

3.2.5 L_s —length of water column within well screen [L].

3.2.6 g —acceleration of gravity [LT^{-2}].

3.2.7 h —hydraulic head in the aquifer [L].

3.2.8 h_o —initial hydraulic head in the aquifer [L].

3.2.9 h_s —hydraulic head in the well screen [L].

3.2.10 r_c —radius of well casing [L].

3.2.11 r_s —radius of well screen [L].

3.2.12 t —time [T].

3.2.13 w —water level displacement from the initial static level [L].

3.2.14 w_o —initial water level displacement [L].

3.2.15 γ —damping constant [T^{-1}].

3.2.16 τ —wavelength [T].

3.2.17 ω —angular frequency [T^{-1}].

3.2.18 m —aquifer thickness, [L].

4. Summary of Test Method

4.1 This test method describes the analytical procedure for analyzing data collected during an instantaneous head (slug) test using a well in which the response is underdamped. The field procedures in conducting a slug test are given in Test Method D 4044. The analytical procedure consists of analyzing the response of water level in the well following the change in water level induced in the well.

4.2 *Theory*—The equations that govern the response of well to an instantaneous change in head are treated at length by Kipp (2). The flow in the aquifer is governed by the following equation for cylindrical flow:

$$\frac{S}{T} \frac{dh}{dt} = \frac{1}{r} \frac{d}{dr} \left(r \frac{dh}{dr} \right) \quad (1)$$

where:

h = hydraulic head,

T = aquifer transmissivity, and

S = storage coefficient.

4.2.1 The initial condition is at $t = 0$ and $h = h_o$ and the outer boundary condition is as $r \rightarrow \infty$ and $h \rightarrow h_o$.

4.3 The flow rate balance on the well bore relates the displacement of the water level in the well-riser to the flow into the well:

$$\pi r_c^2 \frac{dw}{dt} = 2\pi r_s T \frac{\partial h}{\partial r} \Big|_{r=r_s} \quad (2)$$

where:

r_c = radius of the well casing, and

w = displacement of the water level in the well from its initial position.

4.3.1 The third equation describing the system, relating h_s and w , comes from a momentum balance of Bird et al (4) as referenced in Kipp (2).

$$\frac{d}{dt} \int_{-m}^0 \pi r_s^2 \rho v dz = [-\rho v^2 + p_1 - p_2 - \rho gm] \pi r_s^2 \quad (3)$$

where:

v = velocity in the well screen interval,

m = aquifer thickness,

p = pressure,

ρ = fluid density,

g = gravitational acceleration, and

r_s = well screen radius. Well and aquifer geometry are shown in Fig. 1.

Atmospheric pressure is taken as zero.

5. Solution

5.1 The method of van der Kamp (1) assumes the water level response to a sudden change for the underdamped case, except near critical damping conditions, can be approximately described as an exponentially damped cyclic fluctuation that decays exponentially. The water-level fluctuation would then be given by:

$$w(t) = w_o e^{-\gamma t} \cos \omega t \quad (4)$$

5.1.1 The following solution is given by van der Kamp (1).

$$d = \frac{-r_c^2 (g/L)^{1/2} 1n[0.79 r_s^2 (S/T)(g/L)^{1/2}]}{8T} \quad (5)$$

that may be written as:

$$T = b + a 1nT \quad (6)$$

where:

$$b = a 1n[0.79 r_s^2 S(g/L)^{1/2}] \quad (7)$$

$$a = \frac{r_c^2 (g/L)^{1/2}}{8d} \quad (8)$$

$$d = \gamma/(g/L)^{1/2} \quad (9)$$

and

$$L = g/(\omega^2 + \gamma^2) \quad (10)$$