



**SLOVENSKI STANDARD**  
**oSIST prEN IEC 60034-11:2020**  
**01-april-2020**

---

**Električni rotacijski stroji - 11. del: Toplotna zaščita**

Rotating electrical machines - Part 11: Thermal protection

Drehende elektrische Maschinen - Teil 11: Thermischer Schutz

Machines électriques tournantes - Partie 11: Protection thermique

**Ta slovenski standard je istoveten z: prEN IEC 60034-11:2020**

[ksIST FprEN IEC 60034-11:2020](https://standards.iteh.ai/catalog/standards/sist/bbae2dea-350b-4ddd-acc6-830a90141253/ksist-fpren-iec-60034-11-2020)

<https://standards.iteh.ai/catalog/standards/sist/bbae2dea-350b-4ddd-acc6-830a90141253/ksist-fpren-iec-60034-11-2020>

**ICS:**

29.160.01	Rotacijski stroji na splošno	Rotating machinery in general
-----------	------------------------------	-------------------------------

**oSIST prEN IEC 60034-11:2020**

**en,fr,de**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[kSIST FprEN IEC 60034-11:2020](https://standards.iteh.ai/catalog/standards/sist/bbae2dea-350b-4ddd-ae6-830a90141253/ksist-fpren-iec-60034-11-2020)

<https://standards.iteh.ai/catalog/standards/sist/bbae2dea-350b-4ddd-ae6-830a90141253/ksist-fpren-iec-60034-11-2020>



2/1979/CDV

COMMITTEE DRAFT FOR VOTE (CDV)

PROJECT NUMBER:

**IEC 60034-11 ED3**

DATE OF CIRCULATION:

**2020-01-31**

CLOSING DATE FOR VOTING:

**2020-04-24**

SUPERSEDES DOCUMENTS:

**2/1959/CD,2/1978/CC**

IEC TC 2 : ROTATING MACHINERY

SECRETARIAT:

United Kingdom

SECRETARY:

Mr Charles Whitlock

OF INTEREST TO THE FOLLOWING COMMITTEES:

PROPOSED HORIZONTAL STANDARD:

Other TC/SCs are requested to indicate their interest, if any, in this CDV to the secretary.

FUNCTIONS CONCERNED:

 EMC ENVIRONMENT QUALITY ASSURANCE SAFETY SUBMITTED FOR CENELEC PARALLEL VOTING NOT SUBMITTED FOR CENELEC PARALLEL VOTING**Attention IEC-CENELEC parallel voting**

The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Committee Draft for Vote (CDV) is submitted for parallel voting.

The CENELEC members are invited to vote through the CENELEC online voting system.

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE:

**Rotating electrical machines – Part 11: Thermal protection**

PROPOSED STABILITY DATE: 2023

NOTE FROM TC/SC OFFICERS:

**Copyright © 2019 International Electrotechnical Commission, IEC.** All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

## CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references .....	6
3 Definitions .....	6
4 Thermal protection limits .....	7
5 Protection against thermal overloads with slow variation .....	7
6 Protection against thermal overloads with rapid variation.....	8
7 Restart after tripping.....	8
8 Type Tests .....	9
8.1 General .....	9
8.2 Verification of temperature due to the thermal overloads with slow variation.....	9
8.3 Verification of temperature due to thermal overloads with rapid variation.....	9
9 Routine tests .....	10
Figure 1 – Example of thermal overload with slow variation and direct thermal protection .....	10
Figure 2 – Example of thermal overload with slow variation in the case of too intensive intermittent periodic duty with starting (duty S4) and direct thermal protection .....	11
Figure 3 – Example of thermal overload with rapid variation where the thermally critical part has direct thermal protection .....	12
Figure 4 – Example of thermal overload with rapid variation where the thermally critical part has indirect thermal protection.....	13
Table 1 – Maximum winding temperatures for overloads with slow variation.....	8
Table 2 – Maximum winding temperatures for overloads with rapid variation.....	8

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

## ROTATING ELECTRICAL MACHINES –

## Part 11: Thermal protection

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60034-11 has been prepared by IEC technical committee 2: Rotating machinery.

This third edition cancels and replaces the second edition published in 2004. This edition constitutes a technical revision and applies to electrical machines manufactured in accordance with IEC 60034-12.

The main changes with respect to the previous edition are

- the additional specification of winding temperature limits for temperature class 200 (N),
- the increased limits of maximum winding temperatures for overloads with rapid variation,
- the clarification that the motor winding may be permanently damaged after it has been exposed to temperatures according to Table 2,
- a clarification of scope,
- a clarification on the definition of indirect thermal protection,
- a clarifying note in clause 6,
- the conversion of note 3 in clause 6 into normal text including changes in wording,
- the incorporation of note 3 in clause 5 into clause 2,
- a clarification on the test methods for larger motors in clause 8.3.

The text of this standard is based on the following documents:

FDIS	Report on voting
2/1299/FDIS	2/1309/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ksIST FprEN IEC 60034-11:2020](https://standards.iteh.ai/catalog/standards/sist/bbae2dea-350b-4ddd-ace6-830a90141253/ksist-fpren-iec-60034-11-2020)

<https://standards.iteh.ai/catalog/standards/sist/bbae2dea-350b-4ddd-ace6-830a90141253/ksist-fpren-iec-60034-11-2020>

1

## INTRODUCTION

2 Thermal protection systems are based on the principle of protecting or monitoring the vulnerable  
3 machine parts against excessive temperatures. This requires the selection of the appropriate  
4 thermal protection device to suit both the type of protection required and the machine  
5 component to be protected. This standard does not detail the protection methods available or  
6 specify the protection method to be used for particular applications but instead it specifies the  
7 temperature of the protected parts that should not be exceeded if a fault or machine abuse  
8 occurs.

9 The requirements are not intended to guarantee a "normal" machine life for all conditions of  
10 use, but rather to avoid both failure and accelerated premature thermal ageing of the winding  
11 insulation. The requirements result from a compromise since the level of protection should  
12 neither be set so low that it causes nuisance tripping nor so high that it allows continuous  
13 working at temperatures that will seriously affect the life of the winding insulation.

14 Normal insulation life can only be ensured by correct motor application and maintenance.  
15 Frequent operation at above the normal temperature limits, see IEC 60034-1, which cannot be  
16 prevented by built-in thermal protection without risking nuisance tripping may lead to a  
17 noticeable reduction in machine life. It should be noted that the life of the winding insulation is  
18 approximately halved for every 8 K to 10 K increase in the continuous operating temperature.

19 The requirement to incorporate thermal protection in a machine is a matter for agreement. The  
20 application of this standard should be a matter of agreement between the user and the machine  
21 manufacturer.

22

ITEH STANDARD PREVIEW  
(standards.iteh.ai)

[ksIST FprEN IEC 60034-11:2020](https://standards.iteh.ai/catalog/standards/sist/bbae2dea-350b-4ddd-ace6-830a90141253/ksist-fpren-iec-60034-11-2020)

<https://standards.iteh.ai/catalog/standards/sist/bbae2dea-350b-4ddd-ace6-830a90141253/ksist-fpren-iec-60034-11-2020>

23  
24  
25  
26  
27

## ROTATING ELECTRICAL MACHINES –

### Part 11: Thermal protection

#### 28 1 Scope

29 This part of IEC 60034 specifies requirements relating to the use of thermal protectors and  
30 thermal detectors incorporated into the stator windings or placed in other suitable positions in  
31 induction machines in order to protect them against serious damage due to thermal overloads.  
32 It applies to single-speed three-phase 50 Hz or 60 Hz cage induction motors in accordance with  
33 IEC 60034-1 and IEC 60034-12 that:

- 34 • have a rated voltage up to 1 000 V;
- 35 • are intended for direct-on-line or star-delta starting.

36 Not included are:

- 37 • direct protection of the rotor winding; the methods of protection only protect rotor windings  
38 indirectly; for large motors (particularly 2 pole motors) and for motors starting large inertia  
39 loads, special attention needs to be given to rotor heating both when starting and especially  
40 after a "trip" has occurred;
- 41 • the protection of bearings and other mechanical parts;
- 42 • the protection methods to be used for particular applications.

43 NOTE 1 Although temperature values given in this standard are higher than those specified in IEC 60034-1, they  
44 are not in conflict.

45 NOTE 2 Additional requirements may apply to particular motor types such as those used in household appliances,  
46 or for motors used in explosive atmospheres.

#### 47 2 Normative references

48 The following referenced documents are indispensable for the application of this document. For  
49 dated references, only the edition cited applies. For undated references, the latest edition of  
50 the referenced document (including any amendments) applies.

51 IEC 60034-1:2017, *Rotating electrical machines – Part 1: Rating and performance*

52 IEC 60034-12:2016, *Rotating electrical machines – Part 12: Starting performance of single-*  
53 *speed three-phase cage induction motors*

#### 54 3 Terms and definitions

55 For the purposes of this part of IEC 60034, the following terms and definitions apply.

##### 56 3.1 57 thermal protection

58 protection of windings of a machine against excessive temperature resulting from conditions of  
59 overload or loss of cooling

##### 60 3.2 61 thermal protection system

62 system for the protection of a machine winding against excessive temperature resulting from  
63 conditions of overload or loss of cooling by means of either thermal protector(s) or thermal  
64 detector(s)



65 **3.3**66 **thermal detector**

67 electrically insulated device that is only sensitive to temperature, capable of initiating a  
68 switching function in a protection system when its temperature reaches a predetermined level

69 **3.4**70 **thermal protector**

71 electrically insulated device that is sensitive to the temperature of the machine winding which  
72 carries machine current, capable of directly switching off the machine when its temperature  
73 reaches a predetermined level

74 NOTE Some thermal protectors are sensitive to both temperature and current, the combination of which activates  
75 the direct switching off of the machine.

76 **3.5**77 **thermal overload with slow variation**

78 overload condition or loss of cooling that produces a rise of temperature that is sufficiently slow  
79 that the temperature of the thermal protector or detector follows it without appreciable delay

80 **3.6**81 **thermal overload with rapid variation**

82 overload condition or loss of cooling that produces a rise of temperature that is too rapid for the  
83 temperature of the thermal protector or detector to follow without appreciable delay resulting in  
84 a significant temperature difference between the thermal device and the part to be protected

85 **3.7**86 **maximum temperature after tripping**

87 the maximum value of the temperature that is reached by the protected part of the machine  
88 during the period which follows tripping by the thermal protection system

iTeh STANDARD PREVIEW

(standards.iteh.ai)

[ksIST FprEN IEC 60034-11:2020](https://standards.iteh.ai/catalog/standards/sist/bbae2dea-350b-4ddd-ace6-830a90141253/ksist-fpren-iec-60034-11-2020)89 **3.8**90 **direct thermal protection**

91 form of protection where the part of the machine in which the thermal detector(s) or thermal  
92 protector(s) are incorporated is the part for which protection is being provided

<https://standards.iteh.ai/catalog/standards/sist/bbae2dea-350b-4ddd-ace6-830a90141253/ksist-fpren-iec-60034-11-2020>93 **3.9**94 **indirect thermal protection**

95 form of protection where the part of the machine in which the thermal detector(s) or thermal  
96 protector(s) are incorporated (e.g. the stator winding) is not the part for which protection is  
97 being provided (e.g. the rotor winding)

98 **4 Thermal protection limits**

99 Machines shall be capable of operating at rated output and at all operating conditions according  
100 to IEC 60034-1 without activation of the thermal protection device. The thermal protection  
101 device shall limit the winding temperature in accordance with Clauses 5 or 6.

102 **5 Protection against thermal overloads with slow variation**

103 When subjected to an overload or other misuse condition causing overheating with slow  
104 variation, the protection system shall operate to prevent the temperature of the machine winding  
105 from exceeding the values in Table 1.

106 Examples of the rise in temperature as a function of time are shown in Figures 1 and 2.

107

108 **Table 1 – Maximum winding temperatures for overloads with slow variation**

Thermal class	130(B)	155(F)	180(H)	200(N)
Maximum insulated winding temperature °C	145	170	195	215

109  
110 The winding temperature shall be determined by the resistance method in accordance with the  
111 requirements of Clause 8.6.2 of IEC 60034-1.

112 NOTE 1 The limit values Table 1 exceed the thermal classification and thus will reduce the lifetime of the motor.

113 NOTE 2 **The maximum temperature limits are based on experience.** Some of the ways in which a thermal overload  
114 with slow variation may be caused are:

- 115 • Defects in ventilation or the ventilation system due to excessive dust in the ventilation ducts, or dirt on windings  
116 or frame cooling ribs, etc.
- 117 • An excessive rise in ambient temperature or the temperature of the cooling medium.
- 118 • Gradual increasing mechanical overload.
- 119 • Prolonged voltage drop, over-voltage or unbalance in the machine supply.
- 120 • Excessive duty on a motor rated for intermittent duty.
- 121 • Frequency deviations.

## 122 6 Protection against thermal overloads with rapid variation

123 When a thermal overload with rapid variation is applied to the machine, the thermal protection  
124 system shall operate to prevent the temperature of the machine winding from exceeding the  
125 values given in Table 2.

126 A current overload relay does not normally provide protection against repeated rapid overload  
127 variations and the use of a thermal protection device should be considered

128 Examples of the rise in temperature as a function of time are shown in Figures 3 and 4.

129 **Table 2 – Maximum winding temperatures for overloads with rapid variation**

Thermal class	130(B)	155(F)	180(H)	200(N)
Maximum insulated winding temperature °C	225	250	275	295

130  
131 The winding temperature shall be determined by direct measurements such as thermocouples  
132 in accordance with the requirements of Clause 8.5.3 of IEC 60034-1.

133 It is understood that the motor winding may be permanently damaged and may not be able to  
134 operate after it has been exposed to temperatures according to Table 2.

135 NOTE 1 Some of the ways in which a thermal overload with rapid variation may be caused are:

- 136 • Stalling the motor.
- 137 • Phase failure.
- 138 • Starting under abnormal conditions, for example, inertia too great, voltage too low, load torque abnormally high;
- 139 • Sudden and significant increase in load.
- 140 • Starting repeatedly during a short time.

141 NOTE 2 The maximum temperature limits are based on experience taking into account factors such as ambient  
142 temperature, variations in supply voltage and normal requirements for starting motors.

143 **The temperatures in Table 2 must not be confused with the operating temperatures of the**  
144 **winding's thermal protector or thermal detector which have to be significantly below these**  
145 **values. The thermal protector shall be installed at a place where the highest temperatures are**  
146 **expected according to the application and the motor cooling system.**