

ETSI TS 124 501 V17.11.0 (2023-07)



**5G;Non-Access-Stratum (NAS) protocol for 5G System (5GS);
Stage 3
(3GPP TS 24.501 version 17.11.0 Release 17)**

[ETSI TS 124 501 V17.11.0 \(2023-07\)](https://standards.iteh.ai/catalog/standards/sist/b8df2340-f215-4576-92b1-bdd740990ebc/etsi-ts-124-501-v17-11-0-2023-07)

<https://standards.iteh.ai/catalog/standards/sist/b8df2340-f215-4576-92b1-bdd740990ebc/etsi-ts-124-501-v17-11-0-2023-07>



Reference

RTS/TSGC-0124501vhb0

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://standards-portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	24
1 Scope	25
2 References	25
3 Definitions and abbreviations.....	29
3.1 Definitions	29
3.2 Abbreviations	40
4 General	43
4.1 Overview	43
4.2 Coordination between the protocols for 5GS mobility management and 5GS session management	43
4.3 UE domain selection	44
4.3.1 UE's usage setting	44
4.3.2 Domain selection for UE originating sessions / calls.....	44
4.3.3 Change of UE's usage setting.....	46
4.3.4 Change or determination of IMS voice availability	46
4.4 NAS security	47
4.4.1 General.....	47
4.4.2 Handling of 5G NAS security contexts.....	47
4.4.2.1 General	47
4.4.2.2 Establishment of a mapped 5G NAS security context during inter-system change from S1 mode to N1 mode in 5GMM-CONNECTED mode.....	50
4.4.2.3 Establishment of a 5G NAS security context during N1 mode to N1 mode handover	51
4.4.2.4 Establishment of an EPS security context during inter-system change from N1 mode to S1 mode in 5GMM-CONNECTED mode	52
4.4.2.5 Establishment of secure exchange of NAS messages	52
4.4.2.6 Change of security keys	54
4.4.3 Handling of NAS COUNT and NAS sequence number	55
4.4.3.1 General	55
4.4.3.2 Replay protection	56
4.4.3.3 Integrity protection and verification.....	56
4.4.3.4 Ciphering and deciphering	56
4.4.3.5 NAS COUNT wrap around	57
4.4.4 Integrity protection of NAS signalling messages.....	57
4.4.4.1 General	57
4.4.4.2 Integrity checking of NAS signalling messages in the UE	58
4.4.4.3 Integrity checking of NAS signalling messages in the AMF	58
4.4.5 Ciphering of NAS signalling messages	60
4.4.6 Protection of initial NAS signalling messages.....	60
4.4.7 Protection of NAS IEs	62
4.5 Unified access control	63
4.5.1 General.....	63
4.5.2 Determination of the access identities and access category associated with a request for access for UEs not operating in SNPN access mode	65
4.5.2A Determination of the access identities and access category associated with a request for access for UEs operating in SNPN access mode	70
4.5.3 Operator-defined access categories.....	75
4.5.4 Access control and checking.....	77
4.5.4.1 Access control and checking in 5GMM-IDLE mode and in 5GMM-IDLE mode with suspend indication.....	77
4.5.4.2 Access control and checking in 5GMM-CONNECTED mode and in 5GMM-CONNECTED mode with RRC inactive indication	79
4.5.5 Exception handling and avoiding double barring	81

4.5.6	Mapping between access categories/access identities and RRC establishment cause	85
4.6	Network slicing	86
4.6.1	General.....	86
4.6.2	Mobility management aspects.....	88
4.6.2.1	General	88
4.6.2.2	NSSAI storage.....	89
4.6.2.3	Provision of NSSAI to lower layers in 5GMM-IDLE mode.....	94
4.6.2.4	Network slice-specific authentication and authorization.....	96
4.6.2.5	Mobility management based network slice admission control.....	97
4.6.2.6	Provision of NSAG information to lower layers.....	98
4.6.3	Session management aspects	99
4.6.3.0	General	99
4.6.3.1	Session management based network slice admission control	100
4.6.3.2	Support of network slice admission control and interworking with EPC	100
4.6.3.3	Session management based network slice data rate limitation control.....	100
4.7	NAS over non-3GPP access	101
4.7.1	General.....	101
4.7.2	5GS mobility management aspects	101
4.7.2.1	General	101
4.7.2.2	Establishment cause for non-3GPP access.....	102
4.7.3	5GS session management aspects.....	103
4.7.4	Limited service state over non-3GPP access	103
4.7.5	NAS signalling using trusted WLAN access network	104
4.8	Interworking with E-UTRAN connected to EPC	104
4.8.1	General.....	104
4.8.2	Single-registration mode.....	105
4.8.2.1	General	105
4.8.2.2	Single-registration mode with N26 interface	105
4.8.2.3	Single-registration mode without N26 interface	105
4.8.2.3.1	Interworking between NG-RAN and E-UTRAN	105
4.8.2.3.2	Interworking between TNGF or N3IWF connected to 5GCN and E-UTRAN.....	107
4.8.3	Dual-registration mode	108
4.8.4	Core Network selection for UEs not using CIoT 5GS optimizations	109
4.8.4A	Core Network selection and redirection for UEs using CIoT optimizations.....	109
4.8.4A.1	Core network selection.....	109
4.8.4A.2	Redirection of the UE by the core network.....	110
4.9	Disabling and re-enabling of UE's N1 mode capability	110
4.9.1	General.....	110
4.9.2	Disabling and re-enabling of UE's N1 mode capability for 3GPP access.....	110
4.9.3	Disabling and re-enabling of UE's N1 mode capability for non-3GPP access.....	113
4.10	Interworking with ePDG connected to EPC.....	113
4.11	UE configuration parameter updates	113
4.12	Access traffic steering, switching and splitting (ATSSS).....	114
4.13	Support of NAS signalling using wireline access network.....	114
4.14	Non-public network.....	115
4.14.1	General.....	115
4.14.2	Stand-alone non-public network	115
4.14.3	Public network integrated non-public network (PNI-NPN).....	117
4.15	Time synchronization and time sensitive communication.....	118
4.15.1	General.....	118
4.15.2	Void	118
4.15.2.1	Void.....	118
4.15.2.2	Void.....	118
4.15.2.3	Void.....	118
4.15.3	Time synchronization	118
4.15.4	User plane node management	118
4.16	UE radio capability signalling optimisation	119
4.17	5GS mobility management in NB-N1 mode	120
4.18	5GS session management in NB-N1 mode	120
4.19	5GS mobility management in WB-N1 mode for IoT	121
4.20	5GS session management in WB-N1 mode for IoT	121
4.21	Authentication and Key Management for Applications (AKMA)	122

4.22	Uncrewed aerial vehicle identification, authentication, and authorization	122
4.22.1	General.....	122
4.22.2	Authentication and authorization of UAV	122
4.22.3	Authorization of C2 communication	123
4.22.4	Void	124
4.23	NAS over Non-Terrestrial Network	124
4.23.1	General.....	124
4.23.2	List of "PLMNs not allowed to operate at the present UE location"	124
4.23.3	5GS mobility management via a satellite NG-RAN cell	125
4.23.4	5GS session management via a satellite NG-RAN cell	125
4.23.5	Handling multiple tracking area codes from the lower layers.....	125
4.24	Minimization of service interruption.....	126
4.25	Support of MUSIM features.....	127
5	Elementary procedures for 5GS mobility management	128
5.1	Overview	128
5.1.1	General.....	128
5.1.2	Types of 5GMM procedures.....	128
5.1.3	5GMM sublayer states	129
5.1.3.1	General	129
5.1.3.2	5GMM sublayer states	130
5.1.3.2.1	5GMM sublayer states in the UE.....	130
5.1.3.2.1.1	General.....	130
5.1.3.2.1.2	Main states	130
5.1.3.2.1.2.1	5GMM-NUL	130
5.1.3.2.1.2.2	5GMM-DEREGISTERED.....	130
5.1.3.2.1.2.3	5GMM-REGISTERED-INITIATED	130
5.1.3.2.1.2.4	5GMM-REGISTERED	130
5.1.3.2.1.2.5	5GMM-DEREGISTERED-INITIATED.....	130
5.1.3.2.1.2.6	5GMM-SERVICE-REQUEST-INITIATED.....	131
5.1.3.2.1.3	Substates of state 5GMM-DEREGISTERED	131
5.1.3.2.1.3.1	General	131
5.1.3.2.1.3.2	5GMM-DEREGISTERED.NORMAL-SERVICE	131
5.1.3.2.1.3.3	5GMM-DEREGISTERED.LIMITED-SERVICE.....	131
5.1.3.2.1.3.4	5GMM-DEREGISTERED.ATTEMPTING-REGISTRATION	131
5.1.3.2.1.3.5	5GMM-DEREGISTERED.PLMN-SEARCH	131
5.1.3.2.1.3.6	5GMM-DEREGISTERED.NO-SUPI	131
5.1.3.2.1.3.7	5GMM-DEREGISTERED.NO-CELL-AVAILABLE	131
5.1.3.2.1.3.8	5GMM-DEREGISTERED.eCALL-INACTIVE.....	132
5.1.3.2.1.3.9	5GMM-DEREGISTERED.INITIAL-REGISTRATION-NEEDED	132
5.1.3.2.1.4	Substates of state 5GMM-REGISTERED	132
5.1.3.2.1.4.1	General	132
5.1.3.2.1.4.2	5GMM-REGISTERED.NORMAL-SERVICE	132
5.1.3.2.1.4.3	5GMM-REGISTERED.NON-ALLOWED-SERVICE.....	132
5.1.3.2.1.4.4	5GMM-REGISTERED.ATTEMPTING-REGISTRATION-UPDATE.....	132
5.1.3.2.1.4.5	5GMM-REGISTERED.LIMITED-SERVICE	133
5.1.3.2.1.4.6	5GMM-REGISTERED.PLMN-SEARCH	133
5.1.3.2.1.4.7	5GMM-REGISTERED.NO-CELL-AVAILABLE	133
5.1.3.2.1.4.8	5GMM-REGISTERED.UPDATE-NEEDED	133
5.1.3.2.2	5GS update status in the UE	134
5.1.3.2.3	5GMM sublayer states in the network side	134
5.1.3.2.3.1	General.....	134
5.1.3.2.3.2	5GMM-DEREGISTERED	135
5.1.3.2.3.3	5GMM-COMMON-PROCEDURE-INITIATED.....	135
5.1.3.2.3.4	5GMM-REGISTERED.....	135
5.1.3.2.3.5	5GMM-DEREGISTERED-INITIATED	135
5.1.4	Coordination between 5GMM and EMM.....	135
5.1.4.1	General	135
5.1.4.2	Coordination between 5GMM for 3GPP access and EMM with N26 interface	135
5.1.4.3	Coordination between 5GMM for 3GPP access and EMM without N26 interface	136
5.1.5	Coordination between 5GMM and GMM	136
5.2	Behaviour of the UE in state 5GMM-DEREGISTERED and state 5GMM-REGISTERED	136

5.2.1	General.....	136
5.2.2	UE behaviour in state 5GMM-DEREGISTERED	136
5.2.2.1	General.....	136
5.2.2.2	Primary substate selection.....	137
5.2.2.2.1	Selection of the substate after power on.....	137
5.2.2.3	Detailed description of UE behaviour in state 5GMM-DEREGISTERED.....	137
5.2.2.3.1	NORMAL-SERVICE.....	137
5.2.2.3.2	LIMITED-SERVICE.....	138
5.2.2.3.3	ATTEMPTING-REGISTRATION	138
5.2.2.3.4	PLMN-SEARCH.....	139
5.2.2.3.5	NO-SUPI.....	139
5.2.2.3.6	NO-CELL-AVAILABLE	139
5.2.2.3.7	eCALL-INACTIVE.....	139
5.2.2.3.8	INITIAL-REGISTRATION-NEEDED	139
5.2.2.4	Substate when back to state 5GMM-DEREGISTERED from another 5GMM state	139
5.2.3	UE behaviour in state 5GMM-REGISTERED	140
5.2.3.1	General.....	140
5.2.3.2	Detailed description of UE behaviour in state 5GMM-REGISTERED	140
5.2.3.2.1	NORMAL-SERVICE.....	140
5.2.3.2.2	NON-ALLOWED-SERVICE	140
5.2.3.2.3	ATTEMPTING-REGISTRATION-UPDATE	141
5.2.3.2.4	LIMITED-SERVICE.....	142
5.2.3.2.5	PLMN-SEARCH.....	142
5.2.3.2.6	NO-CELL-AVAILABLE	142
5.2.3.2.7	UPDATE-NEEDED	142
5.3	General on elementary 5GMM procedures	143
5.3.1	5GMM modes and N1 NAS signalling connection	143
5.3.1.1	Establishment of the N1 NAS signalling connection.....	143
5.3.1.2	Re-establishment of the N1 NAS signalling connection.....	144
5.3.1.3	Release of the N1 NAS signalling connection	145
5.3.1.4	5GMM-CONNECTED mode with RRC inactive indication.....	149
5.3.1.5	Suspend and resume of the N1 NAS signalling connection.....	152
5.3.2	Permanent identifiers.....	153
5.3.3	Temporary identities.....	156
5.3.4	Registration areas.....	157
5.3.5	Service area restrictions	158
5.3.5.1	General.....	158
5.3.5.2	3GPP access service area restrictions.....	158
5.3.5.3	Wireline access service area restrictions.....	162
5.3.6	Mobile initiated connection only mode	162
5.3.7	Handling of the periodic registration update timer and mobile reachable timer	164
5.3.8	Handling of timer T3502	166
5.3.9	Handling of NAS level mobility management congestion control	166
5.3.10	Handling of DNN based congestion control.....	167
5.3.11	Handling of S-NSSAI based congestion control.....	167
5.3.12	Handling of local emergency numbers	167
5.3.12A	Handling of local emergency numbers received via 3GPP access and non-3GPP access	169
5.3.12A.1	General.....	169
5.3.12A.2	Receiving a REGISTRATION ACCEPT message via non-3GPP access.....	169
5.3.13	Lists of 5GS forbidden tracking areas.....	170
5.3.13A	Forbidden PLMN lists	171
5.3.14	List of equivalent PLMNs.....	171
5.3.15	Transmission failure abnormal case in the UE	171
5.3.16	Extended DRX cycle for UEs in 5GMM-IDLE and 5GMM-CONNECTED mode with RRC inactive indication	171
5.3.17	Service Gap Control.....	172
5.3.18	Restriction on use of enhanced coverage.....	174
5.3.19	Handling of congestion control for transport of user data via the control plane.....	175
5.3.19a	Specific requirements for UE configured to use timer T3245	175
5.3.19a.1	UE not operating in SNPN access operation mode	175
5.3.19a.2	UE operating in SNPN access operation mode.....	175
5.3.20	Specific requirements for UE when receiving non-integrity protected reject messages.....	176

5.3.20.1	General	176
5.3.20.2	Requirements for UE in a PLMN.....	176
5.3.20.3	Requirements for UE in an SNPN.....	180
5.3.21	CIoT 5GS optimizations	184
5.3.22	Interaction between MICO mode with active time and extended idle mode DRX cycle	186
5.3.23	Forbidden wireline access area	186
5.3.24	WUS assistance	187
5.3.25	Paging Early Indication with Paging Subgrouping Assistance	187
5.4	5GMM common procedures.....	188
5.4.1	Primary authentication and key agreement procedure	188
5.4.1.1	General	188
5.4.1.2	EAP based primary authentication and key agreement procedure	188
5.4.1.2.1	General	188
5.4.1.2.2	EAP-AKA' related procedures.....	191
5.4.1.2.3	EAP-TLS related procedures.....	197
5.4.1.2.3A	Procedures related to EAP methods other than EAP-AKA' and EAP-TLS	202
5.4.1.2.3B	Procedures related to EAP methods used for primary authentication of an N5GC device.....	206
5.4.1.2.4	EAP message reliable transport procedure	207
5.4.1.2.4.3	EAP message reliable transport procedure accepted by the UE.....	208
5.4.1.2.5	EAP result message transport procedure	210
5.4.1.3	5G AKA based primary authentication and key agreement procedure	211
5.4.1.3.1	General	211
5.4.1.3.2	Authentication initiation by the network	212
5.4.1.3.3	Authentication response by the UE	212
5.4.1.3.4	Authentication completion by the network.....	213
5.4.1.3.5	Authentication not accepted by the network.....	214
5.4.1.3.6	Authentication not accepted by the UE	216
5.4.1.3.7	Abnormal cases	217
5.4.2	Security mode control procedure	221
5.4.2.1	General	221
5.4.2.2	NAS security mode control initiation by the network.....	221
5.4.2.3	NAS security mode command accepted by the UE.....	224
5.4.2.4	NAS security mode control completion by the network	227
5.4.2.5	NAS security mode command not accepted by the UE.....	227
5.4.2.6	Abnormal cases in the UE.....	227
5.4.2.7	Abnormal cases on the network side	228
5.4.3	Identification procedure.....	228
5.4.3.1	General	228
5.4.3.2	Identification initiation by the network.....	228
5.4.3.3	Identification response by the UE	229
5.4.3.4	Identification completion by the network	229
5.4.3.5	Abnormal cases in the UE.....	229
5.4.3.6	Abnormal cases on the network side.....	229
5.4.4	Generic UE configuration update procedure.....	230
5.4.4.1	General	230
5.4.4.2	Generic UE configuration update procedure initiated by the network	234
5.4.4.3	Generic UE configuration update accepted by the UE.....	238
5.4.4.4	Generic UE configuration update completion by the network.....	244
5.4.4.5	Abnormal cases in the UE.....	244
5.4.4.6	Abnormal cases on the network side.....	245
5.4.5	NAS transport procedure(s)	247
5.4.5.1	General	247
5.4.5.2	UE-initiated NAS transport procedure	247
5.4.5.2.1	General	247
5.4.5.2.2	UE-initiated NAS transport procedure initiation	248
5.4.5.2.3	UE-initiated NAS transport of messages accepted by the network	250
5.4.5.2.4	UE-initiated NAS transport of messages not accepted by the network	254
5.4.5.2.5	Abnormal cases on the network side	257
5.4.5.2.6	Abnormal cases in the UE	261
5.4.5.3	Network-initiated NAS transport procedure	263
5.4.5.3.1	General	263
5.4.5.3.2	Network-initiated NAS transport procedure initiation	264

5.4.5.3.3	Network-initiated NAS transport of messages	268
5.4.6	5GMM status procedure	273
5.4.6.1	General	273
5.4.6.2	5GMM status received in the UE	274
5.4.6.3	5GMM status received in the network	274
5.4.7	Network slice-specific authentication and authorization procedure	274
5.4.7.1	General	274
5.4.7.2	Network slice-specific EAP message reliable transport procedure	275
5.4.7.2.1	Network slice-specific EAP message reliable transport procedure initiation	275
5.4.7.2.2	Network slice-specific EAP message reliable transport procedure accepted by the UE	276
5.4.7.2.3	Abnormal cases on the network side	276
5.4.7.2.4	Abnormal cases in the UE	276
5.4.7.3	Network slice-specific EAP result message transport procedure	277
5.4.7.3.1	Network slice-specific EAP result message transport procedure initiation	277
5.5	5GMM specific procedures	277
5.5.1	Registration procedure	277
5.5.1.1	General	277
5.5.1.2	Registration procedure for initial registration	279
5.5.1.2.1	General	279
5.5.1.2.2	Initial registration initiation	279
5.5.1.2.3	5GMM common procedure initiation	287
5.5.1.2.4	Initial registration accepted by the network	287
5.5.1.2.5	Initial registration not accepted by the network	307
5.5.1.2.6	Initial registration for emergency services not accepted by the network	320
5.5.1.2.6A	Initial registration for initiating an emergency PDU session not accepted by the network	321
5.5.1.2.7	Abnormal cases in the UE	322
5.5.1.2.8	Abnormal cases on the network side	324
5.5.1.3	Registration procedure for mobility and periodic registration update	326
5.5.1.3.1	General	326
5.5.1.3.2	Mobility and periodic registration update initiation	327
5.5.1.3.3	5GMM common procedure initiation	339
5.5.1.3.4	Mobility and periodic registration update accepted by the network	340
5.5.1.3.5	Mobility and periodic registration update not accepted by the network	366
5.5.1.3.6	Mobility and periodic registration update for initiating an emergency PDU session not accepted by the network	379
5.5.1.3.6A	Mobility and periodic registration update for an emergency services fallback not accepted by the network	380
5.5.1.3.7	Abnormal cases in the UE	380
5.5.1.3.8	Abnormal cases on the network side	384
5.5.2	De-registration procedure	387
5.5.2.1	General	387
5.5.2.2	UE-initiated de-registration procedure	389
5.5.2.2.1	UE-initiated de-registration procedure initiation	389
5.5.2.2.2	UE-initiated de-registration procedure completion	390
5.5.2.2.3	UE-initiated de-registration procedure completion for 5GS services over 3GPP access	390
5.5.2.2.4	UE-initiated de-registration procedure completion for 5GS services over non-3GPP access	390
5.5.2.2.5	UE-initiated de-registration procedure completion for 5GS services over both 3GPP access and non-3GPP access	391
5.5.2.2.6	Abnormal cases in the UE	391
5.5.2.2.7	Abnormal cases in the network side	393
5.5.2.3	Network-initiated de-registration procedure	394
5.5.2.3.1	Network-initiated de-registration procedure initiation	394
5.5.2.3.2	Network-initiated de-registration procedure completion by the UE	395
5.5.2.3.3	Network-initiated de-registration procedure completion by the network	405
5.5.2.3.4	Abnormal cases in the UE	405
5.5.2.3.5	Abnormal cases in the network side	406
5.5.3	eCall inactivity procedure	407
5.5.4	Authentication and key agreement procedure for 5G ProSe UE-to-network relay	408
5.5.4.1	General	408
5.5.4.2	ProSe relay transaction identity (PRTI)	409
5.5.4.3	UE-initiated authentication and key agreement procedure initiation	409
5.5.4.4	UE-initiated authentication and key agreement procedure accepted by the network	410

5.5.4.5	UE-initiated authentication and key agreement procedure not accepted by the network.....	411
5.5.4.6	Abnormal cases in the UE.....	411
5.5.4.7	Abnormal cases on the network side.....	411
5.6	5GMM connection management procedures.....	412
5.6.1	Service request procedure.....	412
5.6.1.1	General.....	412
5.6.1.2	Service request procedure initiation.....	416
5.6.1.2.1	UE is not using 5GS services with control plane CIoT 5GS optimization.....	416
5.6.1.2.2	UE is using 5GS services with control plane CIoT 5GS optimization.....	418
5.6.1.3	Common procedure initiation.....	421
5.6.1.4	Service request procedure accepted by the network.....	421
5.6.1.4.1	UE is not using 5GS services with control plane CIoT 5GS optimization.....	421
5.6.1.4.2	UE is using 5GS services with control plane CIoT 5GS optimization.....	425
5.6.1.5	Service request procedure not accepted by the network.....	429
5.6.1.6	Service request procedure for initiating an emergency PDU session not accepted by the network....	441
5.6.1.6A	Service request procedure for an emergency services fallback not accepted by the network.....	441
5.6.1.7	Abnormal cases in the UE.....	441
5.6.1.8	Abnormal cases on the network side.....	446
5.6.2	Paging procedure.....	447
5.6.2.1	General.....	447
5.6.2.2	Paging for 5GS services.....	447
5.6.2.2.1	General.....	447
5.6.2.2.2	Abnormal cases on the network side.....	450
5.6.2.2.3	Abnormal cases in the UE.....	450
5.6.3	Notification procedure.....	450
5.6.3.1	General.....	450
5.6.3.2	Notification procedure initiation.....	451
5.6.3.3	Notification procedure completion.....	452
5.6.3.4	Abnormal cases on the network side.....	453
5.6.3.5	Abnormal cases on the UE side.....	453
6	Elementary procedures for 5GS session management.....	454
6.1	Overview.....	454
6.1.1	General.....	454
6.1.2	Types of 5GSM procedures.....	454
6.1.3	5GSM sublayer states.....	455
6.1.3.1	General.....	455
6.1.3.2	5GSM sublayer states in the UE.....	455
6.1.3.2.1	Overview.....	455
6.1.3.2.2	PDU SESSION INACTIVE.....	456
6.1.3.2.3	PDU SESSION ACTIVE PENDING.....	456
6.1.3.2.4	PDU SESSION ACTIVE.....	456
6.1.3.2.5	PDU SESSION INACTIVE PENDING.....	456
6.1.3.2.6	PDU SESSION MODIFICATION PENDING.....	456
6.1.3.2.7	PROCEDURE TRANSACTION INACTIVE.....	456
6.1.3.2.8	PROCEDURE TRANSACTION PENDING.....	456
6.1.3.3	5GSM sublayer states in the network side.....	457
6.1.3.3.1	Overview.....	457
6.1.3.3.2	PDU SESSION INACTIVE.....	457
6.1.3.3.3	PDU SESSION ACTIVE.....	457
6.1.3.3.4	PDU SESSION INACTIVE PENDING.....	457
6.1.3.3.5	PDU SESSION MODIFICATION PENDING.....	458
6.1.3.3.6	PROCEDURE TRANSACTION INACTIVE.....	458
6.1.3.3.7	PROCEDURE TRANSACTION PENDING.....	458
6.1.4	Coordination between 5GSM and ESM.....	458
6.1.4.1	Coordination between 5GSM and ESM with N26 interface.....	458
6.1.4.2	Coordination between 5GSM and ESM without N26 interface.....	471
6.1.4a	Coordination between 5GSM and SM.....	473
6.1.5	Coordination for interworking with ePDG connected to EPC.....	473
6.2	General on elementary 5GSM procedures.....	474
6.2.1	Principles of PTI handling for 5GSM procedures.....	474
6.2.2	PDU session types.....	476

6.2.3	PDU session management	476
6.2.4	IP address allocation	476
6.2.4.1	General	476
6.2.4.2	IP address allocation via NAS signalling	477
6.2.4.3	Additional RG related requirements for IP address allocation	478
6.2.4.4	Additional requirements of the UE acting as 5G ProSe layer-3 UE-to-network relay UE for IP address allocation	478
6.2.5	Quality of service	479
6.2.5.1	General	479
6.2.5.1.1	QoS rules	479
6.2.5.1.1.1	General	479
6.2.5.1.1.2	Signalled QoS rules	479
6.2.5.1.1.3	Derived QoS rules	480
6.2.5.1.1.4	QoS flow descriptions	481
6.2.5.1.2	Session-AMBR	481
6.2.5.1.2A	Void	481
6.2.5.1.3	UL user data packet matching	481
6.2.5.1.4	Reflective QoS	482
6.2.5.1.4.1	General	482
6.2.5.1.4.2	Derivation of packet filter for UL direction from DL user data packet	482
6.2.5.1.4.3	Creating a derived QoS rule by reflective QoS in the UE	484
6.2.5.1.4.4	Updating a derived QoS rule by reflective QoS in the UE	484
6.2.5.1.4.5	Deleting a derived QoS rule in the UE	485
6.2.5.1.4.6	Ignoring RQI in the UE	485
6.2.5.2	QoS in MA PDU session	485
6.2.6	Local area data network (LADN)	486
6.2.7	Handling of DNN based congestion control	487
6.2.8	Handling of S-NSSAI based congestion control	487
6.2.9	Interaction with upper layers	490
6.2.9.1	General	490
6.2.9.2	URSP	490
6.2.9.3	ProSeP	490
6.2.10	Handling of 3GPP PS data off	490
6.2.11	Multi-homed IPv6 PDU session	492
6.2.12	Handling of network rejection not due to congestion control	492
6.2.13	Handling of Small data rate control	494
6.2.14	Handling of Serving PLMN rate control	495
6.2.15	Handling of Reliable Data Service	496
6.2.16	Handling of header compression for control plane CIoT optimizations	496
6.2.17	Handling of edge computing enhancements	496
6.2.18	Support of redundant PDU sessions	497
6.3	Network-requested 5GSM procedures	498
6.3.1	PDU session authentication and authorization procedure	498
6.3.1.1	General	498
6.3.1.2	PDU EAP message reliable transport procedure	500
6.3.1.2.1	PDU EAP message reliable transport procedure initiation	500
6.3.1.2.2	PDU EAP message reliable transport procedure accepted by the UE	501
6.3.1.2.3	Abnormal cases on the network side	502
6.3.1.2.4	Abnormal cases in the UE	502
6.3.1.3	PDU EAP result message transport procedure	502
6.3.1.3.1	PDU EAP result message transport procedure initiation	502
6.3.1.3.2	Abnormal cases in the UE	503
6.3.1A	Service-level authentication and authorization procedure	503
6.3.1A.1	General	503
6.3.1A.2	Service-level authentication and authorization procedure initiation	504
6.3.1A.3	Service-level authentication and authorization procedure accepted by the UE	505
6.3.1A.4	Abnormal cases on the network side	505
6.3.1A.5	Abnormal cases in the UE	505
6.3.2	Network-requested PDU session modification procedure	505
6.3.2.1	General	505
6.3.2.2	Network-requested PDU session modification procedure initiation	506
6.3.2.3	Network-requested PDU session modification procedure accepted by the UE	511

6.3.2.4	Network-requested PDU session modification procedure not accepted by the UE.....	519
6.3.2.5	Abnormal cases on the network side	524
6.3.2.6	Abnormal cases in the UE	525
6.3.3	Network-requested PDU session release procedure	525
6.3.3.1	General	525
6.3.3.2	Network-requested PDU session release procedure initiation	525
6.3.3.3	Network-requested PDU session release procedure accepted by the UE	528
6.3.3.4	N1 SM delivery skipped.....	537
6.3.3.5	Abnormal cases on the network side	537
6.3.3.6	Abnormal cases in the UE	537
6.4	UE-requested 5GSM procedures.....	538
6.4.1	UE-requested PDU session establishment procedure	538
6.4.1.1	General	538
6.4.1.2	UE-requested PDU session establishment procedure initiation	538
6.4.1.3	UE-requested PDU session establishment procedure accepted by the network	548
6.4.1.4	UE-requested PDU session establishment procedure not accepted by the network.....	562
6.4.1.4.1	General	562
6.4.1.4.2	Handling of network rejection due to congestion control.....	565
6.4.1.4.3	Handling of network rejection not due to congestion control.....	572
6.4.1.5	Handling the maximum number of established PDU sessions.....	579
6.4.1.5A	Handling the maximum number of allowed active user-plane resources for PDU sessions of UEs in NB-N1 mode	581
6.4.1.6	Abnormal cases in the UE	581
6.4.1.7	Abnormal cases on the network side	583
6.4.2	UE-requested PDU session modification procedure.....	584
6.4.2.1	General	584
6.4.2.2	UE-requested PDU session modification procedure initiation.....	585
6.4.2.3	UE-requested PDU session modification procedure accepted by the network	590
6.4.2.4	UE-requested PDU session modification procedure not accepted by the network	590
6.4.2.4.1	General	590
6.4.2.4.2	Handling of network rejection due to congestion control.....	591
6.4.2.4.3	Handling of network rejection not due to congestion control.....	598
6.4.2.5	Abnormal cases in the UE	601
6.4.2.6	Abnormal cases on the network side	602
6.4.3	UE-requested PDU session release procedure	603
6.4.3.1	General	603
6.4.3.2	UE-requested PDU session release procedure initiation	603
6.4.3.3	UE-requested PDU session release procedure accepted by the network.....	604
6.4.3.4	UE-requested PDU session release procedure not accepted by the network.....	604
6.4.3.5	Abnormal cases in the UE	605
6.4.3.6	Abnormal cases on the network side	606
6.5	5GSM status procedure	606
6.5.1	General.....	606
6.5.2	5GSM status received in the UE	607
6.5.3	5GSM status received in the SMF	607
6.6	Miscellaneous procedures	607
6.6.1	Exchange of extended protocol configuration options.....	607
6.6.2	Remote UE report procedure	608
6.6.2.1	General	608
6.6.2.2	Remote UE report procedure initiation	608
6.6.2.3	Remote UE report procedure accepted by the network.....	609
6.6.2.4	Abnormal cases in the UE	609
6.6.2.5	Abnormal cases on the network side	609
7	Handling of unknown, unforeseen, and erroneous protocol data	610
7.1	General	610
7.2	Message too short or too long	610
7.2.1	Message too short	610
7.2.2	Message too long	610
7.3	Unknown or unforeseen procedure transaction identity or PDU Session identity.....	610
7.3.1	Procedure transaction identity.....	610
7.3.2	PDU Session identity.....	611

7.4	Unknown or unforeseen message type	612
7.5	Non-semantical mandatory information element errors	612
7.5.1	Common procedures	612
7.5.2	5GS mobility management	613
7.5.3	5GS session management	613
7.6	Unknown and unforeseen IEs in the non-imperative message part.....	614
7.6.1	IEs unknown in the message	614
7.6.2	Out of sequence IEs	614
7.6.3	Repeated IEs	614
7.7	Non-imperative message part errors.....	614
7.7.1	Syntactically incorrect optional IEs	614
7.7.2	Conditional IE errors	614
7.8	Messages with semantically incorrect contents	615
8	Message functional definitions and contents.....	615
8.1	Overview	615
8.2	5GS mobility management messages.....	615
8.2.1	Authentication request	615
8.2.1.1	Message definition	615
8.2.1.2	Authentication parameter RAND.....	615
8.2.1.3	Authentication parameter AUTN	616
8.2.1.4	Void.....	616
8.2.1.5	EAP message.....	616
8.2.2	Authentication response.....	616
8.2.2.1	Message definition	616
8.2.2.2	Authentication response parameter	616
8.2.2.3	EAP message.....	616
8.2.3	Authentication result.....	616
8.2.3.1	Message definition	616
8.2.3.2	ABBA	617
8.2.4	Authentication failure	617
8.2.4.1	Message definition	617
8.2.4.2	Authentication failure parameter.....	618
8.2.5	Authentication reject.....	618
8.2.5.1	Message definition	618
8.2.5.2	EAP message.....	618
8.2.6	Registration request	618
8.2.6.1	Message definition	618
8.2.6.2	Non-current native NAS key set identifier.....	621
8.2.6.3	5GMM capability.....	621
8.2.6.4	UE security capability.....	621
8.2.6.5	Requested NSSAI	621
8.2.6.6	Last visited registered TAI.....	621
8.2.6.7	S1 UE network capability	621
8.2.6.8	Uplink data status.....	622
8.2.6.9	PDU session status	622
8.2.6.10	MICO indication	622
8.2.6.11	UE status	622
8.2.6.12	Additional GUTI	622
8.2.6.13	Allowed PDU session status	622
8.2.6.14	UE's usage setting	622
8.2.6.15	Requested DRX parameters	622
8.2.6.16	EPS NAS message container.....	622
8.2.6.17	LADN indication.....	623
8.2.6.17A	Payload container type	623
8.2.6.18	Payload container.....	623
8.2.6.19	Network slicing indication	623
8.2.6.20	5GS update type	623
8.2.6.21	NAS message container	623
8.2.6.22	Requested extended DRX parameters.....	623
8.2.6.23	EPS bearer context status	623
8.2.6.24	T3324 value.....	623

8.2.6.25	Mobile station classmark 2.....	624
8.2.6.26	Supported codecs	624
8.2.6.27	UE radio capability ID	624
8.2.6.28	Requested mapped NSSAI.....	624
8.2.6.29	Additional information requested.....	624
8.2.6.30	Requested WUS assistance information.....	624
8.2.6.31	Void.....	624
8.2.6.32	N5GC indication	624
8.2.6.33	Requested NB-N1 mode DRX parameters.....	624
8.2.6.34	UE request type	624
8.2.6.35	Paging restriction	624
8.2.6.35	Service-level-AA container.....	624
8.2.6.36	NID	625
8.2.6.37	MS determined PLMN with disaster condition.....	625
8.2.6.38	Requested PEIPS assistance information	625
8.2.6.39	Requested T3512 value	625
8.2.7	Registration accept.....	625
8.2.7.1	Message definition	625
8.2.7.2	5G-GUTI.....	628
8.2.7.3	Equivalent PLMNs.....	628
8.2.7.4	TAI list	629
8.2.7.5	Allowed NSSAI	629
8.2.7.6	Rejected NSSAI	629
8.2.7.7	Configured NSSAI.....	629
8.2.7.8	5GS network feature support.....	629
8.2.7.9	PDU session status	629
8.2.7.10	PDU session reactivation result.....	629
8.2.7.11	PDU session reactivation result error cause	630
8.2.7.12	LADN information.....	630
8.2.7.13	MICO indication	630
8.2.7.14	Network slicing indication	630
8.2.7.15	Service area list	630
8.2.7.16	T3512 value.....	630
8.2.7.17	Non-3GPP de-registration timer value	630
8.2.7.18	T3502 value.....	630
8.2.7.19	Emergency number list	630
8.2.7.20	Extended emergency number list	630
8.2.7.21	SOR transparent container	630
8.2.7.22	EAP message.....	631
8.2.7.23	NSSAI inclusion mode.....	631
8.2.7.24	Operator-defined access category definitions	631
8.2.7.25	Negotiated DRX parameters	631
8.2.7.26	Non-3GPP NW policies	631
8.2.7.27	Negotiated extended DRX parameters	631
8.2.7.28	T3447 value.....	631
8.2.7.29	T3448 value.....	631
8.2.7.30	T3324 value.....	631
8.2.7.31	EPS bearer context status	631
8.2.7.32	UE radio capability ID	632
8.2.7.33	UE radio capability ID deletion indication.....	632
8.2.7.34	Pending NSSAI	632
8.2.7.35	Ciphering key data	632
8.2.7.36	CAG information list.....	632
8.2.7.37	Truncated 5G-S-TMSI configuration.....	632
8.2.7.38	Negotiated NB-N1 mode DRX parameters.....	632
8.2.7.39	Negotiated WUS assistance information.....	632
8.2.7.40	Extended rejected NSSAI	632
8.2.7.41	Service-level-AA container.....	633
8.2.7.42	Negotiated PEIPS assistance information	633
8.2.7.43	5GS additional request result	633
8.2.7.44	NSSRG information.....	633
8.2.7.45	Disaster roaming wait range.....	633

8.2.7.46	Disaster return wait range	633
8.2.7.47	List of PLMNs to be used in disaster condition	633
8.2.7.48	Forbidden TAI(s) for the list of "5GS forbidden tracking areas for roaming"	633
8.2.7.49	Forbidden TAI(s) for the list of "5GS forbidden tracking areas for regional provision of service"	633
8.2.7.50	Extended CAG information list.....	633
8.2.7.51	NSAG information	633
8.2.8	Registration complete	634
8.2.8.1	Message definition	634
8.2.8.2	SOR transparent container	634
8.2.9	Registration reject.....	634
8.2.9.1	Message definition	634
8.2.9.2	T3346 value.....	635
8.2.9.3	T3502 value.....	635
8.2.9.4	EAP message.....	635
8.2.9.5	Rejected NSSAI	635
8.2.9.6	CAG information list.....	636
8.2.9.7	Extended rejected NSSAI	636
8.2.9.8	Disaster return wait range	636
8.2.9.9	Extended CAG information list.....	636
8.2.9.10	Lower bound timer value	636
8.2.9.11	Forbidden TAI(s) for the list of "5GS forbidden tracking areas for roaming"	636
8.2.9.12	Forbidden TAI(s) for the list of "5GS forbidden tracking areas for regional provision of service"	636
8.2.10	UL NAS transport.....	636
8.2.10.1	Message definition	636
8.2.10.2	PDU session ID	637
8.2.10.3	Old PDU session ID	637
8.2.10.4	Request type	637
8.2.10.5	S-NSSAI	637
8.2.10.6	DNN	637
8.2.10.7	Additional information	638
8.2.10.8	MA PDU session information	638
8.2.10.9	Release assistance indication	638
8.2.11	DL NAS transport.....	638
8.2.11.1	Message definition	638
8.2.11.2	PDU session ID	639
8.2.11.3	Additional information.....	639
8.2.11.4	5GMM cause.....	639
8.2.11.5	Back-off timer value	639
8.2.11.6	Lower bound timer value	639
8.2.12	De-registration request (UE originating de-registration)	639
8.2.12.1	Message definition	639
8.2.13	De-registration accept (UE originating de-registration).....	640
8.2.13.1	Message definition	640
8.2.14	De-registration request (UE terminated de-registration).....	640
8.2.14.1	Message definition	640
8.2.14.2	5GMM cause.....	641
8.2.14.3	T3346 value.....	641
8.2.14.4	Rejected NSSAI	641
8.2.14.5	CAG information list.....	641
8.2.14.6	Extended rejected NSSAI	642
8.2.14.7	Disaster return wait range	642
8.2.14.7A	Extended CAG information list.....	642
8.2.14.8	Lower bound timer value	642
8.2.14.9	Forbidden TAI(s) for the list of "5GS forbidden tracking areas for roaming"	642
8.2.14.10	Forbidden TAI(s) for the list of "5GS forbidden tracking areas for regional provision of service"	642
8.2.15	De-registration accept (UE terminated de-registration).....	642
8.2.15.1	Message definition	642
8.2.16	Service request.....	643
8.2.16.1	Message definition	643
8.2.16.2	Uplink data status.....	643
8.2.16.3	PDU session status	643
8.2.16.4	Allowed PDU session status	643