

ETSI TS 124 501 V16.13.0 (2023-07)



**5G;
Non-Access-Stratum (NAS) protocol for 5G System (5GS);
Stage 3
(3GPP TS 24.501 version 16.13.0 Release 16)**

[ETSI TS 124 501 V16.13.0 \(2023-07\)](https://standards.iteh.ai/catalog/standards/sist/c577fb28-0f2c-4757-b8ab-9e57b8beb0b3/etsi-ts-124-501-v16-13-0-2023-07)

<https://standards.iteh.ai/catalog/standards/sist/c577fb28-0f2c-4757-b8ab-9e57b8beb0b3/etsi-ts-124-501-v16-13-0-2023-07>



ReferenceRTS/TSGC-0124501vgd0

Keywords5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://standards-portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	22
1 Scope	24
2 References	24
3 Definitions and abbreviations.....	28
3.1 Definitions	28
3.2 Abbreviations	35
4 General	38
4.1 Overview	38
4.2 Coordination between the protocols for 5GS mobility management and 5GS session management	38
4.3 UE domain selection	39
4.3.1 UE's usage setting	39
4.3.2 Domain selection for UE originating sessions / calls.....	39
4.3.3 Change of UE's usage setting.....	41
4.3.4 Change or determination of IMS voice availability	41
4.4 NAS security	42
4.4.1 General.....	42
4.4.2 Handling of 5G NAS security contexts.....	42
4.4.2.1 General	42
4.4.2.2 Establishment of a mapped 5G NAS security context during inter-system change from S1 mode to N1 mode in 5GMM-CONNECTED mode.....	45
4.4.2.3 Establishment of a 5G NAS security context during N1 mode to N1 mode handover	46
4.4.2.4 Establishment of an EPS security context during inter-system change from N1 mode to S1 mode in 5GMM-CONNECTED mode	47
4.4.2.5 Establishment of secure exchange of NAS messages	47
4.4.2.6 Change of security keys	49
4.4.3 Handling of NAS COUNT and NAS sequence number	49
4.4.3.1 General	49
4.4.3.2 Replay protection	51
4.4.3.3 Integrity protection and verification.....	51
4.4.3.4 Ciphering and deciphering	51
4.4.3.5 NAS COUNT wrap around	52
4.4.4 Integrity protection of NAS signalling messages.....	52
4.4.4.1 General	52
4.4.4.2 Integrity checking of NAS signalling messages in the UE	53
4.4.4.3 Integrity checking of NAS signalling messages in the AMF	53
4.4.5 Ciphering of NAS signalling messages	55
4.4.6 Protection of initial NAS signalling messages.....	55
4.5 Unified access control	57
4.5.1 General.....	57
4.5.2 Determination of the access identities and access category associated with a request for access for UEs not operating in SNPN access mode	59
4.5.2A Determination of the access identities and access category associated with a request for access for UEs operating in SNPN access mode	65
4.5.3 Operator-defined access categories.....	69
4.5.4 Access control and checking.....	71
4.5.4.1 Access control and checking in 5GMM-IDLE mode and in 5GMM-IDLE mode with suspend indication.....	71
4.5.4.2 Access control and checking in 5GMM-CONNECTED mode and in 5GMM-CONNECTED mode with RRC inactive indication	73
4.5.5 Exception handling and avoiding double barring	75
4.5.6 Mapping between access categories/access identities and RRC establishment cause	79

4.6	Network slicing	80
4.6.1	General.....	80
4.6.2	Mobility management aspects.....	81
4.6.2.1	General	81
4.6.2.2	NSSAI storage.....	82
4.6.2.3	Provision of NSSAI to lower layers in 5GMM-IDLE mode.....	85
4.6.2.4	Network slice-specific authentication and authorization.....	86
4.6.3	Session management aspects	88
4.7	NAS over non-3GPP access	88
4.7.1	General.....	88
4.7.2	5GS mobility management aspects.....	88
4.7.2.1	General	88
4.7.2.2	Establishment cause for non-3GPP access.....	89
4.7.3	5GS session management aspects.....	89
4.7.4	Limited service state over non-3GPP access	90
4.7.5	NAS signalling using trusted WLAN access network.....	90
4.8	Interworking with E-UTRAN connected to EPC	91
4.8.1	General.....	91
4.8.2	Single-registration mode.....	91
4.8.2.1	General	91
4.8.2.2	Single-registration mode with N26 interface	91
4.8.2.3	Single-registration mode without N26 interface	91
4.8.2.3.1	Interworking between NG-RAN and E-UTRAN	91
4.8.2.3.2	Interworking between TNGF or N3IWF connected to 5GCN and E-UTRAN.....	93
4.8.3	Dual-registration mode	94
4.8.4	Core Network selection for UEs not using CIoT 5GS optimizations	95
4.8.4A	Core Network selection and redirection for UEs using CIoT optimizations.....	95
4.8.4A.1	Core network selection.....	95
4.8.4A.2	Redirection of the UE by the core network.....	96
4.9	Disabling and re-enabling of UE's N1 mode capability	96
4.9.1	General.....	96
4.9.2	Disabling and re-enabling of UE's N1 mode capability for 3GPP access.....	96
4.9.3	Disabling and re-enabling of UE's N1 mode capability for non-3GPP access.....	99
4.10	Interworking with ePDG connected to EPC	99
4.11	UE configuration parameter updates	99
4.12	Access traffic steering, switching and splitting (ATSSS).....	100
4.13	Support of NAS signalling using wireline access network.....	100
4.14	Non-public network.....	101
4.14.1	General.....	101
4.14.2	Stand-alone non-public network	101
4.14.3	Public network integrated non-public network (PNI-NPN).....	102
4.15	Time sensitive communication.....	103
4.15.1	General.....	103
4.15.2	Integration with TSN network	103
4.15.2.1	General	103
4.15.2.2	Time synchronization.....	103
4.15.2.3	TSN bridge management.....	103
4.16	UE radio capability signalling optimisation	103
4.17	5GS mobility management in NB-N1 mode	105
4.18	5GS session management in NB-N1 mode	105
4.19	5GS mobility management in WB-N1 mode for IoT	105
4.20	5GS session management in WB-N1 mode for IoT	106
5	Elementary procedures for 5GS mobility management	106
5.1	Overview	106
5.1.1	General.....	106
5.1.2	Types of 5GMM procedures.....	106
5.1.3	5GMM sublayer states	108
5.1.3.1	General	108
5.1.3.2	5GMM sublayer states	108
5.1.3.2.1	5GMM sublayer states in the UE.....	108
5.1.3.2.1.1	General.....	108

5.1.3.2.1	Main states	108
5.1.3.2.1.2.1	5GMM-NULL	108
5.1.3.2.1.2.2	5GMM-DEREGISTERED	109
5.1.3.2.1.2.3	5GMM-REGISTERED-INITIATED	109
5.1.3.2.1.2.4	5GMM-REGISTERED	109
5.1.3.2.1.2.5	5GMM-DEREGISTERED-INITIATED	109
5.1.3.2.1.2.6	5GMM-SERVICE-REQUEST-INITIATED	109
5.1.3.2.1.3	Substates of state 5GMM-DEREGISTERED	109
5.1.3.2.1.3.1	General	109
5.1.3.2.1.3.2	5GMM-DEREGISTERED.NORMAL-SERVICE	109
5.1.3.2.1.3.3	5GMM-DEREGISTERED.LIMITED-SERVICE	109
5.1.3.2.1.3.4	5GMM-DEREGISTERED.ATTEMPTING-REGISTRATION	110
5.1.3.2.1.3.5	5GMM-DEREGISTERED.PLMN-SEARCH	110
5.1.3.2.1.3.6	5GMM-DEREGISTERED.NO-SUPI	110
5.1.3.2.1.3.7	5GMM-DEREGISTERED.NO-CELL-AVAILABLE	110
5.1.3.2.1.3.8	5GMM-DEREGISTERED.eCALL-INACTIVE	110
5.1.3.2.1.3.9	5GMM-DEREGISTERED.INITIAL-REGISTRATION-NEEDED	110
5.1.3.2.1.4	Substates of state 5GMM-REGISTERED	110
5.1.3.2.1.4.1	General	110
5.1.3.2.1.4.2	5GMM-REGISTERED.NORMAL-SERVICE	111
5.1.3.2.1.4.3	5GMM-REGISTERED.NON-ALLOWED-SERVICE	111
5.1.3.2.1.4.4	5GMM-REGISTERED.ATTEMPTING-REGISTRATION-UPDATE	111
5.1.3.2.1.4.5	5GMM-REGISTERED.LIMITED-SERVICE	111
5.1.3.2.1.4.6	5GMM-REGISTERED.PLMN-SEARCH	111
5.1.3.2.1.4.7	5GMM-REGISTERED.NO-CELL-AVAILABLE	111
5.1.3.2.1.4.8	5GMM-REGISTERED.UPDATE-NEEDED	111
5.1.3.2.2	5GS update status in the UE	112
5.1.3.2.3	5GMM sublayer states in the network side	112
5.1.3.2.3.1	General	112
5.1.3.2.3.2	5GMM-DEREGISTERED	113
5.1.3.2.3.3	5GMM-COMMON-PROCEDURE-INITIATED	113
5.1.3.2.3.4	5GMM-REGISTERED	113
5.1.3.2.3.5	5GMM-DEREGISTERED-INITIATED	113
5.1.4	Coordination between 5GMM and EMM	113
5.1.4.1	General	113
5.1.4.2	Coordination between 5GMM for 3GPP access and EMM with N26 interface	114
5.1.4.3	Coordination between 5GMM for 3GPP access and EMM without N26 interface	114
5.1.5	Coordination between 5GMM and GMM	114
5.2	Behaviour of the UE in state 5GMM-DEREGISTERED and state 5GMM-REGISTERED	115
5.2.1	General	115
5.2.2	UE behaviour in state 5GMM-DEREGISTERED	115
5.2.2.1	General	115
5.2.2.2	Primary substate selection	115
5.2.2.2.1	Selection of the substate after power on	115
5.2.2.3	Detailed description of UE behaviour in state 5GMM-DEREGISTERED	115
5.2.2.3.1	NORMAL-SERVICE	115
5.2.2.3.2	LIMITED-SERVICE	116
5.2.2.3.3	ATTEMPTING-REGISTRATION	116
5.2.2.3.4	PLMN-SEARCH	117
5.2.2.3.5	NO-SUPI	117
5.2.2.3.6	NO-CELL-AVAILABLE	117
5.2.2.3.7	eCALL-INACTIVE	117
5.2.2.3.8	INITIAL-REGISTRATION-NEEDED	117
5.2.2.4	Substate when back to state 5GMM-DEREGISTERED from another 5GMM state	117
5.2.3	UE behaviour in state 5GMM-REGISTERED	118
5.2.3.1	General	118
5.2.3.2	Detailed description of UE behaviour in state 5GMM-REGISTERED	118
5.2.3.2.1	NORMAL-SERVICE	118
5.2.3.2.2	NON-ALLOWED-SERVICE	118
5.2.3.2.3	ATTEMPTING-REGISTRATION-UPDATE	118
5.2.3.2.4	LIMITED-SERVICE	119
5.2.3.2.5	PLMN-SEARCH	120

5.2.3.2.6	NO-CELL-AVAILABLE	120
5.2.3.2.7	UPDATE-NEEDED	120
5.3	General on elementary 5GMM procedures	120
5.3.1	5GMM modes and N1 NAS signalling connection	120
5.3.1.1	Establishment of the N1 NAS signalling connection	120
5.3.1.2	Re-establishment of the N1 NAS signalling connection	122
5.3.1.3	Release of the N1 NAS signalling connection	123
5.3.1.4	5GMM-CONNECTED mode with RRC inactive indication	126
5.3.1.5	Suspend and resume of the N1 NAS signalling connection	128
5.3.2	Permanent identifiers	129
5.3.3	Temporary identities	131
5.3.4	Registration areas	132
5.3.5	Service area restrictions	133
5.3.5.1	General	133
5.3.5.2	3GPP access service area restrictions	133
5.3.5.3	Wireline access service area restrictions	136
5.3.6	Mobile initiated connection only mode	136
5.3.7	Handling of the periodic registration update timer and mobile reachable timer	138
5.3.8	Handling of timer T3502	140
5.3.9	Handling of NAS level mobility management congestion control	140
5.3.10	Handling of DNN based congestion control	141
5.3.11	Handling of S-NSSAI based congestion control	141
5.3.12	Handling of local emergency numbers	141
5.3.12A	Handling of local emergency numbers received via 3GPP access and non-3GPP access	142
5.3.12A.1	General	142
5.3.12A.2	Receiving a REGISTRATION ACCEPT message via non-3GPP access	143
5.3.13	Lists of 5GS forbidden tracking areas	143
5.3.13A	Forbidden PLMN lists	144
5.3.14	List of equivalent PLMNs	144
5.3.15	Transmission failure abnormal case in the UE	144
5.3.16	Extended DRX cycle for UEs in 5GMM-IDLE	144
5.3.17	Service Gap Control	145
5.3.18	Restriction on use of enhanced coverage	147
5.3.19	Handling of congestion control for transport of user data via the control plane	148
5.3.19a	Specific requirements for UE configured to use timer T3245	148
5.3.19a.1	UE not operating in SNPN access operation mode	148
5.3.19a.2	UE operating in SNPN access operation mode	149
5.3.20	Specific requirements for UE when receiving non-integrity protected reject messages	149
5.3.20.1	General	149
5.3.20.2	Requirements for UE in a PLMN	149
5.3.20.3	Requirements for UE in an SNPN	153
5.3.21	CIoT 5GS optimizations	156
5.3.22	Interaction between MICO mode with active time and extended idle mode DRX cycle	159
5.3.23	Forbidden wireline access area	159
5.3.24	WUS assistance	159
5.4	5GMM common procedures	160
5.4.1	Primary authentication and key agreement procedure	160
5.4.1.1	General	160
5.4.1.2	EAP based primary authentication and key agreement procedure	160
5.4.1.2.1	General	160
5.4.1.2.2	EAP-AKA' related procedures	163
5.4.1.2.2.1	General	163
5.4.1.2.2.2	Initiation	163
5.4.1.2.2.3	UE successfully authenticates network	163
5.4.1.2.2.4	Errors when handling EAP-request/AKA'-challenge message	164
5.4.1.2.2.5	Network successfully authenticates UE	164
5.4.1.2.2.6	UE handling EAP-AKA' notification message	164
5.4.1.2.2.6A	EAP based Identification initiation by the network	164
5.4.1.2.2.6B	EAP based Identification response by the UE	165
5.4.1.2.2.7	Network sending EAP-success message	165
5.4.1.2.2.8	UE handling EAP-success message	165
5.4.1.2.2.9	Network not successfully authenticates UE	165

5.4.1.2.2.10	Network sending EAP-failure message	165
5.4.1.2.2.11	UE handling EAP-failure message	166
5.4.1.2.2.12	Abnormal cases in the UE.....	168
5.4.1.2.3	EAP-TLS related procedures.....	168
5.4.1.2.3.1	General.....	168
5.4.1.2.3A	Procedures related to EAP methods other than EAP-AKA' and EAP-TLS	171
5.4.1.2.3A.1	General.....	171
5.4.1.2.3B	Procedures related to EAP methods used for primary authentication of an N5GC device.....	173
5.4.1.2.3B.1	General.....	173
5.4.1.2.4	EAP message reliable transport procedure	174
5.4.1.2.4.1	General.....	174
5.4.1.2.4.2	EAP message reliable transport procedure initiation by the network	174
5.4.1.2.4.3	EAP message reliable transport procedure accepted by the UE.....	175
5.4.1.2.4.4	Abnormal cases on the network side.....	175
5.4.1.2.4.5	Abnormal cases in the UE.....	175
5.4.1.2.5	EAP result message transport procedure	177
5.4.1.2.5.1	General.....	177
5.4.1.2.5.2	EAP result message transport procedure initiation by the network	178
5.4.1.3	5G AKA based primary authentication and key agreement procedure	178
5.4.1.3.1	General	178
5.4.1.3.2	Authentication initiation by the network	179
5.4.1.3.3	Authentication response by the UE	179
5.4.1.3.4	Authentication completion by the network.....	180
5.4.1.3.5	Authentication not accepted by the network.....	180
5.4.1.3.6	Authentication not accepted by the UE	182
5.4.1.3.7	Abnormal cases	183
5.4.2	Security mode control procedure	187
5.4.2.1	General	187
5.4.2.2	NAS security mode control initiation by the network.....	187
5.4.2.3	NAS security mode command accepted by the UE.....	190
5.4.2.4	NAS security mode control completion by the network	192
5.4.2.5	NAS security mode command not accepted by the UE.....	193
5.4.2.6	Abnormal cases in the UE.....	193
5.4.2.7	Abnormal cases on the network side	193
5.4.3	Identification procedure	194
5.4.3.1	General	194
5.4.3.2	Identification initiation by the network.....	194
5.4.3.3	Identification response by the UE	194
5.4.3.4	Identification completion by the network	194
5.4.3.5	Abnormal cases in the UE.....	195
5.4.3.6	Abnormal cases on the network side	195
5.4.4	Generic UE configuration update procedure.....	196
5.4.4.1	General	196
5.4.4.2	Generic UE configuration update procedure initiated by the network	198
5.4.4.3	Generic UE configuration update accepted by the UE.....	200
5.4.4.4	Generic UE configuration update completion by the network	203
5.4.4.5	Abnormal cases in the UE.....	204
5.4.4.6	Abnormal cases on the network side	205
5.4.5	NAS transport procedure(s)	206
5.4.5.1	General	206
5.4.5.2	UE-initiated NAS transport procedure	206
5.4.5.2.1	General	206
5.4.5.2.2	UE-initiated NAS transport procedure initiation	207
5.4.5.2.3	UE-initiated NAS transport of messages accepted by the network	209
5.4.5.2.4	UE-initiated NAS transport of messages not accepted by the network	213
5.4.5.2.5	Abnormal cases on the network side	215
5.4.5.2.6	Abnormal cases in the UE	219
5.4.5.3	Network-initiated NAS transport procedure	221
5.4.5.3.1	General	221
5.4.5.3.2	Network-initiated NAS transport procedure initiation	222
5.4.5.3.3	Network-initiated NAS transport of messages	226
5.4.6	5GMM status procedure	229

5.4.6.1	General	229
5.4.6.2	5GMM status received in the UE	229
5.4.6.3	5GMM status received in the network	230
5.4.7	Network slice-specific authentication and authorization procedure	230
5.4.7.1	General	230
5.4.7.2	Network slice-specific EAP message reliable transport procedure	231
5.4.7.2.1	Network slice-specific EAP message reliable transport procedure initiation	231
5.4.7.2.2	Network slice-specific EAP message reliable transport procedure accepted by the UE	232
5.4.7.2.3	Abnormal cases on the network side	232
5.4.7.2.4	Abnormal cases in the UE	232
5.4.7.3	Network slice-specific EAP result message transport procedure	233
5.4.7.3.1	Network slice-specific EAP result message transport procedure initiation	233
5.5	5GMM specific procedures	233
5.5.1	Registration procedure	233
5.5.1.1	General	233
5.5.1.2	Registration procedure for initial registration	234
5.5.1.2.1	General	234
5.5.1.2.2	Initial registration initiation	235
5.5.1.2.3	5GMM common procedure initiation	240
5.5.1.2.4	Initial registration accepted by the network	240
5.5.1.2.5	Initial registration not accepted by the network	253
5.5.1.2.6	Initial registration for emergency services not accepted by the network	262
5.5.1.2.6A	Initial registration for initiating an emergency PDU session not accepted by the network	263
5.5.1.2.7	Abnormal cases in the UE	263
5.5.1.2.8	Abnormal cases on the network side	266
5.5.1.3	Registration procedure for mobility and periodic registration update	268
5.5.1.3.1	General	268
5.5.1.3.2	Mobility and periodic registration update initiation	268
5.5.1.3.3	5GMM common procedure initiation	276
5.5.1.3.4	Mobility and periodic registration update accepted by the network	277
5.5.1.3.5	Mobility and periodic registration update not accepted by the network	295
5.5.1.3.6	Mobility and periodic registration update for initiating an emergency PDU session not accepted by the network	305
5.5.1.3.7	Abnormal cases in the UE	305
5.5.1.3.8	Abnormal cases on the network side	309
5.5.2	De-registration procedure	311
5.5.2.1	General	311
5.5.2.2	UE-initiated de-registration procedure	312
5.5.2.2.1	UE-initiated de-registration procedure initiation	312
5.5.2.2.2	UE-initiated de-registration procedure completion	313
5.5.2.2.3	UE-initiated de-registration procedure completion for 5GS services over 3GPP access	313
5.5.2.2.4	UE-initiated de-registration procedure completion for 5GS services non-3GPP access	314
5.5.2.2.5	UE-initiated de-registration procedure completion for 5GS services over both 3GPP access and non-3GPP access	314
5.5.2.2.6	Abnormal cases in the UE	314
5.5.2.2.7	Abnormal cases in the network side	316
5.5.2.3	Network-initiated de-registration procedure	317
5.5.2.3.1	Network-initiated de-registration procedure initiation	317
5.5.2.3.2	Network-initiated de-registration procedure completion by the UE	317
5.5.2.3.3	Network-initiated de-registration procedure completion by the network	324
5.5.2.3.4	Abnormal cases in the UE	324
5.5.2.3.5	Abnormal cases in the network side	324
5.5.3	eCall inactivity procedure	325
5.6	5GMM connection management procedures	326
5.6.1	Service request procedure	326
5.6.1.1	General	326
5.6.1.2	Service request procedure initiation	329
5.6.1.2.1	UE is not using 5GS services with control plane CIoT 5GS optimization	329
5.6.1.2.2	UE is using 5GS services with control plane CIoT 5GS optimization	332
5.6.1.3	Common procedure initiation	334
5.6.1.4	Service request procedure accepted by the network	334
5.6.1.4.1	UE is not using 5GS services with control plane CIoT 5GS optimization	334

5.6.1.4.2	UE is using 5GS services with control plane CIoT 5GS optimization	336
5.6.1.5	Service request procedure not accepted by the network.....	339
5.6.1.6	Service request procedure for initiating an emergency PDU session not accepted by the network	348
5.6.1.7	Abnormal cases in the UE	349
5.6.1.8	Abnormal cases on the network side	352
5.6.2	Paging procedure	354
5.6.2.1	General	354
5.6.2.2	Paging for 5GS services	354
5.6.2.2.1	General	354
5.6.2.2.2	Abnormal cases on the network side	355
5.6.2.2.3	Abnormal cases in the UE	355
5.6.3	Notification procedure	356
5.6.3.1	General	356
5.6.3.2	Notification procedure initiation	356
5.6.3.3	Notification procedure completion.....	357
5.6.3.4	Abnormal cases on the network side	358
5.6.3.5	Abnormal cases on the UE side.....	358
6	Elementary procedures for 5GS session management	359
6.1	Overview	359
6.1.1	General.....	359
6.1.2	Types of 5GSM procedures	359
6.1.3	5GSM sublayer states	360
6.1.3.1	General	360
6.1.3.2	5GSM sublayer states in the UE	360
6.1.3.2.1	Overview	360
6.1.3.2.2	PDU SESSION INACTIVE	360
6.1.3.2.3	PDU SESSION ACTIVE PENDING	361
6.1.3.2.4	PDU SESSION ACTIVE	361
6.1.3.2.5	PDU SESSION INACTIVE PENDING	361
6.1.3.2.6	PDU SESSION MODIFICATION PENDING	361
6.1.3.2.7	PROCEDURE TRANSACTION INACTIVE.....	361
6.1.3.2.8	PROCEDURE TRANSACTION PENDING	361
6.1.3.3	5GSM sublayer states in the network side	361
6.1.3.3.1	Overview	361
6.1.3.3.2	PDU SESSION INACTIVE	362
6.1.3.3.3	PDU SESSION ACTIVE	362
6.1.3.3.4	PDU SESSION INACTIVE PENDING.....	362
6.1.3.3.5	PDU SESSION MODIFICATION PENDING	362
6.1.3.3.6	PROCEDURE TRANSACTION INACTIVE.....	362
6.1.3.3.7	PROCEDURE TRANSACTION PENDING	362
6.1.4	Coordination between 5GSM and ESM.....	363
6.1.4.1	Coordination between 5GSM and ESM with N26 interface	363
6.1.4.2	Coordination between 5GSM and ESM without N26 interface	374
6.1.4a	Coordination between 5GSM and SM.....	377
6.1.5	Coordination for interworking with ePDG connected to EPC	377
6.2	General on elementary 5GSM procedures.....	377
6.2.1	Principles of PTI handling for 5GSM procedures.....	377
6.2.2	PDU session types	379
6.2.3	PDU session management	379
6.2.4	IP address allocation	379
6.2.4.1	General	379
6.2.4.2	IP address allocation via NAS signalling	380
6.2.4.3	Additional RG related requirements for IP address allocation.....	381
6.2.5	Quality of service.....	381
6.2.5.1	General	381
6.2.5.1.1	QoS rules	381
6.2.5.1.1.1	General.....	381
6.2.5.1.1.2	Signalled QoS rules	382
6.2.5.1.1.3	Derived QoS rules.....	383
6.2.5.1.1.4	QoS flow descriptions.....	383
6.2.5.1.2	Session-AMBR.....	384

6.2.5.1.2A	Void.....	384
6.2.5.1.3	UL user data packet matching	384
6.2.5.1.4	Reflective QoS.....	385
6.2.5.1.4.1	General.....	385
6.2.5.1.4.2	Derivation of packet filter for UL direction from DL user data packet	385
6.2.5.1.4.3	Creating a derived QoS rule by reflective QoS in the UE.....	386
6.2.5.1.4.4	Updating a derived QoS rule by reflective QoS in the UE	387
6.2.5.1.4.5	Deleting a derived QoS rule in the UE	387
6.2.5.1.4.6	Ignoring RQI in the UE.....	387
6.2.5.2	QoS in MA PDU session.....	387
6.2.6	Local area data network (LADN)	388
6.2.7	Handling of DNN based congestion control	389
6.2.8	Handling of S-NSSAI based congestion control.....	389
6.2.9	Interaction with upper layers	391
6.2.9.1	General	391
6.2.9.2	URSP.....	391
6.2.10	Handling of 3GPP PS data off	391
6.2.11	Multi-homed IPv6 PDU session	392
6.2.12	Handling of network rejection not due to congestion control.....	392
6.2.13	Handling of Small data rate control	393
6.2.14	Handling of Serving PLMN rate control.....	394
6.2.15	Handling of Reliable Data Service	395
6.2.16	Handling of header compression for control plane CIoT optimizations	395
6.3	Network-requested 5GSM procedures	395
6.3.1	PDU session authentication and authorization procedure.....	395
6.3.1.1	General	395
6.3.1.2	PDU EAP message reliable transport procedure.....	397
6.3.1.2.1	PDU EAP message reliable transport procedure initiation.....	397
6.3.1.2.2	PDU EAP message reliable transport procedure accepted by the UE	398
6.3.1.2.3	Abnormal cases on the network side	398
6.3.1.2.4	Abnormal cases in the UE	399
6.3.1.3	PDU EAP result message transport procedure.....	399
6.3.1.3.1	PDU EAP result message transport procedure initiation.....	399
6.3.2	Network-requested PDU session modification procedure	399
6.3.2.1	General	399
6.3.2.2	Network-requested PDU session modification procedure initiation	399
6.3.2.3	Network-requested PDU session modification procedure accepted by the UE.....	402
6.3.2.4	Network-requested PDU session modification procedure not accepted by the UE.....	408
6.3.2.5	Abnormal cases on the network side	412
6.3.2.6	Abnormal cases in the UE.....	413
6.3.3	Network-requested PDU session release procedure	413
6.3.3.1	General	413
6.3.3.2	Network-requested PDU session release procedure initiation	413
6.3.3.3	Network-requested PDU session release procedure accepted by the UE.....	415
6.3.3.4	N1 SM delivery skipped.....	422
6.3.3.5	Abnormal cases on the network side	422
6.3.3.6	Abnormal cases in the UE.....	423
6.4	UE-requested 5GSM procedures.....	423
6.4.1	UE-requested PDU session establishment procedure	423
6.4.1.1	General	423
6.4.1.2	UE-requested PDU session establishment procedure initiation	424
6.4.1.3	UE-requested PDU session establishment procedure accepted by the network	430
6.4.1.4	UE requested PDU session establishment procedure not accepted by the network	439
6.4.1.4.1	General	439
6.4.1.4.2	Handling of network rejection due to congestion control.....	442
6.4.1.4.3	Handling of network rejection not due to congestion control.....	448
6.4.1.5	Handling the maximum number of established PDU sessions.....	453
6.4.1.5A	Handling the maximum number of allowed active user-plane resources for PDU sessions of UEs in NB-N1 mode	454
6.4.1.6	Abnormal cases in the UE.....	454
6.4.1.7	Abnormal cases on the network side.....	455
6.4.2	UE-requested PDU session modification procedure.....	456

6.4.2.1	General	456
6.4.2.2	UE-requested PDU session modification procedure initiation	457
6.4.2.3	UE-requested PDU session modification procedure accepted by the network	460
6.4.2.4	UE-requested PDU session modification procedure not accepted by the network	460
6.4.2.4.1	General	460
6.4.2.4.2	Handling of network rejection due to congestion control	461
6.4.2.4.3	Handling of network rejection not due to congestion control	467
6.4.2.5	Abnormal cases in the UE	470
6.4.2.6	Abnormal cases on the network side	471
6.4.3	UE-requested PDU session release procedure	472
6.4.3.1	General	472
6.4.3.2	UE-requested PDU session release procedure initiation	472
6.4.3.3	UE-requested PDU session release procedure accepted by the network	473
6.4.3.4	UE-requested PDU session release procedure not accepted by the network	473
6.4.3.5	Abnormal cases in the UE	473
6.4.3.6	Abnormal cases on the network side	474
6.5	5GSM status procedure	474
6.5.1	General	474
6.5.2	5GSM status received in the UE	474
6.5.3	5GSM status received in the SMF	475
6.6	Miscellaneous procedures	475
6.6.1	Exchange of extended protocol configuration options	475
7	Handling of unknown, unforeseen, and erroneous protocol data	476
7.1	General	476
7.2	Message too short or too long	476
7.2.1	Message too short	476
7.2.2	Message too long	476
7.3	Unknown or unforeseen procedure transaction identity or PDU Session identity	476
7.3.1	Procedure transaction identity	476
7.3.2	PDU Session identity	477
7.4	Unknown or unforeseen message type	478
7.5	Non-semantical mandatory information element errors	478
7.5.1	Common procedures	478
7.5.2	5GS mobility management	479
7.5.3	5GS session management	479
7.6	Unknown and unforeseen IEs in the non-imperative message part	480
7.6.1	IEs unknown in the message	480
7.6.2	Out of sequence IEs	480
7.6.3	Repeated IEs	480
7.7	Non-imperative message part errors	480
7.7.1	Syntactically incorrect optional IEs	480
7.7.2	Conditional IE errors	480
7.8	Messages with semantically incorrect contents	481
8	Message functional definitions and contents	481
8.1	Overview	481
8.2	5GS mobility management messages	481
8.2.1	Authentication request	481
8.2.1.1	Message definition	481
8.2.1.2	Authentication parameter RAND	481
8.2.1.3	Authentication parameter AUTN	482
8.2.1.4	Void	482
8.2.1.5	EAP message	482
8.2.2	Authentication response	482
8.2.2.1	Message definition	482
8.2.2.2	Authentication response parameter	482
8.2.2.3	EAP message	482
8.2.3	Authentication result	482
8.2.3.1	Message definition	482
8.2.3.2	ABBA	483
8.2.4	Authentication failure	483

8.2.4.1	Message definition	483
8.2.4.2	Authentication failure parameter.....	484
8.2.5	Authentication reject.....	484
8.2.5.1	Message definition	484
8.2.5.2	EAP message.....	484
8.2.6	Registration request	484
8.2.6.1	Message definition	484
8.2.6.2	Non-current native NAS key set identifier.....	487
8.2.6.3	5GMM capability.....	487
8.2.6.4	UE security capability.....	487
8.2.6.5	Requested NSSAI	487
8.2.6.6	Last visited registered TAI.....	487
8.2.6.7	S1 UE network capability	487
8.2.6.8	Uplink data status.....	487
8.2.6.9	PDU session status	487
8.2.6.10	MICO indication	487
8.2.6.11	UE status	488
8.2.6.12	Additional GUTI.....	488
8.2.6.13	Allowed PDU session status	488
8.2.6.14	UE's usage setting	488
8.2.6.15	Requested DRX parameters	488
8.2.6.16	EPS NAS message container.....	488
8.2.6.17	LADN indication.....	488
8.2.6.17A	Payload container type	488
8.2.6.18	Payload container.....	488
8.2.6.19	Network slicing indication	489
8.2.6.20	5GS update type	489
8.2.6.21	NAS message container	489
8.2.6.22	Requested extended DRX parameters.....	489
8.2.6.23	EPS bearer context status	489
8.2.6.24	T3324 value.....	489
8.2.6.25	Mobile station classmark 2.....	489
8.2.6.26	Supported codecs	489
8.2.6.27	UE radio capability ID	489
8.2.6.28	Requested mapped NSSAI.....	489
8.2.6.29	Additional information requested.....	490
8.2.6.30	Requested WUS assistance information.....	490
8.2.6.31	Void.....	490
8.2.6.32	N5GC indication	490
8.2.6.33	Requested NB-N1 mode DRX parameters.....	490
8.2.7	Registration accept.....	490
8.2.7.1	Message definition	490
8.2.7.2	5G-GUTI.....	493
8.2.7.3	Equivalent PLMNs.....	493
8.2.7.4	TAI list	493
8.2.7.5	Allowed NSSAI	493
8.2.7.6	Rejected NSSAI	494
8.2.7.7	Configured NSSAI.....	494
8.2.7.8	5GS network feature support.....	494
8.2.7.9	PDU session status	494
8.2.7.10	PDU session reactivation result.....	494
8.2.7.11	PDU session reactivation result error cause	494
8.2.7.12	LADN information.....	494
8.2.7.13	MICO indication	494
8.2.7.14	Network slicing indication	494
8.2.7.15	Service area list	494
8.2.7.16	T3512 value.....	495
8.2.7.17	Non-3GPP de-registration timer value	495
8.2.7.18	T3502 value.....	495
8.2.7.19	Emergency number list	495
8.2.7.20	Extended emergency number list	495
8.2.7.21	SOR transparent container	495

8.2.7.22	EAP message.....	495
8.2.7.23	NSSAI inclusion mode.....	495
8.2.7.24	Operator-defined access category definitions	495
8.2.7.25	Negotiated DRX parameters	495
8.2.7.26	Non-3GPP NW provided policies	495
8.2.7.27	Negotiated extended DRX parameters	496
8.2.7.28	T3447 value.....	496
8.2.7.29	T3448 value.....	496
8.2.7.30	T3324 value.....	496
8.2.7.31	EPS bearer context status	496
8.2.7.32	UE radio capability ID	496
8.2.7.33	UE radio capability ID deletion indication.....	496
8.2.7.34	Pending NSSAI	496
8.2.7.35	Ciphering key data	496
8.2.7.36	CAG information list.....	496
8.2.7.37	Truncated 5G-S-TMSI configuration.....	497
8.2.7.38	Negotiated NB-N1 mode DRX parameters.....	497
8.2.7.39	Negotiated WUS assistance information.....	497
8.2.8	Registration complete	497
8.2.8.1	Message definition	497
8.2.8.2	SOR transparent container	497
8.2.9	Registration reject.....	498
8.2.9.1	Message definition	498
8.2.9.2	T3346 value.....	498
8.2.9.3	T3502 value.....	498
8.2.9.4	EAP message.....	498
8.2.9.5	Rejected NSSAI	498
8.2.9.6	CAG information list.....	498
8.2.10	UL NAS transport.....	499
8.2.10.1	Message definition	499
8.2.10.2	PDU session ID	499
8.2.10.3	Old PDU session ID	499
8.2.10.4	Request type	500
8.2.10.5	S-NSSAI	500
8.2.10.6	DNN	500
8.2.10.7	Additional information.....	500
8.2.10.8	MA PDU session information.....	500
8.2.10.9	Release assistance indication	500
8.2.11	DL NAS transport.....	500
8.2.11.1	Message definition	500
8.2.11.2	PDU session ID	501
8.2.11.3	Additional information.....	501
8.2.11.4	5GMM cause.....	501
8.2.11.5	Back-off timer value	501
8.2.12	De-registration request (UE originating de-registration)	501
8.2.12.1	Message definition	501
8.2.13	De-registration accept (UE originating de-registration).....	502
8.2.13.1	Message definition	502
8.2.14	De-registration request (UE terminated de-registration).....	502
8.2.14.1	Message definition	502
8.2.14.2	5GMM cause.....	503
8.2.14.3	T3346 value.....	503
8.2.14.4	Rejected NSSAI	503
8.2.14.5	CAG information list.....	503
8.2.15	De-registration accept (UE terminated de-registration).....	503
8.2.15.1	Message definition	503
8.2.16	Service request.....	504
8.2.16.1	Message definition	504
8.2.16.2	Uplink data status.....	504
8.2.16.3	PDU session status	504
8.2.16.4	Allowed PDU session status	505
8.2.16.5	NAS message container	505

8.2.17	Service accept	505
8.2.17.1	Message definition	505
8.2.17.2	PDU session status	505
8.2.17.3	PDU session reactivation result.....	505
8.2.17.4	PDU session reactivation result error cause	506
8.2.17.5	EAP message.....	506
8.2.17.6	T3448 value.....	506
8.2.18	Service reject	506
8.2.18.1	Message definition	506
8.2.18.2	PDU session status	506
8.2.18.3	T3346 value.....	507
8.2.18.4	EAP message.....	507
8.2.18.5	T3448 value.....	507
8.2.18.6	CAG information list.....	507
8.2.19	Configuration update command.....	507
8.2.19.1	Message definition	507
8.2.19.2	Configuration update indication	509
8.2.19.3	5G-GUTI.....	509
8.2.19.4	TAI list	509
8.2.19.5	Allowed NSSAI	509
8.2.19.6	Service area list	509
8.2.19.7	Full name for network.....	509
8.2.19.8	Short name for network.....	509
8.2.19.9	Local time zone	509
8.2.19.10	Universal time and local time zone	509
8.2.19.11	Network daylight saving time	509
8.2.19.12	LADN information.....	509
8.2.19.13	MICO indication	509
8.2.19.14	Network slicing indication	509
8.2.19.15	Configured NSSAI	509
8.2.19.16	Rejected NSSAI	510
8.2.19.17	Operator-defined access category definitions	510
8.2.19.18	SMS indication	510
8.2.19.19	T3447 value.....	510
8.2.19.20	CAG information list.....	510
8.2.19.21	UE radio capability ID	510
8.2.19.22	UE radio capability ID deletion indication.....	510
8.2.19.23	5GS registration result.....	510
8.2.19.24	Truncated 5G-S-TMSI configuration.....	510
8.2.19.25	Additional configuration indication	510
8.2.20	Configuration update complete.....	510
8.2.20.1	Message definition	510
8.2.20.2	Void.....	511
8.2.21	Identity request	511
8.2.21.1	Message definition	511
8.2.22	Identity response.....	511
8.2.22.1	Message definition	511
8.2.23	Notification	512
8.2.23.1	Message definition	512
8.2.24	Notification response	512
8.2.24.1	Message definition	512
8.2.24.2	PDU session status	513
8.2.25	Security mode command	513
8.2.25.1	Message definition	513
8.2.25.2	IMEISV request	514
8.2.25.3	Void.....	514
8.2.25.4	Selected EPS NAS security algorithms.....	514
8.2.25.5	Additional 5G security information	514
8.2.25.6	EAP message.....	514
8.2.25.7	ABBA	514
8.2.25.8	Replayed S1 UE security capabilities	515
8.2.26	Security mode complete.....	515