
**Ships and marine technology — Grab
dredger supervisory and control
systems**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 20663:2020](https://standards.iteh.ai/catalog/standards/sist/8f215d34-6bb2-466f-8462-86d08b515766/iso-20663-2020)

<https://standards.iteh.ai/catalog/standards/sist/8f215d34-6bb2-466f-8462-86d08b515766/iso-20663-2020>



iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 20663:2020

<https://standards.iteh.ai/catalog/standards/sist/8f215d34-6bb2-466f-8462-86d08b515766/iso-20663-2020>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms, definitions and abbreviated terms.....	1
3.1 Terms and definitions.....	1
3.2 Abbreviated terms.....	2
4 Components and structure.....	2
4.1 Components.....	2
4.2 Structure.....	2
5 General requirements.....	2
5.1 Operating position and control mode.....	2
5.1.1 Operating position.....	2
5.1.2 Control mode.....	2
5.2 External communication.....	2
5.3 Diagnostic.....	3
5.4 HMI graphics.....	3
5.4.1 Alarm level.....	3
5.4.2 Conventions on graphic colours.....	3
5.4.3 Brightness of the HMI.....	3
6 Functional requirements.....	4
6.1 SCADA.....	4
6.1.1 General description.....	4
6.1.2 Pontoon positioning.....	4
6.1.3 Crane movement.....	4
6.1.4 Grab operation.....	4
6.1.5 Calibration of system.....	5
6.2 DPM.....	5

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 8, *Ships and marine technology*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document describes the supervisory and control system for a number of components, functions and systems that can, but do not have to, be installed on board of a grab dredger. It does not prescribe that all described components, functions and systems need to be installed.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 20663:2020

<https://standards.iteh.ai/catalog/standards/sist/8f215d34-6bb2-466f-8462-86d08b515766/iso-20663-2020>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 20663:2020

<https://standards.iteh.ai/catalog/standards/sist/8f215d34-6bb2-466f-8462-86d08b515766/iso-20663-2020>

Ships and marine technology — Grab dredger supervisory and control systems

1 Scope

This document specifies the components and structure, general requirements, and functional requirements of grab dredger supervisory and control systems.

It is applicable only to the installed components, functions or systems. It covers the design, manufacture and modifications.

2 Normative references

The following referenced documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8384, *Ships and marine technology — Dredgers — Vocabulary*

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

ISO 20663:2020

For the purposes of this document, the terms and definitions given in ISO 8384 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1.1

grab dredger supervisory and control system

GD-SCS

system used for supervising and controlling the operations of a grab dredger

3.1.2

dredging profile monitor

DPM

system used to accurately measure and monitor the grab dredger's position and heading, and the grab bucket's position and depth, via plane view and profile view

3.1.4

opening value

value of opening of the grab bucket, expressed in percent (%), where 0 % means closed and 100 % means fully opened

3.2 Abbreviated terms

DPM	Dredging profile monitor
GD-SCS	Grab dredger supervisory and control system
HMI	Human machine interface
SCADA	Supervisory control and data acquisition

4 Components and structure

4.1 Components

The grab dredger is a dredger that excavates the soil with a grab.

The GD-SCS is an integrated system which consists of a SCADA and a DPM.

The SCADA is used to monitor and control the dredging process with a grab.

The main functions of the DPM are to measure the position and heading of the grab dredger, and the position and depth of the grab bucket, and to provide for visualization in the plan view with a numeric window and side views.

4.2 Structure

By using either a wireless or wired network, the GD-SCS consists of a collector, a controller, monitoring stations, etc. respectively in the grab dredger's control room, the operator's cabin or elsewhere, in order to monitor the dredging and the operations of the grab dredger moving and manipulation equipment.

<https://standards.iteh.ai/catalog/standards/sist/8f215d34-6bb2-466f-8462-86d08b515766/iso-20663-2020>

5 General requirements

5.1 Operating position and control mode

5.1.1 Operating position

The GD-SCS should have a local and, where deemed required, a remote operating position.

5.1.2 Control mode

The GD-SCS should have the following control modes:

- manual: manual operation by handle/button/knob/pedal and HMI;
- emergency: direct operation through hard wire, only for dredging equipment that affects the safety of the grab dredger.

5.2 External communication

The GD-SCS should have the following communication interfaces:

- the position measurement system of the vessel;
- the heading (orientation) measurement system of the vessel;
- the tide measurement.

5.3 Diagnostic

When the equipment start and stop controls, the operation position transfer, or the control mode shift operation fail, the GD-SCS should provide diagnostic information.

5.4 HMI graphics

5.4.1 Alarm level

In HMI graphics, the GD-SCS alarm level can be set in two colours.

EXAMPLE Red is the highest level alarm, meaning danger; yellow is the secondary level alarm, meaning warning or abnormal condition.

This principle can be applied to all graphical symbols, function-keys, and digital data.

5.4.2 Conventions on graphic colours

The HMI graphic colours can be specified as follows.

- a) For HMI graphics, cold tone colours are recommended, and for non-operating graphical interfaces, warm tone colours can be adopted.
- b) The colour matching of the HMI graphics should make the flow chart simple and clear with harmonious and consistent colours. It is advisable that the number of colours adopted not be excessive.
- c) Colour adoption of the HMI graphics can be in accordance with the specifications in [Table 1](#).

Table 1 — Convention on graphical adoptions

Colour	General meaning	Meaning of colour in combination with graphical symbol	Meaning of colour in combination with digital data
Red	Danger	Highest level alarm	Highest level alarm
Yellow	Warning	Abnormal condition, secondary alarm	Abnormal condition, secondary alarm
Grey	Static state	Stop, shut down, disconnection	None
Cyan	Special meaning	Remote control, etc.	None
Blue	Secondary importance	Backup equipment	Tag number
White	Safe, program in activation status	None	Measured value or status value, dynamic data
Green	Safe, program in activation status	Normal operation, working, open, shut down, graphic value	None

5.4.3 Brightness of the HMI

The brightness of the HMI graphics should match that of the environment. For screen in bridge, the HMI can have a “night” display mode, and brightness of the screen should be lowered enough not to affect the sailors lookout in the night.