

ETSI TS 138 521-1 V17.9.0 (2023-08)



5G;
NR;

**User Equipment (UE) conformance specification;
Radio transmission and reception;
Part 1: Range 1 standalone
(3GPP TS 38.521-1 version 17.9.0 Release 17)**



Reference

RTS/TSGR-0538521-1vh90

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://standards.iteh.ai/> <https://portal.etsi.org/People/CommitteeSupportStaff.aspx> [2-7ef0c97bce81/etsi-](https://portal.etsi.org/People/CommitteeSupportStaff.aspx)

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	19
1 Scope	20
2 References	20
3 Definitions, symbols and abbreviations	21
3.1 Definitions	21
3.2 Symbols.....	22
3.3 Abbreviations	24
4 General	26
4.1 Relationship between minimum requirements and test requirements	26
4.2 Applicability of minimum requirements	26
4.3 Specification suffix information.....	26
4.4 Test points analysis	27
4.5 Applicability and test coverage rules.....	27
4.6 Pass fail decision rule of test case	27
5 Operating bands and Channel arrangement.....	28
5.1 General	28
5.2 Operating bands.....	28
5.2A Operating bands for CA	29
5.2A.1 Intra-band CA	29
5.2A.2 Inter-band CA	30
5.2A.2.1 Inter-band CA (two bands).....	30
5.2A.2.2 Inter-band CA (three bands).....	32
5.2A.2.3 Inter-band CA (four bands).....	32
5.2B Operating bands for DC	32
5.2C Operating band combination for SUL	32
5.2D Operating bands for UL MIMO	33
5.2E Operating band for V2X.....	34
5.2E.1 V2X operating bands	34
5.2E.2 V2X operating bands for concurrent operation.....	34
5.3 UE channel bandwidth	34
5.3.1 General.....	34
5.3.2 Maximum transmission bandwidth configuration	35
5.3.3 Minimum guard band and transmission bandwidth configuration.....	35
5.3.4 RB alignment	37
5.3.5 UE channel bandwidth per operating band	37
5.3.6 Asymmetric channel bandwidths	40
5.3A UE channel bandwidth for CA	41
5.3A.1 General.....	41
5.3A.2 Maximum transmission bandwidth configuration for CA	41
5.3A.3 Minimum guard band and transmission bandwidth configuration for CA.....	41
5.3A.4 Void	43
5.3A.5 UE channel bandwidth per operating band for CA	43
5.3E Channel bandwidth for V2X	44
5.3E.1 General.....	44
5.3E.2 Channel bandwidth for V2X concurrent operation.....	45
5.3I Channel bandwidth for RedCap	45
5.4 Channel arrangement.....	45
5.4.1 Channel spacing.....	45
5.4.1.1 Channel spacing for adjacent NR carriers	45
5.4.2 Channel raster	45

5.4.2.1	NR-ARFCN and channel raster.....	45
5.4.2.2	Channel raster to resource element mapping.....	46
5.4.2.3	Channel raster entries for each operating band	46
5.4.3	Synchronization raster	48
5.4.3.1	Synchronization raster and numbering.....	48
5.4.3.2	Synchronization raster to synchronization block resource element mapping.....	49
5.4.3.3	Synchronization raster entries for each operating band.....	49
5.4.4	TX–RX frequency separation	50
5.4A	Channel arrangement for CA.....	51
5.4A.1	Channel spacing for CA.....	51
5.4A.2	Channel raster for CA	52
5.4A.3	Synchronization raster for CA	52
5.4A.4	Tx-Rx frequency separation for CA.....	52
5.4E	Channel arrangement for V2X	52
5.4E.1	Channel spacing.....	52
5.4E.2	Channel raster	52
5.4E.2.1	NR-ARFCN and channel raster.....	52
5.4E.2.2	Channel raster to resource element mapping.....	52
5.4E.2.3	Channel raster entries for each operating band	52
5.4E.3	Synchronization raster for V2X.....	53
5.5	Void.....	53
5.5A	Configurations for CA.....	53
5.5A.0	General.....	53
5.5A.1	Configurations for intra-band contiguous CA.....	53
5.5A.2	Configurations for intra-band non-contiguous CA	55
5.5A.3	Configurations for inter-band CA	55
5.5A.3.1	Configurations for inter-band CA (two bands)	56
5.5A.3.2	Configurations for inter-band CA (three bands)	62
5.5A.3.3	Configurations for inter-band CA (four bands).....	65
5.5B	Configurations for DC.....	65
5.5C	Configurations for SUL	65
6	Transmitter characteristics	68
6.1	General	68
6.1A	General	70
6.1E	General	79
6.2	Transmitter power	83
6.2.1	UE maximum output power.....	83
6.2.2	UE maximum output power reduction.....	89
6.2.3	UE additional maximum output power reduction.....	113
6.2.4	Configured transmitted power	267
6.2A	Transmitter power for CA	273
6.2A.1	UE maximum output power for CA.....	273
6.2A.1.0	Minimum conformance requirements	273
6.2A.1.0.1	Void.....	273
6.2A.1.0.2	Void.....	273
6.2A.1.0.3	UE maximum output power for Inter-band CA.....	273
6.2A.1.0.4	UE maximum output power for Intra-band contiguous CA	275
6.2A.1.0.5	UE maximum output power for Intra-band non-contiguous CA	275
6.2A.1.1	UE maximum output power for CA (2UL CA).....	275
6.2A.2	UE maximum output power reduction for CA.....	279
6.2A.2.0	Minimum conformance requirements	279
6.2A.2.0.1	FFS	279
6.2A.2.0.2	FFS	279
6.2A.2.0.3	Maximum Power Reduction for Inter-band CA	279
6.2A.2.0.4	Maximum Power Reduction for Intra-band contiguous CA.....	280
6.2A.2.0.5	Maximum Power Reduction for Intra-band non-contiguous CA.....	283
6.2A.2.1	UE maximum output power reduction for CA (2UL CA).....	284
6.2A.3	UE additional maximum output power reduction for CA.....	303
6.2A.3.0	Minimum conformance requirements	303
6.2A.3.0.1	UE additional maximum output power reduction for Intra-band contiguous CA.....	303
6.2A.3.0.1.1	A-MPR for CA_NS_04.....	304

6.2A.3.0.1.1.2	Non-contiguous allocations	304
6.2A.3.0.1.1.3	AMPR _{IM3} to meet -25dBm/MHz	305
6.2A.3.0.2	FFS	305
6.2A.3.0.3	UE additional maximum output power reduction for inter-band CA	305
6.2A.3.1	UE additional maximum output power reduction for CA (2UL CA)	306
6.2A.4	Configured output power for CA	317
6.2A.4.0	Minimum conformance requirements	317
6.2A.4.0.1	Configured transmitted power level	317
6.2A.4.0.2	$\Delta T_{IB,c}$ for CA	322
6.2A.4.0.2.1	FFS	322
6.2A.4.0.2.2	FFS	322
6.2A.4.0.2.3	$\Delta T_{IB,c}$ for Inter-band CA	322
6.2A.4.1	Configured transmitted power for CA (2UL CA)	323
6.2B	Transmitter power for NR-DC	329
6.2B.0	General	329
6.2B.1	UE maximum output power for NR-DC	329
6.2B.1.0	Minimum conformance requirements	329
6.2B.1.0.1	FFS	329
6.2B.1.0.2	FFS	329
6.2B.1.0.3	UE maximum output power for inter-band NR-DC	329
6.2B.1.1	UE maximum output power for NR-DC	329
6.2B.2	UE maximum output power reduction for NR-DC	332
6.2B.2.0	Minimum conformance requirements	332
6.2B.2.0.1	FFS	332
6.2B.2.0.2	FFS	332
6.2B.2.0.3	UE maximum output power reduction for Inter-band NR-DC	332
6.2B.2.1	UE maximum output power reduction for NR-DC	332
6.2B.3	UE additional maximum output power reduction for NR-DC	333
6.2B.3.0	Minimum conformance requirements	333
6.2B.3.0.1	FFS	333
6.2B.3.0.2	FFS	333
6.2B.3.0.3	UE additional maximum output power reduction for inter-band NR-DC	333
6.2B.3.1	UE additional maximum output power reduction for NR-DC	334
6.2B.4	Configured output power for NR-DC	336
6.2B.4.0	Minimum conformance requirements	336
6.2B.4.0.1	Configured transmitted power level for NR-DC	336
6.2B.4.0.2	$\Delta T_{IB,c}$ for NR-DC	339
6.2B.4.0.2.1	FFS	339
6.2B.4.0.2.2	FFS	339
6.2B.4.0.2.3	$\Delta T_{IB,c}$ for Inter-band NR-DC	339
6.2B.4.1	Configured transmitted power level for NR-DC	339
6.2C	Transmitter power for SUL	342
6.2C.1	Configured transmitted power for SUL	342
6.2C.2	$\Delta T_{IB,c}$	345
6.2C.3	UE maximum output power for SUL	345
6.2C.3_1	Void	348
6.2C.4	UE maximum output power reduction for SUL	348
6.2C.5	UE additional maximum output power reduction for SUL	356
6.2D	Transmitter power for UL MIMO	386
6.2D.1	UE maximum output power for UL MIMO	386
6.2D.1_1	UE maximum output power for SUL with UL MIMO	390
6.2D.2	UE maximum output power reduction for UL MIMO	394
6.2D.2_1	UE maximum output power reduction for SUL with UL MIMO	414
6.2D.3	UE additional maximum output power reduction for UL MIMO	419
6.2D.3_1	UE additional maximum output power reduction for SUL with UL MIMO	455
6.2D.4	Configured transmitted power for UL MIMO	464
6.2D.4_1	Configured transmitted power for SUL with UL MIMO	467
6.2E	Transmitter power for V2X	470
6.2E.1	UE maximum output power for V2X	470
6.2E.1.0	Minimum conformance requirements	470
6.2E.1.1	UE maximum output power for V2X / non-concurrent operation	471
6.2E.1.1D	UE maximum output power for V2X / non-concurrent operation / SL-MIMO	472

6.2E.2	UE maximum output power reduction for V2X	474
6.2E.2.0	Minimum conformance requirements	474
6.2E.2.1	UE maximum output power reduction for V2X / non-concurrent operation	475
6.2E.2.1D	UE maximum output power reduction for V2X / non-concurrent operation / SL-MIMO	479
6.2E.2.2	UE maximum output power reduction for V2X / concurrent operation.....	482
6.2F	Transmitter power for shared spectrum channel access	485
6.2F.1	UE maximum output power for shared spectrum channel access.....	485
6.2F.2	UE maximum output power reduction.....	487
6.2F.3	UE additional maximum output power reduction for shared spectrum access	487
6.2G	Transmitter power for Tx Diversity.....	493
6.2G.1	UE maximum output power for Tx Diversity	493
6.2G.2	UE maximum output power reduction for Tx Diversity	503
6.2G.3	UE additional maximum output power reduction for Tx Diversity	527
6.2G.4	Configured transmitted power for Tx Diversity.....	537
6.2I	Transmitter power for RedCap.....	541
6.2I.1	UE maximum output power for RedCap	541
6.2I.2	Void	543
6.2I.3	Void	543
6.2I.4	Void	543
6.3	Output power dynamics.....	543
6.3.1	Minimum output power	543
6.3.2	Transmit OFF power.....	545
6.3.3	Transmit ON/OFF time mask	546
6.3.3.1	General	546
6.3.3.2	General ON/OFF time mask	547
6.3.3.3	Transmit power time mask for slot and short or subslot boundaries.....	551
6.3.3.4	PRACH time mask.....	551
6.3.3.5	Void.....	557
6.3.3.6	SRS time mask	557
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks	565
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	565
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries	565
6.3.4	Power control.....	565
6.3.4.1	General	565
6.3.4.2	Absolute power tolerance.....	565
6.3.4.3	Relative power tolerance.....	568
6.3.4.4	Aggregate power tolerance.....	583
6.3A	Output power dynamics for CA	587
6.3A.1	Minimum output power for CA	587
6.3A.1.0	Minimum conformance requirements	587
6.3A.1.1	Minimum output power for CA (2UL CA)	587
6.3A.2	Transmit OFF power for CA.....	589
6.3A.2.0	Minimum conformance requirements	589
6.3A.2.1	Transmit OFF power for CA (2UL CA)	589
6.3A.3	Transmit ON/OFF time mask for CA	590
6.3A.3.0	Minimum conformance requirements	590
6.3A.3.0.1	Transmit ON/OFF time mask for intra-band contiguous CA	590
6.3A.3.0.2	Transmit ON/OFF time mask for intra-band non-contiguous CA	590
6.3A.3.0.3	Transmit ON/OFF time mask for inter-band CA.....	591
6.3A.3.1	Transmit ON/OFF time mask for CA (2UL CA)	592
6.3A.3.1_1	Time mask for switching between two uplink carriers.....	598
6.3A.4	Power control for CA.....	603
6.3A.4.1	Absolute power tolerance for CA.....	603
6.3A.4.1.0	Minimum conformance requirements.....	603
6.3A.4.1.1	Absolute power tolerance for CA (2UL CA).....	603
6.3A.4.2	Relative power tolerance for CA.....	606
6.3A.4.2.0	Minimum conformance requirements.....	606
6.3A.4.2.1	Relative power tolerance for CA (2UL CA).....	606
6.3A.4.3	Aggregate power tolerance for CA	614
6.3A.4.3.0	Minimum conformance requirements.....	614
6.3A.4.3.1	Aggregate power tolerance for CA (2UL CA)	614

6.3B	Output power dynamics for NR-DC.....	618
6.3B.1	Minimum output power for NR-DC	618
6.3B.2	Transmit OFF power for NR-DC.....	618
6.3B.3	Transmit ON/OFF time mask for NR-DC	618
6.3C	Output power dynamics for SUL	618
6.3C.1	Minimum output power for SUL	618
6.3C.2	Transmit OFF power for SUL.....	620
6.3C.3	Transmit ON/OFF time mask for SUL	620
6.3C.3.0	Minimum conformance requirements	620
6.3C.3.0.1	General ON/OFF time mask for SUL.....	620
6.3C.3.0.2	Time mask for switching between two uplink carriers	621
6.3C.3.1	General transmit ON/OFF time mask for SUL	621
6.3C.3.2	General transmit ON/OFF time mask for switching between two uplink carriers	623
6.3C.4	Power control for SUL.....	627
6.3C.4.1	Absolute power tolerance for SUL.....	627
6.3C.4.2	Relative power tolerance for SUL.....	629
6.3C.4.3	Aggregate power tolerance for SUL	634
6.3D	Output power dynamics for UL MIMO	638
6.3D.1	Minimum output power for UL MIMO	638
6.3D.1_1	Minimum output power for SUL with UL MIMO.....	640
6.3D.2	Transmit OFF power for UL MIMO.....	642
6.3D.2_1	Transmit OFF power for SUL with UL MIMO.....	643
6.3D.3	Transmit ON/OFF time mask for UL MIMO	644
6.3D.3_1	Transmit ON/OFF time mask for SUL with UL MIMO.....	649
6.3D.4	Power control for UL MIMO.....	654
6.3D.4.1	Absolute power tolerance for UL MIMO.....	654
6.3D.4.1_1	Absolute power tolerance for SUL with UL MIMO	657
6.3D.4.2	Relative power tolerance for UL MIMO.....	659
6.3D.4.2_1	Relative power tolerance for SUL with UL MIMO	667
6.3D.4.3	Aggregate power tolerance for UL MIMO	672
6.3D.4.3_1	Aggregate power tolerance for SUL with UL MIMO	674
6.3E	Output power dynamics for V2X	676
6.3E.1	Minimum output power for V2X	676
6.3E.1.0	Minimum conformance requirements	676
6.3E.1.1	Minimum output power for V2X / non-concurrent operation	677
6.3E.1.1D	Minimum output power for V2X / non-concurrent operation / SL-MIMO.....	679
6.3E.2	Transmit OFF power for V2X	681
6.3E.2.0	Minimum conformance requirements	681
6.3E.2.1	Transmit OFF power for V2X / non-concurrent operation	681
6.3E.2.1D	Transmit OFF power for V2X / non-concurrent operation / SL-MIMO	682
6.3E.2.2	Transmit OFF power for V2X / con-current operation	683
6.3F	Output power dynamics for shared spectrum channel access.....	683
6.3F.1	Minimum output power	683
6.3F.2	Transmit OFF power for shared spectrum channel access.....	686
6.3F.3	Transmit ON/OFF time mask for shared spectrum channel access	687
6.3F.3.1	General	687
6.3F.3.2	General ON/OFF time mask	687
6.3G	Output power dynamics for Tx Diversity.....	690
6.3G.1	Minimum output power for Tx Diversity	690
6.3G.2	Transmit OFF power for Tx Diversity.....	691
6.3G.3	Transmit ON/OFF time mask for Tx Diversity	692
6.3G.3.1	General ON/OFF time mask for Tx Diversity.....	692
6.3G.3.2	PRACH time mask for Tx Diversity	694
6.3G.3.3	SRS time mask for Tx Diversity	696
6.3G.4	Power control for Tx Diversity	698
6.3G.4.1	Absolute power tolerance for Tx Diversity	698
6.3G.4.2	Relative power tolerance for Tx Diversity.....	698
6.3G.4.3	Aggregate power tolerance for Tx Diversity.....	704
6.4	Transmit signal quality	705
6.4.1	Frequency error.....	705
6.4.2	Transmit modulation quality.....	706
6.4.2.1	Error Vector Magnitude	707

6.4.2.1a	Error Vector Magnitude including symbols with transient period	713
6.4.2.2	Carrier leakage	717
6.4.2.3	In-band emissions	720
6.4.2.4	EVM equalizer spectrum flatness	725
6.4.2.5	EVM equalizer spectrum flatness for Pi/2 BPSK.....	729
6.4.2.6	Phase continuity requirements for DMRS bundling	732
6.4A	Transmit signal quality for CA.....	734
6.4A.1	Frequency error for CA.....	734
6.4A.1.0	Minimum conformance requirements	735
6.4A.1.1	Frequency error for CA (2UL CA)	735
6.4A.2	Transmit modulation quality for CA.....	737
6.4A.2.1	Error Vector Magnitude for CA	737
6.4A.2.1.0	Minimum conformance requirements.....	737
6.4A.2.1.1	Error Vector Magnitude for CA (2UL CA).....	737
6.4A.2.2	Carrier leakage for CA.....	740
6.4A.2.2.0	Minimum conformance requirements.....	740
6.4A.2.2.1	Carrier leakage for CA (2UL CA).....	740
6.4A.2.3	In-band emissions for CA	743
6.4A.2.3.0	Minimum conformance requirements.....	743
6.4A.2.3.1	In-band emissions for CA (2UL CA)	744
6.4B	Transmit signal quality for NR-DC.....	747
6.4B.1	Frequency error for NR-DC.....	747
6.4B.2	Transmit modulation quality for NR-DC.....	748
6.4B.2.1	Error Vector Magnitude for NR-DC	748
6.4B.2.2	Carrier leakage for NR-DC	748
6.4B.2.3	In-band emissions for NR-DC.....	748
6.4C	Transmit signal quality for SUL.....	748
6.4C.1	Frequency error for SUL.....	748
6.4C.2	Transmit modulation quality for SUL.....	749
6.4C.2.1	Error Vector Magnitude for SUL	749
6.4C.2.2	Carrier leakage for SUL	751
6.4C.2.3	In-band emissions for SUL	752
6.4C.2.4	EVM equalizer spectrum flatness for SUL	754
6.4C.2.5	EVM equalizer spectrum flatness for Pi/2 BPSK for SUL	755
6.4D	Transmit signal quality for UL MIMO.....	757
6.4D.1	Frequency error for UL MIMO.....	757
6.4D.1_1	Frequency error for SUL with UL MIMO	759
6.4D.2	Transmit modulation quality for UL MIMO.....	760
6.4D.2.1	Error Vector Magnitude for UL MIMO	761
6.4D.2.1_1	Error Vector Magnitude for SUL with UL MIMO	763
6.4D.2.2	Carrier leakage for UL MIMO	766
6.4D.2.2_1	Carrier leakage for SUL with UL MIMO	769
6.4D.2.3	In-band emissions for UL MIMO	770
6.4D.2.3_1	In-band emissions for SUL with UL MIMO	773
6.4D.2.4	EVM equalizer spectrum flatness for UL MIMO	775
6.4D.2.4_1	EVM equalizer spectrum flatness for SUL with UL MIMO	778
6.4D.3	Time alignment error for UL MIMO	781
6.4D.3_1	Time alignment error for SUL with UL MIMO.....	782
6.4D.4	Requirements for coherent UL MIMO	784
6.4E	Transmit signal quality for V2X.....	786
6.4E.1	Frequency error for V2X	786
6.4E.2	Transmit modulation quality for V2X	786
6.4E.2.1	General	786
6.4E.2.2	Error Vector Magnitude for V2X.....	786
6.4E.2.2.1	Error Vector Magnitude for V2X / non-concurrent operation.....	786
6.4E.2.2.1D	Error Vector Magnitude for V2X / non-concurrent operation / SL-MIMO.....	788
6.4E.2.4	In-band emissions for V2X	789
6.4E.2.4.1	In-band emissions for V2X / non-concurrent operation	789
6.4E.2.4.1D	In-band emissions for V2X / non-concurrent operation / SL-MIMO	792
6.4E.2.4.2	In-band emissions for V2X / con-current operation	793
6.4E.2.5	EVM equalizer spectrum flatness for V2X	795
6.4E.2.5.1	EVM equalizer spectrum flatness for V2X / non-concurrent operation	795

6.4E.2.5.1D	EVM equalizer spectrum flatness for V2X / non-concurrent operation / SL-MIMO	797
6.4E.2.5.2	EVM equalizer spectrum flatness for V2X / con-current operation	798
6.4F	Transmit signal quality for shared spectrum channel access	800
6.4F.1	Frequency error	800
6.4F.2	Transmit modulation quality	801
6.4F.2.0	General	801
6.4F.2.1	Error Vector Magnitude	801
6.4F.2.2	Carrier leakage	804
6.4F.2.3	In-band emissions	807
6.4F.2.4	EVM equalizer spectrum flatness	812
6.4G	Transmit signal quality for Tx Diversity	815
6.4G.1	Frequency error for Tx Diversity	815
6.4G.2	Transmit modulation quality for Tx Diversity	815
6.4G.2.1	Error Vector Magnitude for Tx Diversity	815
6.4G.2.2	Carrier leakage for Tx Diversity	819
6.4G.2.3	In-band emissions for Tx Diversity	820
6.4G.2.4	EVM equalizer spectrum flatness for Tx Diversity	822
6.5	Output RF spectrum emissions	824
6.5.0	General	824
6.5.1	Occupied bandwidth	824
6.5.2	Out of band emission	826
6.5.2.1	General	826
6.5.2.2	Spectrum emission mask	826
6.5.2.3	Additional spectrum emission mask	833
6.5.2.4	Adjacent channel leakage ratio	840
6.5.2.4.1	NR ACLR	840
6.5F.2.4.2	Shared spectrum channel access ACLR with additional requirement for NS_29	843
6.5.2.4.2	UTRA ACLR	845
6.5.3	Spurious emissions	847
6.5.3.1	General spurious emissions	847
6.5.3.2	Spurious emissions for UE co-existence	850
6.5.3.3	Additional spurious emissions	869
6.5.4	Transmit intermodulation	896
6.5A	Output RF spectrum emissions for CA	899
6.5A.1	Occupied bandwidth for CA	899
6.5A.1.0	Minimum conformance requirements	899
6.5A.1.0.1	Void	899
6.5A.1.0.1a	Occupied bandwidth for Intra-band contiguous CA	899
6.5A.1.0.2	Occupied bandwidth for Intra-band non-contiguous CA	899
6.5A.1.0.3	Occupied bandwidth for Inter-band CA	899
6.5A.1.1	Occupied bandwidth for CA (2UL CA)	899
6.5A.2	Out of band emission for CA	902
6.5A.2.1	General	902
6.5A.2.2	Spectrum emission mask	902
6.5A.2.2.0	Minimum conformance requirements	902
6.5A.2.2.1	Spectrum emission mask for CA (2UL CA)	903
6.5A.2.3	Additional spectrum emission mask for CA	908
6.5A.2.3.0	Minimum conformance requirements	908
6.5A.2.3.1	Additional spectrum emission mask for CA (2UL CA)	908
6.5A.2.4	Adjacent channel leakage ratio	910
6.5A.2.4.1	NR ACLR	910
6.5A.2.4.1.0	Minimum conformance requirements	910
6.5A.2.4.1.0.3	NR ACLR for Inter-band CA	912
6.5A.2.4.1.1	NR ACLR for CA (2UL CA)	912
6.5A.2.4.2	UTRA ACLR	915
6.5A.2.4.2.0	Minimum conformance requirements	915
6.5A.2.4.2.1	UTRA ACLR for CA (2UL CA)	915
6.5A.3	Spurious emission for CA	917
6.5A.3.1	General spurious emissions for CA	917
6.5A.3.1.0	Minimum conformance requirements	917
6.5A.3.1.1	General spurious emissions for CA (2UL CA)	918
6.5A.3.2	Spurious emission for UE co-existence	924

6.5A.3.2.0	Minimum conformance requirements.....	924
6.5A.3.2.0.1	Spurious emissions for UE co-existence for intra-band contiguous CA.....	924
6.5A.3.2.0.2	Void	926
6.5A.3.2.0.3	Spurious emissions for UE co-existence for Inter-band CA	926
6.5A.3.2.1	Spurious emissions for UE co-existence for CA (2UL CA).....	933
6.5A.3.3	Additional spurious emissions for CA	944
6.5A.3.3.0	Minimum conformance requirements.....	944
6.5A.3.3.1	Additional spurious emissions for CA (2UL CA)	944
6.5A.4	Transmit intermodulation for CA	946
6.5A.4.0	Minimum conformance requirements	946
6.5A.4.1	Transmit intermodulation for CA (2UL CA)	946
6.5B	Output RF spectrum emissions for NR-DC.....	949
6.5B.1	Occupied bandwidth for NR-DC	949
6.5B.2	Out of band emission for NR-DC	949
6.5B.2.1	General.....	949
6.5B.2.2	Spectrum emission mask.....	949
6.5B.2.4	Adjacent channel leakage ratio	949
6.5B.3	Spurious emission for NR-DC.....	949
6.5B.4	Transmit intermodulation for NR-DC.....	949
6.5C	Output RF spectrum emissions for SUL.....	950
6.5C.1	Occupied bandwidth for SUL	950
6.5C.2	Out of band emission for SUL	951
6.5C.2.1	General	951
6.5C.2.2	Spectrum emission mask for SUL.....	951
6.5C.2.3	Additional spectrum emission mask for SUL	954
6.5C.2.4	Adjacent channel leakage ratio for SUL	955
6.5C.2.4.1	NR ACLR for SUL.....	955
6.5C.2.4.2	UTRA ACLR for SUL	956
6.5C.3	Spurious emissions for SUL	957
6.5C.3.1	General spurious emissions for SUL.....	957
6.5C.3.2	Spurious emissions for UE co-existence for SUL	958
6.5C.3.3	Additional spurious emissions for SUL	960
6.5C.4	Transmit intermodulation for SUL	971
6.5D	Output RF spectrum emissions for UL MIMO.....	972
6.5D.1	Occupied bandwidth for UL MIMO	972
6.5D.1_1	Void	974
6.5D.1_2	Occupied bandwidth for SUL with UL MIMO.....	974
6.5D.2	Out of band emission for UL MIMO	976
6.5D.2.1	General	976
6.5D.2.2	Spectrum emission mask for UL MIMO.....	976
6.5D.2.2_1	Spectrum emission mask for SUL with UL MIMO	981
6.5D.2.3	Additional spectrum emission mask for UL MIMO	985
6.5D.2.4	Adjacent channel leakage ratio for UL MIMO	987
6.5D.2.4.1	NR ACLR for UL MIMO.....	987
6.5D.2.4.1_1	NR ACLR for SUL with UL MIMO	989
6.5D.2.4.2	UTRA ACLR for UL MIMO	990
6.5D.2.4.2_1	UTRA ACLR for SUL with UL MIMO.....	992
6.5D.2_1	Void	995
6.5D.3	Spurious emissions for UL MIMO	995
6.5D.3.1	General spurious emissions for UL MIMO.....	995
6.5D.3.2	Spurious emissions for UE co-existence for UL MIMO.....	997
6.5D.3.3	Additional spurious emissions for UL MIMO	999
6.5D.3_1	Spurious emissions for UL MIMO (Rel-16 onward).....	1003
6.5D.3_1.1	General spurious emissions for UL MIMO (Rel-16 onward)	1003
6.5D.3_1.2	Spurious emission for UE co-existence for UL MIMO (Rel-16 onward).....	1005
6.5D.3_1.3	Additional spurious emissions for UL MIMO (Rel-16 onward).....	1006
6.5D.3_2	Spurious emissions for SUL with UL MIMO.....	1008
6.5D.3_2.1	General spurious emissions for SUL with UL MIMO	1008
6.5D.3_2.2	Spurious emissions for UE co-existence for SUL with UL MIMO	1010
6.5D.3_2.3	Additional spurious emissions for SUL with UL MIMO.....	1011
6.5D.4	Transmit intermodulation for UL MIMO	1016
6.5D.4_1	Transmit intermodulation for SUL with UL MIMO.....	1018

6.5E	Output RF spectrum emissions for V2X	1020
6.5E.1	Occupied bandwidth for V2X.....	1020
6.5E.2	Out of band emission for V2X.....	1020
6.5E.2.1	General.....	1020
6.5E.2.2	Spectrum emission mask for V2X	1020
6.5E.2.2.1	Spectrum emission mask for V2X / non-concurrent operation.....	1020
6.5E.2.2.1D	Spectrum emission mask for V2X / non-concurrent operation / SL-MIMO	1024
6.5E.2.3	Additional Spectrum emission mask for V2X	1026
6.5E.2.3.1	Additional Spectrum emission mask for V2X / non-concurrent operation.....	1026
6.5E.2.3.1D	Additional Spectrum emission mask for V2X / non-concurrent operation / SL-MIMO	1029
6.5E.2.4	Adjacent channel leakage ratio for V2X	1031
6.5E.2.4.1	Adjacent channel leakage ratio for V2X / non-concurrent operation	1031
6.5E.2.4.1D	Adjacent channel leakage ratio for V2X / non-concurrent operation / SL-MIMO	1034
6.5E.3	Spurious emissions for V2X	1035
6.5E.3.1	General spurious emissions for V2X	1035
6.5E.3.2	Spurious emissions for UE co-existence for V2X.....	1035
6.5E.3.2.1	Spurious emissions for UE co-existence for V2X / non-concurrent operation.....	1035
6.5E.3.2.1D	Spurious emissions for UE co-existence for V2X / non-concurrent operation / SL-MIMO.....	1037
6.5E.3.3	Additional spurious emissions requirements for V2X	1038
6.5E.3.3.1	Additional spurious emissions requirements for V2X / non-concurrent operation	1038
6.5F	Output RF spectrum emissions for shared spectrum channel access.....	1040
6.5F.1	Occupied bandwidth for shared spectrum channel access	1040
6.5F.2	Out of band emission for shared spectrum channel access	1040
6.5F.2.1	General	1040
6.5F.2.2	Spectrum emission mask for operation with shared spectrum channel access.....	1040
6.5F.2.4	Adjacent channel leakage ratio for operation with shared spectrum channel access	1043
6.5F.2.4.1	Shared spectrum channel access ACLR	1043
6.5F.3	Spurious emissions for shared spectrum channel access	1045
6.5F.3.1	General spurious emissions	1046
6.5F.3.2	Spurious emissions for UE co-existence	1048
6.5F.4	Transmit intermodulation for shared spectrum channel access	1048
6.5G	Output RF spectrum emissions for Tx Diversity	1050
6.5G.1	Occupied bandwidth for Tx Diversity	1050
6.5G.2	Out of band emission for Tx Diversity	1050
6.5G.2.1	Spectrum emission mask for Tx Diversity	1050
6.5G.2.2	Additional spectrum emission mask for Tx Diversity	1056
6.5G.2.3	Adjacent channel leakage ratio for Tx Diversity.....	1059
6.5G.2.3.1	NR ACLR for Tx Diversity	1059
6.5G.2.3.2	UTRA ACLR for Tx Diversity.....	1061
6.5G.3	Spurious emission for Tx Diversity	1062
6.5G.3.1	General spurious emissions for Tx Diversity	1062
6.5G.3.2	Spurious emissions for UE co-existence for Tx Diversity	1063
6.5G.3.3	Additional spurious emissions for Tx Diversity.....	1064
6.5G.4	Transmit intermodulation for Tx Diversity.....	1065
7	Receiver characteristics	1067
7.1	General	1067
7.1A	General	1068
7.1I	General	1068
7.2	Diversity characteristics	1068
7.3	Reference sensitivity	1068
7.3.1	General.....	1068
7.3.2	Reference sensitivity power level	1068
7.3.3	Δ RIB,c	1093
7.3A	Reference sensitivity for CA	1093
7.3A.0	Minimum conformance requirements	1093
7.3A.0.1	General	1093
7.3A.0.2	Reference sensitivity power level for CA	1093
7.3A.0.2.1	Reference sensitivity power level for Intra-band contiguous CA.....	1093
7.3A.0.2.2	Reference sensitivity power level for Intra-band non-contiguous CA.....	1094
7.3A.0.2.3	Reference sensitivity power level for Inter-band CA	1094

7.3A.0.2.4	Reference sensitivity power level for SDL bands.....	1094
7.3A.0.3	$\Delta R_{IB,c}$ for CA.....	1096
7.3A.0.3.1	General	1096
7.3A.0.3.2	$\Delta R_{IB,c}$ for Inter-band CA.....	1096
7.3A.0.4	Reference sensitivity exceptions due to UL harmonic interference for CA.....	1098
7.3A.0.5	Reference sensitivity exceptions due to intermodulation interference due to 2UL CA	1102
7.3A.0.6	Reference sensitivity exceptions due to cross band isolation for CA.....	1111
7.3A.1	Reference sensitivity power level for 2DL CA without exception	1114
7.3A.1_1	Reference sensitivity power level for 2DL CA exceptions.....	1120
7.3A.2	Reference sensitivity power level for 3DL CA without exceptions.....	1142
7.3A.2_1	Reference sensitivity power level for 3DL CA exceptions.....	1148
7.3A.3	Reference sensitivity power level for 4DL CA.....	1154
7.3A.4	Reference sensitivity power level for 5DL CA.....	1161
7.3B	Reference sensitivity for NR-DC	1161
7.3C	Reference sensitivity for SUL	1161
7.3C.0	Minimum conformance requirements.....	1161
7.3C.0.1	General	1161
7.3C.0.2	Minimum conformance requirements for Reference sensitivity power level.....	1161
7.3C.0.3	$\Delta R_{IB,c}$ for SUL	1163
7.3C.1	General.....	1164
7.3C.2	Reference sensitivity power level for SUL	1164
7.3C.3	Reference sensitivity power level for SUL (3CC)	1177
7.3D	Reference sensitivity for UL MIMO	1177
7.3D.1	General.....	1177
7.3D.2	Reference sensitivity power level for UL MIMO	1178
7.3D.2_1	Reference sensitivity power level for SUL with UL MIMO	1179
7.3D.2_2	Reference sensitivity power level for SUL with UL MIMO (3CC).....	1181
7.3E	Reference sensitivity for V2X.....	1182
7.3E.1	General.....	1182
7.3E.2	Reference sensitivity for V2X / non-concurrent operation	1182
7.3F	Reference sensitivity for shared spectrum channel access	1184
7.3F.1	General.....	1184
7.3F.2	Reference sensitivity power level	1185
7.3F.3	$\Delta R_{IB,c}$	1189
7.3G	Reference sensitivity for Tx Diversity.....	1189
7.3I	Reference sensitivity for RedCap	1189
7.3I.1	General.....	1189
7.3I.2	Reference sensitivity power level	1189
7.4	Maximum input level	1203
7.4A	Maximum input level for CA	1206
7.4A.0	Minimum conformance requirements.....	1206
7.4A.0.1	Maximum input level for Intra-band contiguous CA	1206
7.4A.0.2	Maximum input level for Intra-band non-contiguous CA.....	1206
7.4A.0.3	Maximum input level for Inter-band CA	1207
7.4A.1	Maximum input level for CA (2DL CA)	1207
7.4A.2	Maximum input level for CA (3DL CA)	1210
7.4A.3	Maximum input level for CA (4DL CA)	1214
7.4B	Maximum input level for NR-DC	1218
7.4D	Maximum input level for UL MIMO	1218
7.4D_1	Maximum input level for SUL with UL MIMO.....	1220
7.5	Adjacent channel selectivity.....	1222
7.5A	Adjacent channel selectivity for CA.....	1228
7.5A.0	Minimum conformance requirements.....	1228
7.5A.0.1	Adjacent channel selectivity for Intra-band contiguous CA	1228
7.5A.0.2	Adjacent channel selectivity Intra-band non-contiguous CA.....	1230
7.5A.0.3	Adjacent channel selectivity Inter-band CA	1231
7.5A.1	Adjacent channel selectivity for CA (2DL CA).....	1231
7.5A.2	Adjacent channel selectivity for CA (3DL CA).....	1244
7.5A.3	Adjacent channel selectivity for CA (4DL CA).....	1253
7.5B	Adjacent channel selectivity for NR-DC.....	1261
7.5D	Adjacent channel selectivity for UL MIMO.....	1261
7.5D_1	Adjacent channel selectivity for SUL with UL MIMO	1262

7.5F	Adjacent channel selectivity	1264
7.5F.1	Adjacent channel selectivity for shared spectrum channel access	1264
7.6	Blocking characteristics	1266
7.6.1	General.....	1267
7.6.2	In-band blocking.....	1267
7.6.3	Out-of-band blocking.....	1272
7.6.4	Narrow band blocking	1278
7.6A	Blocking characteristics for CA	1281
7.6A.1	General.....	1281
7.6A.2	Inband blocking for CA	1281
7.6A.2.0	Minimum requirements.....	1281
7.6A.2.0.1	In-band blocking for Intra-band contiguous CA.....	1281
7.6A.2.0.2	In-band blocking for Intra-band non-contiguous CA	1283
7.6A.2.0.3	In-band blocking for Inter-band CA	1283
7.6A.2.1	In-band blocking for CA (2DL CA).....	1283
7.6A.2.2	In-band Blocking for CA (3DL CA)	1290
7.6A.2.3	In-band Blocking for CA (4DL CA)	1298
7.6A.3	Out-of-band blocking for CA.....	1305
7.6A.3.0	Minimum conformance requirements	1305
7.6A.3.0.1	Out-of-band blocking for Intra-band contiguous CA	1305
7.6A.3.0.2	Out-of-band blocking for Intra-band non-contiguous CA	1306
7.6A.3.0.3	Out-of-band blocking for Inter-band CA.....	1306
7.6A.3.1	Out-of-band blocking for CA (2DL CA)	1307
7.6A.3.2	Out-of-band blocking for CA (3DL CA)	1314
7.6A.3.3	Out-of-band blocking for CA (4DL CA)	1321
7.6A.4	Narrow band blocking for CA	1326
7.6A.4.0	Minimum conformance requirements	1326
7.6A.4.0.1	Narrow band blocking for Intra-band contiguous CA	1326
7.6A.4.0.2	Narrow band blocking for Intra-band non-contiguous CA	1326
7.6A.4.0.3	Narrow band blocking for Inter-band CA.....	1327
7.6A.4.1	Narrow band blocking for CA (2DL CA)	1327
7.6A.4.2	Narrow band blocking for CA (3DL CA)	1331
7.6A.4.3	Narrow band blocking for CA (4DL CA)	1334
7.6B	Blocking characteristics for NR-DC.....	1336
7.6C	Blocking characteristics for SUL	1337
7.6C.1	General.....	1337
7.6C.2	In-band blocking for SUL.....	1337
7.6C.2_1	Inband Blocking for SUL with DL CA.....	1338
7.6C.2_1.1	Inband Blocking for SUL with 2 DL CA	1338
7.6C.3	Out-of-band blocking for SUL.....	1340
7.6C.3_1	Out-of-band blocking for SUL with DL CA.....	1343
7.6C.3_1.1	Out-of-band Blocking for SUL with 2 DL CA	1343
7.6D	Blocking characteristics for UL MIMO	1346
7.6D.1	General.....	1346
7.6D.2	In-band blocking for UL MIMO.....	1346
7.6D.2_1	In-band blocking for SUL with UL MIMO	1348
7.6D.3	Out-of-band blocking for UL MIMO.....	1349
7.6D.3_1	Out-of-band blocking for SUL with UL MIMO	1350
7.6D.4	Narrow band blocking for UL MIMO	1352
7.6D.4_1	Narrow band blocking for SUL with UL MIMO.....	1353
7.6E	Blocking characteristics for V2X	1354
7.6E.1	General.....	1354
7.6E.2	In-band blocking for V2X.....	1355
7.6E.2.0	Minimum conformance requirements	1355
7.6E.2.1	In-band blocking for V2X / non-concurrent operation.....	1355
7.6E.2.2	In-band blocking for V2X / con-current operation.....	1355
7.6E.3	Out-of-band blocking for V2X	1356
7.6E.3.0	Minimum conformance requirements	1356
7.6E.3.1	Out-of-band blocking for V2X / non-concurrent operation	1356
7.6E.3.2	Out-of-band blocking for V2X / con-current operation	1356
7.6F	Blocking characteristics for shared spectrum channel access.....	1356
7.6F.1	General.....	1356

7.6F.2	In-band blocking.....	1357
7.6F.2.1	In-band blocking for shared spectrum channel access	1357
7.6F.2.1.1	Test purpose	1357
7.6F.2.1.2	Test applicability	1357
7.6F.2.1.3	Minimum conformance requirements.....	1357
7.6F.2.1.4	Test description	1358
7.6F.2.1.5	Test requirement.....	1359
7.6F.2.2	In-band blocking for Intra-band contiguous shared spectrum channel access CA.....	1360
7.6F.3	7.6F.3.....Out-of-band blocking	1360
7.7	Spurious response.....	1363
7.7A	Spurious response for CA.....	1365
7.7A.0	Minimum conformance requirements.....	1365
7.7A.0.1	Minimum conformance requirements for intra-band contiguous CA	1365
7.7A.0.2	Void.....	1366
7.7A.0.3	Minimum conformance requirements for inter-band CA.....	1366
7.7A.0.4	Minimum conformance requirements for intra-band non-contiguous CA	1366
7.7A.1	Spurious response for CA (2DL CA).....	1366
7.7A.2	Spurious response for CA (3DL CA).....	1368
7.7A.3	Spurious response for CA (4DL CA).....	1369
7.7B	Spurious response for NR-DC.....	1369
7.7D	Spurious response for UL MIMO.....	1369
7.7D_1	Spurious response for SUL with UL MIMO	1370
7.7E	Spurious response for V2X	1371
7.7E.0	Minimum conformance requirements.....	1371
7.7E.1	Spurious response for V2X / non-concurrent operation.....	1372
7.7E.2	Spurious response for V2X / con-current operation	1372
7.7F	Spurious response for shared spectrum channel access.....	1372
7.7F.1	Spurious response for shared spectrum channel access	1372
7.7F.1.1	Test Purpose.....	1372
7.7F.1.2	Test Applicability.....	1372
7.7F.1.3	Minimum Conformance Requirements.....	1372
7.7F.1.4	Test Description	1373
7.7F.1.5	Test Requirements.....	1373
7.7F.2	Intra-band contiguous shared spectrum channel access CA	1374
7.8	Intermodulation characteristics	1374
7.8.1	General.....	1374
7.8.2	Wide band Intermodulation	1374
7.8A	Intermodulation characteristics for CA	1378
7.8A.1	General.....	1378
7.8A.2	Wide band Intermodulation for CA	1378
7.8A.2.0	Minimum conformance requirements	1378
7.8A.2.0.1	Wide band Intermodulation for Intra-band contiguous CA	1378
7.8A.2.0.2	Wide band intermodulation for Intra-band non-contiguous CA	1379
7.8A.2.0.3	Wide band Intermodulation for Inter-band CA	1379
7.8A.2.1	Wide band Intermodulation for CA (2DL CA).....	1380
7.8A.2.2	Wide band Intermodulation for CA (3DL CA).....	1385
7.8A.2.3	Wide band Intermodulation for CA (4DL CA).....	1390
7.8B	Intermodulation characteristics for NR-DC	1393
7.8D	Intermodulation characteristics for UL MIMO	1393
7.8D.1	General.....	1393
7.8D.2	Wide band Intermodulation for UL MIMO	1393
7.8D.2_1	Wide band Intermodulation for SUL with UL MIMO.....	1395
7.8E	Intermodulation characteristics for V2X	1396
7.8E.1	General.....	1396
7.8E.2	Wide band Intermodulation for V2X.....	1396
7.8E.2.0	Minimum conformance requirements	1396
7.8E.2.1	Wide band Intermodulation for V2X / non-concurrent operation.....	1397
7.8E.2.2	Wide band Intermodulation for V2X / con-current operation	1397
7.8F	Intermodulation characteristics for shared spectrum channel access	1397
7.8F.1	General.....	1397
7.8F.2	Wide band Intermodulation for shared spectrum channel access	1397