

# ETSI TS 138 174 V16.8.0 (2023-07)



**5G;  
NR; Integrated Access and Backhaul (IAB)  
radio transmission and reception  
(3GPP TS 38.174 version 16.8.0 Release 16)**

[ETSI TS 138 174 V16.8.0 \(2023-07\)](https://standards.iteh.ai/catalog/standards/sist/e8546100-b420-4e9d-a7b7-a74805cab973/etsi-ts-138-174-v16-8-0-2023-07)

<https://standards.iteh.ai/catalog/standards/sist/e8546100-b420-4e9d-a7b7-a74805cab973/etsi-ts-138-174-v16-8-0-2023-07>



---

Reference

---

RTS/TSGR-0438174vg80

---

Keywords

---

5G

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

---

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://standards-portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

---

**Notice of disclaimer & limitation of liability**

---

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.  
All rights reserved.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

---

# Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

**"must"** and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

|                                                                                       |    |
|---------------------------------------------------------------------------------------|----|
| Intellectual Property Rights .....                                                    | 2  |
| Legal Notice .....                                                                    | 2  |
| Modal verbs terminology.....                                                          | 2  |
| Foreword.....                                                                         | 15 |
| 1 Scope .....                                                                         | 17 |
| 2 References .....                                                                    | 17 |
| 3 Definitions, symbols and abbreviations .....                                        | 18 |
| 3.1 Definitions .....                                                                 | 18 |
| 3.2 Symbols.....                                                                      | 22 |
| 3.3 Abbreviations .....                                                               | 24 |
| 4 General .....                                                                       | 26 |
| 4.1 Relationship with other core specifications.....                                  | 26 |
| 4.2 Relationship between minimum requirements and test requirements .....             | 26 |
| 4.3 Conducted and radiated requirement reference points .....                         | 26 |
| 4.3.2 IAB type 1-H .....                                                              | 26 |
| 4.3.3 IAB type 1-O and IAB type 2-O.....                                              | 27 |
| 4.4 IAB classes.....                                                                  | 28 |
| 4.4.1 IAB-DU classes .....                                                            | 28 |
| 4.4.2 IAB-MT classes.....                                                             | 28 |
| 4.5 Regional requirements.....                                                        | 29 |
| 4.6 Applicability of requirements.....                                                | 29 |
| 4.7 Applicability of RRM requirements in this specification.....                      | 31 |
| 4.7.1 Applicability of signalling characteristics related RRM requirements .....      | 31 |
| 4.8 Requirements for contiguous and non-contiguous spectrum.....                      | 32 |
| 4.9 Requirements for IAB-DU and IAB-MT capable of multi-band operation.....           | 32 |
| 4.10 OTA co-location with other base stations .....                                   | 33 |
| 5 Operating bands and channel arrangement.....                                        | 34 |
| 5.1 General .....                                                                     | 34 |
| 5.2 Operating bands.....                                                              | 35 |
| 5.3 Channel bandwidth.....                                                            | 35 |
| 5.3.1 General.....                                                                    | 35 |
| 5.3.2 Transmission bandwidth configuration.....                                       | 36 |
| 5.3.3 Minimum guardband and transmission bandwidth configuration.....                 | 36 |
| 5.3.4 RB alignment.....                                                               | 36 |
| 5.3.5 IAB-DU and IAB-MT channel bandwidth per operating band.....                     | 36 |
| 5.3A IAB-DU and IAB-MT channel bandwidth for CA.....                                  | 37 |
| 5.4 Channel arrangement.....                                                          | 37 |
| 5.4.1 Channel spacing.....                                                            | 37 |
| 5.4.2 Channel raster .....                                                            | 37 |
| 5.4.2.1 NR-ARFCN and channel raster.....                                              | 37 |
| 5.4.2.2 Channel raster to resource element mapping.....                               | 37 |
| 5.4.2.3 Channel raster entries for each <i>operating band</i> .....                   | 37 |
| 5.4.3 Synchronization raster .....                                                    | 37 |
| 5.4.3.1 Synchronization raster and numbering.....                                     | 37 |
| 5.4.3.2 Synchronization raster to synchronization block resource element mapping..... | 37 |
| 5.4.3.3 Synchronization raster entries for each operating band.....                   | 38 |
| 6 Conducted transmitter characteristics .....                                         | 38 |
| 6.1 General .....                                                                     | 38 |
| 6.2 IAB output power.....                                                             | 38 |
| 6.2.1 General.....                                                                    | 38 |
| 6.2.2 Minimum requirement for IAB type 1-H.....                                       | 39 |
| 6.2.3 Additional requirements (regional).....                                         | 39 |

|             |                                                                                          |    |
|-------------|------------------------------------------------------------------------------------------|----|
| 6.3         | Output power dynamics.....                                                               | 39 |
| 6.3.1       | IAB-DU Output Power Dynamics .....                                                       | 39 |
| 6.3.1.1     | General.....                                                                             | 39 |
| 6.3.1.2     | RE power control dynamic range.....                                                      | 39 |
| 6.3.1.2.1   | General .....                                                                            | 39 |
| 6.3.1.2.2   | Minimum requirement for <i>IAB-DU type 1-H</i> .....                                     | 39 |
| 6.3.1.3     | Total power dynamic range.....                                                           | 39 |
| 6.3.1.3.1   | General .....                                                                            | 39 |
| 6.3.1.3.2   | Minimum requirement for <i>IAB-DU type 1-H</i> .....                                     | 40 |
| 6.3.2       | IAB-MT Output Power Dynamics .....                                                       | 40 |
| 6.3.2.1     | Total power dynamic range.....                                                           | 40 |
| 6.3.2.1.1   | General .....                                                                            | 40 |
| 6.3.2.1.2   | Minimum requirement for <i>IAB-MT type 1-H</i> .....                                     | 40 |
| 6.3.3       | Power control.....                                                                       | 40 |
| 6.3.3.1     | Relative power tolerance for local area IAB-MT type 1-H.....                             | 40 |
| 6.3.3.2     | Aggregate power tolerance for local area IAB-MT type 1-H.....                            | 40 |
| 6.4         | Transmit ON/OFF power .....                                                              | 41 |
| 6.4.1       | Transmitter OFF power .....                                                              | 41 |
| 6.4.1.1     | General .....                                                                            | 41 |
| 6.4.1.3     | Minimum requirement for <i>IAB-DU type 1-H</i> .....                                     | 41 |
| 6.4.1.4     | Minimum requirement for <i>IAB-MT type 1-H</i> .....                                     | 41 |
| 6.4.2       | Transmitter transient period.....                                                        | 41 |
| 6.4.2.1     | General .....                                                                            | 41 |
| 6.4.2.2     | Minimum requirement for <i>IAB-DU type 1-H</i> .....                                     | 42 |
| 6.4.2.3     | Minimum requirement for <i>IAB-MT type 1-H</i> .....                                     | 42 |
| 6.5         | Transmitted signal quality .....                                                         | 42 |
| 6.5.1       | Frequency error.....                                                                     | 42 |
| 6.5.1.1     | IAB-DU frequency error .....                                                             | 42 |
| 6.5.1.2     | IAB-MT frequency error.....                                                              | 42 |
| 6.5.2       | Modulation quality.....                                                                  | 42 |
| 6.5.2.1     | IAB-DU modulation quality.....                                                           | 42 |
| 6.5.2.2     | IAB-MT modulation quality .....                                                          | 43 |
| 6.5.2.2.1   | General .....                                                                            | 43 |
| 6.5.2.2.2   | Minimum requirements for <i>IAB-MT type 1-H</i> .....                                    | 43 |
| 6.5.2.2.3   | EVM frame structure for measurement .....                                                | 43 |
| 6.5.3       | Time alignment error .....                                                               | 43 |
| 6.5.3.1     | IAB-DU time alignment error.....                                                         | 43 |
| 6.6         | Unwanted emissions.....                                                                  | 43 |
| 6.6.1       | General.....                                                                             | 43 |
| 6.6.2       | Occupied bandwidth .....                                                                 | 44 |
| 6.6.2.1     | General .....                                                                            | 44 |
| 6.6.2.2     | Minimum requirement for <i>IAB-DU type 1-H</i> .....                                     | 44 |
| 6.6.2.3     | Minimum requirement for <i>IAB-MT type 1-H</i> .....                                     | 44 |
| 6.6.3       | Adjacent Channel Leakage Power Ratio .....                                               | 44 |
| 6.6.3.1     | General .....                                                                            | 44 |
| 6.6.3.2     | Limits and <i>Basic limits</i> .....                                                     | 45 |
| 6.6.3.3     | Minimum requirement for <i>IAB-DU type 1-H</i> and <i>IAB-MT type 1-H</i> .....          | 47 |
| 6.6.4       | Operating band unwanted emissions .....                                                  | 48 |
| 6.6.4.1     | General .....                                                                            | 48 |
| 6.6.4.2     | <i>Basic limits</i> .....                                                                | 50 |
| 6.6.4.2.1   | <i>Basic limits</i> for Wide Area IAB-DU and Wide Area IAB-MT (Category A) .....         | 50 |
| 6.6.4.2.2   | <i>Basic limits</i> for Wide Area IAB-DU and Wide Area IAB-MT (Category B) .....         | 50 |
| 6.6.4.2.2.1 | Category B requirements .....                                                            | 50 |
| 6.6.4.2.3   | <i>Basic limits</i> for Medium Range IAB-DU (Category A and B).....                      | 51 |
| 6.6.4.2.4   | <i>Basic limits</i> for Local Area IAB-DU and Local Area IAB-MT (Category A and B) ..... | 52 |
| 6.6.4.2.5   | <i>Basic limits</i> for additional requirements.....                                     | 52 |
| 6.6.4.2.5.1 | Limits in FCC Title 47.....                                                              | 52 |
| 6.6.4.3     | Minimum requirements for <i>IAB-DU type 1-H</i> and <i>IAB-MT type 1-H</i> .....         | 52 |
| 6.6.5       | Transmitter spurious emissions.....                                                      | 53 |
| 6.6.5.1     | General.....                                                                             | 53 |
| 6.6.5.2     | <i>Basic limits</i> .....                                                                | 54 |
| 6.6.5.2.1   | General transmitter spurious emissions requirements .....                                | 54 |

|                            |                                                                                  |    |
|----------------------------|----------------------------------------------------------------------------------|----|
| 6.6.5.2.2                  | Additional spurious emissions requirements .....                                 | 54 |
| 6.6.5.2.3                  | Co-location with base stations and IAB-Nodes .....                               | 61 |
| 6.6.5.3                    | Minimum requirements for <i>IAB-DU</i> and <i>IAB-MT type 1-H</i> .....          | 66 |
| 6.7                        | Transmitter intermodulation .....                                                | 66 |
| 6.7.1                      | General.....                                                                     | 66 |
| 6.7.2                      | Minimum requirements for <i>IAB-DU type 1-H</i> and <i>IAB-MT type 1-H</i> ..... | 67 |
| 6.7.2.1                    | Co-location minimum requirements.....                                            | 67 |
| 6.7.2.2                    | Intra-system minimum requirements.....                                           | 67 |
| 7                          | Conducted receiver characteristics .....                                         | 68 |
| 7.1                        | General .....                                                                    | 68 |
| 7.2                        | Reference sensitivity level.....                                                 | 68 |
| 7.2.1                      | <i>IAB-DU</i> reference sensitivity level .....                                  | 68 |
| 7.2.1.1                    | General .....                                                                    | 68 |
| 7.2.1.2                    | Minimum requirements for <i>IAB-DU type 1-H</i> .....                            | 69 |
| 7.2.2                      | <i>IAB-MT</i> reference sensitivity level .....                                  | 69 |
| <b>Table 7.2.2-2: Void</b> | .....                                                                            | 69 |
| 7.2.2.1                    | General.....                                                                     | 69 |
| 7.2.2.2                    | Minimum requirements for <i>IAB-MT type 1-H</i> .....                            | 69 |
| 7.3                        | Dynamic range .....                                                              | 70 |
| 7.3.1                      | <i>IAB-DU</i> dynamic range.....                                                 | 70 |
| 7.3.1.1                    | General .....                                                                    | 70 |
| 7.3.1.2                    | Minimum requirement for <i>IAB-DU type 1-H</i> .....                             | 70 |
| 7.4                        | In-band selectivity and blocking .....                                           | 70 |
| 7.4.1                      | Adjacent Channel Selectivity (ACS) .....                                         | 70 |
| 7.4.1.1                    | General .....                                                                    | 70 |
| 7.4.1.2                    | Minimum requirement for <i>IAB-DU type 1-H</i> .....                             | 71 |
| 7.4.1.3                    | Minimum requirement for <i>IAB-MT type 1-H</i> .....                             | 71 |
| 7.4.2                      | In-band blocking.....                                                            | 72 |
| 7.4.2.1                    | General .....                                                                    | 72 |
| 7.4.2.2                    | Minimum requirement for <i>IAB-DU type 1-H</i> .....                             | 72 |
| 7.4.2.3                    | Minimum requirement for <i>IAB-MT type 1-H</i> .....                             | 72 |
| 7.5                        | Out-of-band blocking .....                                                       | 74 |
| 7.5.1                      | General.....                                                                     | 74 |
| 7.5.2                      | Void .....                                                                       | 74 |
| 7.5.3                      | Minimum requirement for <i>IAB-DU type 1-H</i> .....                             | 74 |
| 7.5.4                      | Co-location minimum requirements for <i>IAB-DU type 1-H</i> .....                | 74 |
| 7.5.5                      | Minimum requirement for <i>IAB-MT type 1-H</i> .....                             | 75 |
| 7.5.6                      | Co-location minimum requirements for <i>IAB-MT type 1-H</i> .....                | 75 |
| 7.6                        | Receiver spurious emissions.....                                                 | 76 |
| 7.6.1                      | General.....                                                                     | 76 |
| 7.6.2                      | <i>IAB-DU</i> receiver spurious emissions .....                                  | 76 |
| 7.6.2.1                    | Basic limits.....                                                                | 76 |
| 7.6.2.2                    | Minimum requirement for <i>IAB-DU type 1-H</i> .....                             | 77 |
| 7.6.3                      | <i>IAB-MT</i> receiver spurious emissions .....                                  | 77 |
| 7.6.3.1                    | Basic limits.....                                                                | 77 |
| 7.6.3.2                    | Minimum requirement for <i>IAB-MT type 1-H</i> .....                             | 78 |
| 7.7                        | Receiver intermodulation .....                                                   | 78 |
| 7.7.1                      | General.....                                                                     | 78 |
| 7.7.2                      | Minimum requirement for <i>IAB-DU type 1-H</i> .....                             | 78 |
| 7.7.3                      | Minimum requirement for <i>IAB-MT type 1-H</i> .....                             | 79 |
| 7.8                        | In-channel selectivity .....                                                     | 79 |
| 7.8.1                      | General.....                                                                     | 79 |
| 7.8.2                      | Minimum requirement for <i>IAB-DU type 1-H</i> .....                             | 79 |
| 8                          | Conducted performance requirements.....                                          | 79 |
| 8.1                        | <i>IAB-DU</i> performance requirements .....                                     | 79 |
| 8.1.1                      | General.....                                                                     | 79 |
| 8.1.2                      | Performance requirements for PUSCH.....                                          | 80 |
| 8.1.2.1                    | Requirements for PUSCH with transform precoding disabled .....                   | 80 |
| 8.1.2.1.1                  | General .....                                                                    | 80 |
| 8.1.2.1.2                  | Minimum requirements .....                                                       | 80 |



|           |                                                               |     |
|-----------|---------------------------------------------------------------|-----|
| 8.1.2.2   | Requirements for PUSCH with transform precoding enabled ..... | 87  |
| 8.1.2.2.1 | General .....                                                 | 87  |
| 8.1.2.2.2 | Minimum requirements .....                                    | 88  |
| 8.1.2.3   | Requirements for UCI multiplexed on PUSCH .....               | 89  |
| 8.1.2.3.1 | General .....                                                 | 89  |
| 8.1.2.3.2 | Minimum requirements .....                                    | 90  |
| 8.1.3     | Performance requirements for PUCCH .....                      | 91  |
| 8.1.3.1   | DTX to ACK probability .....                                  | 91  |
| 8.1.3.1.1 | General .....                                                 | 91  |
| 8.1.3.1.2 | Minimum requirement .....                                     | 92  |
| 8.1.3.2   | Performance requirements for PUCCH format 0 .....             | 92  |
| 8.1.3.2.1 | General .....                                                 | 92  |
| 8.1.3.2.2 | Minimum requirement .....                                     | 92  |
| 8.1.3.3   | Performance requirements for PUCCH format 1 .....             | 93  |
| 8.1.3.3.1 | NACK to ACK requirements .....                                | 93  |
| 8.1.3.3.2 | ACK missed detection requirements .....                       | 94  |
| 8.1.3.4   | Performance requirements for PUCCH format 2 .....             | 95  |
| 8.1.3.4.1 | NACK to ACK requirements .....                                | 95  |
| 8.1.3.4.2 | UCI BLER performance requirements .....                       | 96  |
| 8.1.3.5   | Performance requirements for PUCCH format 3 .....             | 97  |
| 8.1.3.5.1 | General .....                                                 | 97  |
| 8.1.3.5.2 | Minimum requirements .....                                    | 98  |
| 8.1.3.6   | Performance requirements for PUCCH format 4 .....             | 98  |
| 8.1.3.6.1 | General .....                                                 | 98  |
| 8.1.3.6.2 | Minimum requirement .....                                     | 99  |
| 8.1.3.7   | Performance requirements for multi-slot PUCCH .....           | 100 |
| 8.1.3.7.1 | General .....                                                 | 100 |
| 8.1.3.7.2 | Performance requirements for multi-slot PUCCH format 1 .....  | 100 |
| 8.1.4     | Performance requirements for PRACH .....                      | 101 |
| 8.1.4.1   | PRACH false alarm probability .....                           | 101 |
| 8.1.4.1.1 | General .....                                                 | 101 |
| 8.1.4.1.2 | Minimum requirement .....                                     | 102 |
| 8.1.4.2   | PRACH detection requirements .....                            | 102 |
| 8.1.4.2.1 | General .....                                                 | 102 |
| 8.1.4.2.2 | Minimum requirements for normal mode .....                    | 102 |
| 8.2       | IAB-MT requirements .....                                     | 103 |
| 8.2.1     | General .....                                                 | 103 |
| 8.2.2     | Demodulation performance requirements .....                   | 103 |
| 8.2.2.1   | Performance requirements for PDSCH .....                      | 103 |
| 8.2.2.1.1 | General .....                                                 | 103 |
| 8.2.2.1.2 | Minimum requirements .....                                    | 104 |
| 8.2.2.2   | Performance requirements for PDCCH .....                      | 105 |
| 8.2.2.2.1 | General .....                                                 | 105 |
| 8.2.2.2.2 | Minimum requirements .....                                    | 105 |
| 8.2.3     | CSI reporting requirements .....                              | 106 |
| 8.2.3.1   | General .....                                                 | 106 |
| 8.2.3.1.1 | Common test parameters .....                                  | 106 |
| 8.2.3.2   | Reporting of Channel Quality Indicator (CQI) .....            | 108 |
| 8.2.3.2.1 | General .....                                                 | 108 |
| 8.2.3.2.2 | Minimum requirements .....                                    | 108 |
| 8.2.3.3   | Reporting of Precoding Matrix Indicator (PMI) .....           | 109 |
| 8.2.3.3.1 | General .....                                                 | 109 |
| 8.2.3.3.2 | Minimum requirements .....                                    | 111 |
| 8.2.3.4   | Reporting of Rank Indicator (RI) .....                        | 111 |
| 8.2.3.4.1 | General .....                                                 | 111 |
| 8.2.3.4.2 | Minimum requirements .....                                    | 112 |
| 9         | Radiated transmitter characteristics .....                    | 113 |
| 9.1       | General .....                                                 | 113 |
| 9.2       | Radiated transmit power .....                                 | 113 |
| 9.2.1     | General .....                                                 | 113 |

|           |                                                                                                     |     |
|-----------|-----------------------------------------------------------------------------------------------------|-----|
| 9.2.2     | Minimum requirement for IAB-DU type 1-H, IAB-DU type 1-O, IAB-MT type 1-H and IAB-MT type 1-O ..... | 114 |
| 9.2.3     | Minimum requirement for IAB-DU type 2-O and IAB-MT type 2-O .....                                   | 114 |
| 9.2.4     | Configured radiated output power .....                                                              | 114 |
| 9.2.4.1   | IAB-MT configured output power for IAB-MT type 1-H, 1-O and 2-O .....                               | 114 |
| 9.3       | OTA IAB output power .....                                                                          | 114 |
| 9.3.1     | General .....                                                                                       | 114 |
| 9.3.2     | Minimum requirement for IAB-DU type 1-O and IAB-MT type 1-O .....                                   | 115 |
| 9.3.3     | Minimum requirement for IAB type 2-O .....                                                          | 115 |
| 9.4       | OTA output power dynamics .....                                                                     | 115 |
| 9.4.1     | IAB-DU OTA Output Power Dynamics .....                                                              | 115 |
| 9.4.1.1   | General .....                                                                                       | 115 |
| 9.4.1.2   | OTA RE power control dynamic range .....                                                            | 115 |
| 9.4.1.2.1 | General .....                                                                                       | 115 |
| 9.4.1.2.2 | Minimum requirement for <i>IAB-DU type 1-O</i> .....                                                | 116 |
| 9.4.1.3   | OTA total power dynamic range .....                                                                 | 116 |
| 9.4.1.3.1 | General .....                                                                                       | 116 |
| 9.4.1.3.2 | Minimum requirement for <i>IAB-DU type 1-O</i> .....                                                | 116 |
| 9.4.1.3.3 | Minimum requirement for <i>IAB-DU type 2-O</i> .....                                                | 116 |
| 9.4.2     | IAB-MT OTA Output Power Dynamics .....                                                              | 116 |
| 9.4.2.1   | OTA total power dynamic range .....                                                                 | 116 |
| 9.4.2.1.1 | General .....                                                                                       | 116 |
| 9.4.2.1.2 | Minimum requirement for IAB-MT type 1-O .....                                                       | 116 |
| 9.4.2.1.3 | Minimum requirement for IAB-MT type 2-O .....                                                       | 116 |
| 9.4.3     | Power control .....                                                                                 | 117 |
| 9.4.3.1   | Power control for local area IAB-MT type 1-O .....                                                  | 117 |
| 9.4.3.1.1 | Relative EIRP tolerance for local area IAB-MT type 1-O .....                                        | 117 |
| 9.4.3.1.2 | Aggregate EIRP tolerance for local area IAB-MT type 1-O .....                                       | 117 |
| 9.4.3.2   | Power control for local area IAB-MT type 2-O .....                                                  | 117 |
| 9.4.3.2.1 | Relative EIRP tolerance for local area IAB-MT type 2-O .....                                        | 117 |
| 9.4.3.2.2 | Aggregate EIRP tolerance for local area IAB-MT type 2-O .....                                       | 118 |
| 9.5       | OTA transmit ON/OFF power .....                                                                     | 118 |
| 9.5.1     | General .....                                                                                       | 118 |
| 9.5.2     | OTA transmitter OFF power .....                                                                     | 118 |
| 9.5.2.1   | General .....                                                                                       | 118 |
| 9.5.2.2   | Minimum requirement for IAB-DU type 1-O .....                                                       | 118 |
| 9.5.2.3   | Minimum requirement for IAB-DU type 2-O .....                                                       | 119 |
| 9.5.2.4   | Minimum requirement for IAB-MT type 1-O .....                                                       | 119 |
| 9.5.2.5   | Minimum requirement for IAB-MT type 2-O .....                                                       | 119 |
| 9.5.3     | OTA transient period .....                                                                          | 119 |
| 9.5.3.1   | General .....                                                                                       | 119 |
| 9.5.3.2   | Minimum requirement for IAB-DU type 1-O .....                                                       | 119 |
| 9.5.3.3   | Minimum requirement for IAB-DU type 2-O .....                                                       | 119 |
| 9.5.3.4   | Minimum requirement for IAB-MT type 1-O .....                                                       | 119 |
| 9.5.3.5   | Minimum requirement for IAB-MT type 2-O .....                                                       | 119 |
| 9.6       | OTA transmitted signal quality .....                                                                | 119 |
| 9.6.1     | OTA frequency error .....                                                                           | 119 |
| 9.6.1.1   | IAB-DU OTA frequency error .....                                                                    | 119 |
| 9.6.1.2   | IAB-MT OTA frequency error .....                                                                    | 119 |
| 9.6.1.2.1 | General .....                                                                                       | 119 |
| 9.6.1.2.2 | Minimum requirement for IAB-MT type 1-O .....                                                       | 120 |
| 9.6.1.2.3 | Minimum requirement for IAB-MT type 2-O .....                                                       | 120 |
| 9.6.2     | OTA modulation quality .....                                                                        | 120 |
| 9.6.2.1   | IAB-DU OTA modulation quality .....                                                                 | 120 |
| 9.6.2.2   | IAB-MT OTA modulation quality .....                                                                 | 120 |
| 9.6.2.2.1 | General .....                                                                                       | 120 |
| 9.6.2.2.2 | Minimum requirement for IAB-MT type 1-O .....                                                       | 120 |
| 9.6.2.2.3 | Minimum requirement for IAB-MT type 2-O .....                                                       | 120 |
| 9.6.2.2.4 | EVM frame structure for measurement .....                                                           | 120 |
| 9.6.3     | OTA time alignment error .....                                                                      | 121 |
| 9.6.3.1   | IAB-DU OTA time alignment error .....                                                               | 121 |
| 9.7       | OTA unwanted emissions .....                                                                        | 121 |



|             |                                                                                           |     |
|-------------|-------------------------------------------------------------------------------------------|-----|
| 9.7.1       | General.....                                                                              | 121 |
| 9.7.2       | OTA occupied bandwidth.....                                                               | 121 |
| 9.7.2.1     | General.....                                                                              | 121 |
| 9.7.2.2     | Minimum requirement for <i>IAB-DU type 1-O</i> and <i>IAB-DU type 2-O</i> .....           | 122 |
| 9.7.2.3     | Minimum requirement for <i>IAB-MT type 1-O</i> and <i>IAB-MT type 2-O</i> .....           | 122 |
| 9.7.3       | OTA Adjacent Channel Leakage Power Ratio (ACLR).....                                      | 122 |
| 9.7.3.1     | General.....                                                                              | 122 |
| 9.7.3.2     | Minimum requirement for <i>IAB-DU type 1-O</i> and <i>IAB-MT type 1-O</i> .....           | 122 |
| 9.7.3.3     | Minimum requirement for <i>IAB-DU type 2-O</i> and <i>Wide Area IAB-MT type 2-O</i> ..... | 122 |
| 9.7.3.4     | Minimum requirement for <i>Local Area IAB-MT type 2-O</i> .....                           | 124 |
| 9.7.4       | OTA operating band unwanted emissions.....                                                | 126 |
| 9.7.4.1     | General.....                                                                              | 126 |
| 9.7.4.2     | Minimum requirement for <i>IAB-DU type 1-O</i> .....                                      | 126 |
| 9.7.4.3     | Minimum requirement for <i>IAB-MT type 1-O</i> .....                                      | 127 |
| 9.7.4.4     | Additional requirements.....                                                              | 127 |
| 9.7.4.4.1   | Limits in FCC Title 47.....                                                               | 127 |
| 9.7.4.5     | Minimum requirement for <i>IAB-DU type 2-O</i> and <i>IAB-MT type 2-O</i> .....           | 127 |
| 9.7.4.5.1   | General.....                                                                              | 127 |
| 9.7.4.5.2   | OTA operating band unwanted emission limits (Category A).....                             | 128 |
| 9.7.4.5.3   | OTA operating band unwanted emission limits (Category B).....                             | 129 |
| 9.7.4.5.4   | Additional OTA operating band unwanted emission requirements.....                         | 129 |
| 9.7.5       | OTA transmitter spurious emissions.....                                                   | 130 |
| 9.7.5.1     | General.....                                                                              | 130 |
| 9.7.5.2     | Minimum requirement for <i>IAB-DU type 1-O</i> and <i>IAB-MT type 1-O</i> .....           | 130 |
| 9.7.5.2.1   | General.....                                                                              | 130 |
| 9.7.5.2.2   | General OTA transmitter spurious emissions requirements.....                              | 130 |
| 9.7.5.2.3   | Additional spurious emissions requirements.....                                           | 130 |
| 9.7.5.2.4   | Co-location with other base stations and IAB-Nodes.....                                   | 131 |
| 9.7.5.3     | Minimum requirement for <i>IAB-DU type 2-O</i> and <i>IAB-MT type 2-O</i> .....           | 131 |
| 9.7.5.3.1   | General.....                                                                              | 131 |
| 9.7.5.3.2   | General OTA transmitter spurious emissions requirements.....                              | 131 |
| 9.7.5.3.2.1 | General.....                                                                              | 131 |
| 9.7.5.3.2.2 | OTA transmitter spurious emissions (Category A).....                                      | 131 |
| 9.7.5.3.2.3 | OTA transmitter spurious emissions (Category B).....                                      | 131 |
| 9.7.5.3.3   | Additional OTA transmitter spurious emissions requirements.....                           | 132 |
| 9.7.5.3.3.1 | Limits for protection of Earth Exploration Satellite Service.....                         | 132 |
| 9.8         | OTA transmitter intermodulation.....                                                      | 133 |
| 9.8.1       | General.....                                                                              | 133 |
| 9.8.2       | Minimum requirement for <i>IAB-DU type 1-O</i> and <i>IAB-MT type 1-O</i> .....           | 133 |
| 10          | Radiated receiver characteristics.....                                                    | 134 |
| 10.1        | General.....                                                                              | 134 |
| 10.2        | OTA sensitivity.....                                                                      | 135 |
| 10.2.1      | IAB-DU OTA sensitivity.....                                                               | 135 |
| 10.2.1.1    | IAB-DU type 1-H and IAB-DU type 1-O.....                                                  | 135 |
| 10.2.1.2    | IAB-DU type 2-O.....                                                                      | 135 |
| 10.2.2      | IAB-MT OTA sensitivity.....                                                               | 135 |
| 10.2.2.1    | IAB-MT type 1-H and IAB-MT type 1-O.....                                                  | 135 |
| 10.2.2.1.1  | General.....                                                                              | 135 |
| 10.2.2.1.2  | Minimum requirement.....                                                                  | 136 |
| 10.2.2.2    | IAB-MT type 2-O.....                                                                      | 136 |
| 10.3        | OTA reference sensitivity level.....                                                      | 136 |
| 10.3.1      | General.....                                                                              | 136 |
| 10.3.2      | IAB-DU OTA reference sensitivity level.....                                               | 136 |
| 10.3.2.1    | Minimum requirement for <i>IAB-DU type 1-O</i> .....                                      | 136 |
| 10.3.2.2    | Minimum requirement for <i>IAB-DU type 2-O</i> .....                                      | 136 |
| 10.3.3      | IAB-MT OTA reference sensitivity level.....                                               | 136 |
| 10.3.3.1    | General.....                                                                              | 136 |
| 10.3.3.2    | Minimum requirement for <i>IAB-MT type 1-O</i> .....                                      | 137 |
| 10.3.3.3    | Minimum requirement for <i>IAB-MT type 2-O</i> .....                                      | 137 |
| 10.4        | OTA Dynamic range.....                                                                    | 138 |
| 10.4.1      | IAB-DU OTA dynamic range.....                                                             | 138 |

|            |                                                                                             |     |
|------------|---------------------------------------------------------------------------------------------|-----|
| 10.4.1.1   | General .....                                                                               | 138 |
| 10.4.1.2   | Minimum requirement for <i>IAB-DU type 1-O</i> .....                                        | 138 |
| 10.5       | OTA in-band selectivity and blocking .....                                                  | 138 |
| 10.5.1     | OTA adjacent channel selectivity .....                                                      | 138 |
| 10.5.1.1   | General .....                                                                               | 138 |
| 10.5.1.2   | Minimum requirement for <i>IAB-DU type 1-O</i> .....                                        | 139 |
| 10.5.1.3   | Minimum requirement for <i>IAB-DU type 2-O</i> .....                                        | 139 |
| 10.5.1.4   | Minimum requirement for <i>IAB-MT type 2-O</i> .....                                        | 139 |
| 10.5.1.5   | Minimum requirement for <i>IAB-MT type 1-O</i> .....                                        | 140 |
| 10.5.2     | OTA in-band blocking .....                                                                  | 141 |
| 10.6       | OTA out-of-band blocking .....                                                              | 144 |
| 10.6.1     | General .....                                                                               | 144 |
| 10.6.2     | Minimum requirement for <i>IAB-MT type 1-O</i> and <i>IAB-DU type 1-O</i> .....             | 144 |
| 10.6.3     | Minimum requirement for <i>IAB-MT type 2-O</i> and <i>IAB-DU type 2-O</i> .....             | 145 |
| 10.6.4     | Co-location minimum requirement for <i>IAB-MT type 1-O</i> and <i>IAB-DU type 1-O</i> ..... | 146 |
| 10.7       | OTA receiver spurious emissions .....                                                       | 146 |
| 10.7.1     | General .....                                                                               | 146 |
| 10.7.2     | <i>IAB-DU</i> OTA receiver spurious emissions .....                                         | 146 |
| 10.7.2.1   | Minimum requirement for <i>IAB-DU type 1-O</i> .....                                        | 146 |
| 10.7.2.2   | Minimum requirement for <i>IAB-DU type 2-O</i> .....                                        | 146 |
| 10.7.3     | <i>IAB-MT</i> OTA receiver spurious emissions .....                                         | 147 |
| 10.7.3.1   | Minimum requirement for <i>IAB-MT type 1-O</i> .....                                        | 147 |
| 10.7.3.2   | Minimum requirement for <i>IAB-MT type 2-O</i> .....                                        | 147 |
| 10.8       | OTA receiver intermodulation .....                                                          | 148 |
| 10.8.1     | General .....                                                                               | 148 |
| 10.8.2     | Minimum requirement for <i>IAB-DU type 1-O</i> .....                                        | 148 |
| 10.8.3     | Minimum requirement for <i>IAB-DU type 2-O</i> .....                                        | 148 |
| 10.8.4     | Minimum requirement for <i>IAB-MT type 1-O</i> .....                                        | 148 |
| 10.9       | OTA in-channel selectivity .....                                                            | 149 |
| 10.9.1     | General .....                                                                               | 149 |
| 10.9.2     | Minimum requirement for <i>IAB-DU type 1-O</i> .....                                        | 149 |
| 10.9.3     | Minimum requirement for <i>IAB-DU type 2-O</i> .....                                        | 149 |
| 11         | Radiated performance requirements .....                                                     | 149 |
| 11.1       | <i>IAB-DU</i> performance requirements .....                                                | 149 |
| 11.1.1     | General .....                                                                               | 149 |
| 11.1.2     | OTA demodulation branches .....                                                             | 150 |
| 11.1.2     | Performance requirements for PUSCH .....                                                    | 150 |
| 11.1.2.1   | Performance requirements for <i>IAB type 1-O</i> .....                                      | 150 |
| 11.1.2.1.1 | Performance requirements for PUSCH with transform precoding disabled .....                  | 150 |
| 11.1.2.1.2 | Performance requirements for PUSCH with transform precoding enabled .....                   | 150 |
| 11.1.2.1.3 | Performance requirements for UCI multiplexed on PUSCH .....                                 | 150 |
| 11.1.2.2   | Performance requirements for <i>IAB type 2-O</i> .....                                      | 151 |
| 11.1.2.2.1 | Performance requirements for PUSCH with transform precoding disabled .....                  | 151 |
| 11.1.2.2.2 | Performance requirements for PUSCH with transform precoding enabled .....                   | 153 |
| 11.1.2.2.3 | Performance requirements for UCI multiplexed on PUSCH .....                                 | 154 |
| 11.1.3     | Performance requirements for PUCCH .....                                                    | 157 |
| 11.1.3.1   | Performance requirements for <i>IAB type 1-O</i> .....                                      | 157 |
| 11.1.3.1.1 | DTX to ACK probability .....                                                                | 157 |
| 11.1.3.1.2 | Performance requirements for PUCCH format 0 .....                                           | 157 |
| 11.1.3.1.3 | Performance requirements for PUCCH format 1 .....                                           | 157 |
| 11.1.3.1.4 | Performance requirements for PUCCH format 2 .....                                           | 157 |
| 11.1.3.1.5 | Performance requirements for PUCCH format 3 .....                                           | 157 |
| 11.1.3.1.6 | Performance requirements for PUCCH format 4 .....                                           | 158 |
| 11.1.3.1.7 | Performance requirements for multi-slot PUCCH .....                                         | 158 |
| 11.1.3.2   | Performance requirements for <i>IAB type 2-O</i> .....                                      | 158 |
| 11.1.3.2.1 | DTX to ACK probability .....                                                                | 158 |
| 11.1.3.2.2 | Performance requirements for PUCCH format 0 .....                                           | 158 |
| 11.1.3.2.3 | Performance requirements for PUCCH format 1 .....                                           | 159 |
| 11.1.3.2.4 | Performance requirements for PUCCH format 2 .....                                           | 160 |
| 11.1.3.2.5 | Performance requirements for PUCCH format 3 .....                                           | 162 |
| 11.1.3.2.6 | Performance requirements for PUCCH format 4 .....                                           | 163 |

|              |                                                                 |     |
|--------------|-----------------------------------------------------------------|-----|
| 11.1.4       | Performance requirements for PRACH .....                        | 164 |
| 11.1.4.1     | Performance requirements for IAB type 1-O .....                 | 164 |
| 11.1.4.1.1   | PRACH False alarm probability.....                              | 164 |
| 11.1.4.1.2   | PRACH detection requirements .....                              | 164 |
| 11.1.4.2     | Performance requirements for IAB type 2-O .....                 | 164 |
| 11.1.4.2.1   | PRACH false alarm probability.....                              | 164 |
| 11.1.4.2.2   | PRACH missed detection requirements .....                       | 164 |
| 11.2         | IAB-MT performance requirements .....                           | 165 |
| 11.2.1       | General.....                                                    | 165 |
| 11.2.2       | OTA demodulation branches .....                                 | 166 |
| 11.2.2       | Demodulation performance requirements.....                      | 166 |
| 11.2.2.1     | Performance requirements for IAB type 1-O .....                 | 166 |
| 11.2.2.1.1   | Performance requirements for PDSCH .....                        | 166 |
| 11.2.2.1.2   | Performance requirements for PDCCH .....                        | 167 |
| 11.2.2.2     | Performance requirements for IAB type 2-O .....                 | 168 |
| 11.2.2.2.1   | Performance requirements for PDSCH .....                        | 168 |
| 11.2.2.2.2   | Performance requirements for PDCCH .....                        | 170 |
| 11.2.3       | CSI reporting requirements.....                                 | 171 |
| 11.2.3.1     | Performance requirements for IAB type 1-O .....                 | 171 |
| 11.2.3.1.1   | Reporting of Channel Quality Indicator (CQI).....               | 171 |
| 11.2.3.1.2   | Reporting of Precoding Matrix Indicator (PMI).....              | 171 |
| 11.2.3.1.3   | Reporting of Rank Indicator (RI) .....                          | 171 |
| 11.2.3.2     | Performance requirements for IAB type 2-O .....                 | 171 |
| 11.2.3.2.1   | General .....                                                   | 171 |
| 11.2.3.2.2   | Reporting of Channel Quality Indicator (CQI).....               | 173 |
| 11.2.3.2.3   | Reporting of Precoding Matrix Indicator (PMI).....              | 174 |
| 11.2.3.2.4   | Reporting of Rank Indicator (RI) .....                          | 176 |
| 12           | Radio Resource Management requirements.....                     | 178 |
| 12.1         | RRC_CONNECTED state mobility for IAB-MTs.....                   | 178 |
| 12.1.1       | RRC Connection Mobility Control.....                            | 178 |
| 12.1.1.1     | SA: RRC Re-establishment.....                                   | 178 |
| 12.1.1.1.1   | Introduction .....                                              | 178 |
| 12.1.1.1.2   | Requirements .....                                              | 178 |
| 12.1.1.1.2.1 | IAB MT Re-establishment delay requirement .....                 | 178 |
| 12.1.1.2     | Random access .....                                             | 179 |
| 12.1.1.3     | SA: RRC Connection Release with Redirection .....               | 180 |
| 12.1.1.3.1   | Introduction .....                                              | 180 |
| 12.1.1.3.2   | Requirements .....                                              | 180 |
| 12.1.1.3.2.1 | RRC connection release with redirection to NR .....             | 180 |
| 12.2         | Timing .....                                                    | 181 |
| 12.2.1       | IAB-MT transmit timing.....                                     | 181 |
| 12.2.1.1     | Introduction.....                                               | 181 |
| 12.2.1.2     | Requirements .....                                              | 181 |
| 12.2.1.2.1   | Gradual timing adjustment .....                                 | 182 |
| 12.2.3       | IAB-MT timing advance.....                                      | 182 |
| 12.2.4       | Cell phase synchronization accuracy .....                       | 182 |
| 12.2.4.1     | Introduction.....                                               | 182 |
| 12.2.4.2     | Requirements .....                                              | 182 |
| 12.3         | Signalling Characteristics for IAB MTs.....                     | 182 |
| 12.3.1       | Radio Link Monitoring .....                                     | 182 |
| 12.3.1.1     | Introduction.....                                               | 182 |
| 12.3.1.2     | Requirements for SSB based radio link monitoring.....           | 183 |
| 12.3.1.2.1   | Introduction .....                                              | 183 |
| 12.3.1.2.2   | Minimum requirement.....                                        | 183 |
| 12.3.1.2.3   | Measurement restrictions for SSB based RLM .....                | 184 |
| 12.3.1.3     | Requirements for CSI-RS based radio link monitoring.....        | 184 |
| 12.3.1.3.1   | Introduction .....                                              | 184 |
| 12.3.1.3.2   | Minimum requirement.....                                        | 185 |
| 12.3.1.3.3   | Measurement restrictions for CSI-RS based RLM .....             | 186 |
| 12.3.1.4     | Minimum requirement for IAB-MT turning off the transmitter..... | 186 |
| 12.3.1.5     | Minimum requirement for L1 indication.....                      | 186 |

|            |                                                                        |     |
|------------|------------------------------------------------------------------------|-----|
| 12.3.1.6   | Scheduling availability of IAB-MT during radio link monitoring .....   | 187 |
| 12.3.2     | Link Recovery Procedure .....                                          | 187 |
| 12.3.2.1   | Introduction.....                                                      | 187 |
| 12.3.2.2   | Requirements for SSB based beam failure detection .....                | 187 |
| 12.3.2.2.1 | Introduction .....                                                     | 187 |
| 12.3.2.2.2 | Minimum requirement.....                                               | 187 |
| 12.3.2.2.3 | Measurement restriction for SSB based beam failure detection .....     | 188 |
| 12.3.2.3   | Requirements for CSI-RS based beam failure detection.....              | 188 |
| 12.3.2.3.1 | Introduction .....                                                     | 188 |
| 12.3.2.3.2 | Minimum requirement.....                                               | 188 |
| 12.3.2.3.3 | Measurement restrictions for CSI-RS based beam failure detection ..... | 189 |
| 12.3.2.4   | Minimum requirement for L1 indication.....                             | 189 |
| 12.3.2.5   | Requirements for SSB based candidate beam detection .....              | 189 |
| 12.3.2.5.1 | Introduction .....                                                     | 189 |
| 12.3.2.5.2 | Minimum requirement.....                                               | 189 |
| 12.3.2.5.3 | Measurement restriction for SSB based candidate beam detection .....   | 190 |
| 12.3.2.6   | Requirements for CSI-RS based candidate beam detection .....           | 190 |
| 12.3.2.6.1 | Introduction .....                                                     | 190 |
| 12.3.2.6.2 | Minimum requirement.....                                               | 190 |
| 12.3.2.6.3 | Measurement restriction for CSI-RS based candidate beam detection..... | 191 |
| 12.3.2.7   | Scheduling availability of IAB-MT during beam failure detection.....   | 191 |
| 12.3.2.8   | Scheduling availability of IAB-MT during candidate beam detection..... | 191 |

## **Annex A (normative): IAB-MT Reference measurement channels.....193**

|       |                                                                                                                                                        |     |
|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| A.1   | Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking and receiver intermodulation (QPSK, R=1/3) ..... | 193 |
| A.2   | IAB-DU Fixed Reference Channels .....                                                                                                                  | 193 |
| A.2.1 | Fixed Reference Channels for PUSCH performance requirements (QPSK, R=193/1024) .....                                                                   | 193 |
| A.2.2 | Fixed Reference Channels for PUSCH performance requirements (16QAM, R=434/1024) .....                                                                  | 198 |
| A.2.3 | Fixed Reference Channels for PUSCH performance requirements (16QAM, R=658/1024) .....                                                                  | 199 |
| A.2.4 | Fixed Reference Channels for PUSCH performance requirements (64QAM, R=567/1024) .....                                                                  | 202 |
| A.2.5 | PRACH Test preambles.....                                                                                                                              | 204 |
| A.3   | IAB-MT Fixed Reference Channels.....                                                                                                                   | 204 |
| A.3.1 | Fixed Reference Channels for PDSCH performance requirements (16QAM) .....                                                                              | 204 |
| A.3.2 | Fixed Reference Channels for PDSCH performance requirements (64QAM) .....                                                                              | 205 |
| A.3.3 | Fixed Reference Channels for PDSCH performance requirements (256QAM) .....                                                                             | 206 |
| A.3.4 | Fixed Reference Channels for PDCCH performance requirements.....                                                                                       | 207 |
| A.3.5 | Fixed Reference Channels for CSI reporting performance .....                                                                                           | 208 |

## **Annex B (normative): IAB-DU Error Vector Magnitude (FR1) .....211**

## **Annex C (normative): IAB-DU Error Vector Magnitude (FR2) .....212**

## **Annex D (normative): IAB-MT Error Vector Magnitude (FR1) .....213**

|     |                                                                         |     |
|-----|-------------------------------------------------------------------------|-----|
| D.0 | General .....                                                           | 213 |
| D.1 | Reference point for measurement.....                                    | 213 |
| D.2 | Basic unit of measurement .....                                         | 213 |
| D.3 | Modified signal under test.....                                         | 213 |
| D.4 | Estimation of frequency offset .....                                    | 213 |
| D.5 | Estimation of time offset .....                                         | 213 |
| D.6 | Estimation of TX chain amplitude and frequency response parameters..... | 213 |
| D.7 | Averaged EVM .....                                                      | 213 |

## **Annex E (normative): IAB-MT Error Vector Magnitude (FR2) .....215**

|     |                                                                         |     |
|-----|-------------------------------------------------------------------------|-----|
| E.0 | General .....                                                           | 215 |
| E.1 | Reference point for measurement.....                                    | 215 |
| E.2 | Basic unit of measurement .....                                         | 215 |
| E.3 | Modified signal under test.....                                         | 215 |
| E.4 | Estimation of frequency offset .....                                    | 215 |
| E.5 | Estimation of time offset .....                                         | 215 |
| E.6 | Estimation of TX chain amplitude and frequency response parameters..... | 215 |
| E.7 | Averaged EVM .....                                                      | 215 |

|                                                                                              |            |
|----------------------------------------------------------------------------------------------|------------|
| <b>Annex F (normative):</b>                                                                  | <b>217</b> |
| F.1 Characteristics of the interfering signals for IAB-DU                                    | 217        |
| F.2 Characteristics of the interfering signals for IAB-MT                                    | 217        |
| <b>Annex G (normative): IAB-MT RRM Testing</b>                                               | <b>218</b> |
| G.1 IAB-MT RRM test configurations                                                           | 219        |
| G.1.1 Reference measurement channels                                                         | 219        |
| G.1.1.1 PDSCH                                                                                | 219        |
| G.1.1.1.1 TDD                                                                                | 219        |
| G.1.1.2 CORESET for RMSI scheduling                                                          | 222        |
| G.1.1.2.1 TDD                                                                                | 222        |
| G.1.1.3 CORESET for RMC scheduling                                                           | 225        |
| G.1.1.3.1 TDD                                                                                | 225        |
| G.1.2 OFDMA channel noise generator (OCNG)                                                   | 226        |
| G.1.2.1 Generic OFDMA Channel Noise Generator (OCNG)                                         | 226        |
| G.1.2.1.1 OCNG pattern 1: Generic OCNG pattern for all unused REs                            | 226        |
| G.1.2.1.2 OCNG pattern 2: Generic OCNG pattern for all unused REs for 2AoA setup             | 227        |
| G.1.2.1.3 OCNG pattern 3: Generic OCNG pattern for unused REs in the same bandwidth as PDSCH |            |
| RMC                                                                                          | 227        |
| G.1.2.1.4 OCNG pattern 4: Generic OCNG pattern for all unused REs outside SSB slot(s)        | 228        |
| G.1.3 Antenna configurations                                                                 | 228        |
| G.1.3.1 Antenna configurations for FR1                                                       | 228        |
| G.1.3.1.1 Antenna connection for 4 Rx capable IAB-MT                                         | 228        |
| G.1.3.2 Antenna configurations for FR2                                                       | 229        |
| G.1.4 BWP configurations                                                                     | 229        |
| G.1.4.1 Introduction                                                                         | 229        |
| G.1.4.2 Downlink BWP configurations                                                          | 230        |
| G.1.4.2.1 Initial BWP                                                                        | 230        |
| G.1.4.2.2 Dedicated BWP                                                                      | 230        |
| G.1.4.3 Uplink BWP configurations                                                            | 230        |
| G.1.4.3.1 Initial BWP                                                                        | 230        |
| G.1.4.3.2 Dedicated BWP                                                                      | 231        |
| G.1.5 SSB Configurations                                                                     | 231        |
| G.1.5.1 SSB Configurations for FR1                                                           | 231        |
| G.1.5.1.1 SSB pattern 1 in FR1: SSB allocation for SSB SCS=15 kHz                            | 231        |
| G.1.5.1.2 SSB pattern 2 in FR1: SSB allocation for SSB SCS=30 kHz                            | 232        |
| G.1.5.1.3 SSB pattern 3 in FR1: SSB allocation for SSB SCS=15 kHz                            | 232        |
| G.1.5.1.4 SSB pattern 4 in FR1: SSB allocation for SSB SCS=30 kHz                            | 233        |
| G.1.5.1.5 SSB pattern 5 in FR1: SSB allocation for SSB SCS=15 kHz starting from odd SFN      | 233        |
| G.1.5.1.6 SSB pattern 6 in FR1: SSB allocation for SSB SCS=30 kHz starting from odd SFN      | 234        |
| G.1.5.2 SSB Configurations for FR2                                                           | 234        |
| G.1.5.2.1 SSB pattern 1 in FR2: SSB allocation for SSB SCS=120 kHz                           | 234        |
| G.1.5.2.2 SSB pattern 2 in FR2: SSB allocation for SSB SCS=240 kHz                           | 234        |
| G.1.5.2.3 SSB pattern 3 in FR2: SSB allocation for SSB SCS=120 kHz                           | 235        |
| G.1.5.2.4 SSB pattern 4 in FR2: SSB allocation for SSB SCS=240 kHz                           | 235        |
| G.1.5.2.5 SSB pattern 5 in FR2: SSB allocation for SSB SCS=120 kHz                           | 235        |
| G.1.5.2.6 SSB pattern 6 in FR2: SSB allocation for SSB SCS=240 kHz                           | 236        |
| G.1.5.2.7 SSB pattern 7 in FR2: SSB allocation for SSB SCS=120 kHz                           | 236        |
| G.1.5.2.8 SSB pattern 8 in FR2: SSB allocation for SSB SCS=240 kHz                           | 236        |
| G.1.6 SMTC Configurations                                                                    | 237        |
| G.1.6.2 SMTC pattern 2: SMTC period = 20 ms with SMTC duration = 5 ms                        | 237        |
| G.1.6.3 SMTC pattern 3: SMTC period = 160 ms with SMTC duration = 1 ms                       | 237        |
| G.1.6.4 SMTC pattern 4: SMTC period = 20 ms with SMTC duration = 1 ms                        | 237        |
| G.1.6.5 SMTC pattern 5: SMTC period = 20 ms with SMTC duration = 5 ms                        | 237        |
| G.1.7 CSI-RS configurations                                                                  | 238        |
| G.1.7.1 TDD                                                                                  | 238        |
| G.1.8 Angle of Arrival (AoA) for FR2 RRM test cases                                          | 240        |
| G.1.8.1 Setup 1: Single AoA                                                                  | 240        |
| G.1.8.2 Setup 2: 2 AoAs                                                                      | 240        |
| G.1.9 TCI State Configuration                                                                | 241        |
| G.1.9.1 Introduction                                                                         | 241        |
| G.1.9.2 TCI states                                                                           | 241        |



|            |                                                                                                                          |     |
|------------|--------------------------------------------------------------------------------------------------------------------------|-----|
| G.1.10     | Configurations of CSI-RS for tracking .....                                                                              | 241 |
| G.1.10.1   | Configuration of CSI-RS for tracking for FR1.....                                                                        | 241 |
| G.1.10.1.2 | TDD.....                                                                                                                 | 241 |
| G.1.10.2   | Configuration of CSI-RS for tracking for FR2.....                                                                        | 242 |
| G.1.10.2.1 | TDD.....                                                                                                                 | 242 |
| G.2        | IAB-MT RRM test cases.....                                                                                               | 243 |
| G.2.1      | RRC_CONNECTED state mobility for IAB-MTs .....                                                                           | 243 |
| G.2.1.1    | RRC Connection Mobility Control .....                                                                                    | 243 |
| G.2.1.1.1  | RRC Re-establishment .....                                                                                               | 243 |
| G.2.1.1.2  | RRC Connection Release with Redirection.....                                                                             | 254 |
| G.2.2      | Timing .....                                                                                                             | 259 |
| G.2.2.1    | Transmit timing.....                                                                                                     | 259 |
| G.2.2.1.1  | NR IAB-MT Transmit Timing Test for FR1 .....                                                                             | 259 |
| G.2.2.1.2  | NR IAB-MT Transmit Timing Test for FR2 .....                                                                             | 262 |
| G.2.3      | Signalling Characteristics for IAB MTs .....                                                                             | 265 |
| G.2.3.1    | Radio link Monitoring.....                                                                                               | 265 |
| G.2.3.1.1  | Radio Link Monitoring Out-of-sync Test for FR1 PCell configured with SSB-based RLM RS in non-DRX mode .....              | 265 |
| G.2.3.1.2  | Radio Link Monitoring In-sync Test for FR1 PCell configured with SSB-based RLM RS in non-DRX mode .....                  | 268 |
| G.2.3.1.3  | Radio Link Monitoring Out-of-sync Test for FR2 PCell configured with SSB-based RLM RS in non-DRX mode .....              | 272 |
| G.2.3.1.4  | Radio Link Monitoring In-sync Test for FR2 PCell configured with SSB-based RLM RS in non-DRX mode .....                  | 275 |
| G.2.3.1.5  | Radio Link Monitoring Out-of-sync Test for FR1 PCell configured with CSI-RS-based RLM in non-DRX mode .....              | 279 |
| G.2.3.1.6  | Radio Link Monitoring In-sync Test for FR1 PCell configured with CSI-RS-based RLM in non-DRX mode .....                  | 282 |
| G.2.3.1.7  | Radio Link Monitoring Out-of-sync Test for FR2 PCell configured with CSI-RS-based RLM in non-DRX mode .....              | 285 |
| G.2.3.1.8  | Radio Link Monitoring In-sync Test for FR2 PCell configured with CSI-RS-based RLM in non-DRX mode .....                  | 288 |
| G.2.3.2    | Beam Failure Detection and Link Recovery Procedure .....                                                                 | 291 |
| G.2.3.2.1  | Beam Failure Detection and Link Recovery Test for FR1 PCell configured with SSB-based BFD and LR .....                   | 291 |
| G.2.3.2.2  | Beam Failure Detection and Link Recovery Test for FR2 PCell configured with SSB-based BFD and LR .....                   | 295 |
| G.2.3.2.3  | Beam Failure Detection and Link Recovery Test for FR1 PCell configured with CSI-RS-based BFD and LR .....                | 301 |
| G.2.3.2.4  | Beam Failure Detection and Link Recovery Test for FR2 PCell configured with CSI-RS-based BFD and LR in non-DRX mode..... | 305 |

## **Annex H (normative): Conditions for IAB-MT RRM requirements applicability for operating bands.....311**

|         |                                                                                                  |     |
|---------|--------------------------------------------------------------------------------------------------|-----|
| H.1     | Conditions for RRC_CONNECTED state mobility for IAB-MT .....                                     | 311 |
| H.1.1   | Introduction.....                                                                                | 311 |
| H.1.1.1 | Conditions for Measurements on NR Intra-frequency Cells for RRC Connection Re-establishment..... | 311 |
| H.1.1.2 | Conditions for Measurements on NR Inter-frequency Cells for RRC Connection Re-establishment..... | 312 |
| H.1.1.3 | Conditions for Measurements on NR Cells for RRC Connection Release with Redirection.....         | 313 |

## **Annex I (normative): Propagation conditions.....316**

|         |                                                |     |
|---------|------------------------------------------------|-----|
| I.1     | Static propagation condition.....              | 316 |
| I.1.1   | IAB-MT receiver with 2RX.....                  | 316 |
| I.2     | Multi-path fading propagation conditions ..... | 316 |
| I.2.1   | General.....                                   | 316 |
| I.2.2   | Delay profiles.....                            | 317 |
| I.2.2.1 | General .....                                  | 317 |
| I.2.2.2 | Delay profiles for FR1 .....                   | 318 |
| I.2.3   | Combinations of channel model parameters ..... | 319 |
| I.2.4   | MIMO channel correlation matrices .....        | 319 |



|                               |                                                                             |            |
|-------------------------------|-----------------------------------------------------------------------------|------------|
| I.2.4.1                       | General .....                                                               | 319        |
| I.2.4.2                       | MIMO correlation matrices using Uniform Linear Array.....                   | 319        |
| I.2.4.2.1                     | General .....                                                               | 319        |
| I.2.4.2.2                     | Definition of MIMO correlation matrices .....                               | 319        |
| I.2.4.2.3                     | MIMO correlation matrices at high, medium and low level.....                | 321        |
| I.2.4.3                       | Multi-antenna channel models using cross polarized antennas.....            | 323        |
| I.2.4.3.1                     | General .....                                                               | 323        |
| I.2.4.3.2                     | Definition of MIMO correlation matrices using cross polarized antennas..... | 323        |
| I.2.4.3.3                     | Spatial correlation matrices at IAB-MT/UE and IAB-DU/gNB sides.....         | 324        |
| I.2.4.3.4                     | MIMO correlation matrices using cross polarized antennas.....               | 324        |
| I.2.4.3.5                     | Beam steering approach.....                                                 | 325        |
| I.3                           | Physical signals, channels mapping and precoding.....                       | 326        |
| I.3.1                         | General.....                                                                | 326        |
| <b>Annex J (informative):</b> | <b>Change history .....</b>                                                 | <b>328</b> |
| History .....                 |                                                                             | 330        |

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ETSI TS 138 174 V16.8.0 (2023-07)

<https://standards.iteh.ai/catalog/standards/sist/e8546100-b420-4e9d-a7b7-a74805cab973/etsi-ts-138-174-v16-8-0-2023-07>