

ETSI TS 136 101 V13.25.0 (2023-07)



LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio transmission and reception
(3GPP TS 36.101 version 13.25.0 Release 13)

[ETSI TS 136 101 V13.25.0 \(2023-07\)](https://standards.iteh.ai/catalog/standards/sist/79975fee-18e6-43df-ab26-1e68bf15d23e/etsi-ts-136-101-v13-25-0-2023-07)

<https://standards.iteh.ai/catalog/standards/sist/79975fee-18e6-43df-ab26-1e68bf15d23e/etsi-ts-136-101-v13-25-0-2023-07>



Reference

RTS/TSGR-0436101vdp0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://standards-portal.etsi.org/People/CommitteeSupportStaff.aspx> 43df-ab26-

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	25
1 Scope	26
2 References	26
3 Definitions, symbols and abbreviations	26
3.1 Definitions	26
3.2 Symbols.....	28
3.3 Abbreviations	31
4 General	32
4.1 Relationship between minimum requirements and test requirements	32
4.2 Applicability of minimum requirements	32
4.3 Void.....	33
4.3A Applicability of minimum requirements (CA, UL-MIMO, ProSe, Dual Connectivity, UE category 0, UE category M1, UE category NB1).....	33
4.4 RF requirements in later releases	34
5 Operating bands and channel arrangement.....	34
5.1 General	34
5.2 Void.....	34
5.3 Void.....	34
5.4 Void.....	34
5.5 Operating bands.....	34
5.5A Operating bands for CA	36
5.5B Operating bands for UL-MIMO	45
5.5C Operating bands for Dual Connectivity	45
5.5D Operating bands for ProSe.....	46
5.5E Operating bands for UE category 0 and UE category M1	47
5.5F Operating bands for category NB1	47
5.6 Channel bandwidth.....	47
5.6.1 Channel bandwidths per operating band	48
5.6A Channel bandwidth for CA.....	49
5.6A.1 Channel bandwidths per operating band for CA.....	52
5.6B Channel bandwidth for UL-MIMO	69
5.6B.1 Void	69
5.6C Channel bandwidth for Dual Connectivity	69
5.6C.1 Void	70
5.6D Channel bandwidth for ProSe.....	70
5.6D.1 Channel bandwidths per operating band for ProSe.....	70
5.6F Channel bandwidth for category NB1	70
5.7 Channel arrangement.....	71
5.7.1 Channel spacing	71
5.7.1A Channel spacing for CA.....	72
5.7.1F Channel spacing for category NB1	72
5.7.2 Channel raster	72
5.7.2A Channel raster for CA.....	72
5.7.2F Channel raster for category NB1	72
5.7.3 Carrier frequency and EARFCN.....	72
5.7.3F Carrier frequency and EARFCN for category NB1	73
5.7.4 TX–RX frequency separation	74
5.7.4A TX–RX frequency separation for CA	75
5.7.4E TX–RX frequency separation for category M1	75
5.7.4F TX–RX frequency separation for category NB1	75

6	Transmitter characteristics	75
6.1	General	75
6.2	Transmit power	75
6.2.1	Void	75
6.2.2	UE maximum output power	75
6.2.2A	UE maximum output power for CA	76
6.2.2B	UE maximum output power for UL-MIMO	78
6.2.2C	Void	79
6.2.2D	UE maximum output power for ProSe	79
6.2.2E	UE maximum output power for Category M1 UE	79
6.2.2F	UE maximum output power for category NB1	80
6.2.3	UE maximum output power for modulation / channel bandwidth	81
6.2.3A	UE Maximum Output power for modulation / channel bandwidth for CA	81
6.2.3B	UE maximum output power for modulation / channel bandwidth for UL-MIMO	83
6.2.3D	UE maximum output power for modulation / channel bandwidth for ProSe	84
6.2.3E	UE maximum output power for modulation / channel bandwidth for category M1	84
6.2.3F	UE maximum output power for modulation / channel bandwidth for category NB1	85
6.2.4	UE maximum output power with additional requirements	85
6.2.4A	UE maximum output power with additional requirements for CA	94
6.2.4A.1	A-MPR for CA_NS_01 for CA_1C	96
6.2.4A.2	A-MPR for CA_NS_02 for CA_1C	97
6.2.4A.3	A-MPR for CA_NS_03 for CA_1C	97
6.2.4A.4	A-MPR for CA_NS_04	98
6.2.4A.5	A-MPR for CA_NS_05 for CA_38C	99
6.2.4A.6	A-MPR for CA_NS_06	99
6.2.4A.7	A-MPR for CA_NS_07	100
6.2.4A.8	A-MPR for CA_NS_08	101
6.2.4B	UE maximum output power with additional requirements for UL-MIMO	102
6.2.4D	UE maximum output power with additional requirements for ProSe	102
6.2.4E	UE maximum output power with additional requirements for category M1 UE	102
6.2.4F	UE maximum output power with additional requirements for category NB1 UE	104
6.2.5	Configured transmitted power	104
6.2.5A	Configured transmitted power for CA	117
6.2.5B	Configured transmitted power for UL-MIMO	119
6.2.5C	Configured transmitted power for Dual Connectivity	120
6.2.5D	Configured transmitted power for ProSe	121
6.2.5F	Configured transmitted Power for category NB1	123
6.3	Output power dynamics	124
6.3.1	(Void)	124
6.3.2	Minimum output power	124
6.3.2.1	Minimum requirement	124
6.3.2A	UE Minimum output power for CA	124
6.3.2A.1	Minimum requirement for CA	124
6.3.2B	UE Minimum output power for UL-MIMO	124
6.3.2B.1	Minimum requirement	125
6.3.2C	Void	125
6.3.2D	UE Minimum output power for ProSe	125
6.3.2F	UE Minimum output power for category NB1	125
6.3.3	Transmit OFF power	125
6.3.3.1	Minimum requirement	125
6.3.3A	UE Transmit OFF power for CA	126
6.3.3A.1	Minimum requirement for CA	126
6.3.3B	UE Transmit OFF power for UL-MIMO	126
6.3.3B.1	Minimum requirement	126
6.3.3D	Transmit OFF power for ProSe	127
6.3.3F	Transmit OFF power for category NB1	127
6.3.4	ON/OFF time mask	127
6.3.4.1	General ON/OFF time mask	127
6.3.4.2	PRACH and SRS time mask	128
6.3.4.2.1	PRACH time mask	128
6.3.4.2.2	SRS time mask	128
6.3.4.3	Slot / Sub frame boundary time mask	129

6.3.4.4	PUCCH / PUSCH / SRS time mask.....	130
6.3.4A	ON/OFF time mask for CA	131
6.3.4B	ON/OFF time mask for UL-MIMO	131
6.3.4D	ON/OFF time mask for ProSe.....	131
6.3.4D.1	General time mask for ProSe	131
6.3.4D.2	PSSS/SSSS time mask	132
6.3.4D.3	PSSS / SSSS / PSBCH time mask.....	133
6.3.4D.4	PSSCH / SRS time mask.....	134
6.3.4F	ON/OFF time mask for category NB1	134
6.3.4F.1	General ON/OFF time mask	134
6.3.4F.2	NPRACH time mask.....	134
6.3.5	Power Control.....	134
6.3.5.1	Absolute power tolerance.....	134
6.3.5.1.1	Minimum requirements	135
6.3.5.2	Relative Power tolerance.....	135
6.3.5.2.1	Minimum requirements	135
6.3.5.3	Aggregate power control tolerance	136
6.3.5.3.1	Minimum requirement.....	136
6.3.5A	Power control for CA.....	136
6.3.5A.1	Absolute power tolerance.....	136
6.3.5A.1.1	Minimum requirements	137
6.3.5A.2	Relative power tolerance	137
6.3.5A.2.1	Minimum requirements	137
6.3.5A.3	Aggregate power control tolerance	137
6.3.5A.3.1	Minimum requirements	138
6.3.5B	Power control for UL-MIMO	138
6.3.5D	Power Control for ProSe.....	138
6.3.5D.1	Absolute power tolerance.....	138
6.3.5E	Power control for category M1	138
6.3.5E.1	Absolute power tolerance.....	138
6.3.5E.2	Relative Power tolerance.....	138
6.3.5E.3	Aggregate power control tolerance	139
6.3.5E.3.1	Minimum requirement	139
6.3.5F	Power Control for category NB1	139
6.3.5F.1	Absolute power tolerance.....	140
6.3.5F.2	Relative power tolerance.....	140
6.3.5F.3	Aggregate power control tolerance for category NB1	140
6.3.5F.3.1	Minimum requirement.....	141
6.4	Void.....	141
6.5	Transmit signal quality	141
6.5.1	Frequency error.....	141
6.5.1A	Frequency error for CA.....	141
6.5.1B	Frequency error for UL-MIMO	141
6.5.1D	Frequency error for ProSe.....	141
6.5.1E	Frequency error for UE category M1	141
6.5.1F	Frequency error for UE category NB1.....	142
6.5.2	Transmit modulation quality.....	142
6.5.2.1	Error Vector Magnitude	142
6.5.2.1.1	Minimum requirement.....	143
6.5.2.2	Carrier leakage	143
6.5.2.2.1	Minimum requirements	143
6.5.2.3	In-band emissions	143
6.5.2.3.1	Minimum requirements	143
6.5.2.4	EVM equalizer spectrum flatness	144
6.5.2.4.1	Minimum requirements	144
6.5.2A	Transmit modulation quality for CA.....	145
6.5.2A.1	Error Vector Magnitude	146
6.5.2A.2	Carrier leakage for CA.....	146
6.5.2A.2.1	Minimum requirements.....	146
6.5.2A.3	In-band emissions	146
6.5.2A.3.1	Minimum requirement for CA.....	146
6.5.2B	Transmit modulation quality for UL-MIMO	148

6.5.2B.1	Error Vector Magnitude	148
6.5.2B.2	Carrier leakage	148
6.5.2B.3	In-band emissions	148
6.5.2B.4	EVM equalizer spectrum flatness for UL-MIMO	149
6.5.2D	Transmit modulation quality for ProSe	149
6.5.2D.1	Error Vector Magnitude	149
6.5.2D.2	Carrier leakage	149
6.5.2D.3	In-band emissions	149
6.5.2D.4	EVM equalizer spectrum flatness for ProSe	149
6.5.2E	Transmit modulation quality for category M1	149
6.5.2E.1	Error Vector Magnitude	149
The Error Vector Magnitude is defined in section 6.5.2.1.		149
6.5.2E.2	Carrier leakage	149
6.5.2E.2.1	Minimum requirements	150
6.5.2E.3	In-band emissions	150
6.5.2E.3.1	Minimum requirements	150
6.5.2F	Transmit modulation quality for Category NB1	151
6.5.2F.1	Error Vector Magnitude	151
6.5.2F.2	Carrier leakage	151
6.5.2F.3	In-band emissions	151
6.6	Output RF spectrum emissions	152
6.6.1	Occupied bandwidth	152
6.6.1A	Occupied bandwidth for CA	152
6.6.1B	Occupied bandwidth for UL-MIMO	153
6.6.1F	Occupied bandwidth for category NB1	153
6.6.2	Out of band emission	153
6.6.2.1	Spectrum emission mask	153
6.6.2.1.1	Minimum requirement	153
6.6.2.1A	Spectrum emission mask for CA	154
6.6.2.2	Additional spectrum emission mask	155
6.6.2.2.1	Minimum requirement (network signalled value "NS_03", "NS_11", "NS_20", and "NS_21") ..	155
6.6.2.2.2	Minimum requirement (network signalled value "NS_04")	156
6.6.2.2.3	Minimum requirement (network signalled value "NS_06" or "NS_07")	156
6.6.2.2A	Additional Spectrum Emission Mask for CA	157
6.6.2.2A.1	Minimum requirement (network signalled value "CA_NS_04")	157
6.6.2.3	Adjacent Channel Leakage Ratio	157
6.6.2.3.1	Minimum requirement E-UTRA	158
6.6.2.3.1A	Void	158
6.6.2.3.1Aa	Void	158
6.6.2.3.2	Minimum requirements UTRA	158
6.6.2.3.2A	Minimum requirement UTRA for CA	159
6.6.2.3.3A	Minimum requirements for CA E-UTRA	160
6.6.2.4	Void	161
6.6.2.4.1	Void	161
6.6.2A	Void	161
6.6.2B	Out of band emission for UL-MIMO	162
6.6.2C	Void	162
6.6.2D	Out of band emission for ProSe	162
6.6.2F	Out of band emission for category NB1	162
6.6.2F.1	Spectrum emission mask	162
6.6.2F.2	Void	163
6.6.2F.3	Adjacent Channel Leakage Ratio for category NB1	163
6.6.3	Spurious emissions	163
6.6.3.1	Minimum requirements	163
6.6.3.1A	Minimum requirements for CA	164
6.6.3.2	Spurious emission band UE co-existence	165
6.6.3.2A	Spurious emission band UE co-existence for CA	170
6.6.3.3	Additional spurious emissions	177
6.6.3.3.1	Minimum requirement (network signalled value "NS_05")	177
6.6.3.3.2	Minimum requirement (network signalled value "NS_07")	177
6.6.3.3.3	Minimum requirement (network signalled value "NS_08")	177
6.6.3.3.4	Minimum requirement (network signalled value "NS_09")	178

6.6.3.3.5	Minimum requirement (network signalled value "NS_12")	178
6.6.3.3.6	Minimum requirement (network signalled value "NS_13")	178
6.6.3.3.7	Minimum requirement (network signalled value "NS_14")	179
6.6.3.3.8	Minimum requirement (network signalled value "NS_15")	179
6.6.3.3.9	Minimum requirement (network signalled value "NS_16")	179
6.6.3.3.10	Minimum requirement (network signalled value "NS_17")	179
6.6.3.3.11	Minimum requirement (network signalled value "NS_18")	180
6.6.3.3.12	Minimum requirement (network signalled value "NS_19")	180
6.6.3.3.13	Minimum requirement (network signalled value "NS_11")	180
6.6.3.3.14	Minimum requirement (network signalled value "NS_20")	180
6.6.3.3.15	Minimum requirement (network signalled value "NS_21")	181
6.6.3.3.16	Minimum requirement (network signalled value "NS_22")	181
6.6.3.3.17	Minimum requirement (network signalled value "NS_23")	181
6.6.3.3.18	Void	182
6.6.3.3.19	Minimum requirement (network signalled value "NS_04")	182
6.6.3.3.20	Minimum requirement (network signalled value "NS_24")	182
6.6.3.3.21	Minimum requirement (network signalled value "NS_25")	183
6.6.3.3.22	Minimum requirement (network signalled value "NS_26")	183
6.6.3.3.23 -		
	6.6.3.3.27	Void
		183
6.6.3.3.28	Minimum requirement (network signalled value "NS_36")	183
6.6.3.3.29	Void	184
6.6.3.3.30	Void	184
6.6.3.3.31	Void	184
6.6.3.3.32	Void	184
6.6.3.3.33	Void	184
6.6.3.3.34	Void	184
6.6.3.3.35	Minimum requirement (network signalled value "NS_56")	184
6.6.3.3A	Additional spurious emissions for CA	184
6.6.3.3A.1	Minimum requirement for CA_1C (network signalled value "CA_NS_01")	185
6.6.3.3A.2	Minimum requirement for CA_1C (network signalled value "CA_NS_02")	185
6.6.3.3A.3	Minimum requirement for CA_1C (network signalled value "CA_NS_03")	185
6.6.3.3A.4	Minimum requirement for CA_38C (network signalled value "CA_NS_05")	186
6.6.3.3A.5	Minimum requirement for CA_7C (network signalled value "CA_NS_06")	186
6.6.3.3A.6	Minimum requirement for CA_39C and CA_39C-41A (network signalled value "CA_NS_07")	186
6.6.3.3A.7	Minimum requirement for CA_42C (network signalled value "CA_NS_08")	186
6.6.3.3A.8	Minimum requirement for CA_41C (network signalled value "CA_NS_04")	187
6.6.3A	Void	187
6.6.3B	Spurious emission for UL-MIMO	187
6.6.3C	Void	187
6.6.3D	Spurious emission for ProSe	187
6.6.3F	Spurious emission for category NB1	188
6.6A	Void	188
6.6B	Void	188
6.7	Transmit intermodulation	188
6.7.1	Minimum requirement	188
6.7.1A	Minimum requirement for CA	188
6.7.1B	Minimum requirement for UL-MIMO	189
6.7.1F	Minimum requirement for category NB1	189
6.8	Void	190
6.8.1	Void	190
6.8A	Void	190
6.8B	Time alignment error for UL-MIMO	190
6.8B.1	Minimum Requirements	190
7	Receiver characteristics	190
7.1	General	190
7.2	Diversity characteristics	191
7.3	Reference sensitivity power level	191
7.3.1	Minimum requirements (QPSK)	191

7.3.1A	Minimum requirements (QPSK) for CA.....	205
7.3.1B	Minimum requirements (QPSK) for UL-MIMO	231
7.3.1D	Minimum requirements (QPSK) for ProSe.....	231
7.3.1E	Minimum requirements (QPSK) for UE category 0 and M1	232
7.3.1F	Minimum requirements for UE category NB1.....	236
7.3.1F.1	Reference sensitivity for UE category NB1	236
7.3.1F.2	Void.....	236
7.3.2	Void	236
7.4	Maximum input level	236
7.4.1	Minimum requirements.....	236
7.4.1A	Minimum requirements for CA	236
7.4.1B	Minimum requirements for UL-MIMO	238
7.4.1D	Minimum requirements for ProSe	238
7.4.1F	Minimum requirements for category NB1	238
7.4A	Void.....	238
7.4A.1	Void.....	238
7.5	Adjacent Channel Selectivity (ACS).....	238
7.5.1	Minimum requirements.....	238
7.5.1A	Minimum requirements for CA	239
7.5.1B	Minimum requirements for UL-MIMO	243
7.5.1D	Minimum requirements for ProSe	243
7.5.1F	Minimum requirements for category NB1	244
7.6	Blocking characteristics	244
7.6.1	In-band blocking.....	244
7.6.1.1	Minimum requirements.....	244
7.6.1.1A	Minimum requirements for CA.....	245
7.6.1.1D	Minimum requirements for ProSe.....	248
7.6.1.1F	Minimum requirements for category NB1	249
7.6.2	Out-of-band blocking.....	250
7.6.2.1	Minimum requirements.....	250
7.6.2.1A	Minimum requirements for CA.....	251
7.6.2.1D	Minimum requirements for ProSe.....	254
7.6.2.1F	Minimum requirements for category NB1	255
7.6.3	Narrow band blocking	255
7.6.3.1	Minimum requirements.....	255
7.6.3.1A	Minimum requirements for CA.....	256
7.6.3.1D	Minimum requirements for ProSe.....	257
7.6A	Void.....	257
7.6B	Blocking characteristics for UL-MIMO.....	258
7.7	Spurious response.....	258
7.7.1	Minimum requirements.....	258
7.7.1A	Minimum requirements for CA	258
7.7.1B	Minimum requirements for UL-MIMO	260
7.7.1D	Minimum requirements for ProSe	260
7.7.1F	Minimum requirements for UE category NB1.....	260
7.8	Intermodulation characteristics	261
7.8.1	Wide band intermodulation.....	261
7.8.1.1	Minimum requirements.....	261
7.8.1A	Minimum requirements for CA	261
7.8.1B	Minimum requirements for UL-MIMO	264
7.8.1D	Minimum requirements for ProSe	264
7.8.1F	Minimum requirements for category NB1	264
7.8.2	Void	265
7.9	Spurious emissions	265
7.9.1	Minimum requirements.....	265
7.9.1A	Minimum requirements.....	265
7.10	Receiver image.....	266
7.10.1	Void	266
7.10.1A	Minimum requirements for CA	266
8	Performance requirement	267
8.1	General	267

8.1.1	Receiver antenna capability	267
8.1.1.1	Simultaneous unicast and MBMS operations.....	268
8.1.1.2	Dual-antenna receiver capability in idle mode	268
8.1.2	Applicability of requirements	268
8.1.2.1	Applicability of requirements for different channel bandwidths.....	268
8.1.2.2	Definition of CA capability	268
8.1.2.2A	Definition of dual connectivity capability	271
8.1.2.3	Applicability and test rules for different CA configurations and bandwidth combination sets.....	272
8.1.2.3A	Applicability and test rules for different dual connectivity configuration and bandwidth combination set	274
8.1.2.3B	Applicability and test rules for different TDD-FDD CA configurations and bandwidth combination sets.....	275
8.1.2.4	Test coverage for different number of component carriers	276
8.1.2.5	Applicability of performance requirements for Type B receiver	277
8.1.2.6	Applicability of performance requirements for 4Rx capable UEs	277
8.1.2.6.1	Applicability rule and antenna connection for single carrier tests with 2Rx	277
8.1.2.6.2	Applicability rule and antenna connection for CA and DC tests with 2Rx	279
8.1.2.6.3	Applicability rule and antenna connection for single carrier tests with 4Rx	279
8.1.2.6.4	Applicability rule for 256QAM tests	279
8.1.2.7	Applicability of Enhanced Downlink Control Channel Performance Requirements	279
8.1.2.8	Applicability of performance requirements for CDM-multiplexed DM RS with interfering simultaneous transmission (FRC) with multiple CSI-RS configurations	280
8.1.2.8A	Applicability of performance requirements for UE supporting coverage enhancement	280
8.1.3	UE category and UE DL category	281
8.2	Demodulation of PDSCH (Cell-Specific Reference Symbols)	281
8.2.1	FDD (Fixed Reference Channel)	281
8.2.1.1	Single-antenna port performance	281
8.2.1.1.1	Minimum Requirement	282
8.2.1.1.2	Void	285
8.2.1.1.3	Void	285
8.2.1.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	285
8.2.1.2	Transmit diversity performance	286
8.2.1.2.1	Minimum Requirement 2 Tx Antenna Port	286
8.2.1.2.2	Minimum Requirement 4 Tx Antenna Port	286
8.2.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	287
8.2.1.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	288
8.2.1.2.4	Enhanced Performance Requirement Type A - 2 Tx Antenna Ports with TM3 interference model	290
8.2.1.2.5	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	291
8.2.1.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	292
8.2.1.3	Open-loop spatial multiplexing performance	293
8.2.1.3.1	Minimum Requirement 2 Tx Antenna Port	293
8.2.1.3.1B	Enhanced Performance Requirement Type C –2Tx Antenna Ports	297
8.2.1.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	298
8.2.1.3.2	Minimum Requirement 4 Tx Antenna Port	299
8.2.1.3.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	299
8.2.1.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	302
8.2.1.4	Closed-loop spatial multiplexing performance	303
8.2.1.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port.....	303
8.2.1.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port.....	304
8.2.1.4.1B	Enhanced Performance Requirement Type A - Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	305
8.2.1.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	306
8.2.1.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	308

8.2.1.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	309
8.2.1.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	310
8.2.1.4.2A	Enhanced Performance Requirement Type C – Multi-layer Spatial Multiplexing 2Tx Antenna Ports.....	311
8.2.1.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	311
8.2.1.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	314
8.2.1.5	MU-MIMO.....	316
8.2.1.6	[Control channel performance: D-BCH and PCH]	316
8.2.1.7	Carrier aggregation with power imbalance	316
8.2.1.7.1	Minimum Requirement	316
8.2.1.8	Intra-band non-contiguous carrier aggregation with timing offset.....	317
8.2.1.8.1	Minimum Requirement	317
8.2.2	TDD (Fixed Reference Channel).....	318
8.2.2.1	Single-antenna port performance	318
8.2.2.1.1	Minimum Requirement	318
8.2.2.1.2	Void	321
8.2.2.1.3	Void	321
8.2.2.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	321
8.2.2.2	Transmit diversity performance	322
8.2.2.2.1	Minimum Requirement 2 Tx Antenna Port	322
8.2.2.2.2	Minimum Requirement 4 Tx Antenna Port	323
8.2.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	323
8.2.2.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	325
8.2.2.2.4	Enhanced Performance Requirement Type A – 2 Tx Antenna Ports with TM3 interference model	326
8.2.2.2.5	Minimum Requirement 2 Tx Antenna Port (when <i>EIMTA-MainConfigServCell-r12</i> is configured)	327
8.2.2.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	328
8.2.2.2.7	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	329
8.2.2.3	Open-loop spatial multiplexing performance.....	330
8.2.2.3.1	Minimum Requirement 2 Tx Antenna Port	330
8.2.2.3.1A	Soft buffer management test.....	333
8.2.2.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports.....	333
8.2.2.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	334
8.2.2.3.2	Minimum Requirement 4 Tx Antenna Port	335
8.2.2.3.3	Minimum Requirement 2Tx antenna port (demodulation subframe overlaps with aggressor cell ABS).....	335
8.2.2.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	338
8.2.2.4	Closed-loop spatial multiplexing performance	339
8.2.2.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port.....	339
8.2.2.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port.....	340
8.2.2.4.1B	Enhanced Performance Requirement Type A – Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	341
8.2.2.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	342
8.2.2.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	344
8.2.2.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	345
8.2.2.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	346
8.2.2.4.2A	Enhanced Performance Requirement Type C Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	347
8.2.2.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	348
8.2.2.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	350

8.2.2.4.4	Void	352
8.2.2.5	MU-MIMO.....	352
8.2.2.6	[Control channel performance: D-BCH and PCH]	352
8.2.2.7	Carrier aggregation with power imbalance	352
8.2.2.7.1	Minimum Requirement	352
8.2.2.8	Intra-band contiguous carrier aggregation with minimum channel spacing.....	353
8.2.2.8.1	Minimum Requirement	353
8.2.3	TDD FDD CA (Fixed Reference Channel).....	353
8.2.3.1	Single-antenna port performance	354
8.2.3.1.1	Minimum Requirement for FDD PCell	354
8.2.3.1.2	Minimum Requirement for TDD PCell.....	357
8.2.3.2	Open-loop spatial multiplexing performance 2Tx Antenna port.....	359
8.2.3.2.1	Minimum Requirement for FDD PCell	359
8.2.3.2.1A	Soft buffer management test for FDD PCell	362
8.2.3.2.2	Minimum Requirement for TDD PCell.....	363
8.2.3.2.2A	Soft buffer management test for TDD PCell	365
8.2.3.3	Closed-loop spatial multiplexing performance 4Tx Antenna Port.....	366
8.2.3.3.1	Minimum Requirement for FDD PCell	366
8.2.3.3.2	Minimum Requirement for TDD PCell.....	369
8.2.3.4	Minimum Requirement for Closed-loop spatial multiplexing performance 4Tx Antenna Port for dual connectivity	371
8.2.4	LAA	373
8.2.4.1	Closed-loop spatial multiplexing performance 4Tx Antenna Port.....	373
8.2.4.1.1	FDD PCell (FDD single carrier).....	373
8.2.4.1.2	TDD PCell (TDD single carrier)	375
8.3	Demodulation of PDSCH (User-Specific Reference Symbols).....	378
8.3.1	FDD	378
8.3.1.1	Single-layer Spatial Multiplexing	378
8.3.1.1A	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model.....	379
8.3.1.1B	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	381
8.3.1.1C	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference model.....	383
8.3.1.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model.....	384
8.3.1.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference model.....	385
8.3.1.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	387
8.3.1.1G	Single-layer Spatial Multiplexing (CRS assistance information is configured).....	388
8.3.1.1H	Single-layer Spatial Multiplexing (With Enhanced DMRS table configured).....	389
8.3.1.2	Dual-Layer Spatial Multiplexing	390
8.3.1.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing.....	391
8.3.1.3	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	392
8.3.1.3.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource).....	392
8.3.1.3.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources).....	394
8.3.1.3.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	396
8.3.1.3.4	Minimum requirement with Different Cell ID and non-colliding CRS (with single NZP CSI-RS resource and CRS assistance information is configured).....	397
8.3.1.3.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured).....	399
8.3.2	TDD.....	400
8.3.2.1	Single-layer Spatial Multiplexing	401
8.3.2.1A	Single-layer Spatial Multiplexing (with multiple CSI-RS configurations)	403
8.3.2.1B	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model.....	404
8.3.2.1C	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	406
8.3.2.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference.....	408

8.3.2.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model.....	409
8.3.2.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference.....	410
8.3.2.1G	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	411
8.3.2.1H	Single-layer Spatial Multiplexing (CRS assistance information is configured).....	413
8.3.2.1I	Single-layer Spatial Multiplexing (With Enhanced DMRS table configured).....	414
8.3.2.2	Dual-Layer Spatial Multiplexing	415
8.3.2.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing.....	416
8.3.2.3	Dual-Layer Spatial Multiplexing (with multiple CSI-RS configurations)	417
8.3.2.4	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	418
8.3.2.4.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource).....	418
8.3.2.4.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources).....	419
8.3.2.4.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	421
8.3.2.4.4	Minimum requirement with Different Cell ID and non-Colliding CRS (with single NZP CSI-RS resource and CRS assistance information is configured).....	422
8.3.2.4.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured).....	424
8.3.3	LAA	426
8.3.3.1	Dual-Layer Spatial Multiplexing with DM-RS.....	426
8.3.3.1.1	FDD PCell (FDD single carrier).....	426
8.3.3.1.2	TDD Pcell (TDD single carrier)	428
8.4	Demodulation of PDCCH/PCFICH	431
8.4.1	FDD	431
8.4.1.1	Single-antenna port performance	432
8.4.1.2	Transmit diversity performance	432
8.4.1.2.1	Minimum Requirement 2 Tx Antenna Port	432
8.4.1.2.2	Minimum Requirement 4 Tx Antenna Port	432
8.4.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	432
8.4.1.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	435
8.4.1.2.5	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port under Asynchronous Network	438
8.4.1.2.6	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	439
8.4.1.2.7	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Colliding CRS Dominant Interferer.....	440
8.4.1.2.8	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	441
8.4.2	TDD.....	442
8.4.2.1	Single-antenna port performance	443
8.4.2.2	Transmit diversity performance	443
8.4.2.2.1	Minimum Requirement 2 Tx Antenna Port	443
8.4.2.2.2	Minimum Requirement 4 Tx Antenna Port	443
8.4.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	444
8.4.2.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	446
8.4.2.2.5	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Colliding CRS Dominant Interferer.....	449
8.4.2.2.6	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	450
8.4.2.2.7	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Colliding CRS Dominant Interferer.....	451
8.4.2.2.8	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	452
8.4.3	LAA.....	453
8.4.3.1	Transmit diversity performance	453
8.4.3.1.1	FDD Pcell (FDD single carrier).....	453
8.4.3.1.2	TDD Pcell (TDD single carrier)	454

8.5	Demodulation of PHICH.....	455
8.5.1	FDD.....	455
8.5.1.1	Single-antenna port performance	456
8.5.1.2	Transmit diversity performance	456
8.5.1.2.1	Minimum Requirement 2 Tx Antenna Port	456
8.5.1.2.2	Minimum Requirement 4 Tx Antenna Port	456
8.5.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	457
8.5.1.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	458
8.5.1.2.5	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Ports under Asynchronous Network	460
8.5.1.2.6	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Ports with Non-Colliding CRS Dominant Interferer	460
8.5.1.2.7	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Ports with Colliding CRS Dominant Interferer	461
8.5.1.2.8	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Ports with Non-Colliding CRS Dominant Interferer	462
8.5.2	TDD.....	463
8.5.2.1	Single-antenna port performance	464
8.5.2.2	Transmit diversity performance	464
8.5.2.2.1	Minimum Requirement 2 Tx Antenna Port	464
8.5.2.2.2	Minimum Requirement 4 Tx Antenna Port	464
8.5.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	465
8.5.2.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	466
8.5.2.2.5	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Ports with Colliding CRS Dominant Interferer	467
8.5.2.2.6	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Ports with Non-Colliding CRS Dominant Interferer	468
8.5.2.2.7	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Ports with Colliding CRS Dominant Interferer	469
8.5.2.2.8	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Ports with Non-Colliding CRS Dominant Interferer	470
8.6	Demodulation of PBCH	471
8.6.1	FDD.....	471
8.6.1.1	Single-antenna port performance	471
8.6.1.2	Transmit diversity performance	472
8.6.1.2.1	Minimum Requirement 2 Tx Antenna Port	472
8.6.1.2.2	Minimum Requirement 4 Tx Antenna Port	472
8.6.1.2.3	Minimum Requirement 2 Tx Antenna Port under Time Domain Measurement Resource Restriction with CRS Assistance Information	472
8.6.2	TDD.....	473
8.6.2.1	Single-antenna port performance	473
8.6.2.2	Transmit diversity performance	474
8.6.2.2.1	Minimum Requirement 2 Tx Antenna Port	474
8.6.2.2.2	Minimum Requirement 4 Tx Antenna Port	474
8.6.2.2.3	Minimum Requirement 2 Tx Antenna Port under Time Domain Measurement Resource Restriction with CRS Assistance Information	474
8.7	Sustained downlink data rate provided by lower layers	475
8.7.1	FDD (single carrier and CA).....	475
8.7.2	TDD (single carrier and CA)	481
8.7.3	FDD (EPDCCH scheduling).....	484
8.7.4	TDD (EPDCCH scheduling).....	486
8.7.5	TDD FDD CA.....	487
8.7.5.1	Minimum Requirement FDD PCell	488
8.7.5.2	Minimum Requirement TDD PCell	491
8.7.6	FDD (DC).....	494
8.7.7	TDD (DC).....	498
8.7.8	TDD FDD (DC).....	500
8.7.9	Void.....	503

8.7.10	Void	503
8.7.11	Void	503
8.7.11.1	Void.....	503
8.8	Demodulation of EPDCCH	504
8.8.1	Distributed Transmission	504
8.8.1.1	FDD.....	504
8.8.1.1.1	Void.....	505
8.8.1.2	TDD	505
8.8.1.2.1	Void.....	506
8.8.2	Localized Transmission with TM9	506
8.8.2.1	FDD.....	506
8.8.2.1.1	Void.....	507
8.8.2.1.2	Void.....	507
8.8.2.2	TDD	507
8.8.2.2.1	Void.....	508
8.8.2.2.2	Void.....	508
8.8.3	Localized transmission with TM10 Type B quasi co-location type.....	509
8.8.3.1	FDD.....	509
8.8.3.2	TDD	510
8.8.4	Enhanced Downlink Control Channel Performance Requirements Type A - Localized Transmission with CRS Interference Model	512
8.8.4.1	FDD.....	512
8.8.4.2	TDD	513
8.8.5	Enhanced Downlink Control Channel Performance Requirements Type A - Distributed Transmission with TM9 Interference Model	514
8.8.5.1	TDD	514
8.8.6	Enhanced Downlink Control Channel Performance Requirements Type A - Distributed Transmission with TM3 Interference Model	515
8.8.6.1	FDD.....	515
8.9	Demodulation (single receiver antenna).....	516
8.9.1	PDSCH	516
8.9.1.1	FDD and half-duplex FDD (Fixed Reference Channel).....	516
8.9.1.1.1	Transmit diversity performance (Cell-Specific Reference Symbols)	517
8.9.1.1.2	Closed-loop spatial multiplexing performance (Cell-Specific Reference Symbols)	517
8.9.1.1.3	Closed-loop spatial multiplexing performance (User-Specific Reference Symbols)	518
8.9.1.2	TDD (Fixed Reference Channel)	519
8.9.1.2.1	Transmit diversity performance (Cell-Specific Reference Symbols)	520
8.9.1.2.2	Closed-loop spatial multiplexing performance (Cell-Specific Reference Symbols)	520
8.9.1.2.3	Closed-loop spatial multiplexing performance (User-Specific Reference Symbols)	521
8.9.2	PHICH	522
8.9.2.1	FDD and half-duplex FDD.....	522
8.9.2.1.1	Transmit diversity performance.....	522
8.9.2.2	TDD	522
8.9.2.2.1	Transmit diversity performance.....	522
8.9.3	PBCH.....	523
8.9.3.1	FDD and half-duplex FDD.....	523
8.9.3.1.1	Transmit diversity performance.....	523
8.9.3.2	TDD	523
8.9.3.2.1	Transmit diversity performance.....	523
8.10	Demodulation (4 receiver antenna ports)	523
8.10.1	PDSCH	523
8.10.1.1	FDD (Fixed Reference Channel).....	523
8.10.1.1.1	Transmit diversity performance with 2Tx Antenna Ports (Cell-Specific Reference Symbols)	524
8.10.1.1.1A	Transmit diversity performance with Enhanced Performance Requirement Type A - 2 Tx Antenna Ports with TM3 interference model.....	524
8.10.1.1.2	Open-loop spatial multiplexing performance with 2Tx Antenna Ports (Cell-Specific Reference Symbols).....	525
8.10.1.1.3	Closed-loop spatial multiplexing Enhanced Performance Requirements Type A - Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model (Cell-Specific Reference Symbols).....	526
8.10.1.1.4	Closed-loop spatial multiplexing performance, Dual-Layer Spatial Multiplexing 4 Tx Antenna Port (Cell-Specific Reference Symbols)	527