



SLOVENSKI STANDARD

SIST EN 14071:2015+A1:2019

01-september-2019

Nadomešča:
SIST EN 14071:2015

Oprema in pribor za utekočinjeni naftni plin (UNP) - Varnostni ventili za tlačne posode za UNP - Pomožna oprema (vključno z dopolnilom A1)

LPG equipment and accessories - Pressure relief valves for LPG pressure vessels - Ancillary equipment

Flüssiggas-Geräte und Ausrüstungsteile - Druckentlastungsventile für Druckbehälter für Flüssiggas (LPG) - Zusatzausrüstung

(standards.iteh.ai)

Équipements pour GPL et leurs accessoires - Soupapes de sécurité des réservoirs de gaz de pétrole liquéfié (GPL) - Équipement auxiliaire

<http://standards.iteh.ai/catalog/standards/sist/503538f4-069f-4a03-84f9-7875eccc8587/sist-en-14071-2015a1-2019>

Ta slovenski standard je istoveten z: EN 14071:2015+A1:2019

ICS:

23.020.32	Tlačne posode	Pressure vessels
23.060.40	Tlačni regulatorji	Pressure regulators

SIST EN 14071:2015+A1:2019 en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 14071:2015+A1:2019](https://standards.iteh.ai/catalog/standards/sist/303538f4-069f-4a03-849-7875eccc8587/sist-en-14071-2015a1-2019)

<https://standards.iteh.ai/catalog/standards/sist/303538f4-069f-4a03-849-7875eccc8587/sist-en-14071-2015a1-2019>

EUROPEAN STANDARD

EN 14071:2015+A1

NORME EUROPÉENNE

EUROPÄISCHE NORM

May 2019

ICS 23.060.40

English Version

LPG equipment and accessories - Pressure relief valves for LPG pressure vessels - Ancillary equipment

Équipements pour GPL et leurs accessoires - Soupapes
de sécurité des réservoirs de gaz de pétrole liquéfié
(GPL) - Équipement auxiliaire

Flüssiggas-Geräte und Ausrüstungsteile -
Druckentlastungsventile für Druckbehälter für
Flüssiggas (LPG) - Zusatzausrüstung

This European Standard was approved by CEN on 5 March 2015 and includes Amendment 1 approved by CEN on 1 March 2019.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword.....	4
Introduction	5
1 Scope.....	6
2 Normative references.....	6
3 Terms and definitions	7
4 Operating conditions	9
5 Materials.....	9
5.1 General.....	9
5.2 Metallic materials	10
5.3 Non-metallic components	10
5.4 Lubricants, sealants, and adhesives	10
5.5 Inspection Documents.....	10
6 Design.....	11
6.1 Introduction.....	11
6.2 Pressure relief valve isolating devices.....	11
6.2.1 General.....	11
6.2.2 Actuation.....	11
6.2.3 Indication of closure	11
6.2.4 Guiding arrangements.....	12
6.2.5 Isolating mechanism security.....	12
6.2.6 Interchangeability	12
6.3 PRV manifold	12
6.3.1 General.....	12
6.3.2 Indication of port closure.....	15
6.3.3 Port closure	15
6.4 Vent pipe	15
6.4.1 Design.....	15
6.4.2 Materials.....	15
6.4.3 Effect from external conditions.....	15
6.5 Connections.....	15
6.6 Threads.....	15
6.7 Minimum requirements for springs.....	16
7 Testing of the design	16
7.1 General.....	16
7.2 Test requirements	16
7.3 Hydraulic proof test	17
7.4 Relief valve isolator test	17
7.5 Testing of audible signal of isolating devices and residual flow of isolating devices and PRV manifolds.....	17
7.6 Resistance of the isolating mechanism	17
7.7 Over-torque deformation test	18
7.8 Operation test.....	18
7.8.1 General.....	18

7.8.2	System test	18
7.9	Stress cracking test	18
7.9.1	General	18
7.9.2	Mercury(I)nitrate immersion test.....	18
7.9.3	Moist ammonia air stress cracking test.....	19
8	Production testing of isolating devices and PRV manifolds.....	19
9	Marking and labelling	19
9.1	PRV isolating device	19
9.2	Pressure relief valve PRV manifolds.....	19
10	User instructions.....	20
10.1	PRV isolating devices	20
10.2	PRV manifolds.....	20
Annex A (normative) Dimensions of master test pieces for PRV and isolating devices.....		21
Annex ZA (informative) Relationship between this European Standard and the essential requirements of Directive 2014/68/EU (Pressure equipment Directive) aimed to be covered		23
Bibliography		25

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 14071:2015+A1:2019](https://standards.iteh.ai/catalog/standards/sist/303538f4-069f-4a03-84f9-7875eccc8587/sist-en-14071-2015a1-2019)

<https://standards.iteh.ai/catalog/standards/sist/303538f4-069f-4a03-84f9-7875eccc8587/sist-en-14071-2015a1-2019>

EN 14071:2015+A1:2019 (E)**European foreword**

This document (EN 14071:2015+A1:2019) has been prepared by Technical Committee CEN/TC 286 “Liquefied petroleum gas equipment and accessories”, the secretariat of which is held by NSAI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by November 2019 and conflicting national standards shall be withdrawn at the latest by November 2019.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document includes Amendment 1 approved by CEN on 2019-03-01.

This document supersedes A1 EN 14071:2015 A1.

The start and finish of text introduced or altered by amendment is indicated in the text by tags A1 A1.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive(s) see informative Annex ZA, which is an integral part of this document.

A1 *deleted text* A1

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

This European Standard calls for the use of substances and procedures that may be injurious to health and/or the environment if adequate precautions are not taken. It refers only to technical suitability: it does not absolve the user from their legal obligations at any stage.

It is recommended that manufacturers develop an environmental management policy. For guidance, see the EN ISO 14000 series [1], [2] and [3].

It has been assumed in the drafting of this European Standard that the execution of its provisions is entrusted to appropriately qualified and experienced people.

All pressures are gauge pressures unless otherwise stated.

NOTE This European Standard requires measurement of material properties, dimensions and pressures. All such measurements are subject to a degree of uncertainty due to tolerances in measuring equipment etc. It may be beneficial to refer to the leaflet “measurement uncertainty leaflet” SP INFO 2000 27 [5].

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 14071:2015+A1:2019](https://standards.iteh.ai/catalog/standards/sist/303538f4-069f-4a03-84f9-7875eccc8587/sist-en-14071-2015a1-2019)

<https://standards.iteh.ai/catalog/standards/sist/303538f4-069f-4a03-84f9-7875eccc8587/sist-en-14071-2015a1-2019>

EN 14071:2015+A1:2019 (E)**1 Scope**

This European Standard specifies the design, testing and inspection requirements for pressure relief valve isolating devices, valve manifolds, vent pipes and system assemblies which are, where necessary, used with pressure relief valves for use in static pressure vessels for Liquefied Petroleum Gas (LPG) service.

This European Standard addresses both prototype testing and production testing of isolating devices and PRV manifolds.

Pressure relief valves for LPG pressure vessels are specified in EN 14129:2014.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 549:1994, *Rubber materials for seals and diaphragms for gas appliances and gas equipment*

EN 751-1, *Sealing materials for metallic threaded joints in contact with 1st, 2nd and 3rd family gases and hot water - Part 1: Anaerobic jointing compounds*

EN 751-2, *Sealing materials for metallic threaded joints in contact with 1st, 2nd and 3rd family gases and hot water - Part 2: Non-hardening jointing compounds*

EN 751-3, *Sealing materials for metallic threaded joints in contact with 1st, 2nd and 3rd family gases and hot water - Part 3: Unsintered PTFE tapes*

EN 1092-1, *Flanges and their joints - Circular flanges for pipes, valves, fittings and accessories, PN designated - Part 1: Steel flanges*

EN 1503-1:2000, *Valves – Materials for bodies, bonnets and covers – Part 1: Steels specified in European Standards*

EN 1503-2:2000, *Valves – Materials for bodies, bonnets and covers – Part 2: Steels other than those specified in European Standards*

EN 1503-3:2000, *Valves – Materials for bodies, bonnets and covers – Part 3: Cast irons specified in European Standards*

EN 1503-4:2002 *Valves – Materials for bodies, bonnets and covers – Part 4: Copper alloys specified in European Standards*

EN 1563:2011, *Founding – Spheroidal graphite cast irons*

EN 10204:2004, *Metallic products - Types of inspection documents*

EN 10270-3:2011, *Steel wire for mechanical springs - Part 3: Stainless spring steel wire*

EN 12164:2011, *Copper and copper alloys – Rod for free machining purposes*

EN 12165:2011, *Copper and copper alloys – Wrought and unwrought forging stock*

EN 12420, *Copper and copper alloys - Forgings*

EN 13480-3:2012, *Metallic industrial piping – Part 3: Design and calculation*

EN 13906-1, *Cylindrical helical springs made from round wire and bar - Calculation and design - Part 1 : Compression springs*

EN 14129:2014, *LPG Equipment and accessories - Pressure relief valves for LPG pressure vessels*

ISO 6957, *Copper alloys — Ammonia test for stress corrosion resistance*

ASME B1.20.1:2013, *Pipe threads, general purpose (inch)*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

liquefied petroleum gas

LPG

low pressure liquefied gas composed of one or more light hydrocarbons which are assigned to UN 1011, UN 1075, UN 1965, UN 1969 or UN 1978 only and which consists mainly of propane, propene, butane, butane isomers, butene with traces of other hydrocarbon gases

3.2

pressure vessel

assembly of the pressure envelope (including the openings and their closures) and non-pressure-retaining parts attached directly to it

3.3

pressure relief valve (PRV)

self-closing valve which automatically, without the assistance of any energy other than that of the vapour concerned, discharges vapour at a predetermined pressure, and operates with a pop action

Note 1 to entry: This is known as a “safety valve” in ADR.

3.4

pressure relief valve system

PRV system

pressure relief valve(s) for use on the pressure vessel complete with isolating device or PRV manifold, and vent pipe where appropriate

3.5

pressure relief valve isolating device

device fitted between the storage tank and the external pressure relief valve, which permits the replacement of the pressure relief valve without de-pressuring the pressure vessel

3.6

coefficient of discharge

Kd

ratio of the actual measured flow capacity divided by the calculated theoretical capacity for the same fluid at the same operating conditions

EN 14071:2015+A1:2019 (E)

3.7

pressure relief valve manifold**PRV manifold**

device fitted to a storage vessel permitting two or more pressure relief valves to be fitted only one of which can be isolated at a time, which permits replacement of the isolated pressure relief valve without depressurizing the vessel

3.8

discharge capacity

capacity at the flow rating pressure of a pressure relief valve expressed in cubic metres per minute of free air at STP

3.9

vent pipe

open-ended pipe, fitted with a protection cap and attached to the pressure relief valve outlet, to direct discharged fluid away from the protected pressure vessel surface

3.10

design signal flow

limited flow of LPG intended to equalise pressures so that a replacement PRV can be properly fitted to an isolating device; indicate the effectiveness of the internal shut off in an isolating device before the PRV is completely removed; and produce an acoustic signal

3.11

Standard Temperature and Pressure**STP**

15,6 °C (288,7 K), 1,013 bar absolute (0,1013 MPa absolute)

iTech STANDARD PREVIEW

(standards.iteh.ai)

[SIST EN 14071:2015+A1:2019](https://standards.iteh.ai/catalog/standards/sist/303538f4-069f-4a03-84f9-7875eccc8587/sist-en-14071-2015a1-2019)

3.12

flow rating pressure

inlet pressure at which the discharge capacity is measured

<https://standards.iteh.ai/catalog/standards/sist/303538f4-069f-4a03-84f9-7875eccc8587/sist-en-14071-2015a1-2019>

3.13

lift

actual travel of the sealing disc away from the closed position

3.14

sealing element

non-metallic resilient component which effects a seal by contact with the valve seat

3.15

valve seat

normally raised area of the pressure relief valve body on to which the sealing element effects a seal

3.16

maximum allowable pressure**PS**

maximum pressure for which the equipment is designed

Note 1 to entry: All pressures are gauge pressures unless otherwise stated.

3.17

nominal diameter (DN)

numerical designation of the size of a component, which is a convenient round number, approximately equal to the manufacturing dimensions in millimetres (mm)

3.18

external leak tightness

resistance to leakage through the fitting to or from the atmosphere

4 Operating conditions

4.1 Equipment designed in accordance with this European Standard shall be suitable for:

- minimum operating temperature of -20°C ;
- maximum operating temperature of 65°C ;
- maximum allowable pressure of 25 bar; and
- minimum pressure of 50 mbar absolute.

4.2 For some parts of Europe and certain applications, temperatures lower than -20°C can be encountered. For these conditions, a temperature rating of -40°C shall apply.

NOTE 1 In service, temperatures below this can be encountered during short periods, for example, during discharge.

NOTE 2 Vacuum conditions on the isolating device or PRV manifold, arising from butane at low temperature or evacuation of the pressure vessel can expose the valve or fitting to a vacuum of 50 mbar absolute.

5 Materials

5.1 General

5.1.1 All materials in contact with LPG shall be physically and chemically compatible with LPG under all normal operating conditions for which the device is intended to be used.

5.1.2 Material for components shall be selected for adequate strength in service. The material shall resist atmospheric corrosion, brass dezincification, stress corrosion, impact and material failure. Where stress corrosion could be present in a material, stress relieving heat treatment shall be carried out where necessary.

5.1.3 The components exposed to atmosphere shall be manufactured from corrosion resistant materials or suitably protected against corrosion.

NOTE Alternative materials to those listed in 5.2 are not precluded, providing they comply with a standard or specification that ensures control of chemical and physical properties, and quality appropriate to the end use.