

SLOVENSKI STANDARD oSIST prEN ISO 11916-3:2020

01-april-2020

[Not translated]

Soil quality - Determination of selected explosives and related compounds - Part 3: Method using liquid chromatography-tandem mass spectrometry (LC-MS/MS) (ISO/DIS 11916-3:2020)

Bodenbeschaffenheit - Bestimmung von ausgewählten Explosivstoffen und verwandten Verbindungen - Teil 3: Verfahren mittels Flüssigkeitschromatographie mit Tandem-Massenspektrometrie (LC-MS/MS) (ISO/DIS 11916-3:2020)

(standards.iteh.ai)

Qualité du sol - Dosage d'une sélection d'explosifs et de composés apparentés - Partie 3: Méthode utilisant la chromatographie en phase liquide couplée à la spectrométrie de masse en tandem (CL-SM/SM) (ISO/DIS 11916-3:2020)

Ta slovenski standard je istoveten z: prEN ISO 11916-3

ICS:

13.080.10 Kemijske značilnosti tal Chemical characteristics of

soils

oSIST prEN ISO 11916-3:2020 en,fr,de

oSIST prEN ISO 11916-3:2020

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 11916-3:2020 https://standards.iteh.ai/catalog/standards/sist/665af326-7400-45e3-a29d-07370cbbdabf/osist-pren-iso-11916-3-2020

DRAFT INTERNATIONAL STANDARD ISO/DIS 11916-3

Secretariat: DIN

ISO/TC **190**/SC **3**

Voting begins on: Voting terminates on:

2020-02-18 2020-05-12

Soil quality — Determination of selected explosives and related compounds —

Part 3:

Method using liquid chromatography-tandem mass spectrometry (LC-MS/MS)

ICS: 13.080.10

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 11916-3:2020 https://standards.iteh.ai/catalog/standards/sist/665af326-7400-45e3-a29d-07370cbbdabf/osist-pren-iso-11916-3-2020

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.

ISO/CEN PARALLEL PROCESSING



Reference number ISO/DIS 11916-3:2020(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 11916-3:2020 https://standards.iteh.ai/catalog/standards/sist/665af326-7400-45e3-a29d-07370cbbdabf/osist-pren-iso-11916-3-2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

ii

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

(standards.iteh.ai)

This document was prepared by Technical Committee ISO/TC 190, *Soil quality*, Subcommittee SC 3, *Chemical and physical characterization.* oSIST prEN ISO 11916-3:2020

https://standards.iteh.ai/catalog/standards/sist/665af326-7400-45e3-a29d-

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.



COPYRIGHT PROTECTED DOCUMENT

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 copyright@iso.org www.iso.org

Con	Contents				
Intro	duction	v			
1	Scope	1			
2	Normative references	2			
3	Principle				
4	Interferences				
	Reagents				
5 5.1	General				
5.2	Chemicals				
5.2.1	Water, with a electrical conductivity of ≥ 0.01 mS/m (25°C)				
5.2.2	Acetonitrile, CH3CN, HPLC grade or equivalent.				
5.2.3	Methanol, CH30H, HPLCgrade or equivalent				
5.2.4	Ammonium acetate in water, 2,5 mmol/l				
5.2.5	Ammonium acetate in methanol, 2,5 mmol/l	3			
5.3	Standard substances and solutions				
5.3.1	Standard substances	3			
5.3.2					
6	Apparatus (standards.itch.ai) General	4			
6.1					
6.1.1	Amber glass containers with caps containing PTFE coated lining				
6.1.2	Amber glass vials with caps containing septa with PTFE coated lining				
6.1.3	Amber glass conical bottles with ground-in stopper				
6.1.4	Analytical balance, with a precision of at least 0,1 mg				
6.1.5 6.1.6	Laboratory centrifuge, capable of producing an acceleration of at least 1 000 G				
6.2	Equipment for extraction				
6.2.1	Temperature-controlled ultrasonic bath, 35 Hz, effective HF-power of at least 140 W.				
6.2.2	Horizontal mechanical shaker				
6.3	Liquid chromatograph-tandem mass spectrometer (LC-MS/MS)				
6.3.1	LC system, consisting of a pump that supports a pressure of at least 40 MPa (400				
	bar) and an injection system with an appropriate loop capacity depending on	_			
	injection volume.				
6.3.2	Tandem mass spectrometer				
7	Procedure	5			
7.1	Sample pretreatment, sample storage and determination of water content				
7.2	Extraction				
7.2.1	General				
7.2.2	Extraction using ultrasonic waves				
7.2.3	Extraction using mechanical shaking				
7.3	Storage of extract				
8	Liquid chromatography tandem mass spectrometry (LC-MS/MS)				
8.1	General				
8.2	Identification and quantification				
8.3	Calibration	7			

oSIST prEN ISO 11916-3:2020

ISO/DIS 11916-3:2020(E)

9	Calculation of results	8
10	Quality assurance/quality control (QA/QC)	8
11	Expression of results	9
12	Test report	9
	A (informative) Conditions of high performance liquid chromatography tandem mass spectrometry (LC-MS/MS)	. 11
	B (informative) Comparison of LC-MS and LC-MS/MS application for PETN, 1,3,5-TNB and tetryl	. 14
	Descriptions of experiment	
B.2	Ion chromatogram of LC-MS (SIM) and LC-MS/MS (MRM)	14
Annex	C (informative) Comparison of LOD and LOQ in the measurement of HPLC and LC-	
	MS/MSAnalytical conditions of HPLC	17
C.1	Analytical conditions of HPLC	17
	D (informative) Comparison of extractive capability of acetonitrile and methanol	
	when using LC-MS/MS	
D.1	Descriptions of experiment	20
D.2	Results	
D:Ll:		22

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 11916-3:2020 https://standards.iteh.ai/catalog/standards/sist/665af326-7400-45e3-a29d-07370cbbdabf/osist-pren-iso-11916-3-2020

Introduction

Currently two ISO standards exist for the analysis of explosives and related compounds in soil: ISO 11916-1(HPLC/UV method), ISO 11916-2(GC-ECD or MS). According to the results of inter-laboratory trial with ISO 11916-1, it showed some problematic aspects to analyze PETN, 1,3,5-TNB and tetryl. In case of ISO 11916-2, it also gave poor inter-laboratory trial results for 1,3,5-TNB. Therefore, it is necessary to develop new method effectively applicable to the determination of PETN, 1,3,5-TNB and tetryl. In addition to this, lower risk-based PRGs (Preliminary Remediation Goal), new regulatory concerns, and change of land use have created the atmosphere to apply more sensitive and selective instruments to determine explosive and related compounds. From the view of these aspects, liquid chromatography-tandem mass spectrometry (LC-MS/MS) is one of alternative methods for these purposes. LC-MS/MS method provides 10-20 times or more lower detection limit than that of HPLC/UV method. In this document, LC-MS/MS method is intended for the trace analysis of explosives and related compounds and applicable to 12 compounds (1,3-DNB, 1,3,5-TNB, 2,4-DNT, 2,6-DNT, 2,4,6-TNT, 4-A-2,6-DNT, 2-A-4,6-DNT, Tetryl, Hexyl, RDX, HMX, PETN) listed in ISO 11916-1(soil, HPLC/UV method) except for nitrobenzene, 2-nitrotoluene, 3-nitrotoluene and 4-nitrotoluene. In case of nitrobenzene and nitrotoluenes, they have the low sensitivity in LC-MS/MS measurement. In particular, this method is effective for the analysis of PETN, 1,3,5-TNB and tetryl when comparing with the method using HPLC. Also LC-MS/MS method is getting more familiar in ISO standard development (e.g. ISO/CD22104 Water quality--Microcystins, ISO/NP21677 Water quality--HBCD, ISO/CD21675 Water quality--PFAS).

(standards.iteh.ai)

oSIST prEN ISO 11916-3:2020 https://standards.iteh.ai/catalog/standards/sist/665af326-7400-45e3-a29d-07370cbbdabf/osist-pren-iso-11916-3-2020 Soil quality — Determination of selected explosives and related compounds — — Part 3: Method using liquid chromatography-tandem mass spectrometry (LC-MS/MS)

1 Scope

This part of ISO 11916 specifies the measurement of explosives and related nitrocompounds (as given in Table 1) in soil and soil materials. This document is intended for the trace analysis of explosives and related compounds by liquid chromatography–tandem mass spectrometry (LC-MS/MS). Generally, LC-MS/MS measurement shows the lower LOQ (limit of quantification) for each compound in Table 1 than that of high-performance liquid chromatography (HPLC) measurement.

Under the conditions specified in this document, concentrations as low as 0,005 mg/kg to 0,014 mg/kg-dry matter can be determined, depending on the substance. Similar compounds, in particular various nitroaromatics, by-products and degradation products of explosive compounds may be analyzed using this method. However, the applicability should be checked on a case-by-case basis.

Table 1—Explosive and related nitrocompounds for analysis

Compound (standards.iteh.ai	Abbreviation	CAS-RN ^a		
1,3-Dinitrobenzene oSIST prEN ISO 11916-3:2020	1,3-DNB	99-65-0		
1,3,5-Trinitrobenzenetps://standards.iteh.ai/catalog/standards/sist/665af326-	7 403,55ENB 29d-	99-35-4		
2,4-Dinitrotoluene	2,4-DNT	121-14-2		
2,6-Dinitrotoluene	2,6-DNT	606-20-2		
2,4,6-Trinitrotoluene	2,4,6-TNT	118-96-7		
4-Amino-2,6-dinitrotoluene	4-A-2,6-DNT	19406-51-6		
2-Amino-4,6-dinitrotoluene	2-A-4,6-DNT	35572-78-2		
<i>N</i> -Methyl- <i>N</i> -2,4,6-tetranitroaniline	Tetryl	479-45-8		
2,4,6-Trinitro-N-(2,4,6-trinitrophenyl)aniline	Hexyl	131-73-7		
1,3,5-Trinitrohexahydro-1,3,5-triazine	RDX	121-82-4		
1,3,5,7-Tetranitroo ctahydro-1,3,5,7-tetrazocine	НМХ	2691-41-0		
Pentaerythrityltetranitrate	PETN	78-11-5		
a CAS-RN: Chemical Abstract Service-Registry Number				

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 11465, Soil quality — Determination of dry matter and water content on a mass basis — Gravimetric method

3 Principle

Explosive materials in soils are extracted with acetonitrile by using one of the following techniques:

- ultrasonic bath with ultrasonic waves as medium (USE);
- horizontal mechanical shaker at room temperature (MSE);

There are two further extraction procedures such as pressurized liquid extraction (PLE) and soxhlet apparatus that works isothermically at boiling temperature (SOX). However, they might not be suitable for PETN, tetryl and 1,3,5-TNB.

The extract containing the analytes is either injected directly, or if necessary diluted prior to injection, into a reversed-phase high-performance liquid chromatograph-tandem mass spectrometer (LC-MS/MS).

WARNING — Take care when transporting, storing of treating explosive materials. High temperature, high pressure and static electricity shall be prevented when storing explosive materials. Small amounts of explosive materials should be kept moist in a cool, dark place. Soil samples containing explosives with mass fraction of less than 14% do not have a risk of explosion.

4 Interferences

Solvents, reagents, glassware, and other hardware used for sample processing may yield artifacts and/or elevated baselines, causing misinterpretation of the chromatograms. All of these materials shall therefore be demonstrated to be free of contaminants and interferences through the analysis of method blanks.

Samples containing 2,4,6-trinitrobenzoic acid should not be extracted with acetonitrile as it may result in the overestimation of 1,3,5-TNB due to decarboxylation. To avoid this interference, methanol extraction can be an alternative method for 1,3,5-TNB.

5 Reagents

5.1 General

All reagents shall be blank-free and of recognized analytical grade.

5.2 Chemicals

- **5.2.1 Water,** with a electrical conductivity of ≥ 0.01 mS/m (25°C).
- **5.2.2 Acetonitrile,** CH₃CN, HPLC grade or equivalent.
- **5.2.3 Methanol**, CH3OH, HPLCgrade or equivalent.
- **5.2.4 Ammonium acetate in water,** 2,5 mmol/l.

For the preparation, weigh 96,3 mg of ammonium $acetate(C_2H_7NO_2)$ into 500 ml measuring flasks (scale: mg/ml), fill up to the mark with water (5.2.1). Prepare the reagent just before it is used. Before using as a mobile phase, filter the reagent using filter paper (6.1.7). After filtration, degas the filtrate using sonic bath or other methods.

5.2.5 Ammonium acetate in methanol, 2,5 mmol/l.

For the preparation, weigh 96,3 mg of ammonium acetate(C2H7NO2) into 500 ml measuring flasks (scale: mg/ml), fill up to the mark with methanol (5.2.3). Prepare the reagent just before it is used. Before using as a mobile phase, filter the reagent using filter paper (6.1.7). After filtration, degas the filtrate using sonic bath or other methods.

5.3 Standard substances and solutions

iTeh STANDARD PREVIEW

5.3.1 Standard substances

(standards.iteh.ai)

5.3.1.1 Reference substances

oSIST prEN ISO 11916-3:2020

Compounds listed intipabler lards.iteh.ai/catalog/standards/sist/665af326-7400-45e3-a29d-07370cbbdabf/osist-pren-iso-11916-3-2020

5.3.1.2 Method-checking standards

Suitable compound(s) not found in the sample (i.e. 2,5-dinitrotoluene or 1,2-dinitrobenzene). It is recommended that the concentration of method-checking standards in the final extract is ranged from 0,04 mg/l to 0,1 mg/l. Before selecting the method-checking standards, confirm the applicability of those standards according to the analytical conditions of each laboratory.

5.3.2 Standard solutions

5.3.2.1 General

All standard solutions used in this method shall be prepared as described below.

NOTE If commercially available certified standard stock solutions are used, calibration solutions are prepared in volumetric flasks by diluting the stock solutions with acetonitrile (5.2.2).

All dilution steps shall not exceed the factor 100.

5.3.2.2 Single-substance stock solutions

For the preparation, weigh $50 \text{ mg} \pm 0.1 \text{ mg}$ of the reference substances into 50 ml measuring flasks (scale: mg/ml), fill up to the mark with acetonitrile (5.2.2) and let the reference substances dissolve completely.

Transfer the stock solutions to amber-glass flasks and seal with polytetrafluoroethylene (PTFE)-coated screw caps. The stock solutions can be kept in the refrigerator at 2 °C to 6 °C in the dark for up to 6 month.

5.3.2.3 Multi-component stock solutions

Prepare multi-component stock solutions of different concentrations from the various single-substance stock solutions (5.3.2.2) by mixing and diluting with acetonitrile (5.2.2). At concentrations below 1 mg/ml, solutions should be checked after one week as reference substances may decompose.

5.3.2.4 Calibration standard solutions

Calibration standard solutions are prepared by the dilution of multi-component stock solutions. The working range of 0,01 mg/l to 0,2 mg/l is recommendable. A minimum of 5 concentration levels is needed for the calibration.

6 Apparatus

6.1 General

Usual laboratory apparatus and the followings.

- 6.1.1 Amber glass containers with caps containing PTFE coated lining.
- 6.1.2 Amber glass vials with caps containing septa with PTFE coated lining. (Standards.iteh.ai)
- 6.1.3 Amber glass conical bottles with ground-in stopper.

oSIST prEN ISO 11916-3:2020

i leh STANDARD PRE

6.1.4 Analytical balance, with a precision of lat least 0,1 sing 65 af 326-7400-45e3-a29d-

07370cbbdabf/osist-pren-iso-11916-3-2020

- **6.1.5 Laboratory centrifuge,** capable of producing an acceleration of at least 1 000 G.
- **6.1.6 Membrane filter**, 0,45 μm pore size.

Any adsorption of the target compounds shall be avoided. No interfering material shall be eluated. PTFE, polyamide or an equivalent material is recommended.

6.2 Equipment for extraction

6.2.1 Temperature-controlled ultrasonic bath, 35 Hz, effective HF-power of at least 140 W.

Water bath capable of maintaining the temperature at (30 ± 5) °C or at (50 ± 5) °C during ultrasonic extraction.

6.2.2 Horizontal mechanical shaker.

The shaker shall maintain a frequency of 100 cycles/min and offer a shaking width of about 10 cm.