

SLOVENSKI STANDARD

SIST EN 3660-004:2019+AC:2019

01-julij-2019

Nadomešča:

SIST EN 3660-004:2019

Aeronavtika - Dodatki za okrogle in pravokotne električne in optične konektorje - 004. del: Kabelska spojka, tip A, ravna, netesnjena, z razbremenilno sponko - Standard za proizvod (vključno s popravkom AC)

Aerospace series - Cable outlet accessories for circular and rectangular electrical and optical connectors - Part 004: Cable outlet, style A, straight, unsealed with clamp strain relief - Product standard

iTeh STANDARD PREVIEW

Luft- und Raumfahrt - Endgehäuse für elektrische und optische Rund- und Rechtecksteckverbinder - Teil 004: Endgehäuse, Bauform A, gerade Ausführung, nicht abgedichtet, mit Zugentlastungsklemme - Produktnorm

<https://standards.iteh.ai/catalog/standards/sist/4125e88b-08d8-4d69-8569-ac3fde9b1e79/sist-en-3660-004-2019ac-2019>

Série aérospatiale - Accessoires arrière pour connecteurs circulaires et rectangulaires électriques et optiques - Partie 004 : Raccord droit non étanche type A avec brides serre-câbles - Norme de produit

Ta slovenski standard je istoveten z: EN 3660-004:2018+AC:2019

ICS:

31.220.10	Vtiči in vtičnice, konektorji	Plug-and-socket devices. Connectors
49.060	Letalska in vesoljska električna oprema in sistemi	Aerospace electric equipment and systems

SIST EN 3660-004:2019+AC:2019

en,fr,de

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 3660-004:2019+AC:2019

<https://standards.iteh.ai/catalog/standards/sist/4125e88b-08d8-4d69-8569-ac3fde9b1e79/sist-en-3660-004-2019ac-2019>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 3660-004:2018+AC

April 2019

ICS 49.060

Supersedes EN 3660-004:2018

English Version

Aerospace series - Cable outlet accessories for circular and rectangular electrical and optical connectors - Part 004: Cable outlet, style A, straight, unsealed with clamp strain relief - Product standard

Série aérospatiale - Accessoires arrière pour connecteurs circulaires et rectangulaires électriques et optiques - Partie 004 : Raccord droit non étanche type A avec brides serre-câbles - Norme de produit

Luft- und Raumfahrt - Endgehäuse für elektrische und optische Rund- und Rechtecksteckverbinder - Teil 004: Endgehäuse, Bauform A, gerade Ausführung, nicht abgedichtet, mit Zugentlastungsklemme - Produktnorm

This European Standard was approved by CEN on 11 June 2018 and includes Corrigendum 1 issued by CEN on 24 April 2019.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents

Page

European foreword.....	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	4
4 Characteristics	5
5 Designation.....	12
6 Marking.....	12
7 Technical specification.....	12

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 3660-004:2019+AC:2019

<https://standards.iteh.ai/catalog/standards/sist/4125e88b-08d8-4d69-8569-ac3fde9b1e79/sist-en-3660-004-2019ac-2019>

European foreword

This document (EN 3660-004:2018+AC:2019) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2019, and conflicting national standards shall be withdrawn at the latest by October 2019.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document includes Corrigendum 1 issued by CEN on 24 April 2019.

This document supersedes AC EN 3660-004:2018 AC.

The start and finish of text introduced or altered by corrigendum is indicated in the text by tags AC AC.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

EN 3660-004:2018+AC:2019 (E)

1 Scope

This European Standard defines a range of cable outlets, style A, straight, unsealed with clamp strain relief for use under the following conditions:

Associated electrical connector(s) : EN 3660-002

Temperature range, Class N : – 65 °C to 200 °C

Class W : – 65 °C to 175 °C

Class K : – 65 °C to 260 °C

Class A : – 65 °C to 200 °C

AC Class T : – 65 °C to 175 °C

Class Z : – 65 °C to 175 °C AC

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 2591-*, *Aerospace series — Elements of electrical and optical connection — Test methods*

EN 2997 (all parts), *Aerospace series — Connectors, electrical, circular, coupled by threaded ring, fire-resistant or non fire-resistant, operating temperatures – 65 °C to 175 °C continuous, 200 °C continuous, 260 °C peak*

SIST EN 3660-004:2019+AC:2019

<https://standards.iteh.ai/catalog/standards/sist/4125e88b-08d8-4d69-85c3b01e770c/sist-en-3660-004-2019+ac-2019>

EN 3660-001, *Aerospace series — Cable outlet accessories for circular and rectangular electrical and optical connectors — Part 001: Technical specification*

EN 3660-002, *Aerospace series — Cable outlet accessories for circular and rectangular electrical and optical connectors — Part 002: Index of product standards*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 3660-001 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

* All parts quoted in this European Standard.


4 Characteristics

4.1 Dimensions and mass

For dimensions and mass, see Figure 1 and Table 1.

For interface dimensions, see 4.2.

Dimensions in millimetres



Detail Z

Key

- 1 Thread *A*
- 2 Three off wire lock holes equi-spaced for 0,8 mm max. diameter wire
- 3 Teeth *N* (see Table 2)
- 4 Knurled, manufacturer's option
- 5 Marking (see Clause 6)
- 6 Fillister head screw with wire locking hole
- 7 Four blind holes for torque wrench equi-spaced (see Figure 1, detail Z)

NOTE 1 For details X and Y, see 4.2.2.

NOTE 2 Coupling nut to be captive on cable outlet body but free to rotate.

^a The location of blind holes axis can be left to the manufacturer's preference. Location of blind holes is not mandatory.

Figure 1

EN 3660-004:2018+AC:2019 (E)

Table 1

Shell size	<i>A</i> Thread Class 2B inches	$\varnothing B$ max. mm	$\varnothing C$ + 0,64 0 mm	<i>D</i> 0 – 1,57 mm	<i>E</i> ^a 0 – 0,56 mm	<i>K</i> $\pm 1,57$ mm	<i>M</i> ^b Wire accommodation max. min. mm	
08	0,500-20UNF	19,47	12,74	13,72	7,75	22,61	5,2	3,2
10	0,625-24UNEF	22,47	15,88	13,72	7,75	25,40	7,3	4,8
12	0,750-20UNEF	25,47	19,05	13,72	7,75	28,58	9,8	7,4
14	0,875-20UNEF	28,67	22,23	13,72	7,75	28,58	11,3	9,0
16	1,000-20UNEF	31,67	25,40	13,72	7,75	31,75	15,1	12,8
18	1,063-18UNEF	34,67	27,00	13,72	7,75	38,10	16,3	13,2
20	1,188-18UNEF	37,67	30,18	13,72	7,75	41,28	17,9	15,0
22	1,313-18UNEF	40,67	33,35	13,72	7,75	43,18	19,5	16,3
24	1,438-18UNEF	44,07	36,53	13,72	7,75	47,62	20,3	18,0
28	1.750-18UNS	50,97	44,45	17,30	7,75	55,55	20,7	19,0

Shell size	<i>M</i> ₁ ^b Wire accommodation max. min. mm		<i>P</i> $\pm 0,5$ mm	<i>R</i> $\pm 0,5$ mm	Screw size Class 2A inches	<i>T</i> ₁ ^b $\pm 0,8$ mm	<i>T</i> ₂ ^b $\pm 0,8$ mm	<i>U</i> max. mm	<i>V</i> min. mm	Mass Classes N, A, W, T and Z Class K max. g	
08	5,2	3,2	18,6	6,35	6-32UNC	12,7	12,7	2,2	7,30	10,11	22,17
10	7,3	4,8	20,6	6,35	6-32UNC	12,7	12,7	2,2	7,10	11,98	27,48
12	10,6	7,4	24,6	6,35	6-32UNC	12,7	15,9	2,2	6,80	13,59	31,94
14	12,0	9,0	26,1	6,35	6-32UNC	12,7	15,9	2,2	6,60	16,34	37,76
16	16,0	12,8	33,0	6,35	6-32UNC	12,7	15,9	2,2	7,80	18,74	45,50
18	18,0	13,2	36,4	9,53	8-32UNC	15,9	19,1	2,2	9,00	24,78	57,07
20	21,0	15,0	39,0	9,53	8-32UNC	15,9	22,3	2,2	8,80	27,08	62,87
22	24,3	16,3	41,5	9,53	8-32UNC	15,9	25,4	2,2	8,80	29,13	69,09
24	27,5	18,0	44,6	9,53	8-32UNC	15,9	28,6	2,2	9,20	31,66	74,20
28	30,0	19,0	50,8	12,70	8-32UNC	19,5	31,8	2,2	12,1 0	48,63	116,63

^a *E* dimension is taken when the coupling nut is pulled in forward position.

^b *M* and *T* dimensions are for variant **A**; *M*₁ and *T*₁ dimensions are for variants **B**. *M* and *M*₁ diameters are clamp hardware limits and not wire bundle accommodation sizes.

4.2 Interface dimensions

4.2.1 Associated connection

See EN 3660-002.

4.2.2 Front interface

See Figure 2, Figure 3 and Table 2.




Figure 2 — Detail X




Figure 3 — Detail Y

SIST EN 3660-004:2019+AC:2019
<https://standards.iteh.ai/catalog/standards/sist/4125e88b-08d8-4d69-8569-ac3fde9b1e79/sist-en-3660-004-2019ac-2019>

Table 2

Dimensions in millimetres

Shell size	$\varnothing G$ Ref.	$\varnothing H$ $+0,10$ 0	$\varnothing J$ $+0,18$ 0	$\varnothing L$ $+0,18$ 0	N Number of teeth
08	11,10	9,15	7,92	6,68	12
10	14,53	12,36	11,13	9,35	15
12	17,45	15,30	14,07	12,62	21
14	20,62	18,48	17,25	14,68	24
16	23,80	21,65	20,42	17,73	30
18	25,20	23,08	21,85	19,86	33
20	28,37	26,25	25,02	23,04	36
22	31,55	29,43	28,20	26,21	39
24	34,72	32,60	31,37	29,13	42
28	42,75	38,90	37,67	35,10	54