INTERNATIONAL STANDARD



First edition 2018-04

Smart community infrastructures — Smart transportation for compact cities

Infrastructures communautaires intelligentes — Transport intelligent dans les villes compactes

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 37157:2018</u> https://standards.iteh.ai/catalog/standards/sist/2339d0f8-5404-4c2f-a058b12633f0c3a4/iso-37157-2018



Reference number ISO 37157:2018(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 37157:2018</u> https://standards.iteh.ai/catalog/standards/sist/2339d0f8-5404-4c2f-a058b12633f0c3a4/iso-37157-2018



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Page

Contents

Forew	vord		iv
Introduction			
1			
2		ative references	
_			
3		s and definitions	
4	Conce 4.1 4.2	e pt of smart transportation for compact cities General Applicable city issues	1
5	Adoption of smart transportation for compact cities		
	5.1 5.2 5.3	ObjectivesTarget areaSelection of transportation modes5.3.1General5.3.2Service frequency5.3.3Station/stop interval5.3.4Effective area size5.3.5Service network shape5.3.6Coach convenience, ride comfort and safety5.3.7Geographical applicability5.3.8Running performance5.3.9Exclusive tracks5.3.10Promotion of environmentally friendly vehicles and life-cycle performance5.3.11Improvement of land reuse5.3.12Energy savingISO 37157/20185.3.14Rider feesb12633f0c3a4/iso-37157-2018Installation of smart transportation	2 2 2 2 2 2 3 3 3 3 3 3 3 3 3 3 3 4 4
6	Maintaining the quality of smart transportation for compact cities		
	6.1 6.2	General Parameters to be observed	
	6.3	Modification of smart transportation	
Anne	x A (info	ormative) Examples of smart transportation for the development of compact citie s	
Anne	x B (info pollut trans	ormative) Trials given by Paris City in December 2016 to suppress air tion by inviting citizens using engine-driven vehicles to electrically operated portation services	6
Biblic	graphy	V	7

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html. (standards.iteh.ai)

This document was prepared by Technical Committee ISO/TC 268, Sustainable cities and communities, Subcommittee SC 1, Smart community infrastructures 7157:2018 https://standards.iteh.ai/catalog/standards/sist/2339d0f8-5404-4c2f-a058-

In the development of this document, ISO Guide 82 has been taken into account in addressing sustainability issues.

Introduction

A compact city is an urban design concept that invites people back to a small area in a city where the population has decreased or is decreasing. Modal shifts of passengers from public to private transportation have resulted in people moving out of the city centre into the suburbs, since private transportation enables movement without dependent time schedules and fixed routes. The problems associated with public transportation are mainly related to station or stop intervals, service frequency, approaches to stations/stops and service routes and networks. Furthermore, large-scale shopping malls and hospitals are frequently constructed outside cities. Such a situation accelerates the outflow of residents, resulting in the de-urbanization of city centres. Downtown, the public realm and community safety fall into decline, causing more people to move out to the suburbs. This negative spiral continues, changing the character of a city.

One way to pre-empt the deterioration of a city centre is through the creation of a compact city. The concept behind compact cities is that facilities for citizens, such as shopping malls, offices and hospitals, are placed in a small target areas. These facilities are connected to one another by short-interval, high-frequency public transportation which can be easily accessed by citizens. Additionally, this type of transportation reconnects citizens living in the suburbs to the urban centre, with service lines laid radially in relation to the suburbs surrounding the area. This transportation network successfully attracts people into a target area from its periphery and retains them therein. This is a solution to the problem of declining city centres, utilizing smart transportation to resuscitate small downtown areas. This document describes a way to organize smart transportation to create a compact city that regenerates a declining urban centre and rejuvenates its economic, physical and social infrastructure.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 37157:2018 https://standards.iteh.ai/catalog/standards/sist/2339d0f8-5404-4c2f-a058b12633f0c3a4/iso-37157-2018

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 37157:2018</u> https://standards.iteh.ai/catalog/standards/sist/2339d0f8-5404-4c2f-a058b12633f0c3a4/iso-37157-2018

Smart community infrastructures — Smart transportation for compact cities

1 Scope

This document describes criteria to help plan or organize smart transportation for compact cities. It is intended to apply to cities facing a decline in population. Smart transportation can be applied to the issue of population loss as a means of attracting people back to the city.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/

3.1

<u>ISO 37157:2018</u>

compact city https://standards.iteh.ai/catalog/standards/sist/2339d0f8-5404-4c2f-a058city where the majority of facilities and amenities that support life for citizens are accessible within a radius of approximately 1 km

Note 1 to entry: Such facilities and amenities would generally include those that support employment, shopping and commerce, medical and educational needs and cultural activities.

3.2 light rail transit LRT transportation system using t

transportation system using trams or rolling stock

3.3 automated guideway transit

AGT

automated operation-applicable transportation system using polymer tire-supporting rolling stock equipped with guide wheels contacting guide rails for steering

Note 1 to entry: Typical AGT service lines are Bukit Panjang LRT in Singapore, Port Liner in Kobe, Japan, and MIA Mover in Miami International Airport, USA.

4 Concept of smart transportation for compact cities

4.1 General

The facilities of a compact city should be connected by transportation systems that provide a high frequency of service and are easily accessible. In addition, the transportation systems' stations or stops should be located at close intervals, and serviced by vehicles that can successfully start and stop at short intervals. These vehicles need not necessarily be high capacity. Such specific transportation

systems provide people living in the suburbs with easy access to the target area and encourage them to stay therein. By using these transportation systems, the target area begins to be repopulated.

4.2 Applicable city issues

The criteria for smart transportation described in this document are appropriate for addressing the issue of declining population within a city where the goal is to retain and attract more people to the city.

5 Adoption of smart transportation for compact cities

5.1 Objectives

As mentioned in <u>4.2</u>, smart transportation as described in this document can help address the issue of declining population within a city where the goal is to retain the current population and attract more people to the city.

To help achieve this goal, transportation modes which meet the conditions described in 5.3 should be selected.

5.2 Target area

A depopulated area to be repopulated by building facilities for city life, such as shopping centres, offices, hospitals, residential areas, educational facilities and cultural facilities, which are connected by smart transportation. Examples of compact cities using smart transportation are listed in Annex A, Table A.1.

5.3 Selection of transportation modes **modes iteh.ai**)

5.3.1 General

<u>ISO 37157:2018</u>

https://standards.iteh.ai/catalog/standards/sist/2339d0f8-5404-4c2f-a058-

Transportation modes which provide transportation services meeting the conditions specified from 5.3.2 to 5.3.14 should be selected.

NOTE Light rail transit (LRT), buses and automated guideway transit (AGT) are typical transportation modes that foster the development of compact cities.

5.3.2 Service frequency

The transportation service should be provided no less than every 10 min during rush hour.

NOTE Normally, the higher the population density and expected passenger numbers, the higher the service frequency that would be needed.

5.3.3 Station/stop interval

Stations or stops should be placed so that the average distance between them is no more than 300 m, except when it is hard to place stations or stops at this distance due to geographical or traffic conditions or specific local situations.

NOTE Typical exemptions include smart transportation routes on bridges or in tunnels.

5.3.4 Effective area size

The area afflicted by depopulation to be addressed by smart transportation should be contained within a 1-km radius.

5.3.5 Service network shape

Smart transportation service networks should be arranged in a radial formation from the centre of a target area to the suburbs.

5.3.6 Coach convenience, ride comfort and safety

Entry and exit from the transportation vehicle should be easy and accessible for all, including the elderly, children and people with small children. Users with disabilities should be able to enter and exit with minimal or no assistance. Vehicles should provide a comfortable ride for all, including the elderly, children and those with disabilities, with little vibration or noise. Where appropriate, vehicles should be air-conditioned. Vehicles can also include space for bicycles or other large items.

Vehicles should be equipped with handrails, handgrips, hanging straps and non-slip floors for safety, and there should be easy communication channels, especially with a dispatcher, in case of emergency.

NOTE Battery-powered buses provide comfort, and are widely used, because no gear changes are needed, meaning no sudden shocks.

5.3.7 Geographical applicability

Suitable transportation systems should be used in according with the geographical and meteorological conditions they will operate in.

Often, the target area to be developed as a compact city used to be the city centre, with narrow, winding streets. The transportation system should be suitable even in such conditions.

5.3.8 Running performance (standards.iteh.ai)

Vehicles should have acceleration high enough to ensure time saving for travel on such a service line with stops/stations_at_short_intervals_catalog/standards/sist/2339d0f8-5404-4c2f-a058-

b12633f0c3a4/iso-37157-2018

5.3.9 Exclusive tracks

Tracks and/or dedicated street lanes should be placed in service for use by the smart transportation system only.

5.3.10 Promotion of environmentally friendly vehicles and life-cycle performance

Transportation systems which produce low chemical emissions, vibration and noise levels should be used. Furthermore, positive application of technologies should be promoted to develop environmentally friendly vehicles and enhance the life-cycle performance of the transportation.

EXAMPLE To promote environmentally friendly performance, many cities across the world have introduced battery-powered buses, which produce no CO_2 , NOx, SOx or PMs. An example of a successful trial is given in Annex B.

5.3.11 Improvement of land reuse

Transportation modes which allow for the reuse of compact city land for any kind of facilities that do not have a chemical or geological impact should be used.

5.3.12 Energy saving

Transportation systems which can save energy by, for example, using recovered braking energy, minimizing energy consumption, optimizing operation schedules or controlling vehicle running performance should be used.