
Aeronavtika - Dodatki za okrogle in pravokotne električne in optične konektorje - 004. del: Kabelska spojka, tip A, ravna, netesnjena, z razbremenilno sponko - Standard za proizvod

Aerospace series - Cable outlet accessories for circular and rectangular electrical and optical connectors - Part 004: Cable outlet, style A, straight, unsealed with clamp strain relief - Product standard

Luft- und Raumfahrt - Endgehäuse für elektrische und optische Rund- und Rechtecksteckverbinder - Teil 004: Endgehäuse, Bauform A, gerade Ausführung, nicht abgedichtet, mit Zugentlastungsklemme - Produktnorm

Série aérospatiale - Accessoires arrière pour connecteurs circulaires et rectangulaires électriques et optiques - Partie 004 : Raccord, type A, droit, non-étanche, avec brides serre-câbles - Norme de produit

Ta slovenski standard je istoveten z: prEN 3660-004

ICS:

31.220.10	Vtiči in vtičnice, konektorji	Plug-and-socket devices. Connectors
49.060	Letalska in vesoljska električna oprema in sistemi	Aerospace electric equipment and systems

oSIST prEN 3660-004:2020

en,fr,de

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN 3660-004:2020](https://standards.iteh.ai/catalog/standards/sist/7b06b6b1-53f1-4c14-842c-b79c7d489b62/osist-pren-3660-004-2020)

<https://standards.iteh.ai/catalog/standards/sist/7b06b6b1-53f1-4c14-842c-b79c7d489b62/osist-pren-3660-004-2020>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

DRAFT
prEN 3660-004

June 2020

ICS 49.060

Will supersede EN 3660-004:2018+AC:2019

English Version

Aerospace series - Cable outlet accessories for circular and rectangular electrical and optical connectors - Part 004: Cable outlet, style A, straight, unsealed with clamp strain relief - Product standard

Série aérospatiale - Accessoires arrière pour connecteurs circulaires et rectangulaires électriques et optiques - Partie 004 : Raccord droit non étanche type A avec brides serre-câbles - Norme de produit

Luft- und Raumfahrt - Endgehäuse für elektrische und optische Rund- und Rechtecksteckverbinder - Teil 004: Endgehäuse, Bauform A, gerade Ausführung, nicht abgedichtet, mit Zugentlastungsklemme - Produktnorm

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee ASD-STAN.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents

Page

European foreword	3
1 Scope.....	4
2 Normative references.....	4
3 Terms and definitions	4
4 Characteristics	4
4.1 Dimensions and mass	4
4.2 Interface dimensions	7
4.2.1 Associated connection.....	7
4.2.2 Front interface	7
4.3 Material finish	8
4.4 Assembly torque.....	8
4.5 Coupling thread strength torque.....	9
4.6 Tests.....	9
5 Designation	12
6 Marking.....	12
7 Technical specification	12
Bibliography.....	13

iTeh STANDARD PREVIEW
(standards.iteh.ai)

oSIST prEN 3660-004:2020
<https://standards.iteh.ai/catalog/standards/sist/7b06b6b1-53f1-4c14-842c-b79c7d489b62/osist-pren-3660-004-2020>

European foreword

This document (prEN 3660-004:2020) has been prepared by the Aerospace and Defence Industries Association of Europe – Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD-STAN, prior to its presentation to CEN.

This document is currently submitted to the CEN Enquiry.

This document will supersede EN 3660-004:2018+AC:2019.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN 3660-004:2020](https://standards.iteh.ai/catalog/standards/sist/7b06b6b1-53f1-4c14-842c-b79c7d489b62/osist-pren-3660-004-2020)

<https://standards.iteh.ai/catalog/standards/sist/7b06b6b1-53f1-4c14-842c-b79c7d489b62/osist-pren-3660-004-2020>

prEN 3660-004:2020 (E)**1 Scope**

This document defines a range of cable outlets, style A, straight, unsealed with clamp strain relief for use under the following conditions:

Associated electrical connector(s): EN 3660-002

Temperature range, Class N: –65 °C to 200 °C

Class W: –65 °C to 175 °C

Class K: –65 °C to 260 °C

Class A: –65 °C to 200 °C

Class T: –65 °C to 175 °C (nickel PTFE plating)

Class Z: –65 °C to 175 °C (black zinc nickel plating)

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 2591 (all parts), *Aerospace series - Elements of electrical and optical connection - Test methods*

EN 3660-001, *Aerospace series - Cable outlet accessories for circular and rectangular electrical and optical connectors - Part 001: Technical specification*

EN 3660-002, *Aerospace series - Cable outlet accessories for circular and rectangular electrical and optical connectors - Part 002: Index of product standards*

<https://standards.iteh.ai/catalog/standards/sist/7b06b6b1-53f1-4c14-842c-b79c7d489b62/osist-pren-3660-004-2020>

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 3660-001 apply.


ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp/ui>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Characteristics**4.1 Dimensions and mass**

For dimensions and mass, see Figure 1 and Table 1.

For interface dimensions, see 4.2.

**Key**

- 1 Thread A
- 2 3 (three) off-wire lock holes equi-spaced for 0,8 mm max. diameter wire
- 3 Teeth *N* (see Table 2)
- 4 Knurled, manufacturer's option
- 5 Marking (see Clause 6)
- 6 Fillister head screw with wire locking hole
- 7 4 (four) blind holes for torque wrench equi-spaced (see Figure 1, detail Z)

NOTE 1 For details X and Y, see 4.2.2

NOTE 2 Coupling nut to be captive on cable outlet body but free to rotate

a The location of blind holes axis can be left to the manufacturer's preference. Location of blind holes is not mandatory

Figure 1

Table 1

Shell size	A Thread Class 2B inches	$\varnothing B$ max. mm	$\varnothing C$ + 0,64 0 mm	D 0 - 1,57 mm	E ^a 0 - 0,56 mm	K max. mm	M ^b Wire accommodation	
							max.	min.
							mm	
08	0,500-20UNF	19,47	12,74	13,72	7,75	22,61	5,2	3,2
10	0,625-24UNEF	22,47	15,88	13,72	7,75	25,40	7,3	4,8
12	0,750-20UNEF	25,47	19,05	13,72	7,75	28,58	9,8	7,4
14	0,875-20UNEF	28,67	22,23	13,72	7,75	28,58	11,3	9,0
16	1,000-20UNEF	31,67	25,40	13,72	7,75	31,75	15,1	12,8
18	1,063-18UNEF	34,67	27,00	13,72	7,75	38,10	16,3	13,2
20	1,188-18UNEF	37,67	30,18	13,72	7,75	41,28	17,9	15,0
22	1,313-18UNEF	40,67	33,35	13,72	7,75	43,18	19,5	16,3
24	1,438-18UNEF	44,07	36,53	13,72	7,75	47,62	20,3	18,0
28	1,750-18UNS	50,97	44,45	17,30	7,75	55,55	20,7	19,0

iTech STANDARD PREVIEW

Shell size	M ₁ ^b Wire accommodation		P	R	Screw size Class 2A	T ₁ ^b	T ₁ ^b	U	V	Mass Classes	
	max.	min.								N, A, W, T and Z	Class K
	mm	mm			inches	mm	mm	mm	mm	max.	g
08	5,2	3,2	18,6	6,35	6-32UNC	12,7	12,7	2,2	7,30	10,16	22,17
10	7,3	4,8	20,6	6,35	6-32UNC	12,7	12,7	2,2	7,10	13,73	27,48
12	10,6	7,4	24,6	6,35	6-32UNC	12,7	15,9	2,2	6,80	15,09	31,94
14	12,0	9,0	26,1	6,35	6-32UNC	12,7	15,9	2,2	6,60	17,62	37,76
16	16,0	12,8	33,0	6,35	6-32UNC	12,7	15,9	2,2	7,80	21,25	45,50
18	18,0	13,2	36,4	9,53	8-32UNC	15,9	19,1	2,2	9,00	27,48	57,07
20	21,0	15,0	39,0	9,53	8-32UNC	15,9	22,3	2,2	8,80	31,42	62,87
22	24,3	16,3	41,5	9,53	8-32UNC	15,9	25,4	2,2	8,80	33,86	69,09
24	27,5	18,0	44,6	9,53	8-32UNC	15,9	28,6	2,2	9,20	38,17	74,20
28	30,0	19,0	50,8	12,70	8-32UNC	19,5	31,8	2,2	12,10	53,31	116,63

^a E dimension is taken when the coupling nut is pulled in forward position.^b M and T dimensions are for variant A; M₁ and T₁ dimensions are for variants B. M and M₁ diameters are clamp hardware limits and not wire bundle accommodation sizes.

4.2 Interface dimensions

4.2.1 Associated connection

See EN 3660-002.

4.2.2 Front interface

See Figure 2, Figure 3 and Table 2.

Dimensions in millimetres




Figure 2 — Detail X




Figure 3 — Detail Y

STANDARD PREVIEW
(standards.itech.ai)

Table 2

oSIST prEN 3660-004:2020

<https://standards.itech.ai/catalog/standards/sist/7b06b6b1-53f1-4c14-842c-b79c7d489b62/osist-pr-en-3660-004-2020>

Dimensions in millimetres

Shell size	$\varnothing G$ Ref.	$\varnothing H$ + 0,10 0	$\varnothing J$ + 0,18 0	$\varnothing L$ + 0,18 0	N Number of teeth
08	11,10	9,15	7,92	6,68	12
10	14,53	12,36	11,13	9,35	15
12	17,45	15,30	14,07	12,62	21
14	20,62	18,48	17,25	14,68	24
16	23,80	21,65	20,42	17,73	30
18	25,20	23,08	21,85	19,86	33
20	28,37	26,25	25,02	23,04	36
22	31,55	29,43	28,20	26,21	39
24	34,72	32,60	31,37	29,13	42
28	42,75	38,90	37,67	35,10	54

prEN 3660-004:2020 (E)

4.3 Material finish

Material/Finish	Class N:	aluminium/electroless nickel plated
Material/Finish	Class W:	aluminium/olive drab cadmium plated
Material/Finish	Class K:	stainless steel/passivated
Material/Finish	Class A:	aluminium/black anodized
Material/Finish	Class T:	aluminium (nickel PTFE plated)
Material/Finish	Class Z:	aluminium (black zinc nickel plated)

4.4 Assembly torque

These torque values are intended for installation use only, see Table 3.

Table 3

Shell size	Torque Nm $\pm$ 0,5	
	Classes N, W, A, T and Z	Class K
08	4,5 https://standards.iteh.ai/catalog/standards/sist/7b06b6b1-53f1-4c14-842c-b79c7d489b62/osist-pren-3660-004-2020	6,3
10		8,6
12		12,2
14		13,1
16		
18		
20		
22		
24		
28	13,6	16,7