



Designation: D3620 – 04 (Reapproved 2009)

## Standard Specification for Glacial Acetic Acid<sup>1</sup>

This standard is issued under the fixed designation D3620; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

### 1. Scope\*

1.1 This specification covers glacial (99.8 %) acetic acid for use in paint, varnish, lacquer, and related products.

1.2 The following applies to all specified limits in this standard; for purposes of determining conformance with this standard, an observed value or a calculated value shall be rounded off “to the nearest unit” in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E29.

1.3 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

1.5 For specific hazard information and guidance, see the supplier’s Material Safety Data Sheet for materials listed in this specification.

### 2. Referenced Documents

- 2.1 *ASTM Standards*:<sup>2</sup>
- D2191 Test Method for Acetaldehyde Content of Vinyl Acetate
  - D3546 Test Method for Formic Acid in Glacial Acetic Acid
  - E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications
  - E180 Practice for Determining the Precision of ASTM Methods for Analysis and Testing of Industrial and Specialty Chemicals (Withdrawn 2009)<sup>3</sup>
  - E300 Practice for Sampling Industrial Chemicals

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.35 on Solvents, Plasticizers, and Chemical Intermediates.

Current edition approved June 1, 2009. Published June 2009. Originally approved in 1977. Last previous edition approved in 2004 as D3620 – 04. DOI: 10.1520/D3620-04R09.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

<sup>3</sup> The last approved version of this historical standard is referenced on www.astm.org.

E302 Test Methods for Monobasic Organic Acids (Discontinued 2001) (Withdrawn 2001)<sup>3</sup>

E394 Test Method for Iron in Trace Quantities Using the 1,10-Phenanthroline Method

2.2 *U.S. Federal Specification*:

PPP-C-2020 Chemicals, Liquid, Dry, and Paste: Packaging of<sup>4</sup>

### 3. Properties

3.1 Glacial acetic acid shall conform to the following requirements:

Acetic acid, weight %, min	99.8
Freezing point, °C, min	16.2
Color, Pt-Co scale, max	10
Water content, weight %, max	0.16
Iron, ppm (mg/kg), max	0.40
Acetaldehyde, weight %, max	0.05
Formic acid, weight %, max	0.09

### 4. Sampling

4.1 The material shall be sampled in accordance with Practice E300.

### 5. Test Methods

5.1 The properties enumerated in this specification shall be determined in accordance with the following ASTM test methods:

5.1.1 *Purity*—Test Methods E302 estimates the purity from the freezing point.

5.1.2 *Freezing Point*—Test Methods E302.

5.1.3 *Color*—Test Methods E302.

5.1.4 *Water*—Test Methods E302.

5.1.5 *Iron*—Test Method E394, using a 20-mL specimen diluted to 80 mL with water.

5.1.5.1 *Report*—Report the iron content to the nearest 0.01 ppm (mg/kg). Duplicates that agree within 0.07 ppm absolute are acceptable for averaging (95 % confidence level).

5.1.5.2 *Precision*<sup>5</sup>—The precision statements are based upon an interlaboratory study in which one operator in eight different laboratories analyzed two samples of acetic acid in

<sup>4</sup> Available from Standardization Documents Order Desk, DODSSP, Bldg. 4, Section D, 700 Robbins Ave., Philadelphia, PA 19111-5098, http://www.dodssp.daps.mil.

<sup>5</sup> Supporting data have been filed at ASTM International Headquarters and may be obtained by requesting Research Report RR:D01-1010.

\*A Summary of Changes section appears at the end of this standard