

SLOVENSKI STANDARD oSIST prEN ISO 20932-1:2019

01-julij-2019

Tekstilije - Ugotavljanje elastičnosti tkanin - 1. del: Preskusi traku (ISO 20932-1:2018)

Textiles - Determination of the elasticity of fabrics - Part 1: Strip tests (ISO 20932-1:2018)

Textiles - Détermination de l'élasticité des étoffes - Partie 1: Essais sur bande (ISO 20932-1:2018)

Ta slovenski standard je istoveten z: prEN ISO 20932-1

ICS:

59.080.01 Tekstilije na splošno Textiles in general

oSIST prEN ISO 20932-1:2019 en

oSIST prEN ISO 20932-1:2019

Tell ST AND ARD PREWRITE AND STATE OF THE ST

oSIST prEN ISO 20932-1:2019

INTERNATIONAL STANDARD

ISO 20932-1

First edition 2018-11

Textiles — Determination of the elasticity of fabrics —

Part 1: **Strip tests**

Textiles — Détermination de l'élasticité des étoffes —

A Str. Fundades 18







COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Foreword	Con	tents	Page
1 Scope 1 2 Normative references 1 3 Terms and definitions 1 4 Principle 3 5 Sampling 3 6 Apparatus 4 7 Atmosphere for conditioning and testing 5 8 Preparation of test specimens 5 8.1 General 5 8.2 Test specimen preparation 5 8.2.1 Woven fabrics 5 8.2.2 Knitted fabrics 6 8.2.3 Nonwoven fabrics (other than knitted) 8 9.1 Woven and nonwoven fabrics (other than knitted) 8 9.1.1 Method A — Strip test specimens 8 9.2 Knitted fabrics 8 9.2.1 Method B — Loop test specimens 8 9.2.2 Method B — Loop test specimens 9 9.3 Operation 9 10 Recording 10 11 Expressions and calculations of test results 10 12 Test report 11	Forev	vord	iv
2 Normative references 1 3 Terms and definitions 1 4 Principle 3 5 Sampling 3 6 Apparatus 4 7 Atmosphere for conditioning and testing 5 8 Preparation of test specimens 5 8.1 General 5 8.2 Test specimen preparation 5 8.2.1 Woven fabrics 5 8.2.2 Knitted fabrics 6 8.2.3 Nonwoven fabrics 7 9 Procedure 8 9.1 Woven and nonwoven fabrics (other than knitted) 8 9.1.1 Method A — Strip test specimens 9 9.1.2 Method B — Loop test specimens 8 9.1.2 Method B — Loop test specimens 8 9.2.1 Method A — Strip test specimens 8 9.2.2 Method B — Loop test specimens 9 9.3 Operation 9 10 Recording 10 11 Expressions and calculations of test results 10	Intro	luction	v
2 Normative references 1 3 Terms and definitions 1 4 Principle 3 5 Sampling 3 6 Apparatus 4 7 Atmosphere for conditioning and testing 5 8 Preparation of test specimens 5 8.1 General 5 8.2 Test specimen preparation 5 8.2.1 Woven fabrics 5 8.2.2 Knitted fabrics 6 8.2.3 Nonwoven fabrics 7 9 Procedure 8 9.1 Woven and nonwoven fabrics (other than knitted) 8 9.1.1 Method A — Strip test specimens 9 9.1.2 Method B — Loop test specimens 8 9.1.2 Method B — Loop test specimens 8 9.2.1 Method A — Strip test specimens 8 9.2.2 Method B — Loop test specimens 9 9.3 Operation 9 10 Recording 10 11 Expressions and calculations of test results 10	1	Scope	1
3 Terms and definitions 1 4 Principle 3 5 Sampling 3 6 Apparatus 4 7 Atmosphere for conditioning and testing 5 8 Preparation of test specimens 5 8.1 General 5 8.2 Test specimen preparation 5 8.2.1 Woven fabrics 5 8.2.2 Knitted fabrics 6 8.2.3 Nonwoven fabrics (other than knitted) 8 9.1 Woven and nonwoven fabrics (other than knitted) 8 9.1 Woven and nonwoven fabrics pressures 8 9.1 Method A — Strip test specimens 9 9.2 Knitted fabrics 8 9.2 Knitted fabrics 8 9.2.1 Method B — Loop test specimens 9 9.2.2 Method B — Loop test specimens 9 9.3 Operation 9 10 Recording 10 11 Expressions and calculations of test results 10 12 Test report 11<	_	•	
4 Principle 3 5 Sampling 3 6 Apparatus 4 7 Atmosphere for conditioning and testing 5 8 Preparation of test specimens 5 8.1 General 5 8.2 Test specimen preparation 5 8.2.1 Woven fabrics 5 8.2.2 Knitted fabrics 6 8.2.3 Nonwoven fabrics (other than knitted) 8 9.1 Woven and nonwoven fabrics (other than knitted) 8 9.1 Method A — Strip test specimens 8 9.1.1 Method B — Loop test specimens 8 9.2 Knitted fabrics 8 9.2.1 Method B — Loop test specimens 9 9.2.2 Method B — Loop test specimens 9 9.3 Operation 9 10 Recording 10 11 Expressions and calculations of test results 10 12 Test report 11 Annex B (informative) Example of a typical cycling graph 13 Annex D (informative) Example of a pa	_		
5 Sampling 3 6 Apparatus 4 7 Atmosphere for conditioning and testing 5 8 Preparation of test specimens 5 8.1 General 5 8.2 Test specimen preparation 5 8.2.1 Woven fabrics 5 8.2.2 Knitted fabrics 5 8.2.3 Nonwoven fabrics (other than knitted) 8 9.1 Woven and nonwoven fabrics (other than knitted) 8 9.1.1 Method A — Strip test specimens 8 9.1.2 Method B — Loop test specimens 8 9.2.2 Knitted fabrics 8 9.2.1 Method A — Strip test specimens 8 9.2.2 Method B — Loop test specimens 9 9.3 Operation 9 10 Recording 10 11 Expressions and calculations of test results 10 12 Test report 11 Annex A (informative) Example of a typical cycling graph 13 Annex D (informative) Clamping and holding devices 15 Annex D			
6 Apparatus 4 7 Atmosphere for conditioning and testing 5 8 Preparation of test specimens 5 8.1 General 5 8.2 Test specimen preparation 5 8.2.1 Woven fabrics 5 8.2.2 Knitted fabrics 6 8.2.3 Nonwoven fabrics 7 9 Procedure 8 9.1 Woven and nonwoven fabrics (other than knitted) 8 9.1 Method A — Strip test specimens 8 9.1.2 Method B — Loop test specimens 8 9.2 Knitted fabrics 8 9.2.1 Method A — Strip test specimens 8 9.2.2 Method B — Loop test specimens 9 9.3 Operation 9 10 Recording 10 11 Expressions and calculations of test results 10 12 Test report 11 Annex A (informative) Example of a typical cycling graph 13 Annex B (informative) Clamping and holding devices 15 Annex D (informative) Example o	_	•	
7 Atmosphere for conditioning and testing 8 Preparation of test specimens 8.1 General 8.2 Test specimen preparation 5. 8.2.1 Woven fabrics 8.2.2 Knitted fabrics 8.2.3 Nonwoven fabrics 9.1 Woven and nonwoven fabrics (other than knitted) 9.1.1 Method A — Strip test specimens 9.1.2 Method B — Loop test specimens 9.2 Knitted fabrics 8 9.2.1 Nethod A — Strip test specimens 9.1.2 Method B — Loop test specimens 9.2 Knitted fabrics 9.2.1 Method A — Strip test specimens 9.2.2 Method B — Loop test specimens 9.3 Operation 10 Recording 11 Expressions and calculations of test results 12 Test report 13 Annex A (informative) Example of a typical cycling graph 14 Annex C (informative) Clamping and holding devices 15 Annex D (informative) Example of a pattern for cutting test specimens from a laboratory sample 17	5		
8 Preparation of test specimens 5 8.1 General 5 8.2 Test specimen preparation 5 8.2.1 Woven fabrics 5 8.2.2 Knitted fabrics 6 8.2.3 Nonwoven fabrics 7 9 Procedure 8 9.1 Woven and nonwoven fabrics (other than knitted) 8 9.1.1 Method A — Strip test specimens 8 9.1.2 Method B — Loop test specimens 8 9.2.1 Method A — Strip test specimens 8 9.2.1 Method B — Loop test specimens 9 9.3 Operation 9 10 Recording 10 11 Expressions and calculations of test results 10 12 Test report 11 Annex A (informative) Example of a typical cycling graph 13 Annex B (informative) Clamping and holding devices 15 Annex D (informative) Example of a pattern for cutting test specimens from a laboratory sample 17	6	Apparatus	4
8.1 General 5 8.2 Test specimen preparation 5 8.2.1 Woven fabrics 5 8.2.2 Knitted fabrics 6 8.2.3 Nonwoven fabrics 7 9 Procedure 8 9.1 Woven and nonwoven fabrics (other than knitted) 8 9.1.1 Method A — Strip test specimens 8 9.1.2 Method B — Loop test specimens 8 9.2.1 Method A — Strip test specimens 8 9.2.1 Method B — Loop test specimens 9 9.3 Operation 9 10 Recording 10 11 Expressions and calculations of test results 10 12 Test report 11 Annex A (informative) Example of a typical cycling graph 13 Annex B (informative) Clamping and holding devices 15 Annex D (informative) Example of a pattern for cutting test specimens from a laboratory sample 17	7	Atmosphere for conditioning and testing	5
11 Expressions and calculations of test results		8.1 General 8.2 Test specimen preparation 8.2.1 Woven fabrics 8.2.2 Knitted fabrics 8.2.3 Nonwoven fabrics Procedure 9.1 Woven and nonwoven fabrics (other than knitted) 9.1.1 Method A — Strip test specimens 9.1.2 Method B — Loop test specimens 9.2 Knitted fabrics 9.2.1 Method A — Strip test specimens 9.2.2 Method B — Loop test specimens	
12 Test report 11 Annex A (informative) Example of a typical cycling graph 13 Annex B (informative) Procedure for sampling 14 Annex C (informative) Clamping and holding devices 15 Annex D (informative) Example of a pattern for cutting test specimens from a laboratory sample 17	10	Recording	10
Annex A (informative) Example of a typical cycling graph	11	Expressions and calculations of test results	10
Annex B (informative) Procedure for sampling	12	Test report	11
Annex B (informative) Procedure for sampling	Anne	x A (informative) Example of a typical cycling graph	13
Annex C (informative) Clamping and holding devices			
Annex D (informative) Example of a pattern for cutting test specimens from a laboratory sample			
	Anne	D (informative) Example of a pattern for cutting test specimens from a laboratory sample	17

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 38, *Textiles*, Subcommittee SC 24, *Conditioning atmospheres and physical tests for textile fabrics*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

A list of all parts in the ISO 20932 series can be found on the ISO website.

Introduction

This document was developed as a result of technical advancements in yarn and fabric structures and properties, which increase product range and developments.

This document is based on EN 14704-1[1].

Teh S. A. O. Ard grands itell and industry and standard stands of the standard standards of the standard standards of the standard standards of the standards o

oSIST prEN ISO 20932-1:2019

Tell Standards tell adards of the standard of

Textiles — Determination of the elasticity of fabrics —

Part 1:

Strip tests

1 Scope

This document describes the methods of test using strips of fabric in straight strip form or as loops, which can be used to measure elasticity and related properties of fabrics, excluding narrow fabrics.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 139, Textiles — Standard atmospheres for conditioning and testing

ISO 4915, Textiles — Stitch types — Classification and terminology

ISO 7500-1, Metallic materials — Verification of static uniaxial testing machines — Part 1: Tension/compression testing machines — Calibration and verification of the force-measuring system

ISO 10012, Measurement management systems — Requirements for measurement processes and measuring equipment

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/

3.1

narrow fabric

woven or knitted construction intended for use as a trim, binding, edging, strapping or harness, and designed to be used in its full width

3.2

elasticity

<material> ability to recover original size and shape immediately after the removal of the force causing deformation

3.3

constant-rate-of-extension testing machine CRE testing machine

tensile testing machine provided with one clamp, which is stationary, and another clamp, which moves with a constant speed throughout the test, the entire testing system being virtually free from deflection

3.4

strip test specimen

test specimen in which the full width is gripped in the jaws of the testing machine

3.5

loop test specimen

test specimen in which a seam is made to create a loop of the full width of the specimen and which is placed around a loop bar assembly positioned on the testing machine

Note 1 to entry: This method of preparation is useful when any ageing or exposure testing is to be carried out on the specimens after measurement.

3.6

gauge length

distance between the two effective clamping or holding points of a testing device

Note 1 to entry: For strip tests, method A: distance between the two contact points of the line clamps.

Note 2 to entry: For loop tests, method B: half of the circumference around the loop bar assembly.

3.7

slack mounting

insertion of a *strip test specimen* (3.4) in the line clamps of the upper jaw, allowing it to hang freely under its own weight, guided by the hand to ensure perpendicular alignment to the line of pulling force, without any force being applied

3.8

initial length

length of the test specimen between the two effective clamping or holding points, at the beginning of the test (after *slack mounting* (3.7) or under specified pretension)

3.9

pretension

force applied to a test specimen at the beginning of certain tests

Note 1 to entry: Pretension is used to determine the initial length of the test specimen.

[SOURCE: ISO 13934-1:2013, 3.5, modified References to 3.4 and 3.7 have been removed from Note 1 to entry.]

3.10

extension

increase in length of a test specimen during testing

Note 1 to entry: Extension is expressed in units of the length.

3.11

elongation

ratio of the extension (3.10) of the test specimen to its initial length

Note 1 to entry: Elongation is expressed as a percentage.

3.12

maximum force

force at the position when a test specimen is taken to a fixed extension (3.10)

Note 1 to entry: Maximum force is expressed in newtons.

3.13

maximum extension

extension (3.10) recorded in millimetres at the position when a test specimen is taken to a fixed load

Note 1 to entry: Maximum extension is expressed in units of the length.