
**Aircraft — LED based taxiing
lightsystem — General requirements**

*Aéronefs — Système de lumière de roulage à base de LED —
Exigences générales*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 20894:2018](https://standards.iteh.ai/catalog/standards/sist/dfca8927-e236-4022-bd69-a906e734364f/iso-20894-2018)

[https://standards.iteh.ai/catalog/standards/sist/dfca8927-e236-4022-bd69-
a906e734364f/iso-20894-2018](https://standards.iteh.ai/catalog/standards/sist/dfca8927-e236-4022-bd69-a906e734364f/iso-20894-2018)



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 20894:2018

<https://standards.iteh.ai/catalog/standards/sist/dfca8927-e236-4022-bd69-a906e734364f/iso-20894-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 General requirements	2
4.1 General.....	2
4.2 Operating life.....	2
4.3 Illuminance distribution.....	2
4.4 Countermeasure for ultraviolet rays.....	3
4.5 Electromagnetic interference.....	3
4.6 Colour.....	3
4.7 Environmental condition.....	3
4.8 Countermeasure for collision.....	3
4.9 Electrical power source.....	3
5 Quality assurance provisions	3
5.1 Performance characteristics.....	3
5.1.1 General.....	3
5.1.2 Illuminance performance.....	4
5.1.3 Colour.....	4
5.1.4 Operating life.....	4
5.2 Electrical characteristics.....	4
5.2.1 General.....	4
5.2.2 Electromagnetic interference.....	4
5.2.3 Electrical power source.....	4
5.3 Mechanical and thermal characteristics.....	4
5.3.1 General.....	4
5.3.2 Environmental condition.....	4
5.3.3 Thermal analysis.....	4
Bibliography	10

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 1, *Aerospace electrical requirements*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document is the standard of the LED (Light Emitting Diode) Taxi and RTO lights (Runway Turnoff Lights) for aerospace.

LEDs are attractive to users because of their lower power consumption and reduced maintenance efforts as well as their long operating life. However, Taxi and RTO lights require their light source to provide not only a large amount of luminous flux, but also high luminous intensity. Since recent LEDs achieve high luminous intensity, LEDs have come to be adopted as light sources of Taxi and RTO lights.

This document intends to establish a functional requirement set for modern Taxi and RTO lights which adopt LEDs as the light source.

In addition, this document is applied not only to the LED light source, but it can be applied also to other new light sources appearing in the future.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 20894:2018](https://standards.iteh.ai/catalog/standards/sist/dfca8927-e236-4022-bd69-a906e734364f/iso-20894-2018)

<https://standards.iteh.ai/catalog/standards/sist/dfca8927-e236-4022-bd69-a906e734364f/iso-20894-2018>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 20894:2018

<https://standards.iteh.ai/catalog/standards/sist/dfca8927-e236-4022-bd69-a906e734364f/iso-20894-2018>

Aircraft — LED based taxiing lightsystem — General requirements

1 Scope

This document specifies characteristics and interface requirements for the LED taxiing light system.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7137:1995¹⁾, *Aircraft — Environmental conditions and test procedures for airborne equipment*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— IEC Electropedia: available at <http://www.electropedia.org/>

— ISO Online browsing platform: available at <https://www.iso.org/obp>

<https://standards.iteh.ai/catalog/standards/sist/dfca8927-e236-4022-bd69-a906e734364f/iso-20894-2018>

3.1 taxiing light system

system which consists of taxiing lamps and runway turnoff lamps

3.2 RTO light

runway turnoff light

3.3 LED

light emitting diode

[SOURCE: ISO 23570-2:2005, 4.7]

3.4 luminous intensity

photometric measure of the luminous flux per unit area of light travelling in a given direction

3.5 Illuminance

total luminous flux incident on a surface per unit area

1) Endorsement, in part, of the publication EUROCAE ED-14/RTCA DO-160 (a document published jointly by the European Organization for Civil Aviation Electronics and the Radio Technical Commission for Aeronautics).

4 General requirements

4.1 General

Adopting LEDs as the light source, Taxi and RTO lights acquire lower power consumption, reduced maintenance efforts and improved flexibility in design.

Since the existing standard is premised on using a sealed beam lamp for the light source, the functional requirements which correspond to the advantage of LEDs shall be established in this document.

4.2 Operating life

The effective operating life is defined as the time span until the unit no longer meets the photometric minimum performance parameters.

The photometric performance parameters include luminous intensity and chromaticity locus.

The initial luminous intensity and the initial chromaticity locus for LED based lights shall be established. Decrease of the luminous intensity and changes of the chromaticity locus shall also be established, taking into account for aging characteristics of decreasing luminous intensity and changes of chromaticity locus in each components (LEDs, lens, control circuits and so on) because how fast the luminous intensity and the chromaticity locus degrade depend on the characteristic of the LED devices which designers select.

An example for the luminous intensity is shown in [Figure 1](#). An example for the change of chromaticity locus is shown in [Figure 2](#).

4.3 Illuminance distribution

The characteristics of horizontal illuminance distribution shall meet the requirement as shown in [Figure 3](#) using the following formula:

$$E_{\alpha} \geq \cos(\alpha \times 1,145) \times E_C \quad (1)$$

where

- E_{α} is the illuminance distribution inside the illuminated area in direction of α from nose;
- α is the horizontal angle in direction of a ray of luminaire light from airplanes' longitudinal axis on the ground plane; $-74^{\circ} < \alpha < 74^{\circ}$;
- E_C is 54 lux, which corresponds to the conventional requirement of minimum illuminance at "SAE/ARP 693 locations".

$$E_{74^{\circ}} \geq E_{\alpha \max} \times 0,1 \quad (2)$$

The characteristics of vertical illuminance distribution shall meet requirement as shown in [Figure 4](#).

The enhanced characteristics of horizontal illuminance distribution shall meet the requirement as shown in [Figure 5](#) using the following formula:

$$E_{\alpha} \geq \cos(\alpha \times 1,145) \times E_E \quad (3)$$

where

- E_{α} is the illuminance distribution inside the illuminated area in direction of α from nose;
- α is the horizontal angle in direction of a ray of luminaire light from airplanes' longitudinal axis on the ground plane;
- E_E is 70 lux, which corresponds to the enhanced requirement of minimum illuminance at "SAE/ARP 693 locations".
- $$E_{74^{\circ}} \geq E_{\alpha \max} \times 0,1 \quad (4)$$

4.4 Countermeasure for ultraviolet rays

In case a plastic lens is applied, the plastic lens shall be resistant against ultraviolet rays coming from solar radiation or other for the period of the operating life required unless otherwise specified.

4.5 Electromagnetic interference

The system shall be tested for conducted emissions in accordance with the requirements of ISO 7137:1995, Table 1, Section 16, Category B limits unless otherwise specified.

4.6 Colour

It shall be white and allow sufficient perception of colour of airport's markings.

4.7 Environmental condition

The requirements of ISO 7137 shall be adopted and applicable item shall be set in consideration of installed area in an aircraft unless otherwise specified.

4.8 Countermeasure for collision

In case a plastic lens is applied as the countermeasure for collision, the plastic lens shall withstand the environmental condition.

4.9 Electrical power source

The luminaire shall meet all the performance requirements as specified ISO 7137 unless otherwise specified.

5 Quality assurance provisions

5.1 Performance characteristics

5.1.1 General

When performing component testing, the specimen shall be mounted on simulated conditions with the real environmental conditions.

For purposes of demonstrating compliance, all photometric and colour measurements shall be made after a minimum warm up period.