

# ETSI TS 103 859 V12.0.1 (2024-04)



**Publicly Available Specification (PAS);  
O-RAN Fronthaul Control, User and Synchronization Plane  
Specification v12.01;  
(O-RAN.WG4.CUS.0-R003-v12.01)**

[ETSI TS 103 859 V12.0.1 \(2024-04\)](https://standards.iteh.ai/catalog/standards/etsi/3153ba6a-d2fb-4ff2-b131-5a115224977a/etsi-ts-103-859-v12-0-1-2024-04)

<https://standards.iteh.ai/catalog/standards/etsi/3153ba6a-d2fb-4ff2-b131-5a115224977a/etsi-ts-103-859-v12-0-1-2024-04>

## **CAUTION**

*The present document has been submitted to ETSI as a PAS produced by O-RAN Alliance and approved by the ETSI Technical Committee Mobile Standards Group (MSG).*

*ETSI had been assigned all the relevant copyrights related to the document O-RAN.WG4.CUS.0-R003-v12.01 on an "as is basis". Consequently, to the fullest extent permitted by law, ETSI disclaims all warranties whether express, implied, statutory or otherwise including but not limited to merchantability, non-infringement of any intellectual property rights of third parties. No warranty is given about the accuracy and the completeness of the content of the present document.*

---

**Reference**

RTS/MSG-001142

---

**Keywords**

control, front haul, management plane, PAS

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.  
All rights reserved.

# Contents

Intellectual Property Rights .....	15
Foreword.....	15
Modal verbs terminology.....	15
1 Scope .....	16
2 References .....	16
2.1 Normative references .....	16
2.2 Informative references.....	18
3 Definition of terms, symbols and abbreviations.....	19
3.1 Terms.....	19
3.2 Symbols.....	21
3.3 Abbreviations .....	21
3.4 Document conventions .....	22
3.4.1 Terminologies .....	22
3.4.2 Fields and bitmasks in messages.....	23
4 Architecture & requirements .....	24
4.1 Architectural aspects .....	24
4.1.1 Architectural entities.....	24
4.2 Functional split.....	24
4.2.1 Introduction.....	24
4.2.2 Split 7-2x (DL) .....	25
4.2.2.1 Description .....	25
4.2.2.2 Benefits and justification (informative) .....	27
4.2.3 Split 7-2x (UL) .....	28
4.2.3.1 Description .....	28
4.2.3.2 Benefits and justification (informative) .....	29
4.3 Data flows .....	29
4.4 Latency requirements .....	31
4.4.1 Introduction.....	31
4.4.2 Timing parameter relationships .....	32
4.4.2.1 General .....	32
4.4.2.2 O-DU Transmission Window.....	33
4.4.3 U-Plane/ C-Plane timing .....	34
4.4.4 Computed latency methods.....	39
4.4.4.1 Introduction.....	39
4.4.4.2 Fronthaul timing domain.....	41
4.4.4.3 Defined Transport method .....	42
4.4.4.4 Measured Transport method.....	43
4.4.5 Latency categories for O-DU with dynamic timing advance.....	46
4.4.6 Latency categories for O-DU with fixed timing advance .....	48
4.4.7 Non Delay-managed U-Plane traffic .....	49
4.5 Reception window monitoring .....	50
4.6 Transmission windows .....	51
4.6.1 Normal transmission .....	51
4.6.2 Uniformly distributed transmission .....	51
4.6.3 Ordered transmission .....	51
4.6.4 Scheduled transmission.....	52
4.7 O-RU external antenna delay handling .....	53
4.7.1 Introduction.....	53
4.7.2 Minimal O-DU impact method (defined transport method) .....	53
4.7.2.1 Description.....	53
4.7.2.2 Minimal O-DU impact method - Example.....	54
4.8 UL frame timing to DL frame .....	57
4.8.1 Overview .....	57
4.8.2 Carrier types and default values of n-ta-offset.....	58

5	Transport & Protocol Architecture.....	59
5.1	Transport encapsulation types.....	59
5.1.1	Ethernet encapsulation.....	59
5.1.2	IP/UDP encapsulation.....	59
5.1.3	Transport headers.....	60
5.1.3.1	Introduction.....	60
5.1.3.2	eCPRI transport header.....	60
5.1.3.2.1	Overview.....	60
5.1.3.2.2	ecpriVersion (eCPRI protocol revision).....	61
5.1.3.2.3	ecpriReserved (eCPRI reserved).....	61
5.1.3.2.4	ecpriConcatenation (eCPRI concatenation indicator).....	61
5.1.3.2.5	ecpriMessage (eCPRI message type).....	61
5.1.3.2.6	ecpriPayload (eCPRI payload size).....	61
5.1.3.2.7	ecpriRtcid / ecpriPcid (real time control data / IQ data transfer message series identifier).....	62
5.1.3.2.8	ecpriSeqid (message identifier).....	64
5.1.3.3	IEEE 1914.3 transport header.....	66
5.1.3.3.1	Overview.....	66
5.1.3.3.2	RoSubType (sub type / message type).....	66
5.1.3.3.3	RoFlowID (flow identifier).....	67
5.1.3.3.4	RoElength (length).....	67
5.1.3.3.5	RoEorderInfo (order information).....	67
5.2	Protocol architecture.....	68
5.2.1	C-Plane.....	68
5.2.2	U-Plane.....	68
5.2.3	S-Plane.....	69
5.3	Quality of service.....	69
5.4	Data flow identification.....	70
5.5	Fragmentation.....	70
5.5.1	Introduction.....	70
5.5.2	Application layer fragmentation.....	70
5.5.3	Radio transport layer (eCPRI or IEEE-1914.3) fragmentation.....	71
5.5.4	Fragmentation considerations.....	71
6	Security.....	73
6.1	General.....	73
7	C-Plane Protocol.....	74
7.1	General.....	74
7.1.1	C-Plane transport.....	74
7.2	Elementary procedures.....	74
7.2.1	Scheduling and beamforming commands transfer procedure.....	74
7.2.2	Symbol numbering and duration.....	75
7.2.3	Mixed numerology and PRACH handling.....	75
7.2.3.1	Overview.....	75
7.2.3.2	Frequency indexing across multiple numerologies.....	75
7.2.3.3	Slot indexing with mixed numerologies.....	78
7.2.3.4	PRACH formats with multiple PRACH Symbols.....	80
7.2.4	DL precoding configuration parameters and indications.....	80
7.2.5	LAA commands transfer procedure.....	82
7.2.5.1	Introduction.....	82
7.2.5.2	LBT procedure overview.....	82
7.2.5.3	Definitions.....	83
7.2.5.4	General guidelines for the LAA-procedure.....	84
7.2.5.4.1	PDSCH Transmission.....	84
7.2.5.4.2	DRS Transmission.....	84
7.2.5.4.3	Congestion window information transmission.....	85
7.2.6	Dynamic Spectrum Sharing (DSS).....	85
7.2.6.1	Overview.....	85
7.2.6.2	Dynamic Spectrum Sharing (DSS) via dedicated endpoints.....	85
7.2.6.3	Dynamic Spectrum Sharing (DSS) via Section Extension 9 for DSS.....	85
7.2.7	Channel information based beamforming.....	86
7.2.8	ACK/NACK Procedure for C-Plane Messages.....	86

7.2.9	Section Type 4: Slot Configuration Control .....	87
7.2.9.1	Overview .....	87
7.2.9.2	Section Type 4 commands .....	88
7.2.9.2.1	TIME_DOMAIN_BEAM_CONFIG (Time-domain beamforming command) .....	88
7.2.9.2.2	TDD_CONFIG_PATTERN (TDD configuration command) .....	88
7.2.9.3	ACK/NACK support .....	88
7.2.9.4	O-RU handling .....	88
7.2.9.5	Latency requirements .....	89
7.3	Elements for the C-Plane protocol .....	89
7.3.1	Section Types .....	89
7.3.2	Section Extensions .....	90
7.4	Section Type elements .....	90
7.4.1	Overview .....	90
7.4.2	Section Type 0 elements .....	90
7.4.3	Section Type 1 elements .....	92
7.4.4	reserved (reserved for future use) .....	94
7.4.5	Section Type 3 elements .....	94
7.4.6	Section Type 4 elements .....	95
7.4.7	Section Type 5 elements .....	99
7.4.8	Section Type 6 elements .....	100
7.4.9	Section Type 7 elements .....	103
7.4.10	Section Type 8 elements .....	107
7.5	Coding of Section Type IEs .....	108
7.5.1	Transport layer .....	108
7.5.2	Application layer, common .....	108
7.5.2.1	dataDirection (data direction (gNB Tx/Rx)) .....	108
7.5.2.2	payloadVersion (payload version) .....	108
7.5.2.3	filterIndex (filter index) .....	108
7.5.2.4	frameId (frame identifier) .....	109
7.5.2.5	subframeId (subframe identifier) .....	109
7.5.2.6	slotId (slot identifier) .....	109
7.5.2.7	startSymbolId (start symbol identifier) .....	110
7.5.2.8	numberOfsections (number of sections) .....	110
7.5.2.9	sectionType (Section Type) .....	110
7.5.2.10	udCompHdr (user data compression header) .....	110
7.5.2.11	numberOfUEs (number Of UEs) .....	111
7.5.2.12	timeOffset (time offset) .....	111
7.5.2.13	frameStructure (frame structure) .....	111
7.5.2.14	cpLength (cyclic prefix length) .....	112
7.5.2.15	ciCompHdr (channel information compression header) .....	113
7.5.2.16	scs (sub-carrier spacing) .....	114
7.5.2.17	cmdScope (command scope) .....	114
7.5.2.18	numberOfST4Cmds (Number of Section Type 4 commands) .....	115
7.5.3	Application layer, sections .....	115
7.5.3.1	sectionId (section identifier) .....	115
7.5.3.2	rb (resource block indicator) .....	116
7.5.3.3	symInc (symbol number increment command) .....	116
7.5.3.4	startPrbc (starting PRB of data section description) .....	117
7.5.3.5	reMask (resource element mask) .....	117
7.5.3.6	numPrbc (number of contiguous PRBs per data section description) .....	118
7.5.3.7	numSymbol (number of symbols) .....	118
7.5.3.8	ef (extension flag) .....	119
7.5.3.9	beamId (beam identifier) .....	119
7.5.3.10	ueId .....	119
7.5.3.11	freqOffset (frequency offset) .....	119
7.5.3.12	regularizationFactor (regularization factor) .....	120
7.5.3.13	ciIsample, ciQsample (channel information I and Q values) .....	120
7.5.3.14	laaMsgType (LAA message type) .....	121
7.5.3.15	laaMsgLen (LAA message length) .....	121
7.5.3.16	lbtHandle .....	121
7.5.3.17	lbtDeferFactor (listen-before-talk defer factor) .....	121
7.5.3.18	lbtBackoffCounter (listen-before-talk backoff counter) .....	122

7.5.3.19	lbtOffset (listen-before-talk offset) .....	122
7.5.3.20	MCOT (maximum channel occupancy time) .....	122
7.5.3.21	lbtMode (LBT mode) .....	122
7.5.3.22	lbtPdschRes (LBT PDSCH result) .....	122
7.5.3.23	sfStatus (subframe status) .....	123
7.5.3.24	lbtDrsRes (LBT DRS result) .....	123
7.5.3.25	initialPartialSF (Initial partial SF) .....	123
7.5.3.26	lbtBufErr (LBT buffer error) .....	123
7.5.3.27	sfnSf (SFN/SF end) .....	123
7.5.3.28	lbtCWConfig_H (HARQ parameters for congestion window management) .....	124
7.5.3.29	lbtCWConfig_T (TB parameters for congestion window management) .....	124
7.5.3.30	lbtTrafficClass (traffic class priority for congestion window management) .....	124
7.5.3.31	lbtCWR_Rst (notification about packet reception successful or not) .....	124
7.5.3.32	ciCompParam (channel information compression parameter) .....	124
7.5.3.33	reserved (reserved for future use) .....	125
7.5.3.34	numberOfAcks (number of ACKs) .....	125
7.5.3.35	numberOfNacks (number of NACKs) .....	125
7.5.3.36	ackId (ACK Id) .....	125
7.5.3.37	nackId (NACK Id) .....	125
7.5.3.38	st4CmdType (Section Type 4 command type) .....	126
7.5.3.39	st4CmdLen (Section Type 4 command length) .....	126
7.5.3.40	numSlots (number of slots) .....	126
7.5.3.41	ackNackReqId (ACK/NACK Request ID) .....	126
7.5.3.42	symbolMask (TIME_DOMAIN_BEAM_CONFIG symbol mask) .....	127
7.5.3.43	disableTDBFNs (disable sending tdBeamNum) .....	127
7.5.3.44	tdBeamGrp (time-domain beam group identity) .....	127
7.5.3.45	bfwCompHdr (beamforming weight compression header) .....	127
7.5.3.46	disableTDBFWs (disable sending time-domain beamforming weights) .....	128
7.5.3.47	bfwCompParam (beamforming weight compression parameter) .....	128
7.5.3.48	bfWI, bfWQ (beamforming weights I and Q values) .....	128
7.5.3.49	dirPattern (symbol data direction (gNB Tx/Rx) pattern) .....	128
7.5.3.50	guardPattern (guard pattern bitmask) .....	128
7.6	Section Extension elements .....	129
7.6.1	Overview .....	129
7.6.2	Common parameters .....	132
7.6.2.1	extType (extension type) .....	132
7.6.2.2	ef (extension flag) .....	132
7.6.2.3	extLen (extension length) .....	132
7.7	Coding of Section Extension IEs .....	133
7.7.1	SE 1: Beamforming weights .....	133
7.7.1.1	Overview .....	133
7.7.1.2	bfwCompHdr (beamforming weight compression header) .....	133
7.7.1.3	bfwCompParam (beamforming weight compression parameter) .....	134
7.7.1.4	bfwI (beamforming weight in-phase value) .....	135
7.7.1.5	bfwQ (beamforming weight quadrature value) .....	135
7.7.2	SE 2: Beamforming attributes .....	135
7.7.2.1	Overview .....	135
7.7.2.2	bfaCompHdr (beamforming attributes compression header) .....	135
7.7.2.3	bfAzPt (beamforming azimuth pointing parameter) .....	136
7.7.2.4	bfZePt (beamforming zenith pointing parameter) .....	137
7.7.2.5	bfAz3dd (beamforming azimuth beamwidth parameter) .....	137
7.7.2.6	bfZe3dd (beamforming zenith beamwidth parameter) .....	137
7.7.2.7	bfAzSl (beamforming azimuth sidelobe parameter) .....	137
7.7.2.8	bfZeSl (beamforming zenith sidelobe parameter) .....	137
7.7.2.9	zero-padding .....	138
7.7.3	SE 3: DL precoding parameters .....	138
7.7.3.1	Overview .....	138
7.7.3.2	codebookIndex (precoder codebook used for transmission) .....	139
7.7.3.3	layerID (Layer ID for DL transmission) .....	139
7.7.3.4	txScheme (transmission scheme) .....	139
7.7.3.5	numLayers (number of layers used for DL transmission) .....	140
7.7.3.6	crsReMask (CRS resource element mask) .....	140

7.7.3.7	crsSymNum (CRS symbol number indication).....	140
7.7.3.8	crsShift (crsShift used for DL transmission).....	140
7.7.3.9	beamIdAP1 (beam id to be used for antenna port 1).....	141
7.7.3.10	beamIdAP2 (beam id to be used for antenna port 2).....	141
7.7.3.11	beamIdAP3 (beam id to be used for antenna port 3).....	141
7.7.4	SE 4: Modulation compression parameters .....	141
7.7.4.1	Overview .....	141
7.7.4.2	csf (constellation shift flag).....	142
7.7.4.3	modCompScaler (modulation compression scaler value) .....	142
7.7.5	SE 5: Modulation compression additional parameters.....	143
7.7.5.1	Overview .....	143
7.7.5.2	mcScaleReMask (modulation compression power scale RE mask).....	144
7.7.5.3	csf (constellation shift flag).....	144
7.7.5.4	mcScaleOffset (scaling value for modulation compression) .....	144
7.7.6	SE 6: Non-contiguous PRB allocation in time and frequency domain .....	145
7.7.6.1	Overview .....	145
7.7.6.2	rbgSize (resource block group size).....	146
7.7.6.3	rbgMask (resource block group bit mask).....	146
7.7.6.4	symbolMask (symbol bit mask).....	147
7.7.6.5	priority.....	148
7.7.6.6	repetition (repetition flag) .....	148
7.7.7	SE 7: eAxC mask.....	148
7.7.7.1	Overview .....	148
7.7.7.2	eAxCmask (eAxC Mask) .....	148
7.7.8	SE 8: Regularization factor.....	149
7.7.8.1	Overview .....	149
7.7.8.2	regularizationFactor (regularization factor) .....	149
7.7.9	SE 9: Dynamic Spectrum Sharing parameters.....	150
7.7.9.1	Introduction.....	150
7.7.9.2	technology (interface name).....	150
7.7.10	SE 10: Group configuration of multiple ports.....	150
7.7.10.1	Overview .....	150
7.7.10.2	beamGroupType.....	151
7.7.10.3	numPortc .....	151
7.7.10.4	Interaction with other Section Extensions.....	152
7.7.11	SE 11: Flexible beamforming weights.....	153
7.7.11.1	Overview .....	153
7.7.11.2	bfwCompHdr (beamforming weight compression header) .....	154
7.7.11.3	bfwCompParam for PRB bundle x (beamforming weight compression parameter).....	154
7.7.11.4	numBundPrb (Number of bundled PRBs per beamforming weights).....	154
7.7.11.5	bfwI (beamforming weight in-phase value) .....	154
7.7.11.6	bfwQ (beamforming weight quadrature value).....	155
7.7.11.7	disableBFWs (disable beamforming weights).....	155
7.7.11.8	RAD (Reset after PRB discontinuity) .....	155
7.7.11.9	contInd (PRB region continuity flag).....	155
7.7.12	SE 12: Non-contiguous PRB allocation with frequency ranges .....	156
7.7.12.1	Overview .....	156
7.7.12.2	priority (priority of section description).....	157
7.7.12.3	symbolMask (symbol bit mask).....	158
7.7.12.4	offStartPrb(r) (offset of PRB range start).....	158
7.7.12.5	numPrb(r) (number of PRBs in PRB range) .....	158
7.7.13	SE 13: PRB allocation with frequency hopping .....	158
7.7.13.1	Overview .....	158
7.7.13.2	nextSymbolId(n) (next hop start symbol) .....	159
7.7.13.3	nextStartPrbc(n) (next hop startPrbc).....	159
7.7.14	SE 14: Nulling layer information for ueld based beamforming.....	160
7.7.14.1	Overview .....	160
7.7.14.2	nullLayerInd (null layer indication) .....	160
7.7.15	SE 15: Mixed numerology information for ueld based beamforming .....	161
7.7.15.1	Overview .....	161
7.7.15.2	frameStructure (frame structure).....	161
7.7.15.3	freqOffset (frequency offset).....	161

7.7.15.4	cpLength (cyclic prefix length).....	161
7.7.16	SE 16: Antenna mapping in UE channel information based UL beamforming.....	161
7.7.16.1	Overview.....	161
7.7.16.2	antMask.....	162
7.7.17	SE 17: Indication of user port group.....	162
7.7.17.1	Overview.....	162
7.7.17.2	numUeID.....	162
7.7.18	SE 18: Uplink transmission management.....	163
7.7.18.1	Introduction.....	163
7.7.18.2	transmissionWindowOffset.....	163
7.7.18.3	transmissionWindowSize.....	163
7.7.18.4	toT (type of transmission).....	164
7.7.18.5	Interaction with other Section Extensions.....	164
7.7.19	SE 19: Compact beamforming information for multiple port.....	165
7.7.19.1	Overview.....	165
7.7.19.2	disableBFWs (disable beamforming weights).....	166
7.7.19.3	repetition (repeat port info flag).....	166
7.7.19.4	numPortc.....	167
7.7.19.5	priority (priority of section description).....	167
7.7.19.6	symbolMask (resource symbol bitmask).....	167
7.7.19.7	bfwCompHdr.....	167
7.7.19.8	portReMask (RE bitmask per port).....	167
7.7.19.9	portSymbolMask (symbol bitmask per port).....	167
7.7.19.10	bfwCompParam (beamforming weight compression parameter).....	168
7.7.19.11	beamId (beam identifier for a port).....	168
7.7.19.12	bfwI (beamforming weight in-phase value).....	168
7.7.19.13	bfwQ (beamforming weight quadrature-phase value).....	168
7.7.19.14	Interaction with Other Section Extensions.....	169
7.7.20	SE 20: Puncturing extension.....	170
7.7.20.1	Overview.....	170
7.7.20.2	numPuncPatterns (number of puncturing pattern).....	171
7.7.20.3	symbolMask (puncturing pattern symbol mask).....	171
7.7.20.4	startPuncPrb (starting PRB to which one puncturing pattern applies).....	171
7.7.20.5	numPuncPrb (number of contiguous PRBs to which one puncturing pattern applies).....	171
7.7.20.6	puncReMask (puncturing pattern RE mask).....	171
7.7.20.7	rb (resource block indicator).....	171
7.7.20.8	rbgIncl (rbg included flag).....	172
7.7.20.9	rbgSize (rbg size).....	172
7.7.20.10	rbgMask (rbg bitmask).....	172
7.7.20.11	Interaction with Other Extensions.....	172
7.7.21	SE 21: Variable PRB group size for channel information.....	172
7.7.21.1	Overview.....	172
7.7.21.2	ciPrbGroupSize (channel information PRB group size).....	172
7.7.22	SE 22: ACK/NACK request.....	173
7.7.22.1	Overview.....	173
7.7.22.2	ackNackReqId (ACK/NACK request Id).....	173
7.7.23	SE 23: Arbitrary symbol pattern modulation compression parameters.....	173
7.7.23.1	Overview.....	173
7.7.23.2	numSymPrbPattern (number of symbol and resource block patterns).....	174
7.7.23.3	symMask (symbol mask part of symPrbPattern).....	175
7.7.23.4	prbPattern (resource block pattern part of symPrbPattern).....	175
7.7.23.5	numMcScaleOffset (number of modulation compression scaling value per symPrbPattern).....	175
7.7.23.6	mcScaleReMask (modulation compression power scale RE mask).....	175
7.7.23.7	csf (constellation shift flag).....	175
7.7.23.8	Interaction with Other Section Extensions.....	175
7.8	Aspects of C-Plane operation.....	176
7.8.1	Coupling of C-Plane and U-Plane.....	176
7.8.1.1	Overview.....	176
7.8.1.2	Coupling via sectionId value.....	176
7.8.1.3	Coupling via frequency and time.....	177
7.8.1.4	Coupling via frequency and time with priorities.....	178
7.8.1.5	Coupling via frequency and time with priorities (optimized).....	179

7.8.2	O-RUs per endpoint and per C-Plane message limits .....	179
7.8.2.1	O-RU per endpoint processing limits .....	179
7.8.2.1.1	Overview .....	179
7.8.2.1.2	Limits on Number of PRB ranges .....	179
7.8.2.2	O-RU C-Plane message limits.....	180
7.9	C-Plane optimizations .....	180
7.9.1	C-Plane optimization using Section Extension 6.....	180
7.9.2	C-Plane Optimization using Section Extension 7 .....	180
7.9.3	C-Plane optimization using Section Extension 10 .....	180
7.9.3.1	Overview .....	180
7.9.4	C-Plane optimization using Section Extension 11 .....	181
7.9.4.1	Overview .....	181
7.9.4.2	Interaction between Section Extension 11 and Section Extension 6 .....	181
7.9.4.2.1	Overview .....	181
7.9.4.2.2	Interaction when RAD = 1.....	181
7.9.4.2.3	Interaction when RAD = 0.....	182
7.9.4.3	Interaction between Section Extension 11 and Section Extension 12 .....	183
7.9.4.4	Interaction between Section Extension 11 and Section Extension 13 .....	185
7.9.5	C-Plane optimization using Section Extension 12 .....	189
7.9.6	C-Plane optimization using Section Extension 13 .....	189
7.9.7	Coupling via frequency and time with priorities.....	189
7.9.8	Coupling via frequency and time with priorities (optimized) .....	191
7.9.9	U-Plane Operation Without C-Plane .....	192
7.9.10	Modulation compression with Section Extension 10.....	192
7.9.11	Optimization with Section Extension 19 .....	196
7.9.12	Optimizations with Section Extension 20.....	197
7.9.13	Optimizations with ueId indicating non-scheduled PRB range .....	197
8	U-Plane Protocol .....	200
8.1	General .....	200
8.1.1	U-Plane transport .....	200
8.1.2	U-Plane data compression .....	200
8.1.3	Digital power scaling.....	200
8.1.3.1	Definition of IQ power in dBFS.....	200
8.1.3.2	Definition of Gain over Fronthaul Interface.....	201
8.1.3.2.1	DL and UL gain definition commonality .....	201
8.1.3.2.2	DL gain definition .....	203
8.1.3.2.3	UL gain definition .....	204
8.1.3.3	TX power budget for Category A and Category B O-RUs .....	205
8.2	Elementary procedures .....	206
8.2.1	IQ data transfer procedure .....	206
8.2.2	IQ data transfer procedure without C-Plane.....	208
8.3	Elements for the U-Plane protocol .....	209
8.3.1	General.....	209
8.3.2	DL/UL data .....	209
8.3.3	UL/DL data coding of information elements .....	212
8.3.3.0	General .....	212
8.3.3.1	dataDirection (data direction (gNB Tx/Rx)) .....	212
8.3.3.2	payloadVersion (payload version) .....	212
8.3.3.3	filterIndex (filter index).....	212
8.3.3.4	frameId (frame identifier) .....	212
8.3.3.5	subframeId (subframe identifier) .....	212
8.3.3.6	slotId (slot identifier).....	212
8.3.3.7	symbolId (symbol identifier).....	212
8.3.3.8	sectionId (section identifier).....	212
8.3.3.9	rb (resource block indicator) .....	212
8.3.3.10	symInc (symbol number increment command).....	212
8.3.3.11	startPrbu (starting PRB of user plane section) .....	213
8.3.3.12	numPrbu (number of PRBs per user plane section) .....	213
8.3.3.13	udCompHdr (user data compression header) .....	214
8.3.3.14	reserved (reserved for future use).....	214
8.3.3.15	udCompParam (user data compression parameter) .....	215

8.3.3.16	iSample (in-phase sample) .....	215
8.3.3.17	qSample (quadrature sample).....	215
8.3.3.18	sReSMask (selective RE sending mask) .....	215
8.3.3.19	udCompLen (PRB field length) .....	216
8.3.4	DL data precoding .....	216
8.3.5	Data transfer for special cases.....	217
8.3.5.1	Data message mapping and packetization.....	217
8.3.5.2	Uplink data transfer.....	217
8.3.5.3	PRACH data transfer without C-Plane.....	217
8.3.5.4	SRS data transfer without C-Plane.....	217
8.4	U-Plane optimizations .....	217
8.4.1	Coupling via frequency and time .....	217
8.4.2	Data blanking.....	218
8.4.2.1	Overview .....	218
8.4.2.2	PRB blanking .....	218
8.4.2.3	Transmission blanking .....	218
8.5	Aspects of U-Plane operation.....	218
8.5.1	O-RU U-Plane limits .....	218
8.5.1.1	O-RU U-Plane message limits .....	218
9	Counters and KPIs.....	220
9.1	Counters .....	220
10	Specification mandatory and optional capabilities.....	223
10.1	General .....	223
10.2	Mandatory and optional capabilities.....	224
11	S-Plane Protocol.....	232
11.1	General .....	232
11.1.1	Overview .....	232
11.2	Synchronization baseline.....	232
11.2.1	List of reference documents.....	232
11.2.2	Clock model and synchronization topology.....	232
11.2.2.1	Introduction.....	232
11.2.2.2	Topology configuration LLS-C1 and LLS-C2 synchronization.....	233
11.2.2.3	Topology configuration LLS-C3 synchronization .....	236
11.2.2.4	Topology configuration LLS-C4 synchronization .....	238
11.2.3	Clock Synchronization.....	238
11.2.4	Profiles.....	239
11.2.4.1	Physical layer frequency signals (PLFS).....	239
11.2.4.2	PTP.....	240
11.2.4.2.1	Full timing support .....	240
11.2.4.2.2	Partial timing support .....	240
11.2.5	Synchronization accuracy .....	241
11.2.5.1	Introduction.....	241
11.2.5.2	Jitter.....	242
11.2.5.3	Wander.....	242
11.2.5.4	Air interface frequency error.....	242
11.2.5.5	Air interface maximum time error .....	242
11.3	Time and frequency synchronization requirements.....	245
11.3.1	Allowed PTP and PLFS clock types and clock classes.....	245
11.3.1.1	Overview .....	245
11.3.1.2	O-DU synchronization capability options:.....	246
11.3.1.3	O-RU synchronization capability options: .....	246
11.3.2	Frequency and time synchronization requirements across fronthaul network elements .....	247
11.3.2.1	Configurations LLS-C1 and LLS-C2.....	247
11.3.2.2	Configuration LLS-C3 .....	250
11.3.2.3	Configuration LLS-C4 .....	253
11.4	Node synchronization state behavior.....	255
11.4.1	Configurations LLS-C1 and LLS-C2.....	255
11.4.1.1	Overview .....	255
11.4.1.2	M-Plane disconnected .....	255
11.4.1.3	O-RU in the FREERUN state.....	256

11.4.1.4	O-DU in the FREERUN state .....	256
11.4.1.5	Operation in LOCKED/HOLDOVER state .....	257
11.4.2	Configurations LLS-C3 .....	258
11.4.2.1	Overview .....	258
11.4.2.2	M-Plane disconnected .....	258
11.4.2.3	O-RU in the FREERUN State .....	258
11.4.2.4	O-DU in the FREERUN state .....	258
11.4.2.5	Operation in LOCKED/HOLDOVER state .....	259
11.4.3	Configurations LLS-C4 .....	259
11.4.3.1	Overview .....	259
11.4.3.2	M-Plane disconnected .....	259
11.4.3.3	O-RU in the FREERUN state .....	259
11.4.3.4	O-DU in the FREERUN state .....	260
11.4.3.5	Operation in LOCKED/HOLDOVER state .....	260
11.5	S-Plane handling in multiple link scenarios .....	260
11.6	Announce messages .....	260
11.7	Elementary procedures .....	260
11.7.1	PTP time synchronization procedure .....	260
11.7.2	System frame number calculation from GPS time .....	261
12	Beamforming functionality .....	263
12.1	General .....	263
12.2	Hierarchy of radiation structure in O-RU .....	263
12.3	Calibration .....	264
12.4	beamId use for various beamforming methods .....	264
12.4.1	Overview .....	264
12.4.2	Predefined-beam beamforming .....	265
12.4.2.1	Overview .....	265
12.4.2.2	Beam characteristics .....	265
12.4.3	Weight-based dynamic beamforming .....	267
12.4.3.1	Overview .....	267
12.4.3.2	Optional restriction on sending of beamforming weights .....	267
12.4.3.3	Weight-based dynamic frequency-domain or time-domain beamforming (not hybrid) .....	270
12.4.3.4	Weight-based dynamic hybrid beamforming .....	270
12.4.3.4.1	Overview .....	270
12.4.3.4.2	Hybrid beamforming with updatable frequency-domain and time-domain weights .....	270
12.4.3.4.3	Hybrid beamforming with updatable frequency-domain weights and fixed time-domain beams .....	271
12.4.3.4.4	Hybrid beamforming with Section Type 4 'TIME_DOMAIN_BEAM_CONFIG' .....	273
12.4.4	Attribute-based dynamic beamforming .....	274
12.4.5	Channel-information-based beamforming .....	275
12.5	O-RU antenna model .....	275
12.5.1	Overview .....	275
12.5.2	Coordinate systems .....	275
12.5.3	O-RU antenna model parameters .....	276
12.5.4	Identification and ordering of array elements .....	277
12.5.5	Relations between array elements .....	278
12.5.6	Model usage .....	278
13	Support of Shared Cell .....	281
13.1	General .....	281
13.2	Copy and Combine function .....	282
13.2.1	DL Copy function .....	282
13.2.2	UL Combine function .....	282
13.3	Selective transmission and reception using beamId .....	284
13.3.1	Introduction .....	284
13.3.2	Selective transmission function .....	285
13.3.3	Selective reception function .....	286
13.4	Multiple Cells Scenario in Cascade mode .....	287
13.4.1	Introduction .....	287
13.4.2	Multiple Cell scenario in downlink .....	287
13.4.3	Multiple Cell scenario in uplink .....	288

13.5	Delay management for Shared cell.....	290
13.5.1	Introduction.....	290
13.5.2	DL delay management for Shared cell.....	290
13.5.3	UL delay management for Shared cell.....	292
13.5.4	Section Extension 10 support for Shared Cell .....	294
13.6	S-plane for Shared cell .....	295
13.6.1	Introduction.....	295
13.6.2	Node behavior at O-RU in FREERUN state.....	295
13.6.2.1	O-DU.....	295
13.6.2.2	O-RU.....	295
13.7	Cascade-FHM mode.....	295
13.7.1	General.....	295
13.7.2	Copy and Combine function .....	296
13.7.3	Delay management .....	297
14	Support of Shared O-RU .....	300
14.1	General .....	300
14.2	Delay management for Shared O-RU.....	300
14.2.1	General.....	300
14.3	S-Plane for Shared O-RU .....	300
14.3.1	General.....	300
15	Support of Narrowband-IoT .....	301
15.1	Overview (informative).....	301
15.2	NB-IoT Downlink enabling methods .....	301
15.2.1	Extended PRB Grid .....	301
15.3	NB-IoT Downlink use cases.....	303
15.3.1	Overview .....	303
15.3.2	In-band mode with 15 kHz subcarrier spacing of host carrier .....	303
15.3.3	Guard-band mode with 15 kHz subcarrier spacing of host carrier.....	304
15.4	NB-IoT Uplink enabling methods .....	305
15.4.1	Single Section Single Carrier (SSSC).....	305
15.4.2	Single Section Multiple Carriers (SSMC) .....	306
15.4.3	Extended PRB Grid .....	307
15.5	NB-IoT Uplink use cases .....	308
15.5.1	Overview .....	308
15.5.2	General case for in-band and guard-band mode .....	308
15.5.3	Special case of in-band mode and guard-band mode NPUSCH with extended PRB Grid .....	309
15.5.4	NPRACH without C-plane .....	309
15.6	subframeId, slotId and symbolId numbering for NB-IoT.....	310
15.6.1	Overview .....	310
15.6.2	NPUSCH timing .....	310
15.6.3	NPRACH timing.....	310
<b>Annex A (normative):</b>	<b>Compression methods.....</b>	<b>312</b>
A.1	Block floating point compression.....	312
A.1.1	Overview .....	312
A.1.2	Block floating point compression algorithm.....	312
A.1.3	Block floating point decompression algorithm.....	313
A.2	Block scaling compression .....	313
A.2.1	Overview .....	313
A.2.2	Block scaling compression algorithm .....	314
A.2.3	Block scaling decompression algorithm .....	314
A.3	$\mu$ -Law compression .....	314
A.3.1	$\mu$ -Law compression algorithm .....	314
A.3.2	$\mu$ -Law decompression algorithm .....	316
A.3.3	$\mu$ -law udCompParam and IQ data format .....	316
A.4	Beamspace compression type I and type II .....	317
A.4.1	Overview .....	317
A.4.2	Beamspace compression type I.....	317
A.4.2.1	Overview.....	317
A.4.2.2	Beamspace compression algorithm.....	317

A.4.2.3	Beamspace decompression algorithm .....	318
A.4.3	Beamspace compression type II .....	319
A.4.3.1	Overview .....	319
A.4.3.2	Beamspace compression algorithm .....	319
A.4.3.3	Beamspace decompression algorithm .....	321
A.4.3.4	Kronecker product algorithm .....	322
A.5	Modulation compression .....	322
A.6	Selective RE sending .....	325
<b>Annex B (informative): Delay management use cases .....</b>		<b>326</b>
B.1	Introduction .....	326
B.2	Latency categories and sub-categories .....	331
B.3	Example case: Evaluating O-DU / O-RU combinations .....	336
B.4	Example case: Non-ideal transport O-DU/O-RU categories .....	339
<b>Annex C (informative): Void .....</b>		<b>340</b>
<b>Annex D (informative): IQ sample and exponent packetization for different bitwidths .....</b>		<b>341</b>
D.1	IQ sample ordering for big-endian byte order .....	341
D.2	IQ sample ordering for little-endian byte order .....	346
<b>Annex E (informative): OFDM phase compensation .....</b>		<b>352</b>
<b>Annex F (normative): Beamforming attributes frame of reference .....</b>		<b>353</b>
<b>Annex G (informative): LAA Algorithms and Examples .....</b>		<b>355</b>
<b>Annex H (informative): S-Plane detailed frequency and phase error budget analysis, and future ITU-T clock types and classes reference .....</b>		<b>359</b>
H.1	Void .....	359
H.2	Frequency and time error budget analysis .....	359
H.2.1	Overview .....	359
H.2.2	Network limit guidelines for frequency error budget (LLS-C1 and LLS-C2): .....	359
H.2.3	Network limit guidelines for time error budget (LLS-C1 and LLS-C2): .....	360
H.2.4	Network limit guidelines for LLS-C1 and LLS-C2 based on the budget .....	362
H.2.5	Network limit guidelines for frequency error budget (LLS-C3): .....	366
H.2.6	Time error budget for network limit (LLS-C3) .....	368
H.3	Guidelines for the allowed number of switches: .....	368
<b>Annex I (informative): Precoding and examples .....</b>		<b>370</b>
I.1	Case 1: Tx Diversity 1-CRS Port Ant0, 1 PRB: .....	370
I.2	Case 2: Tx Diversity 2-CRS Port Ant0, Ant1, and 1 PRB .....	370
I.3	Case 3: Tx Diversity 4-CRS Port Ant0,1,2,3 and 1 PRB .....	371
I.4	Case 4: TM3/TM4 3 layers, 4 antenna ports .....	373
I.5	CRS location assignment .....	375
I.6	First data layer and non-first data layer association using static eAxC_ID and layerId mapping .....	377
<b>Annex J (informative): Beamforming methods description .....</b>		<b>378</b>
J.1	Introduction .....	378
J.2	Predefined-beam beamforming .....	378
J.3	Weight-based dynamic beamforming .....	378
J.4	Attribute-based dynamic beamforming .....	379
J.5	Channel-information-based beamforming .....	379
<b>Annex K (informative): Layers of array elements .....</b>		<b>381</b>
K.1	General .....	381
K.2	Use Case A .....	381
K.3	Use Case B .....	382
<b>Annex L (informative): Considerations when operating in non-ideal transport environments ...</b>		<b>383</b>
L.1	General .....	383
L.2	Deployment scenarios and performance considerations .....	383
L.2.1	Low impact .....	383

L.2.2	Medium impact .....	383
L.2.3	High impact .....	383
L.3	HARQ .....	384
L.3.1	Introduction.....	384
L.3.2	Synchronous HARQ .....	384
L.3.3	HARQ interleaving .....	384
L.3.4	Predictive HARQ .....	385
L.3.5	Asynchronous HARQ considerations .....	386
L.4	RACH considerations.....	386
L.4.1	Introduction.....	386
L.4.2	Non-Ideal fronthaul RACH designs.....	387
L.4.2.1	Assumptions.....	387
L.4.2.2	Option 1: Semi-persistent resource allocation.....	387
L.4.2.3	Option 2: RACH retransmission estimation.....	388
L.5	Other latency related considerations.....	389
L.6	Bandwidth limitation considerations .....	390
<b>Annex M (informative): Use case of selective transmission and reception .....</b>		<b>392</b>
M.1	General .....	392
M.2	Selective transmission and reception with non beamforming O-RUs and 1-to-1 mapping of global beamId and local beamId .....	392
M.3	Selective transmission and reception with beamforming O-RUs and 1-to-N mapping of global beamId and local beamId .....	393
Change history .....		395
History .....		397

iTech Standards  
(<https://standards.iteh.ai>)  
Document Preview

[ETSI TS 103 859 V12.0.1 \(2024-04\)](https://standards.iteh.ai/catalog/standards/etsi/3153ba6a-d2fb-4ff2-b131-5a115224977a/etsi-ts-103-859-v12-0-1-2024-04)

<https://standards.iteh.ai/catalog/standards/etsi/3153ba6a-d2fb-4ff2-b131-5a115224977a/etsi-ts-103-859-v12-0-1-2024-04>