

SLOVENSKI STANDARD

SIST EN 3660-064:2022

01-julij-2022

Nadomešča:

SIST EN 3660-064:2016

Aeronavtika - Dodatki za okrogle in pravokotne električne in optične konektorje - 064. del: Kabelska spojka, tip K, ravna, za toplotno skrčljive dele, oklopljena, tesnjena, samozapiralna - Standard za proizvod

Aerospace series - Cable outlet accessories for circular and rectangular electrical and optical connectors - Part 064: Cable outlet, style K, straight, for heat shrinkable boot, shielded, sealed, self-locking - Product standard

Luft- und Raumfahrt - Endgehäuse für elektrische und optische Rund- und Rechtecksteckverbinder - Teil 064: Endgehäuse, Bauform K, gerade, für wärmeschrumpfende Bauteile, Schirmanschluß, abgedichtet, selbstsichernd - Produktnorm

<https://standards.iteh.ai/catalog/standards/sist/21d5d45a-6070-4b2b-9912-9906c3/sist-en-3660-064-2022>

Série aérospatiale - Accessoires arrière pour connecteurs circulaires et rectangulaires électriques et optiques - Partie 064 : Raccord, type K, droit, blindé, étanche, pour manchon thermorétractable, à freinage interne - Norme de produit

Ta slovenski standard je istoveten z: EN 3660-064:2022

ICS:

31.220.99	Druge elektromehanske komponente	Other electromechanical components
49.060	Letalska in vesoljska električna oprema in sistemi	Aerospace electric equipment and systems

SIST EN 3660-064:2022

en,fr,de

**iTeh STANDARD
PREVIEW
(standards.iteh.ai)**

SIST EN 3660-064:2022

<https://standards.iteh.ai/catalog/standards/sist/21d5d45a-d070-4d3e-bf64-5977523906e3/sist-en-3660-064-2022>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 3660-064

May 2022

ICS 49.060

Supersedes EN 3660-064:2016

English Version

Aerospace series - Cable outlet accessories for circular and rectangular electrical and optical connectors - Part 064: Cable outlet, style K, straight, for heat shrinkable boot, shielded, sealed, self-locking - Product standard

Série aérospatiale - Accessoires arrière pour connecteurs circulaires et rectangulaires électriques et optiques - Partie 064 : Raccord, type K, droit, blindé, étanche, pour manchon thermorétractable, à freinage interne - Norme de produit

Luft- und Raumfahrt - Endgehäuse für elektrische und optische Rund- und Rechtecksteckverbinder - Teil 064: Endgehäuse, Bauform K, gerade, für wärmeschrumpfende Bauteile, Schirmanschluß, abgedichtet, selbstsichernd - Produktnorm

This European Standard was approved by CEN on 2 September 2019.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	5
4 Characteristics	5
5 Tests	15
6 Designation	23
7 Marking	23
8 Technical specification	23
Annex A (informative) Standard evolution form	24

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 3660-064:2022](https://standards.iteh.ai/catalog/standards/sist/21d5d45a-d070-4d3e-bf64-5977523906e3/sist-en-3660-064-2022)
<https://standards.iteh.ai/catalog/standards/sist/21d5d45a-d070-4d3e-bf64-5977523906e3/sist-en-3660-064-2022>

European foreword

This document (EN 3660-064:2022) has been prepared by the Aerospace and Defence Industries Association of Europe — Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD-STAN, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by November 2022, and conflicting national standards shall be withdrawn at the latest by November 2022.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 3660-064:2016.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

ITEH STANDARD
PREVIEW
(standards.iteh.ai)

SIST EN 3660-064:2022

<https://standards.iteh.ai/catalog/standards/sist/21d5d45a-d070-4d3e-bf64-5977523906e3/sist-en-3660-064-2022>

EN 3660-064:2022 (E)

1 Scope

This document defines a range of cable outlets, style K, straight, shielded, sealed, self-locking (anti-rotational), heat shrinkable boot, and/or metallic bands for use under the following conditions:

The mating connectors are listed in EN 3660-002.

Temperature range,	Class N:	-65 °C to 200 °C;
	Class K:	-65 °C to 260 °C;
	Class W:	-65 °C to 175 °C;
	Class T:	-65 °C to 175 °C (Nickel PTFE plating);
	Class Z:	-65 °C to 175 °C (Black zinc nickel plating).

Associated electrical accessories: EN 3660-033 Metallic band (for shield termination).

These cable outlets are designed for termination of overall shielding braid and/or individual cable shields. They accommodate/permit the termination of heat shrinkable boots.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 2591, *, *Aerospace series — Elements of electrical and optical connection — Test methods*

EN 2997 (all parts), *Aerospace series — Connectors, electrical, circular, coupled by threaded ring, fire-resistant or non fire-resistant, operating temperatures -65 °C to 175 °C continuous, 200 °C continuous, 260 °C peak*

EN 3660-001, *Aerospace series — Cable outlet accessories for circular and rectangular electrical and optical connectors — Part 001: Technical specification*

EN 3660-002, *Aerospace series — Cable outlet accessories for circular and rectangular electrical and optical connectors — Part 002: Index of product standards*

EN 3660-033, *Aerospace series — Cable outlet accessories for circular and rectangular electrical and optical connectors — Part 033: Stainless steel banding band, style Z, for attachment of individual and/or overall screens to cable outlets — Product standard*¹

EN 60529, *Degrees of protection provided by enclosures (IP Code)*

AS85049, *Connector accessories, electrical general specification for*²

DIN 82, *Knurling*

* All its parts quoted in this document.

¹ Published as ASD-STAN Standard at the date of publication of this document by AeroSpace and Defence industries Association of Europe — Standardization (ASD-STAN), <http://www.asd-stan.org/>

² Published by: National (US) Society of Automotive Engineers (SAE), <http://www.sae.org/>

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 3660-001 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

self-locking/anti rotational

a self-locking or anti rotational mechanism provides a nut rotation with moderate torque in the mated direction and provides a greater torque in the unmated direction

4 Characteristics

4.1 Dimensions and mass

For dimensions and mass, see Figures 1 to 6 and Tables 1 to 7.


For cable entry dimensions, see 4.2.

**iTeh STANDARD
PREVIEW
(standards.iteh.ai)**

[SIST EN 3660-064:2022](https://standards.iteh.ai/catalog/standards/sist/21d5d45a-d070-4d3e-bf64-5977523906e3/sist-en-3660-064-2022)

<https://standards.iteh.ai/catalog/standards/sist/21d5d45a-d070-4d3e-bf64-5977523906e3/sist-en-3660-064-2022>

Dimensions in millimetres

**Key**

- 1) Thread C
- 2) Marking
- 3) Number of teeth N
- 4) Four (4) tooling holes spaced 90° apart. $\varnothing 2,60$, depth 1,27
- 5) Straight knurl. Pitch manufacturer's option
- 6) RKV 08 DIN 82. Figure 2. (Please note there may be crossover dependent on diameter and pitch)
- 7) Clearance on thread C
- 8) Break edge

NOTE 1 Cable outlets may be manufactured as cast, fabricated or machined (manufactures option).

NOTE 2 No sharp edges / burrs permissible on internal or external surfaces / joints. Surface finish of $\sqrt{1,6} \mu\text{m max.}$ on all internal surfaces.

Figure 1

Table 1 — Fixed dimensions of shell

Dimensions in millimetres

Shell size	$\varnothing A$ max.	$\varnothing B$ max.	C Thread	E max.	N Number of teeth
08	22,48	15,67	0,500-20UNF	15,3	12
10	25,65	18,64	0,625-24UNEF	15,3	15
12	28,83	21,79	0,750-20UNEF	15,3	21
14	32,00	24,99	0,875-20UNEF	15,3	24
16	35,18	28,24	1,000-20UNEF	15,3	30
18	38,55	30,94	1,0625-18UNEF	15,3	33
20	41,53	34,16	1,1875-18UNEF	15,3	36
22	44,70	37,29	1,3125-18UNEF	15,3	39
24	47,89	40,46	1,4375-18UNEF	15,3	42
28	54,23	49,45	1,750-18UNS	15,3	54

Table 2 — Variable dimensions of wiring chamber

Dimensions in millimetres

Length code wiring chamber	H max.	J min.
A	27,5	8,57
B	35,5	16,57
C	40,5	21,60
D	50,5	31,60
NOTE The code and dimensions of the wiring chamber shall be valid for all sizes of cable outlet.		

Table 3 — Mass for classes N, T, W and Z (1 of 2)

Nominal mass in grams

Shell size code	Cable entry size code												Length code wiring chamber
	A	B	C	D	E	F	G	H	J	K	L	M	
08	10,7	11,3	12,8	13,5	—	—	—	—	—	—	—	—	A
	11,4	12,0	13,1	13,8	—	—	—	—	—	—	—	—	B
	11,9	12,5	15,0	15,8	—	—	—	—	—	—	—	—	C
	12,7	13,3	16,9	17,6	—	—	—	—	—	—	—	—	D
10	12,4	13,1	13,7	14,3	17,4	18,1	—	—	—	—	—	—	A
	13,4	14,1	14,7	15,3	21,1	21,8	—	—	—	—	—	—	B
	14,0	14,7	15,3	15,9	23,4	24,1	—	—	—	—	—	—	C
	15,2	15,9	16,6	17,1	28,0	28,8	—	—	—	—	—	—	D
12	14,5	14,9	15,3	16,1	16,6	17,2	19,7	21,2	—	—	—	—	A
	15,7	16,2	16,6	17,3	17,9	18,4	20,2	22,3	—	—	—	—	B
	16,5	16,9	17,4	18,1	18,7	19,2	21,9	23,4	—	—	—	—	C
	18,1	18,5	18,9	19,6	20,2	20,7	24,2	25,7	—	—	—	—	D
14	17,8	18,2	18,6	19,0	19,2	20,0	21,2	24,4	25,7	—	—	—	A
	19,3	19,7	20,1	20,5	20,8	21,6	22,7	25,7	27,0	—	—	—	B
	20,3	20,7	21,1	21,4	21,7	22,5	23,7	27,0	28,2	—	—	—	C
	22,2	22,6	23,0	23,3	23,6	24,4	25,6	29,5	30,7	—	—	—	D
16	20,0	20,5	20,9	21,2	21,5	21,8	23,0	24,0	28,2	29,7	—	—	A
	21,8	22,3	22,7	23,0	23,3	23,6	24,8	25,8	29,9	31,4	—	—	B
	23,0	23,4	23,8	24,1	24,4	24,7	25,9	27,0	31,4	32,9	—	—	C
	25,2	25,6	26,0	26,4	26,7	27,0	28,1	29,2	34,4	35,9	—	—	D
18	21,2	21,6	22,0	22,4	22,6	22,9	23,5	24,9	29,7	31,2	—	—	A
	23,2	23,6	24,0	24,4	24,6	24,9	25,5	26,9	31,7	33,2	—	—	B
	24,4	24,8	25,2	25,6	25,9	26,2	26,7	28,2	33,3	34,8	—	—	C
	26,9	27,3	27,7	28,1	28,4	28,7	29,2	30,6	36,6	38,1	—	—	D
20	25,7	26,1	26,5	26,9	27,2	27,5	28,0	28,4	29,6	32,8	34,6	—	A
	28,0	28,4	28,8	29,2	29,4	29,7	30,3	30,7	31,9	35,1	36,9	—	B
	29,4	29,8	30,2	30,6	30,9	31,2	31,7	32,1	33,3	37,0	38,8	—	C
	32,3	32,7	33,1	33,4	33,7	34,0	34,6	35,0	36,2	40,8	42,6	—	D
22	27,1	27,5	27,9	28,3	28,5	28,8	29,4	29,8	30,3	31,3	35,4	37,2	A
	29,6	30,0	30,4	30,8	31,1	31,4	32,0	32,3	32,9	33,8	38,1	39,9	B
	31,2	31,6	32,0	32,4	32,7	33,0	33,5	33,9	34,5	35,4	40,2	42,1	C
	34,4	34,8	35,2	35,6	35,9	36,2	36,7	37,1	37,7	38,6	44,5	46,3	D

Table 3 — Mass for classes N, T, W and Z (2 of 2)

Nominal mass in grams

Shell size code	Cable entry size code												Length code wiring chamber
	A	B	C	D	E	F	G	H	J	K	L	M	
24	33,1	33,5	33,9	34,3	34,5	34,9	35,4	35,8	36,4	36,6	37,7	40,6	A
	35,9	36,4	36,8	37,1	37,4	37,7	38,3	38,6	39,2	39,4	40,5	43,4	B
	37,7	38,1	38,5	38,9	39,2	39,5	40,0	40,4	41,0	41,2	42,3	45,8	C
	41,3	41,7	42,1	42,4	42,7	43,0	43,6	44,0	44,5	44,7	45,8	50,5	D
28	43,9	43,5	43,9	44,3	44,5	44,9	45,4	45,8	46,4	46,6	47,0	48,0	A
	46,2	46,7	47,1	47,4	47,7	48,0	48,6	48,9	49,5	49,7	50,1	51,1	B
	48,2	48,6	49,0	49,4	49,7	50,0	50,5	50,9	51,5	51,7	52,1	53,1	C
	52,3	52,7	53,1	53,4	53,7	54,0	54,6	55,0	55,5	55,7	56,8	5,8	D

**iTeh STANDARD
PREVIEW
(standards.iteh.ai)**

[SIST EN 3660-064:2022](https://standards.iteh.ai/catalog/standards/sist/21d5d45a-d070-4d3e-bf64-5977523906e3/sist-en-3660-064-2022)

<https://standards.iteh.ai/catalog/standards/sist/21d5d45a-d070-4d3e-bf64-5977523906e3/sist-en-3660-064-2022>