

ETSI TS 129 274 V16.13.0 (2024-01)



Universal Mobile Telecommunications System (UMTS);

LTE;

5G;

3GPP Evolved Packet System (EPS);

Evolved General Packet Radio Service (GPRS)

Tunnelling Protocol for Control plane (GTPv2-C);

Stage 3

(3GPP TS 29.274 version 16.13.0 Release 16)



Reference

RTS/TSGC-0429274vgd0

Keywords

5G,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2024-01)

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	11
1 Scope	13
2 References	13
3 Definitions, symbols and abbreviations	17
3.1 Definitions	17
3.2 Symbols.....	17
3.3 Abbreviations	17
4 General	19
4.1 GTP Tunnel	19
4.2 Protocol stack	19
4.2.0 General.....	19
4.2.1 UDP header and port numbers	20
4.2.1.0 General	20
4.2.1.1 Initial Messages.....	21
4.2.1.2 Triggered Messages	21
4.2.1.3 Piggybacked Messages.....	21
4.2.2 IP header and IP addresses.....	21
4.2.2.1 Initial Messages.....	21
4.2.2.2 Triggered Messages	22
4.2.2.3 Piggybacked Messages.....	23
4.2.3 Layer 2	23
4.2.4 Layer 1	23
4.2.5 Messages with GTPv2 defined replies: Classification of Initial and Triggered Messages	23
4.3 Transmission Order and Bit Definitions.....	24
5 GTP Header for Control Plane	24
5.1 General format.....	24
5.2 Control Plane GTP Extension Header	24
5.3 GTP-C header for Echo and Version Not Supported Indication messages	24
5.4 EPC specific GTP-C header	25
5.5 Usage of the GTPv2-C Header.....	25
5.5.1 General.....	25
5.5.2 Conditions for sending TEID=0 in GTPv2-C header	26
5.6 Format of the GTPv2-C Message	28
6 GTP-C Message Types and Message Formats	29
6.0 General	29
6.1 Message Format and Type values	29
6.1.0 Message Type	29
6.1.1 Presence requirements of Information Elements	33
6.1.2 Grouped Information Elements.....	34
6.1.3 Information Element instance	35
6.2 Message Granularity.....	35
7 GTP-C messages	36
7.1 Path Management Messages.....	36
7.1.0 General.....	36
7.1.1 Echo Request	36
7.1.2 Echo Response.....	37
7.1.3 Version Not Supported Indication	37
7.2 Tunnel Management Messages	37
7.2.0 General.....	37

7.2.1	Create Session Request	37
7.2.2	Create Session Response	59
7.2.3	Create Bearer Request	72
7.2.4	Create Bearer Response	76
7.2.5	Bearer Resource Command	81
7.2.6	Bearer Resource Failure Indication	84
7.2.7	Modify Bearer Request	87
7.2.8	Modify Bearer Response	108
7.2.9	Delete Session Request and Delete Bearer Request	114
7.2.9.1	Delete Session Request	114
7.2.9.2	Delete Bearer Request	121
7.2.10	Delete Session Response and Delete Bearer Response	127
7.2.10.1	Delete Session Response	127
7.2.10.2	Delete Bearer Response	131
7.2.11	Downlink Data Notification messages	135
7.2.11.1	Downlink Data Notification	135
7.2.11.2	Downlink Data Notification Acknowledge	139
7.2.11.3	Downlink Data Notification Failure Indication	141
7.2.12	Delete Indirect Data Forwarding Tunnel Request	141
7.2.13	Delete Indirect Data Forwarding Tunnel Response	142
7.2.14	Modify Bearer Command and Failure Indication	143
7.2.14.1	Modify Bearer Command	143
7.2.14.2	Modify Bearer Failure Indication	145
7.2.15	Update Bearer Request	147
7.2.16	Update Bearer Response	152
7.2.17	Delete Bearer Command and Failure Indication	157
7.2.17.1	Delete Bearer Command	157
7.2.17.2	Delete Bearer Failure Indication	159
7.2.18	Create Indirect Data Forwarding Tunnel Request	162
7.2.19	Create Indirect Data Forwarding Tunnel Response	165
7.2.20	Void	167
7.2.21	Release Access Bearers Request	167
7.2.22	Release Access Bearers Response	168
7.2.23	Stop Paging Indication	170
7.2.24	Modify Access Bearers Request	170
7.2.25	Modify Access Bearers Response	174
7.2.26	Remote UE Report Notification	177
7.2.27	Remote UE Report Acknowledge	178
7.3	Mobility Management Messages	178
7.3.1	Forward Relocation Request	178
7.3.2	Forward Relocation Response	194
7.3.3	Forward Relocation Complete Notification	197
7.3.4	Forward Relocation Complete Acknowledge	198
7.3.5	Context Request	198
7.3.6	Context Response	202
7.3.7	Context Acknowledge	214
7.3.8	Identification Request	217
7.3.9	Identification Response	218
7.3.10	Forward Access Context Notification	219
7.3.11	Forward Access Context Acknowledge	220
7.3.12	Detach Notification	220
7.3.13	Detach Acknowledge	221
7.3.14	Change Notification Request	222
7.3.15	Change Notification Response	225
7.3.16	Relocation Cancel Request	226
7.3.17	Relocation Cancel Response	227
7.3.18	Configuration Transfer Tunnel	227
7.3.19	RAN Information Relay	229
7.3.20	ISR Status Indication	229
7.3.21	UE Registration Query Request	230
7.3.22	UE Registration Query Response	230
7.4	CS Fallback and SRVCC related messages	231

7.4.1	Suspend Notification.....	231
7.4.2	Suspend Acknowledge.....	232
7.4.3	Resume Notification	233
7.4.4	Resume Acknowledge	234
7.4.5	CS Paging Indication	234
7.4.6	Alert MME Notification	235
7.4.7	Alert MME Acknowledge	235
7.4.8	UE Activity Notification.....	235
7.4.9	UE Activity Acknowledge.....	236
7.5	Non-3GPP access related messages	236
7.5.1	Create Forwarding Tunnel Request	236
7.5.2	Create Forwarding Tunnel Response.....	236
7.6	Reliable Delivery of Signalling Messages.....	237
7.7	Error Handling.....	238
7.7.0	Handling Piggybacked Messages	238
7.7.1	Protocol Errors.....	238
7.7.2	Different GTP Versions	239
7.7.3	GTP Message of Invalid Length.....	239
7.7.4	Unknown GTP Message	239
7.7.5	Unexpected GTP Message.....	239
7.7.6	Missing Information Elements.....	240
7.7.7	Invalid Length Information Element	240
7.7.8	Semantically incorrect Information Element	241
7.7.9	Unknown or unexpected Information Element	241
7.7.10	Repeated Information Elements.....	242
7.7.11	TFT Error Handling	242
7.8	Path Failure	242
7.9	Restoration and Recovery	242
7.9.0	General.....	242
7.9.1	Delete PDN Connection Set Request.....	242
7.9.2	Delete PDN Connection Set Response	243
7.9.3	Update PDN Connection Set Request.....	243
7.9.4	Update PDN Connection Set Response	243
7.9.5	PGW Restart Notification.....	244
7.9.6	PGW Restart Notification Acknowledge	244
7.9.7	PGW Downlink Triggering Notification	245
7.9.8	PGW Downlink Triggering Acknowledge	245
7.10	Fallback to GTPv1 mechanism	246
7.11	Fallback to GTPv0.....	246
7.12	Trace Management Messages.....	247
7.12.1	Trace Session Activation	247
7.12.2	Trace Session Deactivation.....	248
7.13	MBMS Messages	249
7.13.1	MBMS Session Start Request.....	249
7.13.2	MBMS Session Start Response	250
7.13.3	MBMS Session Update Request.....	251
7.13.4	MBMS Session Update Response	252
7.13.5	MBMS Session Stop Request	252
7.13.6	MBMS Session Stop Response.....	252
8	GTP-C Information Elements	253
8.1	Information Element Types	253
8.2	Information Element Format	257
8.2.1	General.....	257
8.2.1A	Information Element with an IE Type Extension field	257
8.2.2	Handling ASN.1/PER encoded parameters	258
8.3	International Mobile Subscriber Identity (IMSI).....	258
8.4	Cause	258
8.5	Recovery (Restart Counter).....	265
8.6	Access Point Name (APN).....	266
8.7	Aggregate Maximum Bit Rate (AMBR)	266
8.8	EPS Bearer ID (EBI).....	266

8.9	IP Address	267
8.10	Mobile Equipment Identity (MEI).....	267
8.11	MSISDN.....	267
8.12	Indication.....	268
8.13	Protocol Configuration Options (PCO).....	273
8.14	PDN Address Allocation (PAA)	273
8.15	Bearer Quality of Service (Bearer QoS).....	274
8.16	Flow Quality of Service (Flow QoS).....	275
8.17	RAT Type.....	275
8.18	Serving Network	276
8.19	EPS Bearer Level Traffic Flow Template (Bearer TFT).....	276
8.20	Traffic Aggregate Description (TAD).....	277
8.21	User Location Information (ULI).....	277
8.21.1	CGI field	278
8.21.2	SAI field	278
8.21.3	RAI field.....	278
8.21.4	TAI field.....	279
8.21.5	ECGI field.....	279
8.21.6	LAI field	279
8.21.7	Macro eNodeB ID field	279
8.21.8	Extended Macro eNodeB ID field	280
8.22	Fully Qualified TEID (F-TEID)	280
8.23	TMSI	282
8.24	Global CN-Id.....	282
8.25	S103 PDN Data Forwarding Info (S103PDF).....	283
8.26	S1-U Data Forwarding (S1UDF).....	283
8.27	Delay Value.....	284
8.28	Bearer Context.....	284
8.29	Charging ID.....	284
8.30	Charging Characteristics	284
8.31	Trace Information.....	285
8.32	Bearer Flags.....	285
8.33	Void.....	286
8.34	PDN Type.....	286
8.35	Procedure Transaction ID (PTI)	286
8.36	Void.....	287
8.37	Void.....	287
8.38	MM Context.....	287
8.39	PDN Connection	297
8.40	PDU Numbers	298
8.41	Packet TMSI (P-TMSI).....	298
8.42	P-TMSI Signature.....	299
8.43	Hop Counter	299
8.44	UE Time Zone	299
8.45	Trace Reference.....	300
8.46	Complete Request Message.....	300
8.47	GUTI	300
8.48	Fully Qualified Container (F-Container).....	301
8.49	Fully Qualified Cause (F-Cause).....	302
8.50	PLMN ID.....	303
8.51	Target Identification.....	304
8.51.1	General.....	304
8.51.2	RNC ID.....	304
8.51.3	Macro eNodeB ID.....	305
8.51.4	Home eNodeB ID	306
8.51.5	Extended Macro eNodeB ID.....	306
8.51.6	Cell Identifier.....	306
8.51.7	gNodeB ID.....	307
8.51.8	Macro ng-eNodeB ID	307
8.51.9	Extended Macro ng-eNodeB ID	307
8.51.10	en-gNB ID	308
8.52	Void.....	309

8.53	Packet Flow ID	309
8.54	RAB Context	309
8.55	Source RNC PDCP context info	310
8.56	Port Number	310
8.57	APN Restriction	310
8.58	Selection Mode	311
8.59	Source Identification	311
8.60	Void	312
8.61	Change Reporting Action	312
8.62	Fully qualified PDN Connection Set Identifier (FQ-CSID)	312
8.63	Channel needed	313
8.64	eMLPP Priority	313
8.65	Node Type	314
8.66	Fully Qualified Domain Name (FQDN)	314
8.67	Private Extension	315
8.68	Transaction Identifier (TI)	315
8.69	MBMS Session Duration	315
8.70	MBMS Service Area	316
8.71	MBMS Session Identifier	316
8.72	MBMS Flow Identifier	316
8.73	MBMS IP Multicast Distribution	316
8.74	MBMS Distribution Acknowledge	317
8.75	User CSG Information (UCI)	318
8.76	CSG Information Reporting Action	318
8.77	RFSP Index	319
8.78	CSG ID	319
8.79	CSG Membership Indication (CMI)	319
8.80	Service indicator	320
8.81	Detach Type	320
8.82	Local Distinguished Name (LDN)	321
8.83	Node Features	321
8.84	MBMS Time to Data Transfer	322
8.85	Throttling	323
8.86	Allocation/Retention Priority (ARP)	323
8.87	EPC Timer	324
8.88	Signalling Priority Indication	325
8.89	Temporary Mobile Group Identity (TMGI)	325
8.90	Additional MM context for SRVCC	325
8.91	Additional flags for SRVCC	326
8.92	Void	326
8.93	MDT Configuration	326
8.94	Additional Protocol Configuration Options (APCO)	327
8.95	Absolute Time of MBMS Data Transfer	328
8.96	H(e)NB Information Reporting	328
8.97	IPv4 Configuration Parameters (IP4CP)	328
8.98	Change to Report Flags	329
8.99	Action Indication	329
8.100	TWAN Identifier	330
8.101	ULI Timestamp	331
8.102	MBMS Flags	331
8.103	RAN/NAS Cause	332
8.104	CN Operator Selection Entity	333
8.105	Trusted WLAN Mode Indication	333
8.106	Node Number	334
8.107	Node Identifier	334
8.108	Presence Reporting Area Action	335
8.109	Presence Reporting Area Information	337
8.110	TWAN Identifier Timestamp	337
8.111	Overload Control Information	338
8.112	Load Control Information	338
8.113	Metric	338
8.114	Sequence Number	339

8.115	APN and Relative Capacity	339
8.116	WLAN Offloadability Indication	339
8.117	Paging and Service Information	340
8.118	Integer Number	340
8.119	Millisecond Time Stamp	341
8.120	Monitoring Event Information	341
8.121	ECGI List	342
8.122	Remote UE Context.....	342
8.123	Remote User ID.....	343
8.124	Remote UE IP Information.....	343
8.125	CIoT Optimizations Support Indication	344
8.126	SCEF PDN Connection.....	344
8.127	Header Compression Configuration	344
8.128	Extended Protocol Configuration Options (ePCO)	345
8.129	Serving PLMN Rate Control	346
8.130	Counter	346
8.131	Mapped UE Usage Type	346
8.132	Secondary RAT Usage Data Report.....	347
8.133	UP Function Selection Indication Flags	348
8.134	Maximum Packet Loss Rate	348
8.135	APN Rate Control Status.....	349
8.136	Extended Trace Information.....	349
8.137	Monitoring Event Extension Information.....	350
8.138	Additional RRM Policy Index.....	350
8.139	V2X Context	351
8.140	PC5 QoS Parameters	351
8.141	Services Authorized	351
8.142	Bit Rate.....	352
8.143	PC5 QoS Flow.....	352
8.144	SGi PTP Tunnel Address.....	352
9	Security.....	353
10	IP - The Networking Technology used by GTP.....	353
10.1	IP Version.....	353
10.2	IP Fragmentation	353
10.3	DSCP.....	354
11	Notification of supported features between peer GTP-C entities.....	354
11.1	General	354
11.1.1	Introduction.....	354
11.1.2	Defining a feature	354
11.2	Dynamic discovery of supported features	355
11.2.1	General.....	355
11.2.2	Features supported by direct peer GTP-C entities	355
12	GTP-C load & overload control mechanism.....	355
12.1	General	355
12.1.1	GTP-C overload problem.....	355
12.1.2	Scenarios leading to overload	356
12.1.3	Load & overload control concepts.....	356
12.2	Load control solution.....	357
12.2.1	Principles of load control	357
12.2.2	Applicability to 3GPP and non-3GPP access based interfaces	357
12.2.3	Node level load control.....	358
12.2.4	APN level load control	358
12.2.4.1	General	358
12.2.4.2	Justifications for APN load control support	358
12.2.4.3	Elements of APN load control	359
12.2.5	Load Control Information.....	359
12.2.5.1	Definition	359
12.2.5.1.1	General description.....	359
12.2.5.1.2	Parameters	360

12.2.5.1.3	Handling of parameters	362
12.2.5.2	Frequency of inclusion	362
12.2.5.3	Limit on maximum number of instances.....	362
12.2.6	Discovery of the support of the feature by the peer node	363
12.2.7	Issues in the network with partial support of the feature	363
12.3	Overload control solution	363
12.3.1	Principles of overload control	363
12.3.2	Applicability to 3GPP and non-3GPP access based interfaces	364
12.3.3	Node level overload control.....	364
12.3.4	APN level overload control	365
12.3.4.1	General	365
12.3.4.2	Elements of APN overload control	365
12.3.5	Overload Control Information	365
12.3.5.1	Definition	365
12.3.5.1.1	General description.....	365
12.3.5.1.2	Parameters	366
12.3.5.1.3	Handling of parameters	368
12.3.5.2	Frequency of inclusion	369
12.3.5.3	Limit on maximum number of instances.....	369
12.3.6	Propagating the MME/S4-SGSN identity to the PGW	369
12.3.7	Updating the PGW with overload control information of the target MME/S4-SGSN	370
12.3.8	The interaction with APN congestion control using the PGW Back-Off Time	370
12.3.9	Message throttling	371
12.3.9.1	General	371
12.3.9.2	Throttling algorithm – "Loss"	371
12.3.9.2.1	Description	371
12.3.9.3	Message prioritization.....	371
12.3.9.3.1	Description	371
12.3.9.3.2	Based on procedures.....	372
12.3.9.3.3	Based on session parameters	373
12.3.9.3.4	Based on the Message Priority signalled in the GTP-C message	373
12.3.10	Enforcement of overload control	374
12.3.10.1	General	374
12.3.10.2	Aspects related to enforcement of the overload control	374
12.3.10.2.1	Good throughput of the network.....	374
12.3.10.2.2	Message processing efficiency at the source GTP-C entity.....	374
12.3.10.2.3	Self-protection by the overloaded GTP-C entity	374
12.3.10.3	Enforcement of overload control between GTP-C entities in direct contact.....	375
12.3.10.4	Enforcement of overload control between remote GTP-C entities	375
12.3.10.4.1	Description	375
12.3.11	Discovery of the support of the feature by the peer node	375
12.3.12	Issues in the network with partial support of the feature	375
12.3.13	Implicit overload control mechanisms.....	376
13	Detection and handling of late arriving requests.....	376
13.1	General	376
13.2	Detection and handling of requests which collide with an existing session context	376
13.2.1	General.....	376
13.2.2	Principles	376
13.3	Detection and handling of requests which have timed out at the originating entity	377
13.3.1	General.....	377
13.3.2	Principles	377
14	Handling of Bearer Contexts Mismatch.....	378
14.1	General	378
14.2	Detection of Bearer Context Mismatch.....	378
14.3	Handling of Bearer Context Mismatch.....	378
14.3.1	General.....	378
14.3.2	Exceptional scenarios	379
Annex A (Informative):	Backward Compatibility Guidelines for Information Elements	380
Annex B (Informative):	Transparent copying of RANAP/S1AP IEs into GTP IEs	381

B.1	General	381
B.2	Handover/Relocation related generic transparent Containers over RANAP, S1-AP and GTP.....	381
B.3	Other RANAP and S1-AP IEs.....	383
Annex C (Normative):	MME/S4-SGSN mapping table between S11/S4 and NAS Cause values.....	384
Annex D (Informative):	GTP-C load and overload control mechanism.....	390
D.1	GTP-C interfaces not supporting Load Control	390
D.2	GTP-C interfaces not supporting Overload Control.....	390
D.3	"Loss" throttling algorithm.....	391
D.3.1	Example of possible implementation	391
D.4	Enforcement of overload control between remote GTP-C entities	391
D.4.1	Example of possible implementation	391
Annex E (Normative):	TWAN mapping table between GTPv2 S2a Cause and non-3GPP access Cause values.....	393
Annex F (Informative):	Change History	397
History		428

iTech Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 129 274 V16.13.0 \(2024-01\)](https://standards.iteh.ai/catalog/standards/etsi/74e47c18-05bd-4889-a845-da32c80ce5f9/etsi-ts-129-274-v16-13-0-2024-01)

<https://standards.iteh.ai/catalog/standards/etsi/74e47c18-05bd-4889-a845-da32c80ce5f9/etsi-ts-129-274-v16-13-0-2024-01>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

- shall** indicates a mandatory requirement to do something
- shall not** indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

- should** indicates a recommendation to do something
- should not** indicates a recommendation not to do something
- may** indicates permission to do something
- need not** indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

- can** indicates that something is possible
- cannot** indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

- will** indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- will not** indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- might** indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

might not indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

is (or any other verb in the indicative mood) indicates a statement of fact

is not (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 129 274 V16.13.0 \(2024-01\)](#)

<https://standards.iteh.ai/catalog/standards/etsi/74e47c18-05bd-4889-a845-da32c80ce5f9/etsi-ts-129-274-v16-13-0-2024-01>

1 Scope

The present document specifies the stage 3 of the control plane of the GPRS Tunnelling Protocol, Version 2 (GTPv2-C).

GTPv2-C shall be used over:

- the S2a, S2b, S3, S4, S5, S8, S10, S11, S16, Sm and Sn signalling interfaces in EPC, specified in 3GPP TS 23.401 [3] and 3GPP TS 23.402 [45].
- the N26 signalling interface between EPC and 5GC, specified in 3GPP TS 23.501 [82] and 3GPP TS 23.502 [83].

GTPv2-C based protocols shall also be used over the Sv (see 3GPP TS 29.280 [15]) and S101/S121 (see 3GPP TS 29.276 [14]) interfaces.

In this document, unless otherwise specified, the S2a, S2b, S5 and S8 interfaces refer to the GTP-based S2a, S2b, S5 and S8 interfaces respectively.

The present document specifies functions, procedures and information which apply to GERAN Iu mode. However, functionality related to GERAN Iu mode is neither maintained nor enhanced.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.003: "Numbering, addressing and identification".
- [3] 3GPP TS 23.401: "General Packet Radio Service (GPRS) enhancements for Evolved Universal Terrestrial Radio Access Network (E-UTRAN) access".
- [4] 3GPP TS 29.060: "General Packet Radio Service (GPRS); GPRS Tunnelling Protocol (GTP) across the Gn and Gp interface".
- [5] 3GPP TS 24.008: "Mobile radio interface Layer 3 specification; Core network protocols; Stage 3".
- [6] IETF RFC 791 (STD 0005): "Internet Protocol", J. Postel.
- [7] IETF RFC 768 (STD 0006): "User Datagram Protocol", J. Postel.
- [8] 3GPP TS 32.251: "Telecommunication Management; Charging Management; Packet Switched (PS) domain charging.
- [9] 3GPP TS 32.298: "Telecommunication Management; Charging Management; Charging Data Record (CDR) parameter classification.
- [10] 3GPP TS 36.413: "Evolved Universal Terrestrial Radio Access Network (E-UTRAN); S1 Application Protocol (S1AP)".
- [11] 3GPP TS 33.102: "3G security; Security architecture".