

INTERNATIONAL
STANDARD

ISO/ASTM
52900

First edition
2015-12-15

Additive manufacturing — General principles — Terminology

Fabrication additive — Principes généraux — Terminologie

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/ASTM 52900:2015](https://standards.iteh.ai/catalog/standards/sist/d9adc3ce-ca51-4c21-b508-00fbb01687d/iso-astm-52900-2015)

<https://standards.iteh.ai/catalog/standards/sist/d9adc3ce-ca51-4c21-b508-00fbb01687d/iso-astm-52900-2015>



Reference number
ISO/ASTM 52900:2015(E)

© ISO/ASTM International 2015

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/ASTM 52900:2015](https://standards.iteh.ai/catalog/standards/sist/d9adc3ce-ca51-4c21-b508-00fbbe01687d/iso-astm-52900-2015)

<https://standards.iteh.ai/catalog/standards/sist/d9adc3ce-ca51-4c21-b508-00fbbe01687d/iso-astm-52900-2015>



COPYRIGHT PROTECTED DOCUMENT

© ISO/ASME International 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester. In the United States, such requests should be sent to ASTM International.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

ASTM International
100 Barr Harbor Drive, PO Box C700
West Conshohocken, PA 19428-2959, USA
Tel. +610 832 9634
Fax +610 832 9635
khooper@astm.org
www.astm.org

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Terms and definitions	1
2.1 General terms.....	1
2.2 Process categories.....	2
2.3 Processing: General.....	3
2.4 Processing: Data.....	6
2.5 Processing: Material.....	8
2.6 Applications.....	9
2.7 Properties.....	10
Annex A (informative) Basic principles	12
Annex B (informative) Alphabetical index	17
Bibliography	19

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/ASTM 52900:2015](https://standards.iteh.ai/catalog/standards/sist/d9adc3ce-ca51-4c21-b508-00fbbe01687d/iso-astm-52900-2015)

<https://standards.iteh.ai/catalog/standards/sist/d9adc3ce-ca51-4c21-b508-00fbbe01687d/iso-astm-52900-2015>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 261, *Additive manufacturing*, in cooperation with ASTM Committee F42, *Additive Manufacturing Technologies*, on the basis of a partnership agreement between ISO and ASTM International with the aim to create a common set of ISO/ASTM standards on Additive Manufacturing.

This first edition of ISO/ASTM 52900 cancels and replaces ASTM F2792.

Introduction

Additive manufacturing is the general term for those technologies that based on a geometrical representation creates physical objects by successive addition of material. These technologies are presently used for various applications in engineering industry as well as other areas of society, such as medicine, education, architecture, cartography, toys and entertainment.

During the development of additive manufacturing technology there have been numerous different terms and definitions in use, often with reference to specific application areas and trademarks. This is often ambiguous and confusing which hampers communication and wider application of this technology.

It is the intention of this International Standard to provide a basic understanding of the fundamental principles for additive manufacturing processes, and based on this, to give clear definitions for terms and nomenclature associated with additive manufacturing technology. The objective of this standardization of terminology for additive manufacturing is to facilitate communication between people involved in this field of technology on a world-wide basis.

This International Standard has been developed by ISO/TC 261 and ASTM F42 in close cooperation on the basis of a partnership agreement between ISO and ASTM International with the aim to create a common set of ISO/ASTM standards on Additive Manufacturing.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/ASTM 52900:2015](https://standards.iteh.ai/catalog/standards/sist/d9adc3ce-ca51-4c21-b508-00fbb01687d/iso-astm-52900-2015)

<https://standards.iteh.ai/catalog/standards/sist/d9adc3ce-ca51-4c21-b508-00fbb01687d/iso-astm-52900-2015>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/ASTM 52900:2015](https://standards.iteh.ai/catalog/standards/sist/d9adc3ce-ca51-4c21-b508-00fbbe01687d/iso-astm-52900-2015)

<https://standards.iteh.ai/catalog/standards/sist/d9adc3ce-ca51-4c21-b508-00fbbe01687d/iso-astm-52900-2015>

Additive manufacturing — General principles — Terminology

1 Scope

This International Standard establishes and defines terms used in additive manufacturing (AM) technology, which applies the additive shaping principle and thereby builds physical 3D geometries by successive addition of material.

The terms have been classified into specific fields of application.

New terms emerging from the future work within ISO/TC 261 and ASTM F42 will be included in upcoming amendments and overviews of this International Standard.

2 Terms and definitions

2.1 General terms

2.1.1

3D printer, noun
machine used for *3D printing* (2.3.1).

2.1.2

additive manufacturing, noun
AM
process of joining materials to make *parts* (2.6.1) from 3D model data, usually *layer* (2.3.10) upon layer, as opposed to subtractive manufacturing and formative manufacturing methodologies

Note 1 to entry: Historical terms: additive fabrication, additive processes, additive techniques, additive layer manufacturing, layer manufacturing, solid freeform fabrication and freeform fabrication.

Note 2 to entry: The meaning of “additive-”, “subtractive-” and “formative-” manufacturing methodologies are further discussed in [Annex A](#).

2.1.3

additive system, noun
additive manufacturing system
additive manufacturing equipment
machine and auxiliary equipment used for *additive manufacturing* (2.1.2)

2.1.4

AM machine, noun
section of the *additive manufacturing system* (2.1.3) including hardware, machine control software, required set-up software and peripheral accessories necessary to complete a *build cycle* (2.3.3) for producing *parts* (2.6.1)

2.1.5

AM machine user, noun
operator of or entity using an *AM machine* (2.1.4)

2.1.6

AM system user, noun
additive system user
operator of or entity using an entire *additive manufacturing system* (2.1.3) or any component of an additive system

2.1.7

front, noun

<of a machine; unless otherwise designated by the machine builder> side of the machine that the operator faces to access the user interface or primary viewing window, or both

2.1.8

material supplier, noun

provider of material/ *feedstock* (2.5.2) to be processed in *additive manufacturing system* (2.1.3)

2.1.9

multi-step process, noun

type of *additive manufacturing* (2.1.2) process in which *parts* (2.6.1) are fabricated in two or more operations where the first typically provides the basic geometric shape and the following consolidates the part to the fundamental properties of the intended material (metallic, ceramic, polymer or composite)

Note 1 to entry: Removal of the support structure and cleaning may be necessary, however in this context not considered as a separate process step.

Note 2 to entry: The principle of *single-step* (2.1.10) and multi-step processes are further discussed in [Annex A](#).

2.1.10

single-step process, noun

type of *additive manufacturing* (2.1.2) process in which *parts* (2.6.1) are fabricated in a single operation where the basic geometric shape and basic material properties of the intended product are achieved simultaneously

Note 1 to entry: Removal of the support structure and cleaning may be necessary, however in this context not considered as a separate process step.

Note 2 to entry: The principle of single-step and *multi-step processes* (2.1.9) are further discussed in [Annex A](#).

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/ASTM 52900:2015

2.2 **Process categories** <https://standards.iteh.ai/catalog/standards/sist/d9adc3ce-ca51-4c21-b508-00fbbe01687d/iso-astm-52900-2015>

2.2.1

binder jetting, noun

additive manufacturing (2.1.2) process in which a liquid bonding agent is selectively deposited to join powder materials

2.2.2

directed energy deposition, noun

additive manufacturing (2.1.2) process in which focused thermal energy is used to fuse materials by melting as they are being deposited

Note 1 to entry: "Focused thermal energy" means that an energy source (e.g. laser, electron beam, or plasma arc) is focused to melt the materials being deposited.

2.2.3

material extrusion, noun

additive manufacturing (2.1.2) process in which material is selectively dispensed through a nozzle or orifice

2.2.4

material jetting, noun

additive manufacturing (2.1.2) process in which droplets of build material are selectively deposited

Note 1 to entry: Example materials include photopolymer and wax.

2.2.5

powder bed fusion, noun

additive manufacturing (2.1.2) process in which thermal energy selectively fuses regions of a *powder bed* (2.5.8)

2.2.6**sheet lamination**, noun

additive manufacturing (2.1.2) process in which sheets of material are bonded to form a *part* (2.6.1)

2.2.7**vat photopolymerization**, noun

additive manufacturing (2.1.2) process in which liquid photopolymer in a vat is selectively cured by light-activated polymerization

2.3 Processing: General**2.3.1****3D printing**, noun

fabrication of objects through the deposition of a material using a print head, nozzle, or another printer technology

Note 1 to entry: Term often used in a non-technical context synonymously with *additive manufacturing* (2.1.2); until present times this term has in particular been associated with machines that are low end in price and/or overall capability.

2.3.2**build chamber**, noun

enclosed location within the *additive manufacturing system* (2.1.3) where the *parts* (2.6.1) are fabricated

2.3.3**build cycle**, noun

single process cycle in which one or more components are built up in *layers* (2.3.10) in the process chamber of the *additive manufacturing system* (2.1.3)

2.3.4**build envelope**, noun

largest external dimensions of the x-, y-, and z-axes within the *build space* (2.3.6) where *parts* (2.6.1) can be fabricated

Note 1 to entry: The dimensions of the build space will be larger than the build envelope.

2.3.5**build platform**, noun

<of a machine> base which provides a surface upon which the building of the *part/s* (2.6.1), is started and supported throughout the build process

Note 1 to entry: In some systems, the *parts* (2.6.1) are built attached to the build platform, either directly or through a support structure. In other systems, such as *powder bed* (2.5.8) systems, no direct mechanical fixture between the build and the platform may be required.

2.3.6**build space**, noun

location where it is possible for *parts* (2.6.1) to be fabricated, typically within the *build chamber* (2.3.2) or on a *build platform* (2.3.5)

2.3.7**build surface**, noun

area where material is added, normally on the last deposited *layer* (2.3.10) which becomes the foundation upon which the next layer is formed

Note 1 to entry: For the first layer, the build surface is often the *build platform* (2.3.5).

Note 2 to entry: In the case of *directed energy deposition* (2.2.2) processes, the build surface can be an existing part onto which material is added.

Note 3 to entry: If the orientation of the material deposition or consolidation means, or both, is variable, it may be defined relative to the build surface.

2.3.8

build volume, noun

total usable volume available in the machine for building *parts* (2.6.1)

2.3.9

feed region, noun

<in *powder bed fusion* (2.2.5)> location/s in the machine where *feedstock* (2.5.2) is stored and from which a portion of the feedstock is repeatedly conveyed to the powder bed during the *build cycle* (2.3.3)

2.3.10

layer, noun

<matter> material laid out, or spread, to create a surface

2.3.11

machine coordinate system, noun

three-dimensional coordinate system as defined by a fixed point on the *build platform* (2.3.5) with the three principal axes labelled x-, y-, and z-, with rotary axis about each of these axis labelled A, B, and C, respectively, where the angles between x-, y- and z- can be Cartesian or defined by the machine manufacturer

Note 1 to entry: Machine coordinate system is fixed relative to the machine, as opposed to coordinate systems associated with the *build surface* (2.3.7) which can be translated or rotated. Machine coordinate system is illustrated in ISO/ASTM 52921.^[6]

2.3.12

manufacturing lot, noun

set of manufactured *parts* (2.6.1) having commonality between *feedstock* (2.5.2), *production run* (2.3.19), *additive manufacturing system* (2.1.3) and *post-processing* (2.5.6) steps (if required) as recorded on a single manufacturing work order

Note 1 to entry: *Additive manufacturing system* (2.1.3) could include one or several *AM machines* (2.1.4) and/or *post-processing* (2.5.6) machine units as agreed by AM (2.1.2) provider and customer.

2.3.13

origin, noun

zero point

(0, 0, 0) <when using x-, y-, and z-coordinates>

designated universal reference point at which the three primary axes in a coordinate system intersect

Note 1 to entry: Coordinate system can be Cartesian or as defined by the machine manufacturer. The concept of origin is illustrated in ISO/ASTM 52921.^[6]

2.3.14

build origin, noun

origin (2.3.13) most commonly located at the centre of the *build platform* (2.3.5) and fixed on the build facing surface, but could be defined otherwise by the build set-up

2.3.15

machine origin, noun

machine home

machine zero point

origin (2.3.13) as defined by the machine manufacturer

2.3.16

overflow region, noun

<in *powder bed fusion* (2.2.5) systems> location/s in the machine where excess powder is stored during a *build cycle* (2.3.3)

Note 1 to entry: For certain machine types the overflow region may consist of one or more dedicated chambers or a powder recycling system.

2.3.17**part location**, noun

location of the *part* (2.6.1) within the *build volume* (2.3.8)

Note 1 to entry: The part location is normally specified by the x-, y- and z-coordinates for the position of the *geometric centre* (2.4.9) of the part's *bounding box* (2.4.3) with respect to the *build volume* (2.3.8) *origin* (2.3.13). Part location is illustrated in ISO/ASTM 52921.[6]

2.3.18**process parameters**, noun

set of operating parameters and system settings used during a *build cycle* (2.3.3)

2.3.19**production run**, noun

all *parts* (2.6.1) produced in one *build cycle* (2.3.3) or sequential series of build cycles using the same *feedstock* (2.5.2) batch and process conditions

2.3.20**system set-up**, noun

configuration of the *additive manufacturing system* (2.1.3) for a build

2.3.21**x-axis**, noun

<of a machine; unless otherwise designated by the machine builder> axis in the *machine coordinate system* (2.3.11) that runs parallel to the *front* (2.1.7) of the machine and perpendicular to the *y-axis* (2.3.22) and *z-axis* (2.3.23).

Note 1 to entry: <unless otherwise designated by the machine builder> The positive x-direction runs from left to right as viewed from the front of the machine while facing toward the *build volume* (2.3.8) *origin* (2.3.13).

Note 2 to entry: It is common that the x-axis is horizontal and parallel with one of the edges of the *build platform* (2.3.5).

2.3.22**y-axis**, noun

<of a machine; unless otherwise designated by the machine builder> axis in the *machine coordinate system* (2.3.11) that runs perpendicular to the *z-axis* (2.3.23) and *x-axis* (2.3.21)

Note 1 to entry: <unless otherwise designated by the machine builder> The positive direction is defined in ISO 841[1] to make a right hand set of coordinates. In the most common case of an upwards z-positive direction, the positive y-direction will then run from the front to the back of the machine as viewed from the front of the machine.

Note 2 to entry: In the case of building in the downwards z-positive direction, the positive y-direction will then run from the back of the machine to the front as viewed from the front of the machine.

Note 3 to entry: It is common that the y-axis is horizontal and parallel with one of the edges of the *build platform* (2.3.5).

2.3.23**z-axis**, noun

<of a machine; unless otherwise designated by the machine builder>, axis in the *machine coordinate system* (2.3.11) that run perpendicular to the *x-axis* (2.3.21) and *y-axis* (2.3.22)

Note 1 to entry: <unless otherwise designated by the machine builder> The positive direction is defined in ISO 841[1] to make a right hand set of coordinates. For processes employing planar, layerwise addition of material, the positive z-direction will then run normal to the *layers* (2.3.10).

Note 2 to entry: For processes employing planar layerwise addition of material, the positive z-direction, is the direction from the first layer to the subsequent layers.

Note 3 to entry: Where addition of material is possible from multiple directions (such as with certain *directed energy deposition* (2.2.2) systems), the z- axis may be identified according to the principles in ISO 841, (4.3.3)[1] which addresses "swivelling or gimballing."