



SLOVENSKI STANDARD
oSIST prEN 17168:2020
01-februar-2020

Železniške naprave - Ploščad pregradnih sistemov

Railway applications - Platform barrier systems

Bahnanwendungen - Bahnsteig-Barrieresysteme

Applications ferroviaires - Systèmes façades de quai

Ta slovenski standard je istoveten z: prEN 17168

ITEH STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 17168:2020](https://standards.iteh.ai/catalog/standards/sist/1339df99-09e9-41b2-bc79-f95d2a0eb203/osist-pren-17168-2020)

<https://standards.iteh.ai/catalog/standards/sist/1339df99-09e9-41b2-bc79-f95d2a0eb203/osist-pren-17168-2020>

ICS:

45.020	Železniška tehnika na splošno	Railway engineering in general
93.100	Gradnja železnic	Construction of railways

oSIST prEN 17168:2020

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

oSIST prEN 17168:2020

<https://standards.iteh.ai/catalog/standards/sist/1339df99-09e9-41b2-bc79-f95d2a0eb203/osist-pren-17168-2020>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

DRAFT
prEN 17168

December 2019

ICS 45.020; 45.120

English Version

Railway applications - Platform barrier systems

Applications ferroviaires - Systèmes façades de quai

Bahnanwendungen - Bahnsteig-Barrieresysteme

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 256.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword	4
Introduction	5
1 Scope	6
2 Normative references	7
3 Terms and definitions	9
4 System design requirements	12
4.1 Physical and structural requirements of the platform barrier	12
4.1.1 General structural requirements.....	12
4.1.2 Structural design principles	13
4.1.3 Structural loading conditions.....	13
4.1.4 Glazing and other panelling materials in facades, including doors and gates.....	15
4.1.5 Fire performance - use as a fire barrier.....	16
4.1.6 Fire performance - fire resistance of materials	16
4.1.7 Requirements for emergency doors/gates.....	16
4.1.8 Requirements for driver access doors/gates	17
4.1.9 Requirements for platform extremity doors/gates	17
4.1.10 Entrapment between the platform barrier and vehicles	19
4.1.11 Environmental requirements.....	23
4.1.12 Acoustic and thermal properties of platform barriers	24
4.1.13 Physical requirements of doors and gates for normal operation	24
4.2 Control and electrical requirements	26
4.2.1 Control system - conditions for opening/closing of doors/gates	26
4.2.2 Detection of door/gate locking and closure.....	27
4.2.3 Door/gate status indications.....	27
4.2.4 Synchronization of vehicle and platform doors/gates.....	27
4.2.5 Audible and visible alerts	28
4.2.6 Integrity of control systems	28
4.2.7 Local control of the doors/gates in a platform barrier system.....	28
4.2.8 Electrical safety - earthing and bonding arrangements.....	29
5 Operational requirements	32
5.1 General operational requirements	32
5.1.1 Maintainability	32
5.1.2 Persons with reduced mobility.....	32
5.1.3 Gauging.....	32
5.1.4 Tripping hazard at vehicle and platform barrier doorways.....	33
5.2 Requirements for mechanical gap fillers operating in conjunction with platform barrier systems	34
6 Testing and verification of platform barrier systems	34
6.1 General	34
6.2 Type tests	35
6.3 Routine tests	35
6.4 Functional testing of the platform barrier system	35
6.5 Integration testing of the barriers with other railway subsystems	35

Annex A (normative) Testing plan.....	36
Annex B (informative) Guidance on structural design	39
Annex C (informative) Principles for earthing and bonding strategies.....	43
C.1 Factors for consideration	43
C.2 Principle A — The platform barrier system is bonded to station earth	43
C.3 Principle B — The platform barrier system is insulated from station earth and also from the traction current return rail (i.e. floating).....	44
C.4 Principle C — The barrier system is bonded to the traction return rail and insulated from station earth	44
C.5 Principle D — The platform barrier is constructed of non-conductive materials.....	46
Annex D (informative) System integration	48
D.1 Purpose	48
D.2 Responsibility	48
D.3 Overall targets	48
D.4 Specific considerations.....	48
D.4.1 Integration with railway control systems and with train operation	48
D.4.2 Control system - conditions for opening/closing of doors/gates.....	48
D.4.3 Accuracy of stopping	50
D.4.4 Alignment.....	50
D.4.5 Visibility of platform-train interface.....	50
D.4.6 Other physical considerations.....	51
Annex E (informative) Guidance on aerodynamic loading from trains.....	52
E.1 Introduction	52
E.2 Technical basis and method	52
E.3 Calculation of equivalent pressures	52
Bibliography	54

prEN 17168:2019 (E)

European foreword

This document (prEN 17168:2019) has been prepared by Technical Committee CEN/TC 256 “Railway Applications”, the secretariat of which is held by DIN.

This document is currently submitted to the CEN Enquiry.

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN 17168:2020

<https://standards.iteh.ai/catalog/standards/sist/1339df99-09e9-41b2-bc79-f95d2a0eb203/osist-pren-17168-2020>

Introduction

Platform barrier systems provide a movable barrier between trains and other guided transit vehicles, and passengers waiting at stations and boarding points.

Platform barrier systems are used increasingly on metro and other rail networks to ensure the safety of passengers on the station platform who are waiting to board vehicles. Such systems are also used on “people-mover” guided systems for short-distance transits, for example at airports. Their use is recommended by EN 62267 for any fully automated transit system.

In particular platform barrier systems can be used to control the risk of:

- incursion by passengers or other persons on the railway track (deliberate or accidental); and
- contact between passengers and moving vehicles.

These risks can be especially significant where there is the possibility of overcrowding on station platforms at busy locations. Barriers may increase the safely useable space in the station for passengers waiting and circulating on the platforms.

Platform barrier systems integrate the operation of the platform barrier doors and gates with opening and closing of train doors and also assist in the management of station operations, to safely permit higher speeds for trains entering and exiting the stations.

Barrier installations can also be part of a continuous partition between the running tracks and the station areas for the purposes of:

- fire safety (including smoke management);
- tunnel and station ventilation (including reduction of the piston effect);
- trackside noise reduction; and
- passenger comfort at climate-controlled stations

Additionally, the terminology used in connection with platform barrier systems, in particular to improve the specification and understanding of safety requirements, should be standardized.

prEN 17168:2019 (E)

1 Scope

This document specifies requirements for the design, construction and operation of platform barrier systems positioned at the edge of a station platform immediately adjacent to the rail or other guided vehicles in stations and boarding points for passenger services. This document includes:

- requirements for the fixed structure and fixed parts along the platform;
- physical requirements for the movable doors and gates normally used by passengers;
- requirements for emergency doors;
- requirements for driver access doors;
- requirements for platform extremity doors; and
- requirements for the management of safety risks that are particular to barrier systems.

This document also gives requirements for the integration of barriers within the overall rail system, including:

- synchronization of vehicle and platform barrier doors or gates;
- audible and visible alerts;
- integrity of control systems;
- testing of the barrier installation;
- operational performance; and
- requirements relating to other interfacing sub-systems, notably signalling and vehicles.

For barrier systems set back from the platform edge, which are used to control access to trains or for crowd management, relevant sections of the document can be used as guidance.

This document applies to all persons involved in the implementation and system integration of a platform barrier system, including infrastructure owners, designers, installers and operators.

This document does not cover barrier systems using bars, ropes, etc. or which operate in a vertical direction.

This document applies to light rail services, e.g. metro and tramway systems and heavy rail services as requested by a project specification. It applies to small systems, working in conjunction with a single vehicle, or with larger systems working with a complete train.

This document applies to platform barrier systems used at sub-surface stations, enclosed surface stations (e.g. those enclosed for the purposes of providing an air-conditioned environment for waiting passengers), and those fully in the open-air.

This document does not cover normative requirements relating to fire performance or fire requirements arising from use of platform barrier systems as fire barriers.

ITeH STANDARD PREVIEW
(standards.iteh.ai)

oSIST prEN 17168:2020
<https://standards.iteh.ai/catalog/standards/sist/1339df99-09e9-41b2-bc79-f95d2a0eb203/osist-pren-17168-2020>

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1090-2, *Execution of steel structures and aluminium structures - Part 2: Technical requirements for steel structures*

EN 1090-3, *Execution of steel structures and aluminium structures - Part 3: Technical requirements for aluminium structures*

EN 1125, *Building hardware - Panic exit devices operated by a horizontal bar, for use on escape routes - Requirements and test methods*

EN 1990:2002, *Eurocode - Basis of structural design*

EN 1991-1-1:2002, *Eurocode 1: Actions on structures - Part 1-1: General actions - Densities, self-weight, imposed loads for buildings*

EN 1991-1-4, *Eurocode 1: Actions on structures - Part 1-4: General actions - Wind actions*

EN 1993-1-1, *Eurocode 3: Design of steel structures - Part 1-1: General rules and rules for buildings*

EN 1993-1-9, *Eurocode 3: Design of steel structures - Part 1-9: Fatigue*

EN 1998-1, *Eurocode 8: Design of structures for earthquake resistance - Part 1: General rules, seismic actions and rules for buildings*

EN 1999-1-1, *Eurocode 9: Design of aluminium structures - Part 1-1: General structural rules*

EN 1999-1-3, *Eurocode 9: Design of aluminium structures - Part 1-3: Structures susceptible to fatigue*

EN ISO 12543-1, *Glass in building - Laminated glass and laminated safety glass - Part 1: Definitions and description of component parts (ISO 12543-1:2011)*

EN 12600, *Glass in building - Pendulum test - Impact test method and classification for flat glass*

EN 13272, *Railway applications - Electrical lighting for rolling stock in public transport systems*

EN 13501-1, *Fire classification of construction products and building elements - Part 1: Classification using data from reaction to fire tests*

EN 13501-2, *Fire classification of construction products and building elements - Part 2: Classification using data from fire resistance tests, excluding ventilation services*

EN 13501-6, *Fire classification of construction products and building elements - Part 6: Classification using data from reaction to fire tests on power, control and communication cables*

EN 14752:2015, *Railway applications - Body side entrance systems for rolling stock*

EN 16584-1, *Railway applications - Design for PRM use - General requirements - Part 1: Contrast*

prEN 17168:2019 (E)

EN 16584-3, *Railway applications - Design for PRM use - General requirements - Part 3: Optical and friction characteristics*

EN 50121-4, *Railway applications - Electromagnetic compatibility - Part 4: Emission and immunity of the signalling and telecommunications apparatus*

EN 50122-1:2011, *Railway applications - Fixed installations - Electrical safety, earthing and the return circuit - Part 1: Protective provisions against electric shock*

EN 50122-2, *Railway applications - Fixed installations - Electrical safety, earthing and the return circuit - Part 2: Provisions against the effects of stray currents caused by d.c. traction systems*

EN 50126-1:2000, *Railway applications — The specification and demonstration of Reliability, Availability, Maintainability and Safety (RAMS) — Part 1: Basic requirements and generic process*

EN 50128, *Railway applications - Communication, signalling and processing systems - Software for railway control and protection systems*

EN 50129, *Railway applications — Communication, signalling and processing systems — Safety related electronic systems for signalling*

EN 50162, *Protection against corrosion by stray current from direct current systems*

HD 60364-4-41, *Low-voltage electrical installations — Part 4-41: Protection for safety — Protection against electric shock*

(standards.iteh.ai)

HD 60364-5-54, *Low-voltage electrical installations - Part 5-54: Selection and erection of electrical equipment - Earthing arrangements and protective conductors*

HD 60364-6, *Low-voltage electrical installations - Part 6: Verification*

EN 60529, *Degrees of protection provided by enclosures (IP Code)*

EN 61000-6-2, *Electromagnetic compatibility (EMC) - Part 6-2: Generic standards - Immunity for industrial environments*

EN 61000-6-4, *Electromagnetic compatibility (EMC) - Part 6-4: Generic standards - Emission standard for industrial environments*

EN 61140, *Protection against electric shock - Common aspects for installation and equipment*

EN 62061, *Safety of machinery - Functional safety of safety-related electrical, electronic and programmable electronic control systems*

EN 62290-2:2014, *Railway applications - Urban guided transport management and command/control systems - Part 2: Functional requirements specification*

EN 62305-1, *Protection against lightning - Part 1: General principles*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

correct alignment

correct position of the doors of the vehicle relative to the corresponding platform barrier doors/gates, to permit safe and efficient transfer of passengers between vehicles and platform

3.2

doorway

section of a platform barrier through which passengers can board or alight from vehicles when platform doors or gates are open

3.3

driver access door/gate

openable panel in a platform door or gate system designed to align with the driving cab door of a train stopped at the station or boarding point

Note 1 to entry: Such panels (if provided) can open with a hinged or sliding action.

3.4

emergency egress device

operating element for manual opening from the trackside, in case of emergency, of any type of platform door or gate

3.5

emergency egress door/gate

panel in a platform door or gate system which can be opened in an emergency, or if the vehicle(s) are not in correct alignment with the platform doors/gates

Note 1 to entry: Emergency egress doors/gates can be of any design - hinged/sliding/push-out, etc.

3.6

entrapment

trapping of a person between the vehicle bodyside and the platform barrier after the vehicle and platform doors or gates have been closed

3.7

façade

complete framework and panels (fixed and moving) of the platform barrier

3.8

finished floor level

level of the platform floor when all surface finishes (e.g. tiles, screed, threshold) have been applied

prEN 17168:2019 (E)

3.9

glazing

glass or equivalent transparent material fixed in frames as part of a platform barrier system

3.10

leading edge

vertical edge of a door or gate, leading during closing movement

3.11

local control panel

centralized control panel adjacent to or in the vicinity of the platform barrier which enables opening and closing of a complete set of doors/gates in a barrier system by a member of operations staff

3.12

mechanical gap filler

movable device mounted at the platform edge, at a platform door or gate, fully automatic and actuated/controlled in conjunction with the barrier system opening/closing sequences

Note 1 to entry: The purpose of a mechanical gap filler is to reduce the horizontal stepping distance to a vehicle to acceptable limits, or to facilitate access to a vehicle by persons with reduced mobility. Its structural integrity does not rely on support from the vehicle.

3.13

operations staff

persons including train crew and station personnel authorized to perform tasks concerning train operation or direct service to passengers

3.14

passive gap filler

strips, of frangible or partly flexible material attached to the barrier doorway threshold such that the clearance between a moving vehicle and the threshold can be safely reduced below that normally specified for gauge clearance between infrastructure and vehicles

3.15

person with reduced mobility (PRM)

person whose mobility when using transport is reduced due to any physical disability (sensory or locomotory, permanent or temporary), intellectual disability or impairment, or any other cause of disability, or as a result of age, and whose situation needs appropriate attention and adaptation to his or her particular needs of the service made available to all passengers

[SOURCE: EU Directive 2007/1371/EC]

3.16

platform

section of pathway, alongside rail tracks at a railway, metro or other guided transit system station at which passengers can board or alight from vehicles

3.17

platform barrier system (PBS)

system providing a protective barrier between vehicle and platform, having power operated movable panels with associated drive and control equipment, such panels moving horizontally and parallel with edge of the platform, allowing passenger transfer through the barrier when a train is positioned at the platform

3.18**platform door**

movable panel or panels and forming part of a platform door system through which passengers normally access and egress vehicles

3.19**platform door system**

platform barrier system in which the movable panels are carried on a portal structure having headers or lintels above the moving panels, carrying all or part of their weight

Note 1 to entry: Such a system can form part of a structure completely enclosing the platform area and separating it entirely from the track on which vehicles move.

3.20**platform extremity door/gate**

panel at the extremity of a platform door or gate system (usually, but not necessarily, at right angles to the main structure) to allow access by authorized persons to the track, or to a tunnel walkway beyond the station, or as emergency egress for persons evacuating from the track area

Note 1 to entry: Such panels can open with a hinged or sliding action.

3.21**platform gate**

movable panel or panels forming part of a platform gate system through which passengers normally access and egress vehicles

3.22**platform gate system**

platform barrier system in which the movable panels are supported from the bottom, or by cantilever arrangement at an intermediate height on the barrier

3.23**routine test**

conformity test made on each individual item of equipment during or after manufacture

3.24**station**

unit comprising buildings and structures containing technical equipment, loading or unloading areas or platforms, and any associated areas for reception and shelter

3.25**synchronization (of doors)**

co-ordinated movement of vehicle doors with platform doors or gates

3.26**system integration**

process of assuring that the design, installation and operation of the barrier system is consistent with the overall safety and operational targets of the complete rail system, of which the barrier system is part

Note 1 to entry: The activity of system integration (particularly in the context of this standard) is elaborated on in Annex D (informative).

prEN 17168:2019 (E)

3.27

train

combination of rolling stock coupled together

[SOURCE: IEC 60050-811: 2017]

3.28

type test

conformity test made of one or more system and its components representative of the production to prove that the design meets the standard and the relevant specifications

3.29

user population

range of persons (including operations staff) expected to use a platform barrier system, defined in terms of their physical characteristics

4 System design requirements

4.1 Physical and structural requirements of the platform barrier

4.1.1 General structural requirements

4.1.1.1 Platform barrier systems form a safety barrier separating customers/passengers from moving trains until it is safe to grant access. As such they shall be designed to resist crowd loading. Platform barriers are also subject to aerodynamic loads induced by trains passing the structure. Platform barrier systems installed in open sections shall also resist wind loading. In addition, platform barrier systems might be subject to pressures generated by tunnel ventilation systems and might be required to resist earthquakes. These separate actions shall be combined in accordance with Structural Eurocodes referenced in this standard. <https://standards.iteh.ai/catalog/standards/sist/1339df99-09e9-41b2-bc79-f95d2a0eb203/osist-pren-17168-2020>

4.1.1.2 Tunnel ventilation systems are normally associated with platform barrier systems that completely enclose the platform area, separating it from the track on which vehicles move. Detailed modelling/simulation shall be undertaken during system integration and shall consider all operating and degraded modes of operation of the ventilation system to determine their effect on the platform door system and how they combine with the aerodynamic actions from trains. In particular, pressures generated by operation of ventilation systems for smoke extraction or fire management shall not inhibit operation of emergency doors in accordance with 4.1.7.

4.1.1.3 Structural design shall take into account the requirements arising from the physical interface with trains intended to operate in conjunction with the barrier system, in particular regarding entrapment (4.1.10) and gauging (5.1.3).

4.1.1.4 General construction of platform barriers shall be in accordance with the Structural Eurocode series. EN 1991-1-1 covers general actions and imposed loads. Imposed loads are defined by categories of use in Clause 6 of EN 1991-1-1. This series of standards explicitly includes barriers on railway platforms, in particular Category C5 which gives requirements for “Areas susceptible to large crowds, e.g. in building for public events like concert hall, sports halls including stands, terraces and access areas and railway platforms.”

4.1.1.5 The Structural Eurocode series of standards mandate the use of Ultimate and Serviceability Limit States to ensure the safety of a structure in extreme conditions (e.g. storm-force winds for open-air systems) and combinations of loads; however, normal operation of the platform doors/gates might not be practicable under all such limit states. At least one Operational Limit State should be specified to reflect normal operation of the barrier system. Further guidance is given in Annex B.

4.1.1.6 Deflection of the platform barrier system towards the track under any loading conditions envisaged in this standard shall not exceed the limits defined by the gauging strategy for the platform barrier system as described in 5.1.3. Plastic deformation may be permitted under Ultimate Limit State as defined by the Eurocodes referenced in Annex B, subject to compliance with the gauging strategy.

4.1.1.7 Infill panels (i.e. glazing, or sheets of other materials, which separate the platform area from the running tracks and are secured to the main structural framework of the barrier system) shall sustain the applied loads.

It is recommended that, in addition, deflection of an infill panel that is structurally safe should not alarm station users through large visible deformations relative to the frame in which the panel is mounted, when subject to normal service conditions. Therefore, for serviceability considerations, the limiting condition for deflection should be that the total horizontal displacement of the infill panel relative to the frame at any point from its original unloaded position does not exceed the deflection limits determined from the relevant structural design code (where applicable) for the material used, or 25 mm, whichever is the smaller.

4.1.1.8 This standard covers the requirements for the platform barrier system. It does not specify requirements for the platforms, or other foundations and structures to which the platform barrier system is secured. Design and construction of platforms, foundations or other structures are covered by other appropriate structural Eurocode documents. However, the load cases considered in such designs shall be consistent with those adopted for the design of the platform barrier system.

4.1.1.9 The calculations used in structural design shall be validated by load testing of a representative structure.

4.1.2 Structural design principles

4.1.2.1 Designs shall be in accordance with the requirements of EN 1990.

4.1.2.2 Where steel is used, structural design shall be in accordance with EN 1993-1-1.

4.1.2.3 Where aluminium is used, structural design shall be in accordance with EN 1999-1-1.

4.1.2.4 In the event that structural materials other than steel or aluminium are used, performance of the design shall be demonstrated to be equivalent with the performance requirements of Eurocodes category C5 as defined in 4.1.1.4.

4.1.2.5 Where required by the relevant National Annex to EN 1998-1 regarding design of structures for earthquake resistance, the provisions of EN 1998-1 shall be applied in addition to the provisions of the other relevant Eurocodes.

4.1.2.6 Where glass is used the thickness of the glazing material may be calculated using validated mathematical analysis. Alternatively, thickness may be determined using empirical national codes.

Use of empirical codes can result in conservative design and increased weight. Calculated methods are recommended where possible.

4.1.3 Structural loading conditions

4.1.3.1 Crowd loading

4.1.3.1.1 Design for horizontal crowd loading shall be in accordance with EN 1991-1-1:2002, 6.4. The characteristic value for the line load q_k as defined in the standard shall be selected from the range for Category C5 from Table 6.12.