

## SLOVENSKI STANDARD oSIST prEN ISO 6501:2020

01-februar-2020

Feronikelj - Specifikacija in zahteve pri dobavi (ISO/DIS 6501:2019)

Ferronickel - Specification and delivery requirements (ISO/DIS 6501:2019)

Ferronickel - Spezifikation und Lieferbedingungen (ISO/DIS 6501:2019)

Ferro-nickel - Spécifications et conditions de livraison (ISO/DIS 6501:2019)

Ta slovenski standard je istovetenz: prENJSO 6501

ICS:

77.100 Železove zlitine Ferroalloys

oSIST prEN ISO 6501:2020 en,fr,de

oSIST prEN ISO 6501:2020

oSIST prEN ISO 6501:2020

# DRAFT INTERNATIONAL STANDARD ISO/DIS 6501

ISO/TC **155** Secretariat: **AFNOR** 

Voting begins on: Voting terminates on:

2019-12-10 2020-03-03

## Ferronickel — Specification and delivery requirements

Ferro-nickel — Spécifications et conditions de livraison

ICS: 77.100

INTO STATION AND PRELIMATE TO STATE OF THE S

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.

## ISO/CEN PARALLEL PROCESSING



Reference number ISO/DIS 6501:2019(E)

© ISO 2019





#### COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Co	Page	
Fore	eword	iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	
4	Information for ordering	
5	Requirements 5.1 Chemical composition 5.2 Form of delivery and formation of lots 5.2.1 General 5.2.2 Ferronickel in ingots 5.2.3 Ferronickel in pieces 5.2.4 Ferronickel in the form of shot 5.3 Contamination	
6	Control  6.1 General  6.2 Sampling for analysis  6.3 Analysis  6.3.1 Ferronickel furnished with analysis certificate  6.3.2 Ferronickel settled with exchange analysis  6.4 Procedures in case of dispute  6.4.1 Contradictory procedure  6.4.2 Arbitration procedure	
7 Ann	6.3.2 Ferronickel settled with exchange analysis 6.4 Procedures in case of dispute 6.4.1 Contradictory procedure 6.4.2 Arbitration procedure  Dispatch and storage  nex A (informative) Examples of ferronickel classification	5

#### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by Technical Committee JSO/TC 155, Nickel and nickel alloys.

This second edition cancels and replaces the first edition (ISO 6501:1988), which has been technically revised.

The main changes compared to the previous edition are as follows:

- Format as per ISO Directives;
- Reduction or elimination of expressions such as "agreement between parties" on ISO 6501 as recommended by ISO (If a standard or part of it is to be agreed, there is no need for that international standard);
- Updated Ferronickel delivery market requirements;
- FeNi classification according chemical composition and combination of Ni content (<u>table 1</u>) and impurities (<u>table 2</u>)
- Cross references

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

.

## Ferronickel — Specification and delivery requirements

#### 1 Scope

This document specifies the technical delivery requirements for the various forms of ferronickel (ingots, pieces and shot) usually supplied for steel making and foundry use.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8049, Ferronickel shot — Sampling for analysis

ISO 8050, Ferronickel ingots or pieces — Sampling for analysis

ISO 14284, Steel and iron — Sampling and preparation of samples for the determination of chemical composition

ISO 6352, Ferronickel — Determination of nickel content — Dimethylglyoxime gravimetric method

#### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>
- IEC Electropedia: available at <a href="http://www.electropedia.org/">http://www.electropedia.org/</a>

#### 3.1

#### ferronickel

a master alloy of iron and nickel having a nickel content equal to or greater than 15 % (m/m), and less than 80 % (m/m), obtained from oxide ores or other nickel-bearing materials

#### 3.2

K

number that represents the lowest nickel content that will be part of the lot to be delivered

#### 3.3

#### splitting limit

maximum acceptable difference between analytical results of nickel or other element agreed by two parties (buyer and seller)

#### 3.4

#### lot

discrete and defined quantity of ferronickel ingots, pieces or shots answering to the same quality specification (chemical composition and physical characteristics)

#### 4 Information for ordering

Orders for ferronickel shall include the following information:

- a) Quantity;
- b) Chemical composition, according to the designations in <a href="Table 1">Table 1</a> and <a href="Table 2">Table 2</a>;
- c) Form of delivery, according to 5.2;
- d) Delivery requirements;
- e) Size distribution;
- f) Requirements for analysis report, packing, etc., as appropriate.
- g) Transportation and storage requirements.

#### 5 Requirements

#### 5.1 Chemical composition

**5.1.1** The Chemical compositions of the various types of ferronickel are specified in <u>Table 1</u> and <u>Table 2</u>.

**5.1.2** In <u>Table 1</u>, only the Nickel content is given.

Table 1 — Ni content in ferronickel

	Chemical composition, % (m/m)						
Designation	Ni Ni	Other elements					
Designation	From	Up to					
	(incl.)	(not incl.)					
FE Ni 20	15 and adha	25					
FE Ni 30	25	35	See <u>Table 2</u>				
FE Ni 40	35	45					
FE Ni 50	45	60					
FE Ni 70	60	80					

**5.1.3** In <u>Table 2</u>, the main constituent elements and usual impurities are given. Other elements may be decided between the parties.

If the purchaser requires closer ranges for the main element contents and/or different limits for specified elements, and/or limits for non-specified elements, and/or if the contents of elements such as arsenic, bismuth, lead, antimony and tin each exceed 0.010 % (m/m), this shall be indicated and agreed upon between supplier and purchaser.

Table 2 –	- Chemical composition of main constituent elements of ferronickel and usual impurities of ferronickel

	Chemical composition, % (m/m)											
Designation	С		Si		P		S		Cr	Со	Cu	Other ele- ments
Designation	From	Up to	From	Up to	From	Up to	From	Up to				
	(incl.)	(not incl.)	(incl.)	(not incl.)	(incl.)	(not incl.)	(incl.)	(not incl.)	Max.	1)	2)	See <u>5.1.3</u>
Low	-	0,030	-	0,20	-	0,010	-	0,030	0,10			
Medium	0,030	1,000	0,20	1,00	0,010	0,020	0,030	0,100	0,50			
High	1,000	2,500	1,00	4,00	0,020	0,030	0,100	0,400	2,0			

<sup>1)</sup>  $\frac{\text{Co}}{Ni} = \frac{1}{20} \text{to} \frac{1}{40}$ , for information only

- **5.1.4** The designation of Ferronickel product is given with the combination of elements of <u>Table 1</u> and <u>Table 2</u>. Example: FE Ni 30 HC MP MS HSi, where L = Low, M = Medium and H = High. Other examples of combination of <u>Table 1</u> and <u>Table 2</u> are given in Annex A.
- **5.1.5** The chemical compositions given in <u>Table 1</u> and <u>Table 2</u> are subject to the precision of the methods of sampling and analysis for ferronickel

### 5.2 Form of delivery and formation of lots

#### 5.2.1 General

Ferronickel may be delivered as agreed between the supplier and the purchaser in various forms, e.g. ingots, pieces or shot. The delivered lots, except by special agreement, shall have a minimum tonnage of 5 t.

#### 5.2.2 Ferronickel in ingots

Ingots may be supplied notched or unnotched. Their maximum mass is 100 kg; their thickness may be within a range of 30 to 150 mm and their length shall not exceed 1100 mm.

Lots may be formed in two different ways:

- from material stocked individually from each tapping operation;
- by blending several heats; in this case, except by special agreement, heats shall be selected in a nickel content range from K to (K + 1) %, K being a whole number.

#### 5.2.3 Ferronickel in pieces

Pieces are either cast or cut from ingots. A lot is formed from only one of these two categories of pieces. The maximum dimension is between 25 and 100 mm. Within a lot, the sizes of pieces shall be uniform.

Lots may be formed in two different ways;

- from material stocked individually from each tapping operation;
- by blending several heats; in this case, except by special agreement, heats shall be selected in a nickel content range from K to (K + 1) %, K being a whole number.

<sup>2)</sup> Cu max 0,20%