



# SLOVENSKI STANDARD SIST EN IEC 61753-1:2019/AC:2019

01-september-2019

---

**Optični spojni elementi in pasivne komponente - Tehnični standard - 1. del:  
Splošno in smernice - Popravek AC (IEC 61753-1:2018/COR1:2019)**

Fibre optic interconnecting devices and passive components - Performance standard -  
Part 1: General and guidance (IEC 61753-1:2018/COR1:2019)

## iTeh STANDARD PREVIEW

Dispositifs d'interconnexion et composants passifs fibroniques - Norme de performance -  
Partie 1: Généralités et recommandations (IEC 61753-1:2018/COR1:2019)

[SIST EN IEC 61753-1:2019/AC:2019](https://standards.iteh.ai/catalog/standards/sist/en-iec-61753-1-2019-ac-2019)

**Ta slovenski standard je istoveten z: EN IEC 61753-1:2018/AC:2019-06**

<https://standards.iteh.ai/catalog/standards/sist/en-iec-61753-1-2019-ac-2019>

---

**ICS:**

33.180.20	Povezovalne naprave za optična vlakna	Fibre optic interconnecting devices
-----------	---------------------------------------	-------------------------------------

**SIST EN IEC 61753-1:2019/AC:2019**      en

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN IEC 61753-1:2019/AC:2019](https://standards.iteh.ai/catalog/standards/sist/3a852c0b-0628-4c21-931a-2197f5993324/sist-en-iec-61753-1-2019-ac-2019)

<https://standards.iteh.ai/catalog/standards/sist/3a852c0b-0628-4c21-931a-2197f5993324/sist-en-iec-61753-1-2019-ac-2019>

EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM

**EN IEC 61753-  
1:2018/AC:2019-06**

June 2019

---

ICS 33.180.20

English Version

**Fibre optic interconnecting devices and passive components -  
Performance standard - Part 1: General and guidance  
(IEC 61753-1:2018/COR1:2019)**

Dispositifs d'interconnexion et composants passifs  
fibroniques - Norme de performance - Partie 1: Généralités  
et recommandations  
(IEC 61753-1:2018/COR1:2019)

To be completed  
(IEC 61753-1:2018/COR1:2019)

This corrigendum becomes effective on 21 June 2019 for incorporation in the English language version of the EN.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN IEC 61753-1:2019/AC:2019](https://standards.iteh.ai/catalog/standards/sist/3a852c0b-0628-4c21-931a-2197f5993324/sist-en-iec-61753-1-2019-ac-2019)  
<https://standards.iteh.ai/catalog/standards/sist/3a852c0b-0628-4c21-931a-2197f5993324/sist-en-iec-61753-1-2019-ac-2019>



European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels**

### Endorsement notice

The text of the corrigendum IEC 61753-1:2018/COR1:2019 was approved by CENELEC as EN IEC 61753-1:2018/AC:2019-06 without any modification.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN IEC 61753-1:2019/AC:2019](https://standards.iteh.ai/catalog/standards/sist/3a852c0b-0628-4c21-931a-2197f5993324/sist-en-iec-61753-1-2019-ac-2019)

<https://standards.iteh.ai/catalog/standards/sist/3a852c0b-0628-4c21-931a-2197f5993324/sist-en-iec-61753-1-2019-ac-2019>

INTERNATIONAL ELECTROTECHNICAL COMMISSION  
COMMISSION ÉLECTROTECHNIQUE INTERNATIONALEIEC 61753-1  
Edition 2.0 2018-08IEC 61753-1  
Édition 2.0 2018-08FIBRE OPTIC INTERCONNECTING DEVICES AND  
PASSIVE COMPONENTS – PERFORMANCE  
STANDARDDISPOSITIFS D'INTERCONNEXION ET  
COMPOSANTS PASSIFS FIBRONIQUES – NORME  
DE PERFORMANCE

Part 1: General and guidance

Partie 1: Généralités et recommandations

## CORRIGENDUM 1

Corrections to the French version appear after the English text.

Les corrections à la version française sont données après le texte anglais.

iTech STANDARD PREVIEW  
(standards.iteh.ai)[SIST EN IEC 61753-1:2019/AC:2019](https://standards.iteh.ai/catalog/standards/sist/en-iec-61753-1-2019-ac-2019)**Table A.15 – Hardened optical connectors and closures – Category S – Outdoor subterranean environment**Replace the existing row starting by "Change of temperature<sup>b</sup>" by the following new row:

Change of temperature <sup>b</sup> IEC 61300-2-22	Temperature range: –30 °C to +60 °C Duration at extreme temperatures: 4 h Temperature change rate: 1 °C/min 12 cycles	S,O,V	S,O,V
--	--	-------	-------

**Table A.27 – Category A, G and S single mode sealed closures**

Replace the existing title by the following new title:

**Table A.27 – Category C, A, G and S single mode sealed closures**