
**Acoustics — Laboratory tests on
noise emission from appliances and
equipment used in water supply
installations —**

Part 3:

**Mounting and operating conditions for
in-line valves and appliances**
*iTeh STANDARD PREVIEW
(standards.iteh.ai)*

*Acoustique — Mesurage en laboratoire du bruit émis par les
robinetteries et les équipements hydrauliques utilisés dans les
installations de distribution d'eau —*

*Partie 3: Conditions de montage et de fonctionnement des
robinetteries et des équipements hydrauliques en ligne*



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 3822-3:2018

<https://standards.iteh.ai/catalog/standards/sist/a4d679c0-8ec1-412a-a1ff-50e597dae2ee/iso-3822-3-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Mounting	1
4.1 General.....	1
4.1.1 General.....	1
4.1.2 Installation.....	2
4.1.3 Connection.....	2
4.2 Fitting to the test pipe.....	2
4.3 Mounting of in-line valves and appliances with screwed conditions.....	2
4.4 Mounting of in-line valves and appliances with provision for soldering in copper connecting pipes.....	2
4.5 Mounting of in-line valves and appliances fitted with copper connecting pipes.....	2
4.6 Mounting of in-line valves or appliances with two inlets.....	2
4.7 Discharge connection.....	3
5 Test procedure	3
5.1 General test conditions.....	3
5.1.1 General.....	3
5.1.2 Water temperature.....	3
5.1.3 Outlets.....	3
5.1.4 Flow regulating and discharge system.....	3
5.1.5 Test pressures.....	3
5.1.6 Water flow rate.....	3
5.2 Procedure for stop valves.....	4
5.3 Procedure for control valves.....	4
5.4 Procedure for valves and appliances operated by water flow.....	4
5.5 Procedure for automatic in-line valves or appliances operated by water pressure.....	5
5.6 Procedure for automatic in-line valves and appliances operated by water temperature.....	5
5.7 Procedure for “safety groups”.....	5
5.7.1 Safety groups without a pressure reducing valve.....	6
5.7.2 Safety groups with a pressure reducing valve.....	6
6 Test report	6
Annex A (informative) Example of low noise flow resistance	7
Bibliography	8

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html. (standards.iteh.ai)

This document was prepared by ISO/TC 43, *Acoustics*, Subcommittee SC 2, *Building acoustics*.

This third edition cancels and replaces the first edition (ISO 3822-3:1997), which has been technically revised. It also incorporates the Amendment ISO 3822-3:1997/Amendment 1:2009.

A list of all the parts in the ISO 3822 series can be found on the ISO website.

Introduction

The method of measurement for laboratory tests on noise emission from appliances and equipment used in water supply installations is specified in ISO 3822-1.

This document gives detailed descriptions for mounting and operating in-line valves and appliances, which control the flow, pressure or temperature of the water in water supply installations in such laboratory tests.

NOTE An in-line valve is one through which water flows and which is permanently installed in a system of rigid pipework upstream of the outlet fitting.

These in-line valves and appliances are for use with cold and/or hot water in buildings (stop valves, check valves, in-line thermostatic and mechanical mixing valves, domestic water meters, valve combinations for installation in water heater feed pipes, pressure reducing valves, flow restrictors, water governors, service valves, in-line temperature and pressure relief valves, etc.).

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 3822-3:2018](https://standards.iteh.ai/catalog/standards/sist/a4d679c0-8ec1-412a-a1ff-50e597dae2ee/iso-3822-3-2018)

<https://standards.iteh.ai/catalog/standards/sist/a4d679c0-8ec1-412a-a1ff-50e597dae2ee/iso-3822-3-2018>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 3822-3:2018

<https://standards.iteh.ai/catalog/standards/sist/a4d679c0-8ec1-412a-a1ff-50e597dae2ee/iso-3822-3-2018>

Acoustics — Laboratory tests on noise emission from appliances and equipment used in water supply installations —

Part 3:

Mounting and operating conditions for in-line valves and appliances

1 Scope

This document specifies the mounting and operating conditions to be used for in-line valves and appliances which control the flow, pressure or temperature of the water in water supply installations, when measuring noise emission resulting from water flow.

It is applicable to in-line valves and appliances of maximum nominal size DN 32 and to systems in which the maximum water flow rate does not exceed 1,6 l/s.

NOTE See ISO 6708; DN is the symbol for “nominal size”. The number of the nominal size is loosely related to the inside diameter (in millimetres) of the in-line valves and appliances.

The procedures described are for general use for all types of in-line valves of conventional design.

2 Normative references

ISO 3822-3:2018

<https://standards.iteh.ai/catalog/standards/sist/a4d679c0-8ec1-412a-a1ff-50e597dae2ee/iso-3822-3-2018>

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 49, *Malleable cast iron fittings threaded to ISO 7-1*

ISO 3822-1, *Acoustics — Laboratory tests on noise emission from appliances and equipment used in water supply installations — Part 1: Method of measurement*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Mounting

4.1 General

4.1.1 General

In-line valves shall be inserted between two straight pieces of pipe of the type and sizes appropriate to the end-connections of the valve. Each straight piece of pipe shall be at least ten diameters long.

4.1.2 Installation

The in-line valves or appliance shall be installed in its normal working position, which is generally vertical or horizontal.

The test shall be carried out for the noisier of the two positions, which shall be determined by a short preliminary test.

If the manufacturer specifies that the appliance may be installed in other positions, then the short preliminary test shall be carried out for these positions.

4.1.3 Connection

The in-line valves or appliance shall be connected to the test pipe in accordance with the appropriate description in 4.3 to 4.7. The connection shall be made so that no air will be trapped therein.

In-line valves or appliances fitted with connections not covered by 4.3 to 4.5 inclusive shall be connected to the test pipe and to the discharge system so as to provide a rigid and watertight connection in accordance with good practice and workmanship.

4.2 Fitting to the test pipe

The test pipe shall end with a galvanised (hot-dip zinc coated) union, taper seat size 1, U11 complying with ISO 49.

In-line valves and appliances, including connecting pipe (see 4.1) shall be connected to the union using if necessary a combination of galvanised (hot-dip zinc coated) fittings complying with ISO 49. Changes in direction shall be accomplished by means of long sweep bends size 1 only.

Reduction or enlargement of size shall only be made at the inlet connection of the connecting pipe. The combination of fittings used shall result in the appliance being in the normal position of use.

4.3 Mounting of in-line valves and appliances with screwed conditions

In-line valves and appliances with screwed connections for galvanised pipes (see 4.1) shall be connected to the test pipe as specified in 4.2.

4.4 Mounting of in-line valves and appliances with provision for soldering in copper connecting pipes

In-line valves and appliances with provision for soldering in copper connecting pipes shall have a piece of copper pipe of the appropriate diameter and at least ten diameters in length, though not more than 300 mm, soldered in each connection. This copper pipe shall be connected to the test pipe as specified in 4.2 and 4.5.

4.5 Mounting of in-line valves and appliances fitted with copper connecting pipes

In-line valves and appliances fitted with copper connecting pipes, which shall be extended, if necessary, to at least ten diameters in length, though not more than 300 mm, shall be connected to the test pipe, as specified in 4.2, using couplings made either by soldering a nipple on to the pipe and using a cap nut or by means of a compression fitting.

4.6 Mounting of in-line valves or appliances with two inlets

In-line valves or appliances with two inlets shall be connected to the test pipe, as specified in 4.3, 4.4 or 4.5, by means of a twin outlet (see ISO 3822-1).

4.7 Discharge connection

The discharge system specified in [5.1.4](#) shall be connected to the outlet of the in-line valve or appliance by one of the methods specified in [4.3](#) to [4.5](#).

5 Test procedure

5.1 General test conditions

5.1.1 General

In-line valves and appliances shall be tested by the method specified in ISO 3822-1.

5.1.2 Water temperature

All in-line valves and appliances, including those which are normally operated with both hot and cold water, shall be tested with water at a temperature not exceeding 25 °C at all inlets.

5.1.3 Outlets

In-line valves and appliances with more than one outlet shall be tested for each outlet separately. The unused outlet(s) shall be closed by a drain cock for venting the valve or appliance.

5.1.4 Flow regulating and discharge system

In-line valves and appliances shall be tested with an adjustable low noise flow resistance connected downstream of the valve.

The noise produced by this flow resistance, including the intrinsic noise of the test arrangement, shall be lower than that of the appliance to be tested by at least 10 dB. An example of such a low noise flow resistance is given in [Annex A](#).

If the specified water flow rate cannot be obtained by adjusting the low noise flow resistance connected to the valve under test, the flow resistance shall be replaced by 1 m of smooth bore flexible hose of the same bore as the outlet of the valve.

5.1.5 Test pressures

The procedures specified in [5.2](#), [5.3](#), [5.4](#), [5.6](#) or [5.7](#) shall be carried out at a flow pressure of 0,3 MPa and then at a flow pressure of 0,5 MPa, without altering the specified setting of the adjustable flow resistance.

NOTE 1 MPa = 10 bar.

5.1.6 Water flow rate

The procedures specified in [5.2](#), [5.3](#), [5.4](#), [5.6](#) or [5.7](#) shall be carried out at a flow rate according to [Table 1](#).