
**Intelligent transport systems —
Localized communications —**

**Part 1:
Fast networking & transport layer
protocol (FNTTP)**

iTeh STANDARD PREVIEW
*Systemes intelligents de transport — Communications localisées —
Partie 1: Réseautique rapide et protocole de la couche transport*
(standards.iteh.ai)

ISO 29281-1:2018

<https://standards.iteh.ai/catalog/standards/sist/fe51645e-7985-4571-93e1-de17a3fb00b7/iso-29281-1-2018>



iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 29281-1:2018

<https://standards.iteh.ai/catalog/standards/sist/fe51645e-7985-4571-93e1-de17a3fb00b7/iso-29281-1-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Abbreviated terms	2
5 General requirements	2
6 Architectures	3
6.1 General context and purpose of FNTTP	3
6.2 FNTTP reference architecture	4
6.3 Communication principles	5
6.3.1 Transmission	5
6.3.2 Reception	5
6.3.3 FNTTP ITS-PNs	5
6.4 Implementation architectures	6
7 Protocol elements	6
7.1 Service access points	6
7.1.1 IN-SAP	6
7.1.2 NF-SAP	6
7.1.3 MN-SAP	6
7.1.4 SN-SAP	6
7.2 FNTTP NPDU	7
7.2.1 General	7
7.2.2 Subtype zero	7
7.2.3 Subtype one	7
7.2.4 Subtype two	7
7.2.5 N-Extensions	7
7.2.6 TPID-FS field	8
7.2.7 TPID-FS zero - information dissemination mode	8
7.2.8 TPID-FS one - general session mode	8
7.2.9 TPID-FS two - LPP support mode	8
7.2.10 T-Extensions	8
7.2.11 FNTTP body	9
7.3 Secure communications	9
7.4 Protocol management elements	9
7.4.1 ITS-AID look-up table	9
7.4.2 Service look-up table	9
7.4.3 Forwarding table	10
8 General protocol procedures	11
8.1 Port management	11
8.2 Maintenance of entries in forwarding tables	11
8.3 Notification of changes in forwarding tables	11
8.4 Initial settings of forwarding tables in ITS-S hosts	12
8.4.1 Allocation and deletion of a port	12
8.4.2 Assignment of communication interfaces	12
8.5 Initial settings of forwarding tables in ITS-S routers	12
8.6 CIP management	13
8.6.1 Purpose of CIPs and basic procedures	13
8.6.2 Forwarding of TX-CIPs from ITS-S host to ITS-S router	13
8.6.3 Forwarding of CIPs from ITS-S router to ITS-S host	14
9 Transmitting packets procedures	14

9.1	General	14
9.2	NF-SAP transmission request	16
9.3	Transport related TX procedures	17
9.3.1	TPID-FS zero TX procedure	17
9.3.2	TPID-FS one TX procedure	17
9.3.3	TPID-FS two TX procedure	17
9.3.4	T-Extensions TX procedures	17
9.4	Network related TX procedures	18
9.4.1	Subtype zero TX procedure	18
9.4.2	Subtype one TX procedure	18
9.4.3	Subtype two TX procedure	19
9.4.4	N-Extensions TX procedures	19
9.5	Send request procedure	20
9.6	Subtype one forwarding from router to host TX procedure	21
10	Receiving packets procedures	21
10.1	General	21
10.2	Checking of FNTF N-Header	23
10.3	Network related RX procedures	23
10.3.1	Subtype zero RX procedure	23
10.3.2	Subtype one RX procedure	23
10.3.3	Subtype two RX procedure	24
10.3.4	N-Extensions RX procedures	24
10.3.5	TPID-FS checking	25
10.3.6	ITS-SFS check and forwarding table update	25
10.4	Transport related RX procedures	26
10.4.1	TPID-FS zero RX procedure	26
10.4.2	TPID-FS one RX procedure	26
10.4.3	TPID-FS two RX procedure	26
10.4.4	T-Extension RX procedures	27
11	NF-SAP services	27
11.1	Overview	27
11.2	General NF-SAP services	27
11.3	NF-FNTP-PORT	28
11.3.1	NF-FNTP-PORT.request	28
11.3.2	NF-FNTP-PORT.confirm	29
11.4	NF-FNTP-COMM	29
11.4.1	NF-FNTP-COMM.request	29
11.4.2	NF-FNTP-COMM.confirm	30
11.4.3	NF-FNTP-COMM.indication	31
12	Dynamic data	32
13	Conformance	32
14	Test methods	32
Annex A (normative) ASN.1 modules		33
Annex B (informative) ASN.1 modules from ISO 16460		40
Annex C (normative) Protocol Implementation Conformance Statement proforma		42
Annex D (normative) Path and flow management support		53
Bibliography		54

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 204, *Intelligent transport systems*.

This second edition cancels and replaces the first edition (ISO 29281-1:2013), which has been technically revised. It also incorporates the Amendment ISO 29281-1:2013/Amd1:2017.

The main changes compared to the previous edition are as follows:

- a complete technical revision in support of the common message format specified in ISO TS 16460 that is harmonized with IEEE WAVE;
- ASN.1 has been aligned with latest developments in ISO TC 204;
- provisioning for path and flow management has been added;
- normative annex related to conformance testing, that contains the PICS proforma, has been added.

A list of all parts in the ISO 29281 series can be found on the ISO website.

Introduction

This document is part of a family of International Standards for communications in Intelligent Transport Systems (ITS) based on the ITS station and communication architecture specified in ISO 21217.

This document is Part 1 of a multipart standard which determines the "Intelligent Transport Systems" (ITS) localized communications.

The FAST Networking & Transport layer Protocol (FNTTP) is a protocol for localized communications. FNTTP comprises

- a basic port mapper protocol, used for localized communications between ITS station units (ITS-SUs),
 - networking related protocol features for
 - null-networking (single-hop communications),
 - N-hop forwarding,
 - ITS station-internal forwarding of packets between ITS station communication units (ITS-SCUs) with ITS-S host role and ITS-S router role,
- extendible with further features;
- transport related protocol features for
 - information dissemination with ITS-AID as destination address,
 - session support with ITS port numbers (ITS-PN) as source address and destination address,
 - LPP,

extendible with further features.

<https://standards.iteh.ai/catalog/standards/sist/fe51645e-7985-4571-93e1-de17a3fb00b7/iso-29281-1-2018>

The first version (2010) of FNTTP was validated in the CVIS project of the European Commission. Feedback from CVIS and other activities resulted in the second version (2013). This third version of FNTTP is the result of harmonization with the IEEE WAVE Short Message Protocol (WSMP); it is based on the common message format specified in ISO TS 16460.

Intelligent transport systems — Localized communications —

Part 1: Fast networking & transport layer protocol (FNTTP)

1 Scope

This document specifies the "Fast Networking & Transport Protocol" (FNTTP) of the ITS-S networking & transport layer.

FNTTP is in support of efficient localized communications distinguishing networking related features and transport related features. FNTTP is extendible in the future without breaking binary backward compatibility.

This document specifies

- message formats and related basic protocol procedures by reference to ISO TS 16460, and
- further requirements for operation of FNTTP in the context of an ITS station specified in ISO 21217.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 8825-2, *Information technology — ASN.1 encoding rules: Specification of Packed Encoding Rules (PER) — Part 2*

ISO/TS 16460, *Intelligent transport systems — Communications access for land mobiles (CALM) — Communication protocol messages for global usage*

ISO 17419, *Intelligent Transport Systems — Cooperative systems — Classification and management of ITS applications in a global context*

ISO 21217, *Intelligent transport systems — Communications access for land mobiles (CALM) — Architecture*

ISO 21218, *Intelligent transport systems — Hybrid communications — Access technology support*

ISO 24102-3¹⁾, *Intelligent transport systems — ITS station management — Part 3: Service access points*

ISO 24102-4²⁾, *Intelligent transport systems — ITS station management — Part 4: Station-internal management communications*

ISO 24102-6, *Intelligent transport systems — ITS station management — Part 6: Path and flow management*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 21217 and the following apply.

1) 2nd edition to be published. Stage at time of publication: ISO/DIS 24102-3.

2) 2nd edition to be published. Stage at time of publication: ISO/DIS 24102-4.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1

ITS-S facility layer service

process residing in the ITS-S facilities layer acting as source or destination of FNTP NPDUs

4 Abbreviated terms

FNTP	Fast networking & transport protocol
ITS-PN	ITS port number
ITS-S	ITS station
ITS-SCU	ITS station communication unit
ITS-SFS	ITS-S facility layer services
ITS-SU	ITS station unit
LM	Localized message
TPID-FS	Transport Protocol Identifier - Feature Selector
TPID	Transport Protocol Identifier
NPDU	Network Protocol Data Unit
UPER	Unaligned Packed Encoding Rules

5 General requirements

All normative requirements related to the specification of the "Localized Message" (LM) in ISO TS 16460 shall be normative requirements in this document.

The Fast Networking & Transport layer Protocol (FNTP) specified in this document is a communications protocol for the LM specified in ISO TS 16460. FNTP and the related LM format shall be identified in FNTP network protocol data units (NPDUs) by the version number three.

The term LM NPDU in ISO TS 16460 is synonym with the term FNTP NPDU specified in this document.

The FNTP is identified at the ITS-S access layer by the Ethertype value 35,152 = 0x8950 published on [9].

An implementation supporting path and flow management shall be in accordance with ISO 24102-6.

An implementation for a distributed ITS-SU, i.e. an ITS-SU consisting of several ITS-SCUs interconnected with an ITS station-internal network, shall be in accordance with ISO 24102-4.

The operational mode of subtype zero combined with TPID-FS zero, see 6.1, constitutes the interoperability mode of an ITS station unit (ITS-SU) with an IEEE WAVE device compliant with IEEE 1609.3[17]. In case of ITS-SUs that are declared to be interoperable with IEEE WAVE devices, this mode shall be used for single-hop broadcast communications with no expected reply if the respective value of ITS-AID as a destination address is registered at [11]. ITS-SUs that are not declared to be interoperable with IEEE WAVE devices may also use TPID-FS one for such broadcast communication.

The binary presentation of the LM is given by the ASN.1 specification presented in [A.2](#) applying unaligned packet encoding rules (UPER).

As

- identical LM formats are used in FNTF and in WSMP specified in IEEE 1609.3[17], and
- the features specifications in IEEE 1609.3[17] is a sub-set of the specification of FNTF,

an implementation of FNTF optionally may support the WAVE short messages from IEEE WAVE devices by considering the following requirements for the interoperability mode:

- 1) The only supported access technology is IEEE 802.11 OCB mode specified in [18], which is given by ISO 21215[3] with US frequency allocation and WAVE-specific details.
- 2) The applicable EtherType value of the WSMP is 35,036 = 0x88DC of WSMP published on [9].
- 3) The only mandatory operational mode in WAVE-conformant devices is WSMP with subtype zero combined with TPID-FS zero.

NOTE Conformance tests for WSMP support are out of scope of this document.

6 Architectures

6.1 General context and purpose of FNTF

The FNTF specified in this document is designed as a protocol of the ITS-S networking & transport layer of the ITS station (ITS-S) architecture recognizing the concept of the bounded, secured and managed ITS-S specified in ISO 21217, and supporting the concept of ITS station communication units (ITS-SCU) and various implementation features; see ISO 24102-1[5] (local station management), ISO 24102-2[6] (remote station management), ISO 24102-3 (management and security service access points), ISO 24102-4 (station-internal management communications), and ISO 24102-6 (path and flow management).

FNTF is designed to enable localized communication between peer "ITS-S facility layer services" (ITS-SFSs) in ITS station units (ITS-SUs) with minimum protocol overhead. ITS-SFS are sources and destinations of FNTF NPDUs.

FNTF uses the LM format specified in ISO TS 16460, ISO TS 16460 specifies networking-related protocol features and transport-related protocol features. Networking-related protocol features are identified by means of a "Subtype" value. Transport-related protocol features are identified by means of a "Transport Protocol Identifier - Feature Selector" (TPID-FS).

Networking-related features supported by FNTF are:

- Subtype 0: Null-networking;
- Subtype 1: ITS station-internal forwarding;
- Subtype 2: N-hop forwarding.

Optional functionality is supported by means of N-Extensions. N-Extensions are type-length-value encoded data elements that contain networking-related information.

Transport-related features supported by FNTF are:

- TPID-FS 0: Information dissemination mode using ITS-AID as a destination port number;
- TPID-FS 1: General session mode using a destination ITS-PN and a source ITS-PN;
- TPID-FS 2: LPP mode.

Optional functionality is supported by means of T-Extensions. T-Extensions are type-length-value encoded data elements that contain transport-related information.

For a given transmission to a peer ITS-SU exactly one networking-related feature (Subtype zero or two) and one transport-related feature (TPID-FS zero, one, or two) is selected. For ITS station-internal forwarding the Subtype one FNTF N-Header precedes a complete FNTF-NPDU.

NOTE DSRC application layer legacy systems support specified in [8] makes use of FNTF.

FNTF supports hybrid communications by supporting any kind of ad-hoc access technology, e.g. ITS-M5[3], IR[2], 60GHz[4]. FNTF connects source and destination "endpoints" at the ITS-S facilities layers in peer ITS stations, where these endpoints are identified by "ITS-Port Numbers" (ITS-PNs), and where peer ITS station units are uniquely identified by a Link-ID of the access layer specified in ISO 21218. Consequently, FNTF basically is a port mapper protocol. FNTF may also be used for information dissemination, where an "ITS Application Identifier" (ITS-AID) takes the role of a destination port number.

6.2 FNTF reference architecture

Figure 1 illustrates the location of FNTF in the ITS station (ITS-S) specified in ISO 21217, and the station-internal relations with other protocol entities.




Figure 1 — FNTF reference architecture

"Port management" of FNTF is specified in 8.1.

Management of FNTF is supported in general with a "CI Selection Management" initially introduced in ISO 24102-1[5], with technical details of "Path and Flow Management" specified in ISO 24102-6[8].

Other management approaches are also possible, e.g. within a different station architecture, as long as interoperability based on the LM and on the functional protocol behaviour specified in this document is ensured.

6.3 Communication principles

6.3.1 Transmission

Transmission requests may be presented by the ITS-S facilities layer via the NF-SAP. Sources of messages in the ITS-S facilities layer are identified by ITS-PNs. Destinations of messages in the ITS-S facilities layer are identified by ITS-PNs or by well-known registered ITS-AIDs, dependent on TPID-FS. ITS-PNs may either be well-known registered numbers or dynamically assigned numbers. The registry of ITS-PNs is at [11].

Well-known registered ITS-AIDs are mapped to locally assigned ITS-PNs (i.e. dynamically assigned ITS-PNs - PORT_DYN, specified in ISO 17419) enabling a harmonized service access point towards the ITS-S facilities layer that uses only ITS-PNs but no ITS-AIDs.

Valid transmission requests to a groupcast MAC address are given by a "well-known" destination address (ITS-PN or ITS-AID) in combination with an existing groupcast VCI. The value of the source address (ITS-PN), if used, is irrelevant with respect of validity of a transmission request in case no reply is expected. Replies to groupcast messages are expected e.g. in case of the service advertisement message specified in ISO 24102-5[7].

Valid transmission requests to a unicast MAC address are given by any valid destination address in combination with an existing unicast VCI. The value of the source address, if present, is irrelevant with respect of validity of a transmission request in case no reply is expected.

Transmission requests are presented by the FNTTP to the ITS-S access layer using services of the IN-SAP.

In implementations in accordance with ISO 24102-6, validity of a transmission request is given by a valid ITS-S-FlowID.

6.3.2 Reception

Reception notifications are presented by the ITS-S access layer to the FNTTP using services of the IN-SAP.

Sources and destinations of messages are identified by ITS-PNs contained in the FNTTP NPDU. ITS-AIDs used as destination address in FNTTP NPDUs (TPID-FS = 0) are mapped to dynamically assigned ITS-PNs enabling a harmonized service access point NF-SAP towards the ITS-S facilities layer.

Valid notified packets addressed to an ITS-PN are given by a known destination port address (ITS-PN). Valid notified packets addressed to an ITS-AID are given by a known ITS-AID that is mapped to an ITS-PN. Which CI was used for reception of the packet, and which is the source port address of the packet, are not relevant for the validity of the packet, but are relevant for a potential reply.

Received packets indicating an FNTTP version number that is not supported generally are invalid.

Notifications of received packets are presented by the FNTTP to the ITS-S facilities layer using services of the NF-SAP.

6.3.3 FNTTP ITS-PNs

ITS port numbers (ITS PNs) are two octet unsigned Integer numbers of ASN.1 type `PortNumber` specified in ISO 17419. ISO 17419 distinguishes well-known registered ITS-PNs (PORT_REG) and dynamically assigned ITS-PNs (PORT_DYN), and presents initial number allocations for PORT_REGs.

NOTE Static well-known ITS-PN numbers and ITS-AIDs are assigned to ITS applications by a registration authority; see ISO 17419. There are no dynamically assigned ITS-AIDs.

Dynamically assigned ITS-PNs (PORT_DYN) are unique only in the ITS-SCU that performed the assignment. In distributed implementations specified in ISO 21217, i.e. ITS-SUs consisting of several ITS-SCUs interconnected via an ITS station-internal network, always a pair of ITS-PNs are to be allocated, i.e. one value assigned in an ITS-SCU with host role, and a corresponding value assigned in an ITS-SCU with router role. This leads to the service look-up table specified in [7.4.2](#).

Allocation and deletion of dynamic and static well-known "ITS Port Numbers" (ITS-PNs) and ITS-AIDs in an ITS station is specified [8.1](#).

6.4 Implementation architectures

FNTTP supports the implementation architectures introduced in ISO 21217.

7 Protocol elements

7.1 Service access points

NOTE SAPs are functional descriptions which in many cases are not implemented as observable interfaces. Thus in general SAPs are not testable. The requirements set up in this document with respect of SAPs thus just mean the functional behaviour rather than a specific implementation. As far as related ASN.1 definitions are given, these become mandatory as soon as the defined elements become observable, e.g. within a PDU for ITS station-internal management communications specified in ISO 24102-4[7].

7.1.1 IN-SAP

The FNTTP interacts with the ITS-S access layer specified in ISO 21217 using service functionality of the IN-SAP specified in ISO 21218.

The FNTTP supports the IN-UNITDATA service functionality of the IN-SAP specified in ISO 21218.

The FNTTP may support the IN-UNITDATA-STATUS and IN-UNITDATAACK service functionality of the IN-SAP specified in ISO 21218.

NOTE Usage of the information given by the IN-UNITDATA-STATUS service is not specified in this document.

7.1.2 NF-SAP

The FNTTP interacts with the ITS-S facilities layer specified in ISO 21217 offering service functionality of the NF-SAP specified in [Clause 11](#) and in [A.2](#).

The FNTTP provides the NF-FNTTP-PORT service functionality and the NF-FNTTP-COMM service functionality of the NF-SAP specified in this document.

7.1.3 MN-SAP

The FNTTP interacts with the ITS-S management entity specified in ISO 21217 using service functionality of the MN-SAP specified in ISO 24102-3. This functionality is specified in [A.3](#) by means of appropriate ASN.1 type definitions.

7.1.4 SN-SAP

The FNTTP may interact with the ITS-S management entity specified in ISO 21217 using service functionality of the SN-SAP specified in ISO 24102-3. This functionality is specified in [A.3](#) by means of appropriate ASN.1 type definitions.

7.2 FNTF NPDU

7.2.1 General

The format of FNTF NPDUs is identical to the format of LM NPDUs specified in ISO TS 16460:2016, 5.3.

7.2.2 Subtype zero

Support of subtype zero specified in ISO TS 16460 (Null-Networking) is mandatory. This is the default networking mode.

7.2.3 Subtype one

Support of subtype one specified in ISO TS 16460 is mandatory only in case an implementation supports an ITS station-internal network interconnecting several ITS-SCUs. Subtype one is only used for ITS station-internal forwarding of FNTF NPDUs. Usage of this subtype in links between peer ITS-SUs is prohibited.

The field "ITS-SCU-ID ITS-S host" contains the ITS-SCU-ID of the ITS-S host. ITS-SCU-ID is specified in ISO 24102-4, with its ASN.1 type `ITS-scuId` specified in ISO 17419.

The field "Link-ID VCI in ITS-S router" contains the Link-ID of the VCI in these ITS-S router. The format of Link-ID is specified in ISO 21218.

Usage of subtype one in the "Original N-Header" field is prohibited.

7.2.4 Subtype two

Support of subtype two specified in ISO TS 16460 is optional. Subtype two may be used to achieve resilience or minimum communication distance specified in ISO 17423^[1]. Subtype two is restricted to broadcast or multicast dissemination of information disregard whether a reply is expected or not. Subtype two may be requested either in the NF-FNTF-COMM.request service primitive by indicating a Hop Count larger than zero, or by the ITS station management. The ITS station management may require an upper limit of Hop Count smaller than or equal to the possible maximum value of three.

7.2.5 N-Extensions

[Table 1](#) presents currently identified N-Extensions.

Table 1 — N-Extensions

Name	Element ID	Comment
Transmit Power Used	4	Applicable for the access technology specified in ISO 21215 ^[3] . Details specified in IEEE 1609.3 ^[17] .
802.11 Channel Number used	15	Applicable for the access technology specified in ISO 21215 ^[3] . Details specified in IEEE 1609.3 ^[17] .
802.11 Data Rate used	16	Applicable for the access technology specified in ISO 21215 ^[3] . Details specified in IEEE 1609.3 ^[17] .
^a CIPs are constructed from I-Parameters specified in ISO 21218 and may depend on the ITS-S access technology selected for communications. Further details of CIPs are outside the scope of this document.		

Table 1 (continued)

Name	Element ID	Comment
Communication Interface receive parameters (RX-CIP)	80	Generally applicable. Specified in ISO 21218 and in this document. ^a Used for Subtype one to notify communication interface parameters in the ITS-SCU with router role related to the received FNTTP NPDU.
Communication Interface transmit parameters (TX-CIP)	81	Generally applicable. Specified in ISO 21218 and in this document. ^a Used for Subtype one to request settings of communication interface parameters in the ITS-SCU with router role.
Channel Busy Ratio	82	Generally applicable, e.g. for channel congestion algorithms. Usage is not specified in this document.
^a CIPs are constructed from I-Parameters specified in ISO 21218 and may depend on the ITS-S access technology selected for communications. Further details of CIPs are outside the scope of this document.		

7.2.6 TPID-FS field

Details of the FNTTP T-Header are selected by the value contained in the TPID-FS field of the FNTTP N-Header.

7.2.7 TPID-FS zero - information dissemination mode

Support of TPID-FS zero is mandatory for ITS-SUs that are declared to be interoperable with IEEE WAVE devices. This "Information Dissemination Mode" is a transport mode of operation for transmission of FNTTP NPDUs to multiple receivers (broadcast mode or multicast mode) if no reply is expected, and if the ITS-SFS identified by an ITS-AID uses only a single transport layer port.

NOTE ITS-SUs that are not declared to be interoperable with IEEE WAVE devices can use TPID-FS one for dissemination of information (broadcasting of information).

7.2.8 TPID-FS one - general session mode

Support of TPID-FS one is mandatory. This "General Session Mode" is the default transport mode of operation for transmission of FNTTP NPDUs to a single receiver (unicast mode) and to multiple receivers if a reply is expected. It is also used for transmission of FNTTP NPDUs to multiple receivers if no reply is expected, and the related ITS-SFS has several receive ports.

7.2.9 TPID-FS two - LPP support mode

Support of TPID-FS two is optional.

7.2.10 T-Extensions

[Table 2](#) presents currently identified T-Extensions.

Table 2 — T-Extensions

Name	Element ID	Comment
Packet Identifier	83	The "Packet Identifier" element is optionally included in the LM T-Header to identify uniquely a specific packet in a sequence of packets from a specific transmitter. A related procedure is not specified so far.

NOTE Support for resilience by FNTF (acknowledgement of messages) is being developed for a next version of this document. This support for resilience will likely require FNTF management PDUs with source / destination ITS-PNs set to the value zero. So far FNTF can support resilience by selecting the ISO 21218 IN_SAP service for acknowledged MAC frames.

7.2.11 FNTF body

The FNTF body field contains the "User Data" part of an ITS-FPDU specified in ISO 21217. The length of the "User Data" field expressed in multiples of octets is contained in the "Length of User Data" field of the T-Header.

7.3 Secure communications

FNTF NPDUs basically are not secured, as security means typically are assumed to be applied at the higher layers, e.g. ITS-S facilities layer or ITS-S applications.

Secured modes of operation may be identified in the future with either new subtypes or new TPID-FSs.

7.4 Protocol management elements

7.4.1 ITS-AID look-up table

ISO 29281-1:2018

<https://standards.iteh.ai/catalog/standards/sist/fe51645e-7985-4571-93e1-3d7a2a0b0050/iso-29281-1-2018>

In order to map well-known ITS-AID numbers used as destination address in T-Headers of TPID-FS zero to dynamically assigned ITS-PNs (PORT_DYN), or if available to well-known registered ITS-PNs (PORT_REG), the FNTF maintains respective look-up information. Assignments shall be done locally in ITS-SCUs with host role.

7.4.2 Service look-up table

The FNTF maintains look-up information as illustrated in [Figure 2](#).

ITS-S router	ITS-S host		
Link Port <i>PortNumber</i>	Service		
	Service Port <i>PortNumber</i>	ITS-SCU-ID	Service Priority

Figure 2 — Service look-up table

"Link Port" contains the ITS port number (ITS-PN) used in the FNTF T-Header in the link to a peer station, pointing indirectly to the ITS-SFS in the ITS-S host. "Service Port" contains the ITS-PN which points directly to the ITS-SFS in the ITS-S host. In case of dynamically assigned ITS-PNs, the allocation