

SLOVENSKI STANDARD SIST EN 474-1:2007+A6:2019

01-december-2019

Stroji za zemeljska dela - Varnost - 1. del: Splošne zahteve

Earth-moving machinery - Safety - Part 1: General requirements

Erdbaumaschinen - Sicherheit - Teil 1: Allgemeine Anforderungen

Engins de terrassement - Sécurité - Partie 1: Prescriptions générales

Ta slovenski standard je istoveten z: EN 474-1:2006+A6:2019

SIST EN 474-1:2007+A6:2019

https://standards.iteh.ai/catalog/standards/sist/d087668b-6b0c-41e5-81a6-5591d50db091/sist-en-474-1-2007a6-2019

<u>ICS:</u>

53.100 Stroji za zemeljska dela Earth-moving machinery

SIST EN 474-1:2007+A6:2019 en,fr,de

SIST EN 474-1:2007+A6:2019

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 474-1:2007+A6:2019</u> https://standards.iteh.ai/catalog/standards/sist/d087668b-6b0c-41e5-81a6-5591d50db091/sist-en-474-1-2007a6-2019 EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM EN 474-1:2006+A6

October 2019

ICS 53.100

Supersedes EN 474-1:2006+A5:2018

English Version

Earth-moving machinery - Safety - Part 1: General requirements

Engins de terrassement - Sécurité - Partie 1: Prescriptions générales Erdbaumaschinen - Sicherheit - Teil 1: Allgemeine Anforderungen

This European Standard was approved by CEN on 1 October 2017 and includes Amendment 6 approved by CEN on 9 August 2019.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

5591d50db091/sist-en-474-1-2007a6-2019



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Con	tents	Page
Euro	pean foreword	3
Introduction		5
1	Scope	6
2	Normative references	7
3	Terms and definitions	10
4	List of significant hazards	12
5	Safety requirements and/or measures	12
6	Verification of safety requirements/measures	30
7	Information for use	31
Anne	ex A (normative) List of significant hazards	36
Anne	ex B (normative) \land Requirements for attachment and quick coupler 🔄	41
Anne	ex C (informative) Requirements for no-text safety signs.R.F	42
Anne	ex D (normative) Requirements for elevating operator's station	44
	ex E (normative) Requirements for lifting device(s) used for object handling application	n 46
Anne	ex F (normative) Requirements for earth-moving machinery used in underground working in non-explosive atmosphere	52
Anne	ex G (normative) A Demolition machinery	
Anne	ex ZA (informative) As Relationship between this European Standard and the essential requirements of Directive 2006/42/EC machinery, and amending Directive	
	95/16/EC (recast) [2006 L157] aimed to be covered	
Ribli	ography	65

European foreword

This document (EN 474-1:2006+A6:2019) has been prepared by Technical Committee CEN/TC 151 "Construction equipment and building material machines — Safety", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2020, and conflicting national standards shall be withdrawn at the latest by April 2020.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document includes Corrigendum 1 issued by CEN on 2014-03-05, Amendment 1, approved by CEN on 2009-01-04, Amendment 3, approved by CEN on 2013-01-06, Amendment 4, approved by CEN on 2013-08-10, Amendment 5, approved by CEN on 2017-10-01 and Amendment 6, approved by CEN on 2019-08-09.

This document supersedes (As) EN 474-1:2006+A5:2018 (As).

The modifications of the related CEN Corrigendum have been implemented at the appropriate places in the text and are indicated by the tags AC.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive.

For relationship with EU Directive(s), see (A) informative Annex ZA (A), which is an integral part of this document. (A)

EN 474 "Earth-moving machinery — Safety" comprises the following parts:

- Part 1: General requirements
- Part 2: Requirements for tractor-dozers
- Part 3: Requirements for loaders
- Part 4: Requirements for backhoe-loaders
- Part 5: Requirements for hydraulic excavators
- Part 6: Requirements for dumpers
- Part 7: Requirements for scrapers
- Part 8: Requirements for graders
- Part 9: Requirements for pipe-layers
- Part 10: Requirements for trenchers

- Part 11: Requirements for earth and landfill compactors
- Part 12: Requirements for cable excavators

For specific machines covered by other parts of the standard, this European Standard is intended for use in combination with relevant other parts of the series.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 474-1:2007+A6:2019 https://standards.iteh.ai/catalog/standards/sist/d087668b-6b0c-41e5-81a6-5591d50db091/sist-en-474-1-2007a6-2019

Introduction

This part of EN 474 is a type C standard as stated in EN ISO 12100-1:2003.

The machinery concerned and the extent to which hazards, hazardous situations and events are covered are indicated in the scope of this European Standard.

When provisions of this type C standard are different from those which are stated in type A or B standards, the provisions of this type C standard take precedence over the provisions of the other standards, for machines that have been designed and built according to the provisions of this type C standard.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 474-1:2007+A6:2019 https://standards.iteh.ai/catalog/standards/sist/d087668b-6b0c-41e5-81a6-5591d50db091/sist-en-474-1-2007a6-2019

1 Scope

This (A) European Standard (A) specifies the general safety requirements for earth-moving machinery described in EN ISO 6165:2006, except rollers and horizontal directional drill.

NOTE 1 Rollers are covered by EN 500.

NOTE 2 Horizontal directional drills are covered by EN 791.

This European Standard (3) also applies to derivative machinery (see 3.1.2) designed primarily for use with equipment to loosen, pick-up, move, transport, distribute and grade earth and rock.

This A European Standard a gives the common safety requirements for earth-moving machinery families and is intended to be used in conjunction with one of the EN 474 parts 2 to 12. These machine specific parts (EN 474-2 to -12) do not repeat the requirements from A EN 474-1:2006+A1:2009 A, but add or replace the requirements for the family in question.

NOTE 3 The requirements specified in this part of the standard are common to two or more families of earthmoving machinery.

A This part gives specific requirements for demolition machinery.

Specific requirements in EN 474 parts 2 to 12 take precedence over the respective requirements of (A_1) EN 474-1:2006+A1:2009 (A_1) .

For multipurpose machinery the parts of the standard that cover the specific functions and applications have to be used e.g. a compact loader also used as a trencher shall use the relevant requirements of EN 474 parts 1, 3 and 10.

The standard also covers general requirements for attachments intended to be used with earth moving machine families covered in the scope, itch ai/catalog/standards/sist/d087668b-6b0c-41e5-81a6-

Except for part 12 this European Standard does not deal With the electrical hazards related to the main circuits and drives of machinery when the principal source of energy is electrical.

(A) This European Standard does not deal with towing of trailers. (A)

This European Standard deals with all significant hazards, hazardous situations and events relevant to earth-moving machinery, when used as intended and under conditions of misuse which are reasonably foreseeable by the manufacturer (see Clause 4). This European Standard specifies the appropriate technical measures to eliminate or reduce risks arising from the significant hazards, hazardous situations and events during commissioning, operation and maintenance of earth-moving machinery.

This European Standard is not applicable to earth moving machines, which are manufactured before the date of publication of this European Standard by CEN.

6

¹⁾ For travelling on public roads the national traffic regulations apply until harmonised requirements are available. (A CENstandard is under preparation.)

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 286-2:1992, Simple unfired pressure vessels designed to contain air or nitrogen — Part 2: Pressure vessels for air braking and auxiliary systems for motor vehicles and their trailers

EN 287-1:2004, Qualification test of welders — Fusion welding — Part 1: Steels

EN 356:1999, Glass in building — Security glazing — Testing and classification of resistance against manual attack

EN 474-5:2006+A3:2013, Earth-moving machinery — Safety — Part 5: Requirements for hydraulic excavators

EN 474-12:2006+A1:2008, Earth-moving machinery — Safety — Part 12: Requirements for cable excavators [4]

 A_1 deleted text A_1

EN 982:1996, Safety of machinery — Safety requirements for fluid power systems and their components — Hydraulics iTeh STANDARD PREVIEW

EN 1677-2:2000, Components for slings — Safety — Part 2: Forged steel lifting hooks with latch, Grade 8

A) EN 12643:1997+A1:2008 (A), Earth-moving machinery — Rubber-tyred machines — Steering requirements (ISO 5010:1992, modified) EN 474-12007+A6:2019

https://standards.iteh.ai/catalog/standards/sist/d087668b-6b0c-41e5-81a6-

EN 13309:2000, Construction machinery 14st Electromagnetic Compatibility of machines with internal electrical power supply

A1) deleted text (A1

EN 60529:1991, Degrees of protection provided by enclosures (IP code) (IEC 60529:1989)

EN 61310-1:1995, Safety of machinery — Indication, marking and actuation — Part 1: Requirements for visual, auditory and tactile signals (IEC 61310-1:1995)

EN ISO 2860:1999, Earth-moving machinery — Minimum access dimensions (ISO 2860:1992)

As EN ISO 2867:2011, Earth-moving machinery — Access systems (ISO 2867:2011) (As

 \triangle EN ISO 3411:2007, Earth-moving machinery — Physical dimensions of operators and minimum operator space envelope (ISO 3411:2007) \triangle

EN ISO 3449:2008, Earth-moving machinery — Falling-object protective structures — Laboratory tests and performance requirements (ISO 3449:2005) (A)

EN ISO 3450:1996, Earth-moving machinery — Braking systems of rubber-tyred machines — System and performance requirements and test procedures (ISO 3450:1996)

EN ISO 3457:2003, Earth-moving machinery — Guards — Definitions and requirements (ISO 3457:2003)

(A) EN ISO 3471:2008, Earth-moving machinery — Roll-over protective structures — Laboratory tests and performance requirements (ISO 3471:2008)

EN ISO 4414:2010, Pneumatic fluid power — General rules and safety requirements for systems and their components (ISO 4414:2010) (44)

EN ISO 4871:2009 (44), Acoustics — Declaration and verification of noise emission values of machinery and equipment (ISO 4871:1996)

EN ISO 5353:1998, Earth-moving machinery, and tractors and machinery for agriculture and forestry — Seat index point (ISO 5353:1995)

EN ISO 6165:2006, Earth-moving machinery — Basic types — A deleted text (A) Identification and terms and definitions (ISO 6165:2006)

EN ISO 6682:1995, Earth-moving machinery — Zones of comfort and reach for controls (ISO 6682:1986 including Amendment 1:1989)

EN ISO 6683:2005, Earth-moving machinery — Seat belts and seat belt anchorages — Performance requirements and tests (ISO 6683:2005)

EN ISO 7096:2000, Earth-moving machinery — Laboratory evaluation of operator seat vibration (ISO 7096:2000)

EN ISO 11688-1:1998, Acoustics — Recommended practice for the design of low-noise machinery and equipment — Part 1: Planning (ISO/TR 11688-1:1995) (41)

EN ISO 12100-1:2003, Safety of machinery — Basic concepts, general principles for design — Part 1: Basic terminology, methodology (ISO 12100-1:2003)

EN ISO 12100-2:2003, Safety of machinery — Basic concepts, general principles for design — Part 2: Technical principles (ISO 12100-2:2003)

SIST EN 474-1:2007+A6:2019

EN ISO 13732-1:2006, Ergonomics of the thermal environment 476 Methods for the assessment of human responses to contact with surfaces — Part 1: Hot surfaces (150 13732-1:2006)

A) EN ISO 13849-1:2008, Safety of machinery — Safety-related parts of control systems — Part 1: General principles for design (ISO 13849-1:2006) (A)

ISO 3795:1989, Road vehicles, and tractors and machinery for agriculture and forestry — Determination of burning behaviour of interior materials

ISO 3864-1:2002, *Graphical symbols* — *Safety colours and safety signs* — *Part 1: Design principles for safety signs in work places and public areas*

ISO 3864-2:2004, Graphical symbols — Safety colours and safety signs — Part 2: Design principles for product safety labels

 $\boxed{\text{A}}$ ISO 4250-3:2006 $\boxed{\text{A}}$, Earth-mover tyres and rims — Part 3: Rims

ISO 5006:2017, Earth-moving machinery — Operator's field of view — Test method and performance criteria (45)

ISO 6011:2003, Earth-moving machinery — Visual display of machine operation

 ${\tt ISO~6014:1986,} \textit{Earth-moving machinery} - \textit{Determination of ground speed}$

ISO 6016:1998, Earth-moving machinery — Methods of measuring the masses of whole machines, their equipment and components

- | ISO 6395:2008, Earth-moving machinery Determination of sound power level Dynamic test conditions (A)
- [A] ISO 6396:2008 [A], Earth-moving machinery Determination of emission sound pressure level at operator's position Dynamic test conditions
- ISO 6405-1:2004, Earth-moving machinery Symbols for operator controls and other displays Part 1: Common symbols
- ISO 6405-2:1993, Earth-moving machinery Symbols for operator controls and other displays Part 2: Specific symbols for machines, equipment and accessories
- ISO 6749:1984, Earth-moving machinery Preservation and storage
- ISO 8643:1997, Earth-moving machinery Hydraulic excavator and backhoe loader boom-lowering control device Requirements and tests
- ISO 9533:1989, Earth-moving machinery Machine mounted forward and reverse audible warning alarm Sound test method
- [4] ISO 10262:1998, Earth-moving machinery Hydraulic excavators Laboratory tests and performance requirements for operator protective guards [4]
- [A] ISO/DIS 10263-2:2007, Earth-moving machinery Operator enclosure environment Part 2: Air filter element test method [A] STANDARD PREVIEW
- \triangle ISO/DIS 10263-3:2007, Earth-moving machinery the Operator enclosure environment Part 3: Pressurization test method \triangle
- M ISO/DIS 10263-4:2007, Earth-moving machinery operator enclosure environment Part 4: Heating, ventilating and dir conditioning (HVAC) test method and performance (1)
- ISO 10264:1990, Earth-moving machinery Key-locked starting systems
- [A] ISO 10265:2008 (A], Earth-moving machinery Crawler machines Performance requirements and test procedures for braking systems
- ISO 10532:1995, Earth-moving machinery Machine-mounted retrieval device Performance requirements
- ISO 10533:1993, Earth-moving machinery Lift-arm support devices
- ISO 10570:2004, Earth-moving machinery Articulated frame lock Performance requirements
- ISO 10968:2004, Earth-moving machinery Operator's controls
- ISO 11112:1995, Earth-moving machinery Operator's seat Dimensions and requirements
- ISO 11862:1993, Earth-moving machinery Auxiliary starting aid electrical connector
- ISO 12508:1994, Earth-moving machinery Operator station and maintenance areas Bluntness of edges
- ISO 12509:2004, Earth-moving machinery Lighting, signalling and marking lights, and reflex-reflector devices
- (As ISO 13031:2016, Earth-moving machinery Quick couplers Safety

ISO 13333:1994, Earth-moving machinery — Dumper body support and operator's cab tilt support devices

ISO 14396:2002, Reciprocating internal combustion engines — Determination and method for the measurement of engine power — Additional requirements for exhaust emission tests in accordance with ISO 8178

ISO 14401-1:2004, Earth-moving machinery — Field of vision of surveillance and rear-view mirrors — Part 1: Test methods

ISO 14401-2:2004, Earth-moving machinery — Field of vision of surveillance and rear-view mirrors — Part 2: Performance criteria

ISO 15817:2005, Earth-moving machinery — Safety requirements for remote operator control

[A] ISO 15998:2008 (A], Earth-moving machinery — Machine-control systems (MCS) using electronic components — Performance criteria and tests for functional safety

3 Terms and definitions

For the purposes of this A document A docume

Earth-moving machinery and their families are defined in EN ISO 6165:2006.

NOTE Definitions used in EN and ISO standards referred to in this European Standard are also valid for this document. (standards.iteh.ai)

3.1 <u>SIST EN 474-1:2007+A6:2019</u>

earth-moving machinery https://standards.iteh.ai/catalog/standards/sist/d087668b-6b0c-41e5-81a6-

self-propelled or towed machine on wheels crawler or legs chaving equipment and/or attachment (working tool), primarily designed to perform excavating, loading, transporting, spreading, compacting or trenching of earth, rock or similar materials

NOTE An earth-moving machine is normally operated by a ride-on operator but can also be remote – or pedestrian –controlled.

3.1.1

compact machine

earth-moving machinery having an operating mass (see ISO 6016:1998) of 4 500 kg or less, or compact excavators having an operating mass (see ISO 6016:1998) of 6 000 kg or less

3.1.2

derivative machinery

earth-moving machinery fitted with equipment and/or attachment which modifies its function

NOTE For the European Economic Area (EEA) the equipment or attachment or a piece of equipment as defined in ISO 6016:1998 which modifies the function of the machine and is intended to be assembled by the operator can be "interchangeable equipment" in the sense of the Machinery Directive.

3.2

attachment (working tool)

component or assembly of components, which can be mounted onto the base machine or equipment (see ISO 6746-1:2003. ISO 6746-2:2003 and ISO 6016:1998) for a specific use

Note 1 to entry: Attachments might be, in the meaning of the Machinery Directive 2006/42/EC, either interchangeable equipment or tools. The term 'attachments' is used in this standard to cover both.

A_6 3.3

quick coupler

device mounted on an earth-moving machine to allow the quick interchange of attachments

Note 1 to entry: Quick couplers are also commonly referred to under many different names, including "quick hitch" and "attachment bracket". For the purposes of this International Standard, only the term "quick coupler" is used.".

[SOURCE: ISO 13031:2016, 3.1]

Note 2 to entry: Quick couplers are generally considered to be interchangeable equipment when placed on the market separately, whether or not installed on the machine before first use, and when it is reasonably foreseeable that they might be installed or removed by the operator (e.g. for installation on another machine).

3.4

3.5

object handling

application of earth-moving machinery comprising lifting, lowering and transporting of a load by use of lifting accessories, whereby the assistance of a person or the operator of the machine is required for hooking, unhooking or stabilising (whilst transporting) the load

NOTE 1 If the load is picked-up by a self-acting device and no assistance of a person is required for hooking, unhooking and stabilising the load, this work is considered as usual earth-moving application.

NOTE 2 Lifting accessories are, e.g., wire ropes, chains or textile straps; loads in object handling application are, e.g., pipes, vessels; self-acting devices are, e.g., grabs, clamshell buckets, log clamps, vacuum lifting device, magnetic plate and fork.

SIST EN 474-12007+A62019

https://standards.iteh.ai/catalog/standards/sist/d087668b-6b0c-41e5-81a6-5591d50db091/sist-en-474-1-2007a6-2019

maximum rated operating/lift capacity in object handling

maximum capacity which can be lifted at least in one position of the working range as specified by the manufacturer (e.g. on the rated object handling capacity table) in the most stable configuration (e.g. outriggers down)

NOTE The term "rated operating capacity" is defined in ISO 14397-1:2002 and used in $\boxed{\mathbb{A}}$ EN 474-3:2006+A1:2009 $\boxed{\mathbb{A}}$ and $\boxed{\mathbb{A}}$ EN 474-4:2006+A1:2009 $\boxed{\mathbb{A}}$. The term "rated lift capacity" is defined in ISO 10567:1992 and used in $\boxed{\mathbb{A}}$ EN 474-5:2006+A3:2013 $\boxed{\mathbb{A}}$. Both terms are equivalent.

$A_4 > 3.6$

demolition machine

machine based on earth moving machinery (see EN ISO 6165) and including equipment and attachment (working tool – e.g. processor or breaker) specifically designed to demolish, cut, loosen, separate, pick up, transport and distribute component parts of buildings, civil engineering structures

3.7

processor

attachment with tooth, teeth and/or cutting edges, used for demolition or deconstruction

3.8

hydraulic hammer or breaker

equipment which uses the hydraulic power source of the carrier machine to accelerate a piston (sometimes gas-assisted), which then hits a tool

Note 1 to entry: The stress wave generated by kinetic action flows through the tool into the material, which causes the material to break. Hydraulic hammers need a supply of pressurised oil to function. The complete carrier/hammer unit is controlled by an operator, usually seated in the cabin of the carrier.

3.9

high reach equipment

multi piece rigid or telescopic equipment with the primary function of operating specialised attachments for the demolition of structures at heights that cannot be reached by standard backhoe equipment

3.10

base machine

machine with a cab or canopy and operator protective structures if required, without equipment or attachments but possessing the necessary mountings for such equipment and attachments

[SOURCE: ISO 6016:2008, 3.1.1] (4)

4 List of significant hazards

See Annex A.

NOTE Annex A (normative) contains all the significant hazards, hazardous situations and events, as far as they are dealt with in this European Standard, identified by risk assessment as common to two or more machinery families and which require action to eliminate or reduce the risk.

(standards.iteh.ai)

5 Safety requirements and/or measures

SIST EN 474-1:2007+A6:2019

5.1 General

https://standards.iteh.ai/catalog/standards/sist/d087668b-6b0c-41e5-81a6-5591d50db091/sist-en-474-1-2007a6-2019

Earth-moving machinery shall comply with the safety requirements and/or protective measures of this European Standard, as far as not modified by requirements of the relevant specific part of the standard series. In addition, the machine shall be designed according to the principles of EN ISO 12100-1:2003 and EN ISO 12100-2:2003 for hazards relevant but not significant which are not dealt with by this European Standard.

5.2 Access

5.2.1 General requirements

Adequate access systems shall be provided to the operator's station and areas where routine maintenance has to be performed by the operator as described in the operator's manual. Access 45 systems 45 shall comply with 45 EN ISO 2867:2011 45.

Effect of mud on the means of access shall be minimised by adequate design.

5.2.2 Access to articulated machines

On machines with articulated frames and in the fully articulated steering position, a minimum clearance of 150 mm for the lower limbs shall be provided (A) between firm structures and components with (A) relative movement in the path of the access systems to the operator's station, as illustrated in Figure 1.

Dimensions in millimetres




Figure 1 — Minimum clearance of lower limbs at access to the operator's station on machines with articulated steering

iTeh STANDARD PREVIEW

 A_5 deleted text A_5

(standards.iteh.ai)

5.3 Operator's station

SIST EN 474-1:2007+A6:2019

5591d50db091/sist-en-474-1-2007a6-2019

5.3.1.1 Machinery equipment

(A) The driving position of ride-on drivers shall be designed and constructed in such a way that a driver's cab may be fitted, provided this does not increase the risk and there is room for it. (A)

Machines with an operating mass less than 1 500 kg are not required to have a cab.

Machines with an operating mass greater than or equal to 1 500 kg shall be equipped with a cab, unless the foreseeable adverse weather conditions allow all-year operation without a cab (negotiated between manufacturer and user).

Machines shall be equipped with a cab and a contamination protective system if the machine is intended for use in unhealthy environments, e.g. contaminated areas (negotiated between manufacturer and user). See 5.14.1.

If a hazard due to projection of splinters exists, e.g. operation with a hydraulic- or demolition-hammer, an adequate protection such as bullet proof glass, mesh guard or an equivalent protection is required.

5.3.1.2 Minimum space

The minimum space available to the operator shall be as defined in [A] EN ISO 3411:2007 (A) (except as amended in 5.3.2.5).

For compact machines the minimum space envelope width (dimension 920 mm in A) EN ISO 3411:2007, Figure 4 (A) may be reduced to 650 mm.

The minimum space and location of the controls at the operator's station shall meet the requirements specified in EN ISO 6682:1995.