

# SLOVENSKI STANDARD oSIST prEN ISO 8666:2020

01-september-2020

Mala plovila - Osnovni podatki (ISO/FDIS 8666:2020)

Small craft - Principal data (ISO/FDIS 8666:2020)

Petits navires - Données principales (ISO/FDIS 8666:2020

Ta slovenski standard je istoveten z: prEN ISO 8666

ICS:

47.080 Čolni Small craft

oSIST prEN ISO 8666:2020 en,fr,de

**oSIST prEN ISO 8666:2020** 

**FINAL DRAFT** 

## INTERNATIONAL **STANDARD**

ISO/FDIS 8666

ISO/TC **188** 

Secretariat: SIS

Voting begins on: 2020-07-10

Voting terminates on: 2020-10-02

## Small craft — Principal data

Princ

onnées principales

onnées prin

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STAN-DARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number ISO/FDIS 8666:2020(E)

ISO/FDIS 8666:2020(E)

Helps: 1standards. itelia standards is standards is standards is standards in the standards



#### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

## ISO/FDIS 8666:2020(E)

Contents					
Fore	eword		<b>v</b>		
1	Scop	e	1		
2	-	native references			
3		ns and definitions			
4	Sym	bols, designations and units	3		
5		surements			
	5.1	General			
	5.2	Longitudinal			
		5.2.2 Maximum length, $L_{\rm max}$	4		
		5.2.4 Waterline length, $L_{\rm WL}$			
	5.3	Athwartship			
		<u>•</u>			
		5.3.1 General	8		
		5.3.3 Beam of hull, $B_{\rm H}$	8		
		5.3.4 Beam, waterline, $B_{WL}$	8		
		5.3.5 Maximum beam, waterline, $B_{\text{Whmax}}$	8		
	Г 4	5.3.6 Beam between hull centres, B <sub>CB</sub>	8		
	5.4	Verucal State Maximum donth D	9		
		5.4.2 Midshin denth D	9 9		
		5.4.3 Freehoard F	10		
		5.4.4 Draught T	10		
		5.4.5 Draught, air, <i>H</i> <sub>2</sub>	10		
		5.4.6 Headroom	11		
	5.5	Other data	11		
		5.5.2 Reference sail area, A <sub>S</sub>			
		5.5.3 Standard sail area, A' <sub>S</sub>			
		5.5.4 Windage area, A <sub>lv</sub>			
_					
6		Ses			
	6.1 6.2	Mass, net shipping, $m_N$			
	6.3	Mass, gross shipping, $m_{ m G}$			
	0.5	6.3.1 Items of equipment included in $m_{LC}$			
		6.3.2 Items of equipment and other items not included in $m_{LC}$	15		
	6.4	Performance test mass, $m_{\rm P}$	15		
	6.5	Mass of the craft when towed on a trailer, $m_{\mathrm{T}}$	16		
		6.5.1 General			
		6.5.2 Items of equipment included in $m_{\rm T}$			
		6.5.3 Items of equipment not included in $m_{\rm T}$			
		6.5.4 Exclusions, inclusions			
		6.6 Maximum load, $m_{ m ML}$			
7		ling conditions			
	7.1	Test condition			
	7.2	Ready-for-use condition			
	7.3				
	7.4 7.5	1 3			
	7.3 7.6	Minimum operating condition			
	, .0	op op op			

### oSIST prEN ISO 8666:2020

### ISO/FDIS 8666:2020(E)

	7.7	Loaded arrival condition	21
	7.8	Maximum load condition	21
8	Tolei	rances	21
	8.1	Published data	21
	8.2	Preliminary specification	22
		Reference lengths	22
Anne		nformative) Relationship between this European Standard and the essential irements of Directive 2013/53/EU aimed to be covered	23
Bibli	ograph	y	25

Helps: 18tandards iteliar and a figure and a

### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by Technical Committee ISO/TC 188, Small craft, in collaboration with

This document was prepared by Technical Committee ISO/TC 188, *Small craft*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 464, *Small craft*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This third edition cancels and replaces the second edition (ISO 8666:2016), of which it constitutes a minor revision. The changes compared to the previous edition are as follows:

- the document has been aligned to the latest edition of the ISO/IEC Directives, Part 2, resulting in the addition of Clause 2, Normative references, and the renumbering of the remaining clauses; all cross-references have been accordingly updated;
- the "allowance for the maximum mass of optional equipment and fittings not included in the manufacturer's basic outfit" has been moved from 6.6 (Maximum load, former 5.6) to 7.8 (Maximum load condition, former 6.8).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

**oSIST prEN ISO 8666:2020** 

I el SI A Randards it eliated esta de la entre e

## Small craft — Principal data

### 1 Scope

This document establishes definitions of main dimensions and related data and of mass specifications and loading conditions. It applies to small craft having a length of the hull ( $L_{\rm H}$ ) of up to 24 m.

#### 2 Normative references

There are no normative references in this document.

#### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

NOTE For units, see <u>Clause 4</u>.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>
- IEC Electropedia: available at <a href="http://www.electropedia.org/">http://www.electropedia.org/</a>

#### 3.1

#### waterline

WL

intersection line of the water's surface with the craft's hull when the craft (3.15) is affoat

#### 3.2

### maximum load waterline

reference waterline

vv Lref

waterline (3.1) of the craft (3.15) when upright in the maximum loaded displacement (3.6)

#### 3.3

#### sheerline

intersection between deck and hull, for rounded deck edges the natural intersection, or, where no deck is fitted or the hull extends above the deck (bulwark), the upper edge of the craft's hull

Note 1 to entry: The upper position of the sheerline depends on the inclination between the hull/deck intersection and the actual deck.

#### 3.4

#### transom beam

 $B_{\text{\tiny T}}$ 

maximum width of the hull at the transom at or below the *sheerline* (3.3), excluding extensions, handles and fittings

Note 1 to entry: Where spray rails act as chines or part of the planing surface, they are included in the transom beam measurement.

Note 2 to entry: For craft (3.15) with a rounded or pointed stern or with a transom beam of less than half the maximum beam of the craft, the transom beam,  $B_{\rm T}$ , is the widest beam at or below the sheerline at the aft quarter length of the hull.

#### ISO/FDIS 8666:2020(E)

#### 3.5

#### displacement

mass of water displaced by the *craft* (3.15), including all appendages

#### loaded displacement

mass of water displaced by the *craft* (3.15), including all appendages, when in the fully loaded readyfor-use condition

Note 1 to entry: Fully loaded ready-for use condition is described in 7.3.

#### 3.7

#### displacement volume

 $V_{\rm D}$ 

volume of water displaced by the *craft* (3.15) that corresponds to the *displacement* (3.5)

Note 1 to entry: Where the density of water used to calculate the volume of displacement is not salt water at a density of 1 025 kg/m<sup>3</sup>, the density of water used to calculate the volume of displacement is specified.

#### 3.8

#### tank capacity

net usable volume of the tank(s) for the craft (3.15) in design trim (3.13) at rest at the maximum load waterline (3.2)

#### 3.9

wing mast spar characterized by its cross-section which shows a smooth transition at the aft end into the sail, thus, contributing to its driving force

3.10 non-sailing boat craft (3.15) for which the primary means of propulsion is other than by wind power, having reference sail area (3.12)  $(A_S)$  < 0,07  $(m_{I.D.C})^{2/3}$ 

#### 3.11

#### sailing boat

craft (3.15) for which the primary means of propulsion is by wind power, having reference sail area  $(3.12) (A_S) \ge 0.07 (m_{LDC})^{2/3}$ 

#### 3.12

#### reference sail area

actual profile area of sails set abaft a mast, plus the maximum profile areas of all masts, plus reference triangle area(s) forward of each mast

#### 3.13

#### design trim

longitudinal attitude of the craft (3.15) when upright, with crew, fluids, stores, and equipment in the position(s) and load condition(s) designated by the designer or builder

#### 3.14

#### underway

not at anchor, or made fast to the shore, or aground

#### 3.15

#### craft

#### small craft

recreational boat, and other watercraft using similar equipment, of up to 24 m length of hull  $(L_{\rm H})$ 

### 4 Symbols, designations and units

Unless specifically otherwise defined, the symbols, designations and units used in this document are given in  $\underline{\text{Table 1}}$ .

Table 1 — Symbols, designations and units

Symbol	Designation	Unit	Clause
$A_{ m lV}$	Windage area	m <sup>2</sup>	<u>5.5.4</u>
$A_{\mathrm{S}}$	Reference sail area	m <sup>2</sup>	<u>5.5.2</u>
A' <sub>S</sub>	Standard sail area	m <sup>2</sup>	<u>5.5.3</u>
$B_{\mathrm{CB}}$	Beam between hull centres	m	<u>5.3.6</u>
$B_{ m H}$	Beam of hull	m	<u>5.3.3</u>
$B_{\max}$	Maximum beam	m	<u>5.3.2</u>
$B_{ m WL}$	Beam, waterline	m	<u>5.3.4</u>
$B_{ m WLmax}$	Maximum beam, waterline	m	<u>5.3.5</u>
$B_{ m T}$	Transom beam	, m	<u>3.4</u>
$D_{\max}$	Maximum depth	m oge	<u>5.4.1</u>
$D_{\mathrm{LWL/2}}$	Midship depth	m ash	<u>5.4.2</u>
F	Freeboard	m <sub>M</sub> A3aco.A	<u>5.4.3</u>
$F_{A}$	Freeboard Freeboard, aft Freeboard, forward Freeboard, amidships Draught, air Length of the hull	ash o so	<u>5.4.3.2</u>
$F_{ m F}$	Freeboard, forward	d. dard mist	5.4.3.4
$F_{M}$	Freeboard, amidships	Stall-Pim	<u>5.4.3.3</u>
$H_{\rm a}$	Draught, air Length of the hull Maximum length Waterline length  Cross shipping mass	m m	<u>5.4.5</u>
$L_{ m H}$	Length of the hull	m	<u>5.2.3</u>
$L_{\max}$	Maximum length	m	<u>5.2.2</u>
$L_{ m WL}$	Waterline length	m	<u>5.2.4</u>
$m_{\mathrm{G}}$	Gross shipping mass	kg	<u>6.2</u>
$m_{ m LDC}$	Length of the hull  Maximum length  Waterline length  Gross shipping mass  Loaded displacement  Light craft mass	kg	<u>3.6</u>
$m_{ m LC}$	Light craft mass	kg	<u>6.3</u>
$m_{ m N}$	Net shipping mass	kg	<u>6.1</u>
$m_{ m P}$	Performance test mass	kg	<u>6.4</u>
$m_{ m T}$	Mass of craft when towed on trailer	kg	<u>6.5</u>
$m_{ m ML}$	Maximum load	kg	<u>6.6</u>
T	Draught	m	<u>5.4.4</u>
$T_{C}$	Draught, canoe body	m	<u>5.4.4.4</u>
$T_{\max}$	Draught, maximum	m	<u>5.4.4.2</u>
$T_{\min}$	Draught, minimum	m	<u>5.4.4.3</u>
$V_{ m D}$	Displacement volume	m <sup>3</sup>	<u>3.7</u>
V	Volume of the craft	m <sup>3</sup>	<u>5.5.5</u>
$V_{ m H}$	Volume of the hull	m <sup>3</sup>	<u>5.5.5.2</u>
$V_{ m S}$	Volume of the superstructure	m <sup>3</sup>	<u>5.5.5.3</u>
WL	Waterline		<u>3.1</u>
$WL_{ref}$	Maximum load waterline		<u>3.2</u>
β	Deadrise angle	degrees	<u>5.5.1</u>