
Mala plovila - Gorljive cevi za gorivo (ISO/DIS 8469:2020)

Small craft - Non-fire-resistant fuel hoses (ISO/DIS 8469:2020)

Kleine Wasserfahrzeuge - Nicht feuerwiderstandsfähige Kraftstoffschläuche (ISO/DIS 8469:2020)

Petits navires - Tuyaux souples pour carburant non résistants au feu (ISO/DIS 8469:2020)

STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: prEN ISO 8469

<https://standards.iteh.ai/catalog/standards/sist/6056942a-3c02-4266-a575-1154f3b559ae/ksist-fpren-iso-8469-2020>

ICS:

13.220.40	Sposobnost vžiga in obnašanje materialov in proizvodov pri gorenju	Ignitability and burning behaviour of materials and products
47.020.30	Sistemi cevi	Piping systems
47.080	Čolni	Small craft

oSIST prEN ISO 8469:2020

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[kSIST FprEN ISO 8469:2020](https://standards.iteh.ai/catalog/standards/sist/6056942a-3c02-4266-a575-1154f3b559ae/ksist-fpren-iso-8469-2020)

<https://standards.iteh.ai/catalog/standards/sist/6056942a-3c02-4266-a575-1154f3b559ae/ksist-fpren-iso-8469-2020>

DRAFT INTERNATIONAL STANDARD

ISO/DIS 8469

ISO/TC 188

Secretariat: SIS

Voting begins on:
2020-02-19Voting terminates on:
2020-05-13

Small craft — Non-fire-resistant fuel hoses

Petits navires — Tuyaux souples pour carburant non résistants au feu

ICS: 47.080

iTeh STANDARD PREVIEW (standards.iteh.ai)

[kSIST FprEN ISO 8469:2020](https://standards.iteh.ai/catalog/standards/sist/6056942a-3c02-4266-a575-1154f3b559ae/ksist-fpren-iso-8469-2020)<https://standards.iteh.ai/catalog/standards/sist/6056942a-3c02-4266-a575-1154f3b559ae/ksist-fpren-iso-8469-2020>

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.

ISO/CEN PARALLEL PROCESSING



Reference number
ISO/DIS 8469:2020(E)

© ISO 2020

iTeh STANDARD PREVIEW (standards.iteh.ai)

[kSIST FprEN ISO 8469:2020
https://standards.iteh.ai/catalog/standards/sist/6056942a-3c02-4266-a575-
1154f3b559ae/ksist-fpren-iso-8469-2020](https://standards.iteh.ai/catalog/standards/sist/6056942a-3c02-4266-a575-1154f3b559ae/ksist-fpren-iso-8469-2020)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 General requirements	2
5 Hose inner diameter	2
6 Physical tests on finished hose	2
6.1 General	2
6.2 Test liquids	3
6.3 Bursting pressure	3
6.4 Vacuum collapse test	3
6.5 Volume change in test liquids	3
6.6 Mass reduction of test hose	3
6.7 Effect of ozone	4
6.8 Fuel permeation	4
6.9 Cold flex test	4
6.10 Abrasion test —	4
6.11 Dry heat resistance test	5
6.12 Oil resistance test	5
6.13 Adhesion test	5
7 Marking	5
Annex A (normative) Fuel permeation test (or equivalent test method)	6
Annex ZA (informative) Relationship between this European Standard and the essential requirements of Directive 2013/53/EU aimed to be covered	8
Bibliography	9

ISO/DIS 8469:2020(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 188, *Small craft*.

This fourth edition cancels and replaces the third edition (ISO 8469:2013), which has been technically revised.

The main changes compared to the previous edition are as follows:

- requirements for low permeation fuel hoses have been added;
- clarifies the test fluids for petrol;
- test fixture Figure A.1 has been revised to remove the vented capillary tube.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Small craft — Non-fire-resistant fuel hoses

1 Scope

This document specifies general requirements and physical tests for non-fire-resistant hoses for conveying petrol or petrol blended with ethanol, and diesel fuel or diesel fuel blended with FAME, designed for a working pressure not exceeding 0,34 MPa for hoses with inner diameter up to and including 10 mm and 0,25 MPa for hoses up to 63 mm inner diameter in craft of hull length up to 24 m.

It applies to hoses for small craft with permanently installed fuel systems.

Specifications for fire-resistant hoses are given in ISO 7840: 2004. Specifications for permanently installed fuel systems are given in ISO 10088:2009.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1307:2006, *Rubber and plastics hoses — Hose sizes, minimum and maximum inside diameters, and tolerances on cut-to-length hoses*

ISO 1402:2009, *Rubber and plastics hoses and hose assemblies — Hydrostatic testing*

ISO 1817:2015, *Rubber, vulcanized or thermoplastic — Determination of the effect of liquids*

ISO 7233:2016, *Rubber and plastics hoses and hose assemblies — Determination of resistance to vacuum*

ISO 7326:2016, *Rubber and plastics hoses — Assessment of ozone resistance under static conditions*

EN 14214:2012+A2:2019, *Automotive fuels — Fatty acid methyl esters (FAME) for diesel engines — Requirements and test methods*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

FAME

Fatty Acid Methyl Esters

esters of fatty acids. The physical characteristics of fatty acid esters are closer to those of fossil diesel fuels than pure vegetable oils, but properties depend on the type of vegetable oil

3.2

tube

interior liner of the fuel hose that is normally in contact with the fuel.

ISO/DIS 8469:2020(E)

4 General requirements

Hoses complying with this International Standard shall present a smooth inner surface free from pores, other defects and chemical contaminants.

Hoses shall demonstrate suitability for marine use by complying with the requirements of the tests in [Clause 6](#). Hoses intended to be used for both petrol and diesel fuels must be tested with both test fluids separately in sections requiring preconditioning. They shall be marked according to [Clause 7](#).

5 Hose inner diameter

[Table 1](#) gives some of the inner diameters based on series R 10 of ISO 3:1973. Tolerances shall conform to ISO 1307:2006.

Table 1 — Inner diameters and tolerances

Dimensions in millimetres

Inner diameter, <i>d</i>	Tolerance
3,2	± 0,5
4	
5	
6,3	± 0,75
7	
8	
9,5	
10	
12,5	
16	
19	
20	
25	
31,5	
38	
40	± 1,5
50	
63	

6 Physical tests on finished hose

6.1 General

New samples shall be used for each of the tests below.

6.2 Test liquids

a) Petrol:

- 1) a mixture by volume of 90 % of liquid C specified in ISO 1817:2015, Table A.1 and 10 % by volume of ethanol. (CE10)

b) Diesel:

- 1) a mixture by volume of 90 % liquid F specified in ISO 1817:2015 and 10 % by volume of Fatty Acid Methyl Esters (FAME), specified in EN 14214:2012+A2:2019.

6.3 Bursting pressure

Fill three hoses or sample lengths from hoses with the applicable test liquids as specified in 6.2, and store them for 40 days in air at a temperature of $40\text{ °C} \pm 2\text{ °C}$. For type 15 fuel hose (see 6.9) the 40 day test period may be reduced to 28 days.

Empty the liquid out and fill the hoses or sample lengths with cold water, subject them to hydrostatic pressure as specified in ISO 1402:2009.

The bursting pressure shall be at least 1,4 MPa for hoses with an inner diameter of 10 mm or less and 1,00 MPa for hoses with an inner diameter of more than 10 mm.

6.4 Vacuum collapse test

Carry out the test in accordance with ISO 7233:2016, method A, using the test conditions specified in Table 2.

Table 2 — Pressure conditions for the vacuum collapse test

Inner diameter, d mm	Vacuum kPa
$d \leq 10$	80
$10 < d \leq 25$	35
$d > 25$	No test required

The test duration shall be 60 s and the diameter of the sphere $0,8 d$ (inner diameter of the hose). The sphere shall pass freely through the hose while under vacuum.

6.5 Volume change in test liquids

Determine the change of volume of the hose test sample (tube and cover) by the procedure specified in ISO 1817:2015. Completely submerge the test pieces in test liquids as specified in 6.2 at a temperature of $40\text{ °C} \pm 2\text{ °C}$ for 40 days.

If the hose is made of a homogeneous compound (with or without reinforcement), the swelling shall not exceed 35 % by volume as measured by displacement in water. For hose with an inner layer of fuel-resistant material and a cover of another material mainly intended for weather and ozone resistance, the increase in volume shall not exceed 35 % for the tube and 120 % for the cover.

6.6 Mass reduction of test hose

Determine the reduction in mass of the hose by the procedure specified in ISO 1817:2015. Fill three hoses or sample lengths from the hoses with test liquids, as specified in 6.2, and store them for 40 days in air at a temperature of $40\text{ °C} \pm 2\text{ °C}$. For type 15 fuel hose (see 6.9) the 40 day test period may be reduced to 28 days.