

ETSI TS 123 501 V17.12.0 (2024-04)



**5G;
System architecture for the 5G System (5GS)
(3GPP TS 23.501 version 17.12.0 Release 17)**

Document Preview

[ETSI TS 123 501 V17.12.0 \(2024-04\)](https://standards.iteh.ai/catalog/standards/etsi/1c597ae4-14e7-4b2b-be96-7922336bdbcd/etsi-ts-123-501-v17-12-0-2024-04)

<https://standards.iteh.ai/catalog/standards/etsi/1c597ae4-14e7-4b2b-be96-7922336bdbcd/etsi-ts-123-501-v17-12-0-2024-04>



ReferenceRTS/TSGS-0223501vhc0

Keywords5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2024-04)

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	19
1 Scope	20
2 References	20
3 Definitions and abbreviations.....	25
3.1 Definitions	25
3.2 Abbreviations	31
4 Architecture model and concepts	34
4.1 General concepts	34
4.2 Architecture reference model	35
4.2.1 General.....	35
4.2.2 Network Functions and entities	36
4.2.3 Non-roaming reference architecture	37
4.2.4 Roaming reference architectures.....	40
4.2.5 Data Storage architectures	44
4.2.5a Radio Capabilities Signalling optimisation.....	45
4.2.6 Service-based interfaces	46
4.2.7 Reference points	47
4.2.8 Support of non-3GPP access.....	50
4.2.8.0 General	50
4.2.8.1 General Concepts to Support Trusted and Untrusted Non-3GPP Access	50
4.2.8.1A General Concepts to support Wireline Access	51
4.2.8.2 Architecture Reference Model for Trusted and Untrusted Non-3GPP Accesses	52
4.2.8.2.1 Non-roaming Architecture.....	52
4.2.8.2.2 LBO Roaming Architecture.....	53
4.2.8.2.3 Home-routed Roaming Architecture	55
4.2.8.3 Reference Points for Non-3GPP Access	57
4.2.8.3.1 Overview	57
4.2.8.3.2 Requirements on Ta.....	58
4.2.8.4 Architecture Reference Model for Wireline Access network.....	58
4.2.8.5 Access to 5GC from devices that do not support 5GC NAS over WLAN access.....	59
4.2.8.5.1 General	59
4.2.8.5.2 Reference Architecture	60
4.2.8.5.3 Network Functions	60
4.2.8.5.4 Reference Points	60
4.2.9 Network Analytics architecture	61
4.2.10 Architecture Reference Model for ATSSS Support.....	61
4.2.11 Architecture for 5G multicast-broadcast services	62
4.2.12 Architecture for Proximity based Services (ProSe) in 5GS	62
4.2.13 Architecture enhancements for Edge Computing	62
4.2.14 Architecture for Support of Uncrewed Aerial Systems connectivity, identification and tracking	63
4.2.15 Architecture to support WLAN connection using 5G credentials without 5GS registration	63
4.3 Interworking with EPC.....	64
4.3.1 Non-roaming architecture	64
4.3.2 Roaming architecture	65
4.3.3 Interworking between 5GC via non-3GPP access and E-UTRAN connected to EPC.....	67
4.3.3.1 Non-roaming architecture	67
4.3.3.2 Roaming architecture	68
4.3.4 Interworking between ePDG connected to EPC and 5GS	70
4.3.4.1 Non-roaming architecture	70
4.3.4.2 Roaming architectures.....	71
4.3.5 Service Exposure in Interworking Scenarios	73

4.3.5.1	Non-roaming architecture	73
4.3.5.2	Roaming architectures.....	74
4.4	Specific services	75
4.4.1	Public Warning System	75
4.4.2	SMS over NAS	75
4.4.2.0	General	75
4.4.2.1	Architecture to support SMS over NAS	75
4.4.2.2	Reference point to support SMS over NAS	77
4.4.2.3	Service based interface to support SMS over NAS	77
4.4.3	IMS support	77
4.4.4	Location services	78
4.4.4.1	Architecture to support Location Services	78
4.4.4.2	Reference point to support Location Services.....	78
4.4.4.3	Service Based Interfaces to support Location Services.....	78
4.4.5	Application Triggering Services	78
4.4.6	5G LAN-type Services.....	78
4.4.6.1	User plane architecture to support 5G LAN-type service	78
4.4.6.2	Reference points to support 5G LAN-type service	79
4.4.7	MSISDN-less MO SMS Service.....	79
4.4.8	Architecture to enable Time Sensitive Communication and Time Synchronization	79
4.4.8.1	General	79
4.4.8.2	Architecture to support IEEE Time Sensitive Networking	79
4.4.8.3	Architecture for AF requested support of Time Sensitive Communication and Time Synchronization	80
5	High level features.....	81
5.1	General	81
5.2	Network Access Control	82
5.2.1	General.....	82
5.2.2	Network selection	82
5.2.2a	Void	82
5.2.3	Identification and authentication.....	82
5.2.4	Authorisation	82
5.2.5	Access control and barring	82
5.2.6	Policy control.....	83
5.2.7	Lawful Interception.....	83
5.3	Registration and Connection Management.....	83
5.3.1	General.....	83
5.3.2	Registration Management	83
5.3.2.1	General	83
5.3.2.2	5GS Registration Management states.....	84
5.3.2.2.1	General	84
5.3.2.2.2	RM-DEREGISTERED state.....	84
5.3.2.2.3	RM-REGISTERED state	84
5.3.2.2.4	5GS Registration Management State models	85
5.3.2.3	Registration Area management	85
5.3.2.4	Support of a UE registered over both 3GPP and Non-3GPP access	87
5.3.3	Connection Management	88
5.3.3.1	General	88
5.3.3.2	5GS Connection Management states.....	89
5.3.3.2.1	General	89
5.3.3.2.2	CM-IDLE state	89
5.3.3.2.3	CM-CONNECTED state	89
5.3.3.2.4	5GS Connection Management State models	90
5.3.3.2.5	CM-CONNECTED with RRC Inactive state	90
5.3.3.3	NAS signalling connection management	92
5.3.3.3.1	General	92
5.3.3.3.2	NAS signalling connection establishment	93
5.3.3.3.3	NAS signalling connection Release.....	93
5.3.3.4	Support of a UE connected over both 3GPP and Non-3GPP access	93
5.3.4	UE Mobility.....	93
5.3.4.1	Mobility Restrictions.....	93

5.3.4.1.1	General	93
5.3.4.1.2	Management of Service Area Restrictions	96
5.3.4.2	Mobility Pattern	98
5.3.4.3	Radio Resource Management functions.....	98
5.3.4.3.1	General	98
5.3.4.3.2	Preferred band(s) per data radio bearer(s)	99
5.3.4.3.3	Redirection to dedicated frequency band(s) for an S-NSSAI	99
5.3.4.3.4	Network Slice based cell reselection and Random Access.....	100
5.3.4.4	UE mobility event notification	100
5.3.5	Triggers for network analytics	101
5.4	3GPP access specific aspects.....	101
5.4.1	UE reachability in CM-IDLE.....	101
5.4.1.1	General	101
5.4.1.2	UE reachability allowing mobile terminated data while the UE is CM-IDLE.....	102
5.4.1.3	Mobile Initiated Connection Only (MICO) mode.....	102
5.4.2	UE reachability in CM-CONNECTED.....	103
5.4.3	Paging strategy handling.....	104
5.4.3.1	General	104
5.4.3.2	Paging Policy Differentiation.....	104
5.4.3.3	Paging Priority	105
5.4.4	UE Radio Capability handling.....	105
5.4.4.1	UE radio capability information storage in the AMF.....	105
5.4.4.1a	UE radio capability signalling optimisation (RACS).....	106
5.4.4.2	Void.....	110
5.4.4.2a	UE Radio Capability Match Request	110
5.4.4.3	Paging assistance information.....	110
5.4.4a	UE MM Core Network Capability handling.....	111
5.4.4b	UE 5GSM Core Network Capability handling	112
5.4.5	DRX (Discontinuous Reception) framework.....	112
5.4.6	Core Network assistance information for RAN optimization.....	113
5.4.6.1	General	113
5.4.6.2	Core Network assisted RAN parameters tuning.....	113
5.4.6.3	Core Network assisted RAN paging information.....	114
5.4.7	NG-RAN location reporting	114
5.4.8	Support for identification and restriction of using unlicensed spectrum.....	115
5.4.9	Wake Up Signal Assistance	116
5.4.9.1	General	116
5.4.9.2	Group Wake Up Signal	116
5.4.10	Support for identification and restriction of using NR satellite access	116
5.4.11	Support for integrating NR satellite access into 5GS.....	117
5.4.11.1	General	117
5.4.11.2	Support of RAT types defined in 5GC for satellite access.....	117
5.4.11.3	Void.....	117
5.4.11.4	Verification of UE location	117
5.4.11.5	Network selection for NR satellite access	118
5.4.11.6	Support of Mobility Registration Update	118
5.4.11.7	Tracking Area handling for NR satellite access	118
5.4.11.8	Support for mobility Forbidden Area and Service Area Restrictions for NR satellite access	118
5.4.12	Paging Early Indication with Paging Subgrouping Assistance	119
5.4.12.1	General	119
5.4.12.2	Core Network Assistance for PEIPS	119
5.5	Non-3GPP access specific aspects	120
5.5.0	General.....	120
5.5.1	Registration Management	120
5.5.2	Connection Management	120
5.5.3	UE Reachability	122
5.5.3.1	UE reachability in CM-IDLE	122
5.5.3.2	UE reachability in CM-CONNECTED.....	122
5.6	Session Management	122
5.6.1	Overview	122
5.6.2	Interaction between AMF and SMF	125
5.6.3	Roaming.....	127

5.6.4	Single PDU Session with multiple PDU Session Anchors	128
5.6.4.1	General	128
5.6.4.2	Usage of an UL Classifier for a PDU Session.....	129
5.6.4.3	Usage of IPv6 multi-homing for a PDU Session.....	130
5.6.5	Support for Local Area Data Network.....	132
5.6.6	Secondary authentication/authorization by a DN-AAA server during the establishment of a PDU Session	134
5.6.7	Application Function influence on traffic routing	136
5.6.7.1	General	136
5.6.7.2	Enhancement of UP path management based on the coordination with AFs	143
5.6.8	Selective activation and deactivation of UP connection of existing PDU Session	144
5.6.9	Session and Service Continuity	145
5.6.9.1	General	145
5.6.9.2	SSC mode.....	145
5.6.9.2.1	SSC Mode 1.....	145
5.6.9.2.2	SSC Mode 2.....	146
5.6.9.2.3	SSC Mode 3.....	146
5.6.9.3	SSC mode selection.....	146
5.6.10	Specific aspects of different PDU Session types	147
5.6.10.1	Support of IP PDU Session type	147
5.6.10.2	Support of Ethernet PDU Session type	147
5.6.10.3	Support of Unstructured PDU Session type	149
5.6.10.4	Maximum Transfer Unit size considerations	150
5.6.11	UE presence in Area of Interest reporting usage by SMF.....	151
5.6.12	Use of Network Instance.....	152
5.6.13	Always-on PDU session	152
5.6.14	Support of Framed Routing	153
5.6.15	Triggers for network analytics.....	153
5.7	QoS model.....	154
5.7.1	General Overview	154
5.7.1.1	QoS Flow	154
5.7.1.2	QoS Profile.....	154
5.7.1.2a	Alternative QoS Profile.....	155
5.7.1.3	Control of QoS Flows	155
5.7.1.4	QoS Rules	156
5.7.1.5	QoS Flow mapping	156
5.7.1.6	DL traffic	158
5.7.1.7	UL Traffic	159
5.7.1.8	AMBR/MFBR enforcement and rate limitation.....	159
5.7.1.9	Precedence Value.....	160
5.7.1.10	UE-Slice-MBR enforcement and rate limitation.....	160
5.7.1.11	QoS aspects of home-routed roaming	160
5.7.2	5G QoS Parameters.....	161
5.7.2.1	5QI	161
5.7.2.2	ARP.....	161
5.7.2.3	RQA	161
5.7.2.4	Notification control	162
5.7.2.4.1	General	162
5.7.2.4.1a	Notification Control without Alternative QoS Profiles	162
5.7.2.4.1b	Notification control with Alternative QoS Profiles	162
5.7.2.4.2	Usage of Notification control with Alternative QoS Profiles at handover	163
5.7.2.4.3	Usage of Notification control with Alternative QoS Profiles during QoS Flow establishment and modification.....	164
5.7.2.5	Flow Bit Rates.....	164
5.7.2.6	Aggregate Bit Rates	165
5.7.2.7	Default values	165
5.7.2.8	Maximum Packet Loss Rate.....	166
5.7.2.9	Wireline access network specific 5G QoS parameters.....	166
5.7.3	5G QoS characteristics.....	166
5.7.3.1	General.....	166
5.7.3.2	Resource Type.....	167
5.7.3.3	Priority Level	167

5.7.3.4	Packet Delay Budget	167
5.7.3.5	Packet Error Rate	168
5.7.3.6	Averaging Window	168
5.7.3.7	Maximum Data Burst Volume	169
5.7.4	Standardized 5QI to QoS characteristics mapping	169
5.7.5	Reflective QoS	174
5.7.5.1	General	174
5.7.5.2	UE Derived QoS Rule	174
5.7.5.3	Reflective QoS Control	175
5.7.6	Packet Filter Set	176
5.7.6.1	General	176
5.7.6.2	IP Packet Filter Set	176
5.7.6.3	Ethernet Packet Filter Set	177
5.8	User Plane Management	177
5.8.1	General	177
5.8.2	Functional Description	178
5.8.2.1	General	178
5.8.2.2	UE IP Address Management	178
5.8.2.2.1	General	178
5.8.2.2.2	Routing rules configuration	180
5.8.2.2.3	The procedure of Stateless IPv6 Address Autoconfiguration	180
5.8.2.3	Management of CN Tunnel Info	181
5.8.2.3.1	General	181
5.8.2.3.2	Void	181
5.8.2.3.3	Management of CN Tunnel Info in the UPF	181
5.8.2.4	Traffic Detection	181
5.8.2.4.1	General	181
5.8.2.4.2	Traffic Detection Information	181
5.8.2.5	Control of User Plane Forwarding	182
5.8.2.5.1	General	182
5.8.2.5.2	Data forwarding between the SMF and UPF	182
5.8.2.5.3	Support of Ethernet PDU Session type	183
5.8.2.6	Charging and Usage Monitoring Handling	184
5.8.2.6.1	General	184
5.8.2.6.2	Activation of Usage Reporting in UPF	184
5.8.2.6.3	Reporting of Usage Information towards SMF	185
5.8.2.7	PDU Session and QoS Flow Policing	185
5.8.2.8	PCC Related Functions	185
5.8.2.8.1	Activation/Deactivation of predefined PCC rules	185
5.8.2.8.2	Enforcement of Dynamic PCC Rules	186
5.8.2.8.3	Redirection	186
5.8.2.8.4	Support of PFD Management	187
5.8.2.9	Functionality of Sending of "End marker"	187
5.8.2.9.0	Introduction	187
5.8.2.9.1	UPF Constructing the "End marker" Packets	187
5.8.2.9.2	SMF Constructing the "End marker" Packets	188
5.8.2.10	UP Tunnel Management	188
5.8.2.11	Parameters for N4 session management	188
5.8.2.11.1	General	188
5.8.2.11.2	N4 Session Context	190
5.8.2.11.3	Packet Detection Rule	190
5.8.2.11.4	QoS Enforcement Rule	193
5.8.2.11.5	Usage Reporting Rule	196
5.8.2.11.6	Forwarding Action Rule	199
5.8.2.11.7	Usage Report generated by UPF	202
5.8.2.11.8	Multi-Access Rule	203
5.8.2.11.9	Bridge Information	204
5.8.2.11.10	Void	204
5.8.2.11.11	Session Reporting Rule	204
5.8.2.11.12	Session reporting generated by UPF	205
5.8.2.11.13	Void	205
5.8.2.11.14	TSC Management Information	205

5.8.2.11.15	Downlink Data Report generated by UPF	206
5.8.2.12	Reporting of the UE MAC addresses used in a PDU Session	206
5.8.2.13	Support for 5G VN group communication.....	206
5.8.2.13.0	General	206
5.8.2.13.1	Support for unicast traffic forwarding of a 5G VN.....	207
5.8.2.13.2	Support for unicast traffic forwarding update due to UE mobility	208
5.8.2.13.3	Support for user plane traffic replication in a 5G VN	209
5.8.2.14	Inter PLMN User Plane Security functionality	211
5.8.2.15	Reporting of satellite backhaul to SMF.....	211
5.8.2.16	Support for L2TP tunnelling on N6	211
5.8.3	Explicit Buffer Management.....	212
5.8.3.1	General	212
5.8.3.2	Buffering at UPF	212
5.8.3.3	Buffering at SMF	213
5.8.4	SMF Pause of Charging.....	213
5.9	Identifiers	213
5.9.1	General.....	213
5.9.2	Subscription Permanent Identifier	213
5.9.2a	Subscription Concealed Identifier.....	214
5.9.3	Permanent Equipment Identifier	214
5.9.4	5G Globally Unique Temporary Identifier	214
5.9.5	AMF Name	215
5.9.6	Data Network Name (DNN)	215
5.9.7	Internal-Group Identifier.....	215
5.9.8	Generic Public Subscription Identifier.....	216
5.9.9	AMF UE NGAP ID	216
5.9.10	UE Radio Capability ID.....	216
5.10	Security aspects	216
5.10.1	General.....	216
5.10.2	Security Model for non-3GPP access	217
5.10.2.1	Signalling Security	217
5.10.3	PDU Session User Plane Security.....	217
5.11	Support for Dual Connectivity, Multi-Connectivity.....	219
5.11.1	Support for Dual Connectivity.....	219
5.12	Charging.....	220
5.12.1	General.....	220
5.12.2	Usage Data Reporting for Secondary RAT.....	220
5.12.3	Secondary RAT Periodic Usage Data Reporting Procedure.....	221
5.13	Support for Edge Computing.....	221
5.14	Policy Control	222
5.15	Network slicing	222
5.15.1	General.....	222
5.15.2	Identification and selection of a Network Slice: the S-NSSAI and the NSSAI	223
5.15.2.1	General	223
5.15.2.2	Standardised SST values	224
5.15.3	Subscription aspects.....	225
5.15.4	UE NSSAI configuration and NSSAI storage aspects	225
5.15.4.1	General	225
5.15.4.1.1	UE Network Slice configuration	225
5.15.4.1.2	Mapping of S-NSSAIs values in the Allowed NSSAI and in the Requested NSSAI to the S-NSSAIs values used in the HPLMN.....	228
5.15.4.2	Update of UE Network Slice configuration	228
5.15.5	Detailed Operation Overview	229
5.15.5.1	General	229
5.15.5.2	Selection of a Serving AMF supporting the Network Slices.....	229
5.15.5.2.1	Registration to a set of Network Slices.....	229
5.15.5.2.2	Modification of the Set of Network Slice(s) for a UE.....	234
5.15.5.2.3	AMF Re-allocation due to Network Slice(s) Support.....	236
5.15.5.3	Establishing a PDU Session in a Network Slice	236
5.15.6	Network Slicing Support for Roaming	237
5.15.7	Network slicing and Interworking with EPS	238
5.15.7.1	General	238

5.15.7.2	Idle mode aspects	238
5.15.7.3	Connected mode aspects	239
5.15.8	Configuration of Network Slice availability in a PLMN	239
5.15.9	Operator-controlled inclusion of NSSAI in Access Stratum Connection Establishment	240
5.15.10	Network Slice-Specific Authentication and Authorization	241
5.15.11	Network Slice Admission Control	242
5.15.11.0	General	242
5.15.11.1	Network Slice Admission Control for maximum number of UEs	243
5.15.11.2	Network Slice Admission Control for maximum number of PDU sessions	244
5.15.11.3	Network Slice Admission Control for Roaming	244
5.15.11.4	Network Slice status notifications and reports to a consumer NF	245
5.15.11.5	Support of Network Slice Admission Control and Interworking with EPC	245
5.15.12	Support of subscription-based restrictions to simultaneous registration of network slices	246
5.15.12.1	General	246
5.15.12.2	UE and UE configuration aspects	247
5.15.13	Support of data rate limitation per Network Slice for a UE	248
5.15.14	Network Slice AS Groups support	248
5.16	Support for specific services	249
5.16.1	Public Warning System	249
5.16.2	SMS over NAS	249
5.16.2.1	General	249
5.16.2.2	SMS over NAS transport	250
5.16.3	IMS support	250
5.16.3.1	General	250
5.16.3.2	IMS voice over PS Session Supported Indication over 3GPP access	250
5.16.3.2a	IMS voice over PS Session Supported Indication over non-3GPP access	251
5.16.3.3	Homogeneous support for IMS voice over PS Session supported indication	251
5.16.3.4	P-CSCF address delivery	252
5.16.3.5	Domain selection for UE originating sessions / calls	252
5.16.3.6	Terminating domain selection for IMS voice	253
5.16.3.7	UE's usage setting	253
5.16.3.8	Domain and Access Selection for UE originating SMS	253
5.16.3.8.1	UE originating SMS for IMS Capable UEs supporting SMS over IP	253
5.16.3.8.2	Access Selection for SMS over NAS	253
5.16.3.9	SMF support for P-CSCF restoration procedure	254
5.16.3.10	IMS Voice Service via EPS Fallback or RAT fallback in 5GS	254
5.16.3.11	P-CSCF discovery and selection	254
5.16.3.12	HSS discovery and selection	255
5.16.4	Emergency Services	255
5.16.4.1	Introduction	255
5.16.4.2	Architecture Reference Model for Emergency Services	258
5.16.4.3	Mobility Restrictions and Access Restrictions for Emergency Services	258
5.16.4.4	Reachability Management	258
5.16.4.5	SMF and UPF selection function for Emergency Services	259
5.16.4.6	QoS for Emergency Services	259
5.16.4.7	PCC for Emergency Services	259
5.16.4.8	IP Address Allocation	259
5.16.4.9	Handling of PDU Sessions for Emergency Services	259
5.16.4.9a	Handling of PDU Sessions for normal services for Emergency Registered UEs	260
5.16.4.10	Support of eCall Only Mode	260
5.16.4.11	Emergency Services Fallback	260
5.16.5	Multimedia Priority Services	261
5.16.6	Mission Critical Services	263
5.17	Interworking and Migration	264
5.17.1	Support for Migration from EPC to 5GC	264
5.17.1.1	General	264
5.17.1.2	User Plane management to support interworking with EPS	266
5.17.1.3	QoS handling for home routed roaming	266
5.17.2	Interworking with EPC	266
5.17.2.1	General	266
5.17.2.2	Interworking Procedures with N26 interface	270
5.17.2.2.1	General	270

5.17.2.2.2	Mobility for UEs in single-registration mode	270
5.17.2.3	Interworking Procedures without N26 interface	271
5.17.2.3.1	General	271
5.17.2.3.2	Mobility for UEs in single-registration mode	272
5.17.2.3.3	Mobility for UEs in dual-registration mode	273
5.17.2.3.4	Redirection for UEs in connected state	274
5.17.2.4	Mobility between 5GS and GERAN/UTRAN	274
5.17.3	Interworking with EPC in presence of Non-3GPP PDU Sessions	276
5.17.4	Network sharing support and interworking between EPS and 5GS	276
5.17.5	Service Exposure in Interworking Scenarios	276
5.17.5.1	General	276
5.17.5.2	Support of interworking for Monitoring Events	277
5.17.5.2.1	Interworking with N26 interface	277
5.17.5.2.2	Interworking without N26 interface	277
5.17.5.3	Availability or expected level of a service API	277
5.17.6	Void	278
5.17.7	Configuration Transfer Procedure between NG-RAN and E-UTRAN	278
5.17.7.1	Architecture Principles for Configuration Transfer between NG-RAN and E-UTRAN	278
5.17.7.2	Addressing, routing and relaying	279
5.17.7.2.1	Addressing	279
5.17.7.2.2	Routing	279
5.17.7.2.3	Relaying	280
5.18	Network Sharing	280
5.18.1	General concepts	280
5.18.2	Broadcast system information for network sharing	281
5.18.2a	PLMN list handling for network sharing	281
5.18.3	Network selection by the UE	281
5.18.4	Network selection by the network	282
5.18.5	Network Sharing and Network Slicing	282
5.19	Control Plane Load Control, Congestion and Overload Control	282
5.19.1	General	282
5.19.2	TNLA Load Balancing and TNLA Load Re-Balancing	283
5.19.3	AMF Load Balancing	283
5.19.4	AMF Load Re-Balancing	283
5.19.5	AMF Control Of Overload	284
5.19.5.1	General	284
5.19.5.2	AMF Overload Control	284
5.19.6	SMF Overload Control	285
5.19.7	NAS level congestion control	285
5.19.7.1	General	285
5.19.7.2	General NAS level congestion control	285
5.19.7.3	DNN based congestion control	286
5.19.7.4	S-NSSAI based congestion control	288
5.19.7.5	Group specific NAS level congestion control	289
5.19.7.6	Control Plane data specific NAS level congestion control	289
5.20	External Exposure of Network Capability	290
5.20a	Data Collection from an AF	292
5.21	Architectural support for virtualized deployments	292
5.21.0	General	292
5.21.1	Architectural support for N2	292
5.21.1.1	TNL associations	292
5.21.1.2	NGAP UE-TNLA-binding	293
5.21.1.3	N2 TNL association selection	293
5.21.2	AMF Management	293
5.21.2.1	AMF Addition/Update	293
5.21.2.2	AMF planned removal procedure	294
5.21.2.2.1	AMF planned removal procedure with UDSF deployed	294
5.21.2.2.2	AMF planned removal procedure without UDSF	295
5.21.2.3	Procedure for AMF Auto-recovery	297
5.21.3	Network Reliability support with Sets	298
5.21.3.1	General	298
5.21.3.2	NF Set and NF Service Set	299

5.21.3.3	Reliability of NF instances within the same NF Set.....	299
5.21.3.4	Reliability of NF Services	299
5.21.4	Network Function/NF Service Context Transfer	299
5.21.4.1	General	299
5.22	System Enablers for priority mechanism.....	300
5.22.1	General.....	300
5.22.2	Subscription-related Priority Mechanisms	300
5.22.3	Invocation-related Priority Mechanisms	301
5.22.4	QoS Mechanisms applied to established QoS Flows	302
5.23	Supporting for Asynchronous Type Communication	302
5.24	3GPP PS Data Off	303
5.25	Support of OAM Features	304
5.25.1	Support of Tracing: Signalling Based Activation/Deactivation of Tracing	304
5.25.2	Support of OAM-based 5G VN group management.....	304
5.25.3	Signalling Based Activation of QoE Measurement Collection.....	304
5.26	Configuration Transfer Procedure.....	305
5.26.1	Architecture Principles for Configuration Transfer	305
5.26.2	Addressing, routing and relaying.....	305
5.26.2.1	Addressing	305
5.26.2.2	Routing.....	306
5.26.2.3	Relaying.....	306
5.27	Enablers for Time Sensitive Communications and Time Synchronization	306
5.27.0	General.....	306
5.27.1	Time Synchronization.....	306
5.27.1.1	General	306
5.27.1.2	Distribution of timing information.....	308
5.27.1.2.1	Distribution of 5G internal system clock.....	308
5.27.1.2.2	Distribution of grandmaster clock and time-stamping.....	308
5.27.1.3	Support for multiple (g)PTP domains	311
5.27.1.4	DS-TT and NW-TT Time Synchronization functionality	311
5.27.1.5	Detection of (g)PTP Sync and Announce timeouts.....	312
5.27.1.6	Distribution of Announce messages and best master clock selection	313
5.27.1.7	Support for PTP grandmaster function in 5GS.....	314
5.27.1.8	Exposure of Time Synchronization.....	314
5.27.1.9	Support for derivation of Uu time synchronization error budget	315
5.27.1a	Periodic deterministic communication.....	316
5.27.2	TSC Assistance Information (TSCAI) and TSC Assistance Container (TSCAC).....	316
5.27.2.1	General	316
5.27.2.2	TSC Assistance Container determination based on PSFP.....	317
5.27.2.3	TSC Assistance Container determination by TSCTSF.....	318
5.27.2.4	TSCAI determination based on TSC Assistance Container	318
5.27.3	Support for TSC QoS Flows	319
5.27.4	Hold and Forward Buffering mechanism.....	320
5.27.5	5G System Bridge delay	320
5.28	Support of integration with TSN, Time Sensitive Communications and Time Synchronization	321
5.28.1	5GS bridge management for TSN.....	321
5.28.2	5GS Bridge configuration for TSN.....	323
5.28.3	Port and user plane node management information exchange in 5GS	324
5.28.3.1	General	324
5.28.3.2	Transfer of port or user plane node management information	326
5.28.3.3	VLAN Configuration Information for TSN	326
5.28.4	QoS mapping tables for TSN.....	326
5.29	Support for 5G LAN-type service	328
5.29.1	General.....	328
5.29.2	5G VN group management	328
5.29.3	PDU Session management.....	329
5.29.4	User Plane handling	330
5.30	Support for non-public networks.....	331
5.30.1	General.....	331
5.30.2	Stand-alone non-public networks	331
5.30.2.0	General	331
5.30.2.1	Identifiers	332

5.30.2.2	Broadcast system information.....	332
5.30.2.3	UE configuration and subscription aspects	333
5.30.2.4	Network selection in SNPN access mode	334
5.30.2.4.1	General	334
5.30.2.4.2	Automatic network selection	335
5.30.2.4.3	Manual network selection.....	335
5.30.2.5	Network access control	335
5.30.2.6	Cell (re-)selection in SNPN access mode.....	336
5.30.2.7	Access to PLMN services via stand-alone non-public networks.....	336
5.30.2.8	Access to stand-alone non-public network services via PLMN	336
5.30.2.9	SNPN connectivity for UEs with credentials owned by Credentials Holder	337
5.30.2.9.1	General	337
5.30.2.9.2	Credentials Holder using AAA Server for primary authentication and authorization	337
5.30.2.9.3	Credentials Holder using AUSF and UDM for primary authentication and authorization.....	338
5.30.2.10	Onboarding of UEs for SNPNs	339
5.30.2.10.1	General	339
5.30.2.10.2	Onboarding Network is an SNPN	340
5.30.2.10.3	Onboarding Network is a PLMN.....	345
5.30.2.10.4	Remote Provisioning of UEs in Onboarding Network	345
5.30.2.11	UE Mobility support for SNPN.....	347
5.30.3	Public Network Integrated NPN	347
5.30.3.1	General	347
5.30.3.2	Identifiers	348
5.30.3.3	UE configuration, subscription aspects and storage.....	348
5.30.3.4	Network and cell (re-)selection, and access control.....	349
5.30.3.5	Support of emergency services in CAG cells.....	350
5.31	Support for Cellular IoT	350
5.31.1	General.....	350
5.31.2	Preferred and Supported Network Behaviour	351
5.31.3	Selection, steering and redirection between EPS and 5GS	351
5.31.4	Control Plane CIoT 5GS Optimisation	352
5.31.4.1	General	352
5.31.4.2	Establishment of N3 data transfer during Data Transport in Control Plane CIoT 5GS Optimisation.....	353
5.31.4.3	Control Plane Relocation Indication procedure	354
5.31.5	Non-IP Data Delivery (NIDD).....	354
5.31.6	Reliable Data Service.....	354
5.31.7	Power Saving Enhancements.....	355
5.31.7.1	General	355
5.31.7.2	Extended Discontinuous Reception (DRX) for CM-IDLE and CM-CONNECTED with RRC-INACTIVE.....	355
5.31.7.2.1	Overview	355
5.31.7.2.2	Paging for extended idle mode DRX in E-UTRA and NR connected to 5GC	357
5.31.7.2.3	Paging for a UE registered in a tracking area with heterogeneous support of extended idle mode DRX.....	358
5.31.7.3	MICO mode with Extended Connected Time	358
5.31.7.4	MICO mode with Active Time	358
5.31.7.5	MICO mode and Periodic Registration Timer Control	359
5.31.8	High latency communication.....	359
5.31.9	Support for Monitoring Events	360
5.31.10	NB-IoT UE Radio Capability Handling.....	361
5.31.11	Inter-RAT idle mode mobility to and from NB-IoT	361
5.31.12	Restriction of use of Enhanced Coverage	361
5.31.13	Paging for Enhanced Coverage.....	362
5.31.14	Support of rate control of user data.....	363
5.31.14.1	General	363
5.31.14.2	Serving PLMN Rate Control.....	363
5.31.14.3	Small Data Rate Control	363
5.31.15	Control Plane Data Transfer Congestion Control	365
5.31.16	Service Gap Control.....	365
5.31.17	Inter-UE QoS for NB-IoT.....	366
5.31.18	User Plane CIoT 5GS Optimisation.....	366

5.31.19	QoS model for NB-IoT	367
5.31.20	Category M UEs differentiation.....	368
5.32	Support for ATSSS.....	368
5.32.1	General.....	368
5.32.2	Multi Access PDU Sessions	370
5.32.3	Policy for ATSSS Control	372
5.32.4	QoS Support.....	372
5.32.5	Access Network Performance Measurements.....	374
5.32.5.1	General principles	374
5.32.5.1a	Address of PMF messages	376
5.32.5.2	Round Trip Time Measurements.....	377
5.32.5.2a	Packet Loss Rate Measurements	378
5.32.5.3	Access Availability/Unavailability Report.....	378
5.32.5.4	Protocol stack for user plane measurements and measurement reports.....	379
5.32.5.5	UE Assistance Operation	380
5.32.6	Support of Steering Functionalities	380
5.32.6.1	General	380
5.32.6.2	High-Layer Steering Functionalities	382
5.32.6.2.1	MPTCP Functionality.....	382
5.32.6.3	Low-Layer Steering Functionalities.....	383
5.32.6.3.1	ATSSS-LL Functionality.....	383
5.32.7	Interworking with EPS.....	384
5.32.7.1	General	384
5.32.7.2	Interworking with N26 Interface.....	384
5.32.7.3	Interworking without N26 Interface.....	385
5.32.8	ATSSS Rules	385
5.33	Support for Ultra Reliable Low Latency Communication.....	388
5.33.1	General.....	388
5.33.2	Redundant transmission for high reliability communication	389
5.33.2.1	Dual Connectivity based end to end Redundant User Plane Paths.....	389
5.33.2.2	Support of redundant transmission on N3/N9 interfaces	391
5.33.2.3	Support for redundant transmission at transport layer	393
5.33.3	QoS Monitoring to Assist URLLC Service	393
5.33.3.1	General	393
5.33.3.2	Per QoS Flow per UE QoS Monitoring.....	393
5.33.3.3	GTP-U Path Monitoring.....	394
5.34	Support of deployments topologies with specific SMF Service Areas.....	395
5.34.1	General.....	395
5.34.2	Architecture	396
5.34.2.1	SBA architecture	396
5.34.2.2	Non-roaming architecture	396
5.34.2.3	Roaming architecture	397
5.34.3	I-SMF selection, V-SMF reselection	398
5.34.4	Usage of an UL Classifier for a PDU Session controlled by I-SMF.....	399
5.34.5	Usage of IPv6 multi-homing for a PDU Session controlled by I-SMF.....	400
5.34.6	Interaction between I-SMF and SMF for the support of traffic offload by UPF controlled by the I-SMF	400
5.34.6.1	General	400
5.34.6.2	N4 information sent from SMF to I-SMF for local traffic offload.....	401
5.34.7	Event Management	402
5.34.7.1	UE's Mobility Event Management	402
5.34.7.2	SMF event exposure service	402
5.34.7.3	AMF implicit subscription about events related with the PDU Session	402
5.34.8	Support for Cellular IoT	403
5.34.9	Support of the Deployment Topologies with specific SMF Service Areas feature within and between PLMN(s).....	403
5.34.10	Support for 5G LAN-type service.....	403
5.35	Support for Integrated access and backhaul (IAB).....	403
5.35.1	IAB architecture and functional entities	403
5.35.2	5G System enhancements to support IAB	405
5.35.3	Data handling and QoS support with IAB	405
5.35.4	Mobility support with IAB	405