



SLOVENSKI STANDARD
SIST EN 300 417-2-2 V1.1.2:2003
01-december-2003

DfYbcg]b`a i `hjd`Y_g]fUb`Y`fHAŁŁ; YbYf] bY`nU hYj Y`nUdfYbcgbc`Z b_V]cbUbcgh
cdfYa YĚ &&"XY. : i b_W]Y`Zn] bY[UcXgY_Ud`Ugh]`nUg]b\ fcbc`X][]HJbc \]YfU\]c
fG8 <Ł]b`d`Yn]c\ fcbc`X][]HJbc \]YfU\]c`fD8 <ŁĚDfcZfa UgdYW]Z_UW]U]nUj Y`c
g_`UXbcgh]`nj YXVY`fŁ GL

Transmission and Multiplexing (TM); Generic requirements of transport functionality of equipment; Part 2-2: Synchronous Digital Hierarchy (SDH) and Plesiochronous Digital Hierarchy (PDH) physical section layer functions; Implementation Conformance Statement (ICS) proforma specification

(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/2dd66971-44ab-4f2d-984d-de486ce3f294/sist-en-300-417-2-2-v1-1-2-2003>

Ta slovenski standard je istoveten z: EN 300 417-2-2 Version 1.1.2

ICS:

33.040.20 Prenosni sistem Transmission systems

SIST EN 300 417-2-2 V1.1.2:2003 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 417-2-2 V1.1.2:2003

<https://standards.iteh.ai/catalog/standards/sist/2dd66971-44ab-4f2d-984d-de486ce3f294/sist-en-300-417-2-2-v1-1-2-2003>

EN 300 417-2-2 V1.1.2 (1998-11)

European Standard (Telecommunications series)

**Transmission and Multiplexing (TM);
Generic requirements of transport functionality of equipment;
Part 2-2: Synchronous Digital Hierarchy (SDH) and
Plesiochronous Digital Hierarchy (PDH)
physical section layer functions;
Implementation Conformance Statement (ICS)
proforma specification**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 417-2-2 V1.1.2:2003](https://standards.iteh.ai/catalog/standards/sist/2dd66971-44ab-4f2d-984d-de486ce3f294/sist-en-300-417-2-2-v1-1-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/2dd66971-44ab-4f2d-984d-de486ce3f294/sist-en-300-417-2-2-v1-1-2-2003>



Reference

REN/TM-01015-2-2 (3v0iiddc.PDF)

Keywords

ICS, PDH, SDH, STM, transmission, testing

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C

Association à but non lucratif enregistrée à la

Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr

Individual copies of this ETSI deliverable

can be downloaded from

<http://www.etsi.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1998.
All rights reserved.

Contents

Intellectual Property Rights.....	9
Foreword	9
Introduction	10
1 Scope.....	11
2 References.....	11
3 Definitions and abbreviations	12
3.1 Definitions	12
3.2 Abbreviations.....	12
4 Conformance to this ICS proforma specification	14
Annex A (normative): ICS proforma for EN 300 417-2-1.....	15
A.1 Guidance for completing the ICS proforma.....	15
A.1.1 Purposes and structure	15
A.1.2 Abbreviations and conventions	15
A.1.3 Instructions for completing the ICS proforma	17
Annex B (normative): ICS proforma for STM-1 optical section layer.....	18
B.1 Identification of the implementation.....	18
B.1.1 Date of the statement	18
B.1.2 IUT identification	18
B.1.3 SUT identification.....	18
B.1.4 Product supplier	19
B.1.5 Client	19
B.1.6 ICS contact person.....	20
B.2 Identification of the EN.....	20
B.3 Global statement of conformance of OS1 layer.....	20
B.4 OS1 layer description.....	21
B.5 OS1 layer transmission tables.....	22
B.5.1 OS1 source operating wavelength range, OS1_TT_So.....	22
B.5.2 OS1 source spectral characteristics, OS1_TT_So.....	23
B.5.3 OS1 source optical characteristics, OS1_TT_So	24
B.5.4 OS1 receiver characteristics, OS1_TT_Sk.....	25
B.5.5 OS1 regeneration characteristics, OS1/RS1_A_So, OS1/RS1_A_Sk.....	26
B.6 Defect, fault and performance monitoring.....	27
B.6.1 Port status management	27
B.6.2 Defect detection and clearance criteria	27
B.6.3 Consequent action activation and clearance criteria	28
B.6.4 Defect correlation	29
B.6.5 Performance monitoring	29
Annex C (normative): ICS proforma for STM-4 optical section layer.....	30
C.1 Identification of the implementation.....	30
C.1.1 Date of the statement	30
C.1.2 IUT identification	30
C.1.3 SUT identification.....	30
C.1.4 Product supplier.....	31
C.1.5 Client	31
C.1.6 ICS contact person.....	32

C.2	Identification of the EN.....	32
C.3	Global statement of conformance of OS4 layer.....	32
C.4	OS4 layer description.....	33
C.5	OS4 layer transmission tables.....	34
C.5.1	OS4 source operating wavelength range, OS4_TT_So.....	34
C.5.2	OS4 source spectral characteristics, OS4_TT_So.....	35
C.5.3	OS4 source optical characteristics, OS4_TT_So.....	36
C.5.4	OS4 receiver characteristics, OS4_TT_Sk.....	37
C.5.5	OS4 regeneration characteristics, OS4/RS4_A_So, OS4/RS4_A_Sk.....	38
C.6	OS4 layer defect, fault and performance monitoring tables.....	39
C.6.1	Port status management.....	39
C.6.2	Defect detection and clearance criteria.....	39
C.6.3	Consequent action activation and clearance criteria.....	40
C.6.4	Defect correlation.....	41
C.6.5	Performance monitoring.....	41
Annex D (normative): ICS proforma for STM-16 optical section layer.....		42
D.1	Identification of the implementation.....	42
D.1.1	Date of the statement.....	42
D.1.2	IUT identification.....	42
D.1.3	SUT identification.....	42
D.1.4	Product supplier.....	43
D.1.5	Client.....	43
D.1.6	ICS contact person.....	44
D.2	Identification of the EN.....	44
D.3	Global statement of conformance of OS16 layer.....	44
D.4	OS16 layer description.....	45
D.5	OS16 layer transmission tables.....	46
D.5.1	OS16 source operating wavelength range, OS16_TT_So.....	46
D.5.2	OS16 source spectral characteristics, OS16_TT_So.....	46
D.5.3	OS16 source optical characteristics, OS16_TT_So.....	47
D.5.4	OS16 receiver characteristics, OS16_TT_Sk.....	48
D.5.5	OS16 regeneration characteristics, OS16/RS16_A_So, OS16/RS16_A_Sk.....	49
D.6	OS16 layer defect, fault and performance monitoring tables.....	50
D.6.1	Port status management.....	50
D.6.2	Defect detection and clearance criteria.....	50
D.6.3	Consequent action activation and clearance criteria.....	51
D.6.4	Defect correlation.....	52
D.6.5	Performance monitoring.....	52
Annex E (normative): ICS proforma for STM-1 electrical section layer.....		53
E.1	Identification of the implementation.....	53
E.1.1	Date of the statement.....	53
E.1.2	IUT identification.....	53
E.1.3	SUT identification.....	53
E.1.4	Product supplier.....	54
E.1.5	Client.....	54
E.1.6	ICS contact person.....	55

E.2	Identification of the EN.....	55
E.3	Global statement of conformance of ES1 layer	55
E.4	ES1 layer description	56
E.5	ES1 layer transmission tables	56
E.5.1	ES1 layer data stream.....	56
E.5.2	ES1 layer connection function, ES1_C	56
E.5.3	ES1 layer trail termination functions, ES1_TT_So and ES1_TT_Sk	57
E.5.4	ES1 to RS1 adaptation functions, ES1/RS1_A_So and ES1/RS1_A_Sk.....	58
E.6	ES1 layer defect, fault and performance monitoring tables.....	59
E.6.1	Port status management	59
E.6.2	Defect detection and clearance criteria	60
E.6.3	Consequent action activation and clearance criteria	60
E.6.4	Defect correlation	61
E.6.5	Performance monitoring	61
Annex F (normative): ICS proforma for E4 electrical section layer		62
F.1	Identification of the implementation.....	62
F.1.1	Date of the statement	62
F.1.2	IUT identification	62
F.1.3	SUT identification.....	62
F.1.4	Product supplier	63
F.1.5	Client	63
F.1.6	ICS contact person.....	64
F.2	Identification of the EN.....	64
F.3	Global statement of conformance of E4 layer	64
F.4	E4 layer description	65
F.5	E4 layer transmission tables.....	65
F.5.1	E4 layer data stream.....	65
F.5.2	E4 layer connection function, E4_C	65
F.5.3	E4 layer trail termination functions, E4_TT_So and E4_TT_Sk	66
F.5.4	E4 to P4x adaptation functions, E4/P4x_A_So and E4/P4x_A_Sk	67
F.5.5	E4to P4e adaptation functions, E4/P4e_A_So and E4/P4e_A_Sk	68
F.5.6	E4 to P4s adaptation functions, E4/P4s_A_So and E4/P4s_A_Sk	69
F.6	E4 layer defect, fault and performance monitoring tables.....	70
F.6.1	Port status management	70
F.6.2	Defect detection and clearance criteria	71
F.6.3	Consequent action activation and clearance criteria	71
F.6.4	Defect correlation	72
Annex G (normative): ICS proforma for E31 electrical section layer		73
G.1	Identification of the implementation.....	73
G.1.1	Date of the statement	73
G.1.2	IUT identification	73
G.1.3	SUT identification.....	73
G.1.4	Product supplier	74
G.1.5	Client	74
G.1.6	ICS contact person.....	75

G.2	Identification of the EN.....	75
G.3	Global statement of conformance of E31 layer	75
G.4	E31 layer description	76
G.5	E31 layer transmission tables.....	76
G.5.1	E31 layer data stream.....	76
G.5.2	E31 layer connection function, E31_C	76
G.5.3	E31 layer trail termination functions, E31_TT_So and E31_TT_Sk.....	77
G.5.4	E31 to P31x adaptation functions, E31/P31x_A_So and E31/P31x_A_Sk.....	78
G.5.5	E31to P31e adaptation functions, E31/P31e_A_So and E31/P31e_A_Sk.....	79
G.5.6	E31 to P31s adaptation functions, E31/P31s_A_So and E31/P31s_A_Sk	80
G.6	E31 layer defect, fault and performance monitoring tables	81
G.6.1	Port status management	81
G.6.2	Defect detection and clearance criteria	82
G.6.3	Consequent action activation and clearance criteria	82
G.6.4	Defect correlation	83
Annex H (normative): ICS proforma for E22 electrical section layer		84
H.1	Identification of the implementation.....	84
H.1.1	Date of the statement	84
H.1.2	IUT identification	84
H.1.3	SUT identification.....	84
H.1.4	Product supplier.....	85
H.1.5	Client	85
H.1.6	ICS contact person.....	86
H.2	Identification of the EN.....	86
H.3	Global statement of conformance of E22 layer	86
H.4	E22 layer description.....	87
H.5	E22 layer transmission tables.....	87
H.5.1	E22 layer data stream.....	87
H.5.2	E22 layer connection function, E22_C	87
H.5.3	E22 layer trail termination functions, E22_TT_So and E22_TT_Sk.....	88
H.5.4	E22 to P22x adaptation functions, E22/P22x_A_So and E22/P22x_A_Sk.....	89
H.5.5	E22to P22e adaptation functions, E22/P22e_A_So and E22/P22e_A_Sk.....	90
H.6	E22 layer defect, fault and performance monitoring tables	91
H.6.1	Port status management	91
H.6.2	Defect detection and clearance criteria	91
H.6.3	Consequent action activation and clearance criteria	92
H.6.4	Defect correlation	93
Annex J (normative): ICS proforma for E12 electrical section layer		94
J.1	Identification of the implementation.....	94
J.1.1	Date of the statement	94
J.1.2	IUT identification	94
J.1.3	SUT identification.....	94
J.1.4	Product supplier.....	95
J.1.5	Client	95
J.1.6	ICS contact person.....	96

J.2	Identification of the EN.....	96
J.3	Global statement of conformance of E12 layer	96
J.4	E12 layer description	97
J.5	E12 layer transmission tables.....	97
J.5.1	E12 layer data stream.....	97
J.5.2	E12 electrical section connection function, E12_C	97
J.5.3	E12layer trail termination functions, E12_TT_So and E12_TT_Sk.....	98
J.5.4	E12 to P12x adaptation functions, E12/P12x_A_So and E12/P12x_A_Sk.....	100
J.5.5	E12 to P12s adaptation functions, E12/P12s_A_So and E12/P12s_A_Sk	101
J.6	E12 layer defect, fault and performance monitoring tables	104
J.6.1	Port status management	104
J.6.2	Defect detection and clearance criteria	104
J.6.3	Consequent action activation and clearance criteria	105
J.6.4	Defect correlation	106
Annex K (normative): ICS proforma for T12 electrical section layer		107
K.1	Identification of the implementation.....	107
K.1.1	Date of the statement	107
K.1.2	IUT identification	107
K.1.3	SUT identification.....	107
K.1.4	Product supplier	108
K.1.5	Client	108
K.1.6	ICS contact person.....	109
K.2	Identification of the EN.....	109
K.3	Global statement of conformance of T12 layer	109
K.4	T12 layer description	110
K.5	T12 layer transmission tables.....	110
K.5.1	T12 layer data stream.....	110
K.5.2	T12layer connection function, T12_C	110
K.5.3	T12layer trail termination functions, T12_TT_So and T12_TT_Sk.....	110
K.5.4	T12 to SD adaptation functions, T12/SD_A_So and T12/SD_A_Sk	111
K.6	T12 layer defect, fault and performance monitoring tables	111
K.6.1	Port status management	112
K.6.2	Defect detection and clearance criteria	112
K.6.3	Consequent action activation and clearance criteria	112
K.6.4	Defect correlation	113
Annex L (normative): ICS proforma for E0 electrical section layer		114
L.1	Identification of the implementation.....	114
L.1.1	Date of the statement	114
L.1.2	IUT identification	114
L.1.3	SUT identification.....	114
L.1.4	Product supplier	115
L.1.5	Client	115
L.1.6	ICS contact person.....	116
L.2	Identification of the EN.....	116
L.3	Global statement of conformance of E0 layer	116
L.4	E0 layer description	117
L.5	E0 layer transmission tables.....	117
L.5.1	E0 layer data stream.....	117
L.5.2	E0 layer connection function, E0_C	117

L.5.3	E0 layer trail termination functions, E0_TT_So and E0_TT_Sk	118
L.5.4	E0 to P0s adaptation functions, E0/P0s_A_So and E0/P0s_A_Sk	119
L.6	E0 layer defect, fault and performance monitoring tables	120
L.6.1	Port status management	120
L.6.2	Defect detection and clearance criteria	120
L.6.3	Consequent action activation and clearance criteria	120
L.6.4	Defect correlation	121
	Bibliography	122
	History	123

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 417-2-2 V1.1.2:2003](https://standards.iteh.ai/catalog/standards/sist/2dd66971-44ab-4f2d-984d-de486ce3f294/sist-en-300-417-2-2-v1-1-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/2dd66971-44ab-4f2d-984d-de486ce3f294/sist-en-300-417-2-2-v1-1-2-2003>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Transmission and Multiplexing (TM).

The present document is one of a family of documents that has been produced in order to provide inter-vendor and inter-operator compatibility of Synchronous Digital Hierarchy (SDH) equipment.

The present document is part 2-2 of a multi-part EN covering the Generic requirements of transport functionality of equipment, as identified below:

Part 1-1: "Generic processes and performance".

Part 1-2: "General information about Implementation Conformance Statement (ICS) proforma".

Part 1-3 "Generic processes and performance; Abstract Test Suite (ATS)".

Part 2-1: "Synchronous Digital Hierarchy (SDH) and Plesiochronous Digital Hierarchy (PDH) physical section layer functions".

Part 2-2: "Synchronous Digital Hierarchy (SDH) and Plesiochronous Digital Hierarchy (PDH) physical section layer functions; Implementation Conformance Statement (ICS) proforma specification".

Part 2-3: "Synchronous Digital Hierarchy (SDH) and Plesiochronous Digital Hierarchy (PDH) physical section layer functions; Abstract Test Suite (ATS)".

Part 3-1: "Synchronous Transport Module-N (STM-N) regenerator and multiplex section layer functions".

Part 3-2: "Synchronous Transport Module-N (STM-N) regenerator and multiplex section layer functions; Implementation Conformance Statement (ICS) proforma specification".

Part 3-3: "Synchronous Transport Module-N (STM-N) regenerator and multiplex section layer functions; Abstract Test Suite (ATS)".

Part 4-1: "Synchronous Digital Hierarchy (SDH) path layer functions".

Part 4-2: "Synchronous Digital Hierarchy (SDH) path layer functions; Implementation Conformance Statement (ICS) proforma specification".

Part 4-3: "Synchronous Digital Hierarchy (SDH) path layer functions; Abstract Test Suite (ATS)".

Part 5-1: "Plesiochronous Digital Hierarchy (PDH) path layer functions".

Part 5-2: "Plesiochronous Digital Hierarchy (PDH) path layer functions; Implementation Conformance Statement (ICS) proforma specification".

Part 5-3: "Plesiochronous Digital Hierarchy (PDH) path layer functions; Abstract Test Suite (ATS)".

Part 6-1: "Synchronization layer functions".

Part 6-2: "Synchronization layer functions; Implementation Conformance Statement (ICS) proforma specification".

Part 6-3: "Synchronization layer functions; Abstract Test Suite (ATS)".

Part 7-1: "Auxiliary layer functions".

Part 7-2: "Auxiliary layer functions; Implementation Conformance Statement (ICS) proforma specification".

Part 7-3: "Auxiliary layer functions; Abstract Test Suite (ATS)".

Parts 2 to 7 specify the layers and their atomic functions.

NOTE 1: The present document does not currently address configuration management.

NOTE 2: The SDH radio equipment functional blocks are addressed by ETSI WG TM4.

Various of the above parts have previously been published as parts of ETS 300 417.

They have been converted to parts of EN 300 417 without technical changes, but some editorial changes have been necessary (e.g. references). In particular:

- Parts 2-1 and 3-2 have been modified to take account of editorial errors present in edition 1.
- Part 1-1 has had its title change of to align with other parts published at a later date.

Also note that in the meantime parts 8-1, 8-2 and 8-3 have been stopped.

Transposition dates	
Date of adoption of this EN:	24 October 1997
Date of latest announcement of this EN (doa):	28 February 1998
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 August 1998
Date of withdrawal of any conflicting National Standard (dow):	31 August 1998

Introduction

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a telecommunication specification. Such a statement is called an Implementation Conformance Statement (ICS).

A client of a test laboratory who requests a conformance / approval test shall provide to the test laboratory a completed ICS proforma for each layer to be tested and a detailed system description of the implementation.

The ICS proforma is not another complete description of the related specification, but rather a compact form of its static conformance requirements, to be used by the test laboratory to identify which test shall be performed on a given implementation. Not every feature of a profile specification is contained in the related ICS proforma. For particular cases requiring specific information the ICS can refer to the appropriate clause of the related specification by means of references, notes and or comments.

The ICS proforma captures the implementation flexibility allowed by the related specification and details which option are left to the implementor, which are conditionally dependent on other option taken by the implementor.

1 Scope

The present document provides the Implementation Conformance Statement (ICS) proforma specification for the Synchronous Digital Hierarchy (SDH) equipment physical section layer functions defined in EN 300 417-2-1 [7] in compliance with the relevant requirements, and in accordance with the relevant guidance given in ISO/IEC 9646-7 [10] and ETS 300 406 [5].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] ETS 300 166 (1993): "Transmission and Multiplexing (TM); Physical and electrical characteristics of hierarchical digital interfaces for equipment using the 2 048 kbit/s - based plesiochronous or synchronous digital hierarchies".
- [2] ETS 300 167 (1993): "Transmission and Multiplexing (TM); Functional characteristics of 2 048 kbit/s interfaces".
- [3] ETS 300 232: "Transmission and Multiplexing (TM); Optical interfaces for equipments and systems relating to the Synchronous Digital Hierarchy [ITU-T Recommendation G.957 (1993) modified]".
- [4] ETS 300 337 (1993): "Transmission and Multiplexing (TM); Generic frame structures for the transport of various signals (including Asynchronous Transfer Mode (ATM) cells and Synchronous Digital Hierarchy (SDH) elements) at the CCITT Recommendation G.702 hierarchical rates of 2 048 kbit/s, 34 368 kbit/s and 139 264 kbit/s".
- [5] ETS 300 406 (1995): "Methods for testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".
- [6] EN 300 417-1-1 (1996): "Transmission and Multiplexing (TM); Generic requirements of transport functionality of equipment; Part 1-1: Generic processes and performance".
- [7] EN 300 417-2-1 (1997): "Transmission and Multiplexing (TM); Generic requirements of transport functionality of equipment; Part 2-1: Synchronous Digital Hierarchy (SDH) and Plesiochronous Digital Hierarchy (PDH) physical section layer functions".
- [8] EN 300 417-6-1 (1998): "Transmission and Multiplexing (TM); Generic requirements of transport functionality of equipment; Part 6-1: Synchronization layer functions".
- [9] ISO/IEC 9646-1 (1994): "Information technology; Open systems interconnection; Conformance testing methodology and framework; Part 1: General concepts".
- [10] ISO/IEC 9646-7 (1995): "Information technology; Open systems interconnection; Conformance testing methodology and framework; Part 7: Implementation Conformance Statements".
- [11] ITU-T Recommendation G.652 (1993): "Characteristics of a single-mode optical fibre cable".
- [12] ITU-T Recommendation G.653 (1993): "Characteristics of a dispersion-shifted single-mode optical fibre cable".

- [13] ITU-T Recommendation G.654 (1993): "Characteristics of a 1550 nm wavelength loss-minimized single-mode optical fibre cable".
- [14] CCITT Recommendation G.706 (1991): "Frame alignment and cyclic redundancy check (CRC) procedures relating to basic frame structures defined in Recommendation G.704".
- [15] CCITT Recommendation G.703 (1991): "Physical / electrical characteristics of hierarchical digital interfaces".
- [16] CCITT Recommendation G.704 (1991): "Synchronous frame structures used at primary and secondary hierarchical levels".
- [17] CCITT Recommendation G.742 (1988): "Second order digital multiplex equipment operating at 8448 kbit/s and using positive justification".
- [18] CCITT Recommendation G.751 (1988): "Digital multiplex equipments operating at third order bit rate of 34 368 kbit/s and fourth order bit rate of 139 264 kbit/s and using positive justification".
- [19] ITU-T Recommendation G.823 (1993): "The control of jitter and wander within digital networks which are based on the 2 048 kbit/s hierarchy".
- [20] ITU-T Recommendation G.825 (1993): "The control of jitter and wander within digital networks which are based on the synchronous digital hierarchy (SDH)".
- [21] ITU-T Recommendation G.957 (1993): "Optical interfaces for equipments and systems relating to the synchronous digital hierarchy".
- [22] ITU-T Recommendation G.958 (1993): "Digital line systems based on the synchronous digital hierarchy for use on optical fibre cables".

(standards.iteh.ai)

3 Definitions and abbreviations

SIST EN 300 417-2-2 V1.1.2:2003

<https://standards.iteh.ai/catalog/standards/sist/2dd66971-44ab-4f2d-984d-de486ce3f294/sist-en-300-417-2-2-v1-1-2-2003>

3.1 Definitions

For the purposes of the present document, the following definitions apply:

- terms defined in EN 300 417-2-1 [7];
- terms defined in ISO/IEC 9646-1 [9] and in ISO/IEC 9646-7 [10].

In particular, the following terms defined in ISO/IEC 9646-1 [9] apply:

Implementation Conformance Statement (ICS): A statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented. The ICS can take several forms: protocol ICS, profile ICS, profile specific ICS, information object ICS, etc.

ICS proforma: A document, in the form of a questionnaire, which when completed for an implementation or system becomes an ICS.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

A	Adaptation function
AI	Adapted Information
AIS	Alarm Indication Signal
BER	Bit Error Ratio
C	Connection function
CI	Characteristic Information
CID	Consecutive Identical Digits

CMI	Coded Mark Inversion
CP	Connection Point
D	Data
EMF	Equipment Management Function
EMS	Equipment Management System
E0	Electrical interface signal 64 kbit/s
E12	Electrical interface signal 2 048 kbit/s
E22	Electrical interface signal 8 448 kbit/s
E31	Electrical interface signal 34 368 kbit/s
E4	Electrical interface signal 139 264 kbit/s
ES1	STM-1 electrical interface signal 155 520 kbit/s
EX	EXtinction ratio
FAS	Frame Alignment Signal
FS	Frame Start
HDB3	High Density Bipolar of order 3
IF	In Frame
ICS	Implementation Conformance Statement
ID	IDentifier
IUT	Implementation Under Test
LED	Light Emitting Diode
LOF	Loss Of Frame
LOS	Loss Of Signal
MI	Management Information
MLM	Multi-Longitudinal Mode (laser)
MON	MONitored
N_B	Near-end Block
NE	Network Element
NMON	Not MONitored
OFS	Out of Frame Second
OOF	Out Of Frame state
OS	Optical Section
OS1	STM-1 Optical Section
OS4	STM-4 Optical Section
OS16	STM-16 Optical Section
P0s	64 kbit/s layer (transparent)
P12s	2 048 kbit/s PDH path layer with synchronous 125 µs frame structure according to ETS 300 167 [2]
P12x	2 048 kbit/s layer (transparent)
P22e	8 448 kbit/s PDH path layer with 4 plesiochronous 2 048 kbit/s
P22x	8 448 kbit/s layer (transparent)
P31e	34 368 kbit/s PDH path layer with 4 plesiochronous 8 448 kbit/s
P31s	34 368 kbit/s PDH path layer with synchronous 125 µs frame structure according to ETS 300 337 [4]
P31x	34 368 kbit/s layer (transparent)
P4e	139 264 kbit/s PDH path layer with 4 plesiochronous 34 368 kbit/s
P4s	139 264 kbit/s PDH path layer with synchronous 125 µs frame structure according to ETS 300 337 [4]
P4x	139 264 kbit/s layer (transparent)
PDH	Plesiochronous Digital Hierarchy
QL	Quality Level
RS	Regenerator Section
RS1	STM-1 Regenerator Section
RS4	STM-4 Regenerator Section
RS16	STM-16 Regenerator Section
SEC	SDH Equipment Clock
SCS	System Conformance Statement
SD	Synchronization Distribution layer
SDH	Synchronous Digital Hierarchy
Sk	Sink
SLM	Single-Longitudinal Mode (laser)

STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 417-2-2 V1.1.2:2003

<https://standards.iteh.ai/catalog/standards/sist/2dd66971-44ab-4f2d-984d-8c4b0cc3294/sist-en-300-417-2-2-v1-1-2-2003>

6440003294/sist-en-300-417-2-2-v1-1-2-2003