

ETSI TS 138 104 V15.20.0 (2024-05)



5G; NR; Base Station (BS) radio transmission and reception (3GPP TS 38.104 version 15.20.0 Release 15)

[ETSI TS 138 104 V15.20.0 \(2024-05\)](https://standards.iteh.ai/catalog/standards/etsi/359b5d26-9a0f-40bc-9125-f43d0f0d7601/etsi-ts-138-104-v15-20-0-2024-05)

<https://standards.iteh.ai/catalog/standards/etsi/359b5d26-9a0f-40bc-9125-f43d0f0d7601/etsi-ts-138-104-v15-20-0-2024-05>



ReferenceRTS/TSGR-0438104vfk0

Keywords5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2024-05)

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope	13
2 References	13
3 Definitions, symbols and abbreviations	14
3.1 Definitions	14
3.2 Symbols.....	18
3.3 Abbreviations	20
4 General	22
4.1 Relationship with other core specifications.....	22
4.2 Relationship between minimum requirements and test requirements	22
4.3 Conducted and radiated requirement reference points	22
4.3.1 BS type 1-C	22
4.3.2 BS type 1-H	23
4.3.3 BS type 1-O and BS type 2-O	24
4.4 Base station classes	24
4.5 Regional requirements.....	25
4.6 Applicability of requirements.....	26
4.7 Requirements for contiguous and <i>non-contiguous spectrum</i>	27
4.8 Requirements for BS capable of multi-band operation	27
4.9 OTA co-location with other base stations	29
5 Operating bands and channel arrangement	30
5.1 General	30
5.2 Operating bands	30
5.3 BS channel bandwidth	31
5.3.1 General.....	31
5.3.2 Transmission bandwidth configuration	32
5.3.3 Minimum guardband and <i>transmission bandwidth configuration</i>	32
5.3.4 RB alignment.....	34
5.3A BS channel bandwidth for CA.....	38
5.3A.1 Transmission bandwidth configuration for CA	38
5.3A.2 Minimum guardband and <i>transmission bandwidth configuration</i> for CA	38
5.4 Channel arrangement.....	40
5.4.1 Channel spacing.....	40
5.4.1.1 Channel spacing for adjacent NR carriers	40
5.4.1.2 Channel spacing for CA	40
5.4.2 Channel raster	41
5.4.2.1 NR-ARFCN and channel raster.....	41
5.4.2.2 Channel raster to resource element mapping.....	41
5.4.2.3 Channel raster entries for each <i>operating band</i>	42
5.4.3 Synchronization raster	43
5.4.3.1 Synchronization raster and numbering.....	43
5.4.3.2 Synchronization raster to synchronization block resource element mapping.....	44
5.4.3.3 Synchronization raster entries for each <i>operating band</i>	44
6 Conducted transmitter characteristics	46
6.1 General	46
6.2 Base station output power	46
6.2.1 General.....	46
6.2.2 Minimum requirement for BS type 1-C.....	47
6.2.3 Minimum requirement for BS type 1-H	47

6.2.4	Additional requirements (regional).....	47
6.3	Output power dynamics.....	47
6.3.1	General.....	47
6.3.2	RE power control dynamic range	47
6.3.2.1	General	47
6.3.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	47
6.3.3	Total power dynamic range	48
6.3.3.1	General	48
6.3.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	48
6.4	Transmit ON/OFF power	49
6.4.1	Transmitter OFF power	49
6.4.1.1	General	49
6.4.1.2	Minimum requirement for <i>BS type 1-C</i>	49
6.4.1.3	Minimum requirement for <i>BS type 1-H</i>	49
6.4.2	Transmitter transient period	49
6.4.2.1	General	49
6.4.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	50
6.4.2.3	Void.....	50
6.5	Transmitted signal quality	50
6.5.1	Frequency error.....	50
6.5.1.1	General	50
6.5.1.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	51
6.5.2	Modulation quality.....	51
6.5.2.1	General	51
6.5.2.2	Minimum Requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	51
6.5.2.3	EVM frame structure for measurement.....	51
6.5.3	Time alignment error	51
6.5.3.1	General	51
6.5.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	52
6.6	Unwanted emissions.....	52
6.6.1	General.....	52
6.6.2	Occupied bandwidth	53
6.6.2.1	General	53
6.6.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	53
6.6.3	Adjacent Channel Leakage Power Ratio	53
6.6.3.1	General	53
6.6.3.2	Limits and <i>Basic limits</i>	53
6.6.3.3	Minimum requirement for <i>BS type 1-C</i>	56
6.6.3.4	Minimum requirement for <i>BS type 1-H</i>	57
6.6.4	Operating band unwanted emissions	57
6.6.4.1	General	57
6.6.4.2	<i>Basic limits</i>	59
6.6.4.2.1	<i>Basic limits</i> for Wide Area BS (Category A)	59
6.6.4.2.2	<i>Basic limits</i> for Wide Area BS (Category B).....	59
6.6.4.2.2.1	Category B requirements (Option 1).....	59
6.6.4.2.2.2	Category B requirements (Option 2).....	61
6.6.4.2.3	<i>Basic limits</i> for Medium Range BS (Category A and B).....	61
6.6.4.2.4	<i>Basic limits</i> for Local Area BS (Category A and B).....	62
6.6.4.2.5	<i>Basic limits</i> for additional requirements	62
6.6.4.2.5.1	Limits in FCC Title 47.....	62
6.6.4.2.5.2	Protection of DTT.....	62
6.6.4.3	Minimum requirements for <i>BS type 1-C</i>	63
6.6.4.4	Minimum requirements for <i>BS type 1-H</i>	63
6.6.5	Transmitter spurious emissions.....	63
6.6.5.1	General	63
6.6.5.2	<i>Basic limits</i>	64
6.6.5.2.1	General transmitter spurious emissions requirements	64
6.6.5.2.2	Protection of the BS receiver of own or different BS	64
6.6.5.2.3	Additional spurious emissions requirements	65
6.6.5.2.4	Co-location with other base stations.....	72
6.6.5.3	Minimum requirements for <i>BS type 1-C</i>	77
6.6.5.4	Minimum requirements for <i>BS type 1-H</i>	77

6.7	Transmitter intermodulation.....	77
6.7.1	General.....	77
6.7.2	Minimum requirements for <i>BS type 1-C</i>	78
6.7.2.1	Co-location minimum requirements.....	78
6.7.2.2	Additional requirements.....	78
6.7.3	Minimum requirements for <i>BS type 1-H</i>	79
6.7.3.1	Co-location minimum requirements.....	79
6.7.3.2	Intra-system minimum requirements.....	79
6.7.3.3	Additional requirements.....	80
7	Conducted receiver characteristics.....	81
7.1	General.....	81
7.2	Reference sensitivity level.....	81
7.2.1	General.....	81
7.2.2	Minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i>	82
7.3	Dynamic range.....	83
7.3.1	General.....	83
7.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	83
7.4	In-band selectivity and blocking.....	86
7.4.1	Adjacent Channel Selectivity (ACS).....	86
7.4.1.1	General.....	86
7.4.1.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	86
7.4.1.3	Void.....	88
7.4.1.4	Void.....	88
7.4.2	In-band blocking.....	88
7.4.2.1	General.....	88
7.4.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	88
7.4.2.3	Void.....	90
7.4.2.4	Void.....	90
7.5	Out-of-band blocking.....	90
7.5.1	General.....	90
7.5.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	90
7.5.3	Co-location minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i>	91
7.5.4	Void.....	92
7.6	Receiver spurious emissions.....	92
7.6.1	General.....	92
7.6.2	Basic limits.....	92
7.6.3	Minimum requirement for <i>BS type 1-C</i>	93
7.6.4	Minimum requirement for <i>BS type 1-H</i>	93
7.7	Receiver intermodulation.....	93
7.7.1	General.....	93
7.7.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	93
7.8	In-channel selectivity.....	98
7.8.1	General.....	98
7.8.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	98
8	Conducted performance requirements.....	101
8.1	General.....	101
8.1.1	Scope and definitions.....	101
8.1.2	Void.....	101
8.2	Performance requirements for PUSCH.....	101
8.2.1	Requirements for PUSCH with transform precoding disabled.....	101
8.2.1.1	General.....	101
8.2.1.2	Minimum requirements.....	102
8.2.2	Requirements for PUSCH with transform precoding enabled.....	109
8.2.2.1	General.....	109
8.2.2.2	Minimum requirements.....	110
8.2.3	Requirements for UCI multiplexed on PUSCH.....	111
8.2.3.1	General.....	111
8.2.3.2	Minimum requirements.....	112
8.3	Performance requirements for PUCCH.....	113
8.3.1	DTX to ACK probability.....	113

8.3.1.1	General	113
8.3.1.2	Minimum requirement	113
8.3.2	Performance requirements for PUCCH format 0	113
8.3.2.1	General	113
8.3.2.2	Minimum requirements	114
8.3.3	Performance requirements for PUCCH format 1	114
8.3.3.1	NACK to ACK requirements	114
8.3.3.1.1	General	114
8.3.3.1.2	Minimum requirements	115
8.3.3.2	ACK missed detection requirements	116
8.3.3.2.1	General	116
8.3.3.2.2	Minimum requirements	116
8.3.4	Performance requirements for PUCCH format 2	117
8.3.4.1	ACK missed detection requirements	117
8.3.4.1.1	General	117
8.3.4.1.2	Minimum requirements	117
8.3.4.2	UCI BLER performance requirements	117
8.3.4.2.1	General	117
8.3.4.2.2	Minimum requirements	118
8.3.5	Performance requirements for PUCCH format 3	118
8.3.5.1	General	118
8.3.5.2	Minimum requirements	119
8.3.6	Performance requirements for PUCCH format 4	120
8.3.6.1	General	120
8.3.6.2	Minimum requirement	121
8.3.7	Performance requirements for multi-slot PUCCH	121
8.3.7.1	General	121
8.3.7.2	Performance requirements for multi-slot PUCCH format 1	121
8.3.7.2.1	NACK to ACK requirements	121
8.3.7.2.1.1	General	121
8.3.7.2.1.2	Minimum requirements	122
8.3.7.2.2	ACK missed detection requirements	122
8.3.7.2.2.1	General	122
8.3.7.2.2.2	Minimum requirements	122
8.4	Performance requirements for PRACH	123
8.4.1	PRACH False alarm probability	123
8.4.1.1	General	123
8.4.1.2	Minimum requirement	123
8.4.2	PRACH detection requirements	123
8.4.2.1	General	123
8.4.2.2	Minimum requirements	123
9	Radiated transmitter characteristics	125
9.1	General	125
9.2	Radiated transmit power	125
9.2.1	General	125
9.2.2	Minimum requirement for <i>BS type 1-H</i> and <i>BS type 1-O</i>	125
9.2.3	Minimum requirement for <i>BS type 2-O</i>	126
9.3	OTA base station output power	126
9.3.1	General	126
9.3.2	Minimum requirement for <i>BS type 1-O</i>	126
9.3.3	Minimum requirement for <i>BS type 2-O</i>	127
9.3.4	Additional requirements (regional)	127
9.4	OTA output power dynamics	127
9.4.1	General	127
9.4.2	OTA RE power control dynamic range	127
9.4.2.1	General	127
9.4.2.2	Minimum requirement for <i>BS type 1-O</i>	127
9.4.3	OTA total power dynamic range	127
9.4.3.1	General	127
9.4.3.2	Minimum requirement for <i>BS type 1-O</i>	127
9.4.3.3	Minimum requirement for <i>BS type 2-O</i>	128

9.5	OTA transmit ON/OFF power.....	128
9.5.1	General.....	128
9.5.2	OTA transmitter OFF power.....	128
9.5.2.1	General.....	128
9.5.2.2	Minimum requirement for <i>BS type 1-O</i>	128
9.5.2.3	Minimum requirement for <i>BS type 2-O</i>	128
9.5.3	OTA transient period.....	128
9.5.3.1	General.....	128
9.5.3.2	Minimum requirement for <i>BS type 1-O</i>	129
9.5.3.3	Minimum requirement for <i>BS type 2-O</i>	129
9.6	OTA transmitted signal quality.....	129
9.6.1	OTA frequency error.....	129
9.6.1.1	General.....	129
9.6.1.2	Minimum requirement for <i>BS type 1-O</i>	129
9.6.1.3	Minimum requirement for <i>BS type 2-O</i>	129
9.6.2	OTA modulation quality.....	130
9.6.2.1	General.....	130
9.6.2.2	Minimum Requirement for <i>BS type 1-O</i>	130
9.6.2.3	Minimum Requirement for <i>BS type 2-O</i>	130
9.6.2.3.1	EVM frame structure for measurement.....	130
9.6.3	OTA time alignment error.....	130
9.6.3.1	General.....	130
9.6.3.2	Minimum requirement for <i>BS type 1-O</i>	130
9.6.3.3	Minimum requirement for <i>BS type 2-O</i>	131
9.7	OTA unwanted emissions.....	131
9.7.1	General.....	131
9.7.2	OTA occupied bandwidth.....	132
9.7.2.1	General.....	132
9.7.2.2	Minimum requirement for <i>BS type 1-O</i> and <i>BS type 2-O</i>	132
9.7.3	OTA Adjacent Channel Leakage Power Ratio (ACLR).....	132
9.7.3.1	General.....	132
9.7.3.2	Minimum requirement for <i>BS type 1-O</i>	132
9.7.3.3	Minimum requirement for <i>BS type 2-O</i>	132
9.7.4	OTA operating band unwanted emissions.....	134
9.7.4.1	General.....	134
9.7.4.2	Minimum requirement for <i>BS type 1-O</i>	134
9.7.4.2.1	Additional requirements.....	135
9.7.4.2.1.1	Protection of DTT.....	135
9.7.4.2.1.2	Limits in FCC Title 47.....	135
9.7.4.3	Minimum requirement for <i>BS type 2-O</i>	135
9.7.4.3.1	General.....	135
9.7.4.3.2	OTA operating band unwanted emission limits (Category A).....	136
9.7.4.3.3	OTA operating band unwanted emission limits (Category B).....	137
9.7.4.3.4	Additional OTA operating band unwanted emission requirements.....	137
9.7.4.3.4.1	Protection of Earth Exploration Satellite Service.....	137
9.7.5	OTA transmitter spurious emissions.....	138
9.7.5.1	General.....	138
9.7.5.2	Minimum requirement for <i>BS type 1-O</i>	138
9.7.5.2.1	General.....	138
9.7.5.2.2	General OTA transmitter spurious emissions requirements.....	138
9.7.5.2.3	Protection of the BS receiver of own or different BS.....	138
9.7.5.2.4	Additional spurious emissions requirements.....	138
9.7.5.2.5	Co-location with other base stations.....	139
9.7.5.3	Minimum requirement for <i>BS type 2-O</i>	139
9.7.5.3.1	General.....	139
9.7.5.3.2	General OTA transmitter spurious emissions requirements.....	139
9.7.5.3.2.1	General.....	139
9.7.5.3.2.2	OTA transmitter spurious emissions (Category A).....	139
9.7.5.3.2.3	OTA transmitter spurious emissions (Category B).....	140
9.7.5.3.3	Additional OTA transmitter spurious emissions requirements.....	140
9.7.5.3.3.1	Limits for protection of Earth Exploration Satellite Service.....	140
9.8	OTA transmitter intermodulation.....	141

9.8.1	General.....	141
9.8.2	Minimum requirement for <i>BS type 1-O</i>	141
10	Radiated receiver characteristics	142
10.1	General	142
10.2	OTA sensitivity	143
10.2.1	<i>BS type 1-H</i> and <i>BS type 1-O</i>	143
10.2.1.1	General	143
10.2.1.2	Minimum requirement	143
10.2.2	<i>BS type 2-O</i>	143
10.3	OTA reference sensitivity level	144
10.3.1	General.....	144
10.3.2	Minimum requirement for <i>BS type 1-O</i>	144
10.3.3	Minimum requirement for <i>BS type 2-O</i>	145
10.4	OTA dynamic range	146
10.4.1	General.....	146
10.4.2	Minimum requirement for <i>BS type 1-O</i>	146
10.5	OTA in-band selectivity and blocking.....	155
10.5.1	OTA adjacent channel selectivity	155
10.5.1.1	General	155
10.5.1.2	Minimum requirement for <i>BS type 1-O</i>	155
10.5.1.3	Minimum requirement for <i>BS type 2-O</i>	156
10.5.2	OTA in-band blocking.....	157
10.5.2.1	General	157
10.5.2.2	Minimum requirement for <i>BS type 1-O</i>	157
10.5.2.3	Minimum requirement for <i>BS type 2-O</i>	160
10.6	OTA out-of-band blocking	160
10.6.1	General.....	160
10.6.2	Minimum requirement for <i>BS type 1-O</i>	160
10.6.2.1	General minimum requirement	160
10.6.2.2	Co-location minimum requirement	161
10.6.3	Minimum requirement for <i>BS type 2-O</i>	162
10.6.3.1	General minimum requirement	162
10.7	OTA receiver spurious emissions.....	162
10.7.1	General.....	162
10.7.2	Minimum requirement for <i>BS type 1-O</i>	162
10.7.3	Minimum requirement for <i>BS type 2-O</i>	163
10.8	OTA receiver intermodulation	164
10.8.1	General.....	164
10.8.2	Minimum requirement for <i>BS type 1-O</i>	164
10.8.3	Minimum requirement for <i>BS type 2-O</i>	168
10.9	OTA in-channel selectivity.....	169
10.9.1	General.....	169
10.9.2	Minimum requirement for <i>BS type 1-O</i>	169
10.9.3	Minimum requirement for <i>BS type 2-O</i>	172
11	Radiated performance requirements.....	174
11.1	General	174
11.1.1	Scope and definitions.....	174
11.1.2	OTA demodulation branches	174
11.1.3	Void	175
11.2	Performance requirements for PUSCH	175
11.2.1	Requirements for <i>BS type 1-O</i>	175
11.2.1.1	Requirements for PUSCH with transform precoding disabled	175
11.2.1.2	Requirements for PUSCH with transform precoding enabled	175
11.2.1.3	Requirements for UCI multiplexed on PUSCH	175
11.2.2	Requirements for <i>BS type 2-O</i>	175
11.2.2.1	Requirements for PUSCH with transform precoding disabled	175
11.2.2.1.1	General	175
11.2.2.1.2	Minimum requirements	176
11.2.2.2	Requirements for PUSCH with transform precoding enabled	178
11.2.2.2.1	General	178

11.2.2.2.2	Minimum requirements	178
11.2.2.3	Requirements for UCI multiplexed on PUSCH	179
11.2.2.3.1	General	179
11.2.2.3.2	Minimum requirements	180
11.3	Performance requirements for PUCCH	181
11.3.1	Requirements for <i>BS type 1-O</i>	181
11.3.1.1	DTX to ACK probability	181
11.3.1.2	Performance requirements for PUCCH format 0	182
11.3.1.3	Performance requirements for PUCCH format 1	182
11.3.1.4	Performance requirements for PUCCH format 2	182
11.3.1.5	Performance requirements for PUCCH format 3	182
11.3.1.6	Performance requirements for PUCCH format 4	182
11.3.2	Requirements for <i>BS type 2-O</i>	182
11.3.2.1	DTX to ACK probability	182
11.3.2.2	Performance requirements for PUCCH format 0	182
11.3.2.2.1	General	182
11.3.2.2.2	Minimum requirements	183
11.3.2.3	Performance requirements for PUCCH format 1	183
11.3.2.3.1	NACK to ACK requirements	183
11.3.2.3.1.1	General	183
11.3.2.3.1.2	Minimum requirements	184
11.3.2.3.2	ACK missed detection requirements	184
11.3.2.3.2.1	General	184
11.3.2.3.2.2	Minimum requirements	184
11.3.2.4	Performance requirements for PUCCH format 2	185
11.3.2.4.1	ACK missed detection requirements	185
11.3.2.4.1.1	General	185
11.3.2.4.1.2	Minimum requirements	185
11.3.2.4.2	UCI BLER performance requirements	186
11.3.2.4.2.1	General	186
11.3.2.4.2.2	Minimum requirements	186
11.3.2.5	Performance requirements for PUCCH format 3	187
11.3.2.5.1	General	187
11.3.2.5.2	Minimum requirements	187
11.3.2.6	Performance requirements for PUCCH format 4	188
11.3.2.6.1	General	188
11.3.2.6.2	Minimum requirements	188
11.4	Performance requirements for PRACH	189
11.4.1	Requirements for <i>BS type 1-O</i>	189
11.4.1.1	PRACH False alarm probability	189
11.4.1.2	PRACH detection requirements	189
11.4.2	Requirements for <i>BS type 2-O</i>	189
11.4.2.1	PRACH False alarm probability	189
11.4.2.1.1	General	189
11.4.2.1.2	Minimum requirement	189
11.4.2.2	PRACH detection requirements	189
11.4.2.2.1	General	189
11.4.2.2.2	Minimum requirements	190

Annex A (normative): Reference measurement channels191

A.1	Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking, receiver intermodulation and in-channel selectivity (QPSK, R=1/3)	191
A.2	Fixed Reference Channels for dynamic range (16QAM, R=2/3)	192
A.3	Fixed Reference Channels for performance requirements (QPSK, R=193/1024)	192
A.4	Fixed Reference Channels for performance requirements (16QAM, R=658/1024)	197
A.5	Fixed Reference Channels for performance requirements (64QAM, R=567/1024)	201
A.6	PRACH Test preambles	203

Annex B (normative):	Error Vector Magnitude (FR1)	204
B.1	Reference point for measurement	204
B.2	Basic unit of measurement	204
B.3	Modified signal under test	205
B.4	Estimation of frequency offset	205
B.5	Estimation of time offset	205
B.5.1	General	205
B.5.2	Window length	206
B.6	Estimation of TX chain amplitude and frequency response parameters	207
B.7	Averaged EVM	208
Annex C (normative):	Error Vector Magnitude (FR2)	210
C.1	Reference point for measurement	210
C.2	Basic unit of measurement	210
C.3	Modified signal under test	211
C.4	Estimation of frequency offset	211
C.5	Estimation of time offset	211
C.5.1	General	211
C.5.2	Window length	212
C.6	Estimation of TX chain amplitude and frequency response parameters	212
C.7	Averaged EVM	214
Annex D (normative):	Characteristics of the interfering signals	216
Annex E:	Void	217
Annex F (normative):	Relationship between EIRP based regulatory requirements and 3GPP requirements	218
F.1	General	218
F.2	Relationship between EIRP based regulatory requirements and conducted requirements	218
F.3	Relationship between EIRP based regulatory requirements and OTA requirements	219
Annex G (Normative):	Propagation conditions	220
G.1	Static propagation condition	220
G.2	Multi-path fading propagation conditions	220
G.2.1	Delay profiles	220
G.2.1.1	Delay profiles for FR1	221
G.2.1.2	Delay profiles for FR2	222
G.2.2	Combinations of channel model parameters	223
G.2.3	MIMO Channel Correlation Matrices	224
G.2.3.1	MIMO Correlation Matrices using Uniform Linear Array (ULA)	224
G.2.3.1.1	Definition of MIMO Correlation Matrices	224
G.2.3.1.2	MIMO Correlation Matrices at High, Medium and Low Level	228
G.2.3.2	Multi-Antenna channel models using cross polarized antennas	230
G.2.3.2.1	Definition of MIMO Correlation Matrices using cross polarized antennas	231
G.2.3.2.2	Spatial Correlation Matrices at UE and gNB sides	231
G.2.3.2.2.1	Spatial Correlation Matrices at UE side	231
G.2.3.2.2.2	Spatial Correlation Matrices at gNB side	232
G.2.3.2.3	MIMO Correlation Matrices using cross polarized antennas	232

Annex H (informative):	Change history	233
History		242

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 138 104 V15.20.0 \(2024-05\)](#)

<https://standards.iteh.ai/catalog/standards/etsi/359b5d26-9a0f-40bc-9125-f43d0f0d7601/etsi-ts-138-104-v15-20-0-2024-05>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 138 104 V15.20.0 \(2024-05\)](https://standards.iteh.ai/catalog/standards/etsi/359b5d26-9a0f-40bc-9125-f43d0f0d7601/etsi-ts-138-104-v15-20-0-2024-05)

<https://standards.iteh.ai/catalog/standards/etsi/359b5d26-9a0f-40bc-9125-f43d0f0d7601/etsi-ts-138-104-v15-20-0-2024-05>

1 Scope

The present document establishes the minimum RF characteristics and minimum performance requirements of NR Base Station (BS).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] ITU-R Recommendation SM.329: "Unwanted emissions in the spurious domain".
- [3] Recommendation ITU-R SM.328: "Spectra and bandwidth of emissions".
- [4] 3GPP TR 25.942: "RF system scenarios".
- [5] 3GPP TS 38.141-1: "NR; Base Station (BS) conformance testing; Part 1: Conducted conformance testing".
- [6] 3GPP TS 38.141-2: "NR; Base Station (BS) conformance testing; Part 2: Radiated conformance testing".
- [7] Recommendation ITU-R M.1545: "Measurement uncertainty as it applies to test limits for the terrestrial component of International Mobile Telecommunications-2000".
- [8] "Title 47 of the Code of Federal Regulations (CFR)", Federal Communications Commission.
- [9] 3GPP TS 38.211: "NR; Physical channels and modulation".
- [10] 3GPP TS 38.213: "NR; Physical layer procedures for control".
- [11] 3GPP TS 38.331: "NR; Radio Resource Control (RRC); Protocol specification".
- [12] ECC/DEC/(17)06: "The harmonised use of the frequency bands 1427-1452 MHz and 1492-1518 MHz for Mobile/Fixed Communications Networks Supplemental Downlink (MFCN SDL)".
- [13] 3GPP TS 36.104: "Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception".
- [14] 3GPP TS 37.105: "Active Antenna System (AAS) Base Station (BS) transmission and reception".
- [15] 3GPP TS 38.212: "NR; Multiplexing and channel coding".
- [16] 3GPP TR 38.901: "Study on channel model for frequencies from 0.5 to 100 GHz".
- [17] 3GPP TS 38.101-1: "NR; User Equipment (UE) radio transmission and reception; Part 1: Range 1 Standalone".
- [18] 3GPP TS 38.101-2: "NR; User Equipment (UE) radio transmission and reception; Part 2: Range 2 Standalone".
- [19] ERC Recommendation 74-01, "Unwanted emissions in the spurious domain".