

ETSI TS 138 141-1 V15.16.0 (2024-05)



**5G;
NR;**
Base Station (BS) conformance testing
Part 1: Conducted conformance testing
(3GPP TS 38.141-1 version 15.16.0 Release 15)

[ETSI TS 138 141-1 V15.16.0 \(2024-05\)](https://standards.iteh.ai/catalog/standards/etsi/94ca4816-e42f-4508-a8b5-10ec064313d4/etsi-ts-138-141-1-v15-16-0-2024-05)

<https://standards.iteh.ai/catalog/standards/etsi/94ca4816-e42f-4508-a8b5-10ec064313d4/etsi-ts-138-141-1-v15-16-0-2024-05>



Reference

RTS/TSGR-0438141-1vfg0

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	13
1 Scope	14
2 References	14
3 Definitions, symbols and abbreviations	16
3.1 Definitions	16
3.2 Symbols.....	18
3.3 Abbreviations	19
4 General conducted test conditions and declarations.....	21
4.1 Measurement uncertainties and test requirements	21
4.1.1 General.....	21
4.1.2 Acceptable uncertainty of Test System.....	21
4.1.2.1 General	21
4.1.2.2 Measurement of transmitter	22
4.1.2.3 Measurement of receiver	23
4.1.2.4 Measurement of performance requirements.....	26
4.1.3 Interpretation of measurement results.....	26
4.2 Conducted requirement reference points	26
4.2.1 <i>BS type I-C</i>	26
4.2.2 <i>BS type I-H</i>	27
4.3 Base station classes	28
4.4 Regional requirements.....	28
4.5 BS configurations	29
4.5.1 <i>BS type I-C</i>	29
4.5.1.1 Transmit configurations	29
4.5.1.1.1 General	29
4.5.1.1.2 Transmission with multiple transmitter antenna connectors.....	30
4.5.1.2 Receive configurations.....	30
4.5.1.2.1 General	30
4.5.1.2.2 Reception with multiple receiver antenna connectors, receiver diversity.....	30
4.5.1.3 Duplexers	31
4.5.1.4 Power supply options	31
4.5.1.5 Ancillary RF amplifiers.....	31
4.5.2 <i>BS type I-H</i>	32
4.5.2.1 Transmit configurations	32
4.5.2.2 Receive configurations.....	33
4.5.2.3 Power supply options	33
4.5.3 BS with integrated Iuant BS modem	33
4.6 Manufacturer declarations	33
4.7 Test configurations	38
4.7.1 General.....	38
4.7.2 Test signal used to build Test Configurations.....	38
4.7.3 NRTC1: Contiguous spectrum operation.....	38
4.7.3.1 NRTC1 generation	38
4.7.3.2 NRTC1 power allocation	39
4.7.4 NRTC2: Contiguous CA occupied bandwidth.....	39
4.7.4.1 NRTC2 generation	39
4.7.4.2 NRTC2 power allocation	39
4.7.5 NRTC3: Non-contiguous spectrum operation	40
4.7.5.1 NRTC3 generation	40
4.7.5.2 NRTC3 power allocation	40
4.7.6 NRTC4: Multi-band test configuration for full carrier allocation.....	40

4.7.6.1	NRTC4 generation	40
4.7.6.2	NRTC4 power allocation	41
4.7.7	NRTC5: Multi-band test configuration with high PSD per carrier	41
4.7.7.1	NRTC5 generation	41
4.7.7.2	NRTC5 power allocation	41
4.8	Applicability of requirements	42
4.8.1	General	42
4.8.2	Requirement set applicability	42
4.8.3	Applicability of test configurations for single-band operation	42
4.8.4	Applicability of test configurations for multi-band operation	43
4.8.5	Additional conformance	44
4.9	RF channels and test models	45
4.9.1	RF channels	45
4.9.2	Test models	46
4.9.2.1	General	46
4.9.2.2	FR1 test models	46
4.9.2.2.1	FR1 test model 1.1 (NR-FR1-TM1.1)	48
4.9.2.2.2	FR1 test model 1.2 (NR-FR1-TM1.2)	48
4.9.2.2.3	FR1 test model 2 (NR-FR1-TM2)	49
4.9.2.2.4	FR1 test model 2a (NR-FR1-TM2a)	49
4.9.2.2.5	FR1 test model 3.1 (NR-FR1-TM3.1)	50
4.9.2.2.6	FR1 test model 3.1a (NR-FR1-TM3.1a)	50
4.9.2.2.7	FR1 test model 3.2 (NR-FR1-TM3.2)	50
4.9.2.2.8	FR1 test model 3.3 (NR-FR1-TM3.3)	51
4.9.2.3	Data content of Physical channels and Signals for NR-FR1-TM	52
4.9.2.3.1	PDCCH	52
4.9.2.3.2	PDSCH	52
4.10	Requirements for contiguous and non-contiguous spectrum	53
4.11	Requirements for BS capable of multi-band operation	54
4.12	Format and interpretation of tests	55
5	Operating bands and channel arrangement	55
6	Conducted transmitter characteristics	56
6.1	General	56
6.1.1	BS type 1-C	56
6.1.2	BS type 1-H	56
6.2	Base station output power	56
6.2.1	Definition and applicability	56
6.2.2	Minimum requirement	57
6.2.3	Test purpose	57
6.2.4	Method of test	57
6.2.4.1	Initial conditions	57
6.2.4.2	Procedure	57
6.2.5	Test requirement	58
6.3	Output power dynamics	58
6.3.1	General	58
6.3.2	RE power control dynamic range	58
6.3.2.1	Definition and applicability	58
6.3.2.2	Minimum requirement	58
6.3.2.3	Test purpose	59
6.3.3	Total power dynamic range	59
6.3.3.1	Definition and applicability	59
6.3.3.2	Minimum requirement	59
6.3.3.3	Test purpose	59
6.3.3.4	Method of test	59
6.3.3.4.1	Initial conditions	59
6.3.3.4.2	Procedure	59
6.3.3.5	Test requirements	60
6.4	Transmit ON/OFF power	60
6.4.1	Transmitter OFF power	60
6.4.1.1	Definition and applicability	60

6.4.1.2	Minimum requirement	60
6.4.1.3	Test purpose	61
6.4.1.4	Method of test	61
6.4.1.5	Test requirements	61
6.4.2	Transmitter transient period	61
6.4.2.1	Definition and applicability	61
6.4.2.2	Minimum requirement	61
6.4.2.3	Test purpose	61
6.4.2.4	Method of test	62
6.4.2.4.1	Initial conditions	62
6.4.2.4.2	Procedure	62
6.4.2.5	Test requirements	62
6.5	Transmitted signal quality	63
6.5.1	General	63
6.5.2	Frequency error	63
6.5.2.1	Definition and applicability	63
6.5.2.2	Minimum Requirement	63
6.5.2.3	Test purpose	63
6.5.2.4	Method of test	63
6.5.2.5	Test Requirements	63
6.5.3	Modulation quality	63
6.5.3.1	Definition and applicability	63
6.5.3.2	Minimum Requirement	64
6.5.3.3	Test purpose	64
6.5.3.4	Method of test	64
6.5.3.4.1	Initial conditions	64
6.5.3.4.2	Procedure	64
6.5.3.5	Test requirements	65
6.5.4	Time alignment error	66
6.5.4.1	Definition and applicability	66
6.5.4.2	Minimum requirement	66
6.5.4.3	Test purpose	67
6.5.4.4	Method of test	67
6.5.4.4.1	Initial conditions	67
6.5.4.4.2	Procedure	67
6.5.4.5	Test requirement	68
6.6	Unwanted emissions	68
6.6.1	General	68
6.6.2	Occupied bandwidth	68
6.6.2.1	Definition and applicability	68
6.6.2.2	Minimum Requirements	69
6.6.2.3	Test purpose	69
6.6.2.4	Method of test	69
6.6.2.4.1	Initial conditions	69
6.6.2.4.2	Procedure	69
6.6.2.5	Test requirements	70
6.6.3	Adjacent Channel Leakage Power Ratio (ACLR)	70
6.6.3.1	Definition and applicability	70
6.6.3.2	Minimum requirement	70
6.6.3.3	Test purpose	71
6.6.3.4	Method of test	71
6.6.3.4.1	Initial conditions	71
6.6.3.4.2	Procedure	71
6.6.3.5	Test requirements	72
6.6.3.5.1	General requirements	72
6.6.3.5.2	Limits and <i>basic limits</i>	72
6.6.3.5.3	<i>BS type 1-C</i>	74
For Band n41 operation in Japan, absolute ACLR limits shall be applied to the sum of the absolute ACLR power over all <i>antenna connectors</i> for <i>BS type 1-C</i> . 6.6.3.5.4		
	<i>H</i>	75
6.6.4	Operating band unwanted emissions	75
6.6.4.1	Definition and applicability	75

6.6.4.2	Minimum requirement	76
6.6.4.3	Test purpose	77
6.6.4.4	Method of test	77
6.6.4.4.1	Initial conditions	77
6.6.4.4.2	Procedure	77
6.6.4.5	Test requirements	78
6.6.4.5.1	General requirements	78
6.6.4.5.2	Basic limits for Wide Area BS (Category A)	78
6.6.4.5.3	Basic limits for Wide Area BS (Category B)	79
6.6.4.5.3.1	Category B requirements (Option 1)	79
6.6.4.5.3.2	Category B requirements (Option 2)	80
6.6.4.5.4	Basic limits for Medium Range BS (Category A and B)	81
6.6.4.5.5	Basic limits for Local Area BS (Category A and B)	83
6.6.4.5.6	Basic limits for additional requirements	84
6.6.4.5.6.1	Limits in FCC Title 47	84
6.6.4.5.6.2	Protection of DTT	84
6.6.4.5.6.3	(void)	84
6.6.4.5.7	<i>BS type 1-C</i>	84
6.6.4.5.8	<i>BS type 1-H</i>	85
6.6.5	Transmitter spurious emissions	85
6.6.5.1	Definition and applicability	85
6.6.5.2	Minimum requirement	85
6.6.5.3	Test purpose	85
6.6.5.4	Method of test	85
6.6.5.4.1	Initial conditions	85
6.6.5.4.2	Procedure	86
6.6.5.5	Test requirements	87
6.6.5.5.1	Basic limits	87
6.6.5.5.1.1	Tx spurious emissions	87
6.6.5.5.1.2	Protection of the BS receiver of own or different BS	87
6.6.5.5.1.3	Additional spurious emissions requirements	88
6.6.5.5.1.4	Co-location with other base stations	95
6.6.5.5.2	(void)	100
6.6.5.5.3	<i>BS type 1-C</i>	100
6.6.5.5.4	<i>BS type 1-H</i>	100
6.7	Transmitter intermodulation	100
6.7.1	Definition and applicability	100
6.7.2	Minimum requirement	101
6.7.3	Test purpose	101
6.7.4	Method of test	101
6.7.4.1	Initial conditions	101
6.7.4.2	Procedure	101
6.7.5	Test requirements	102
6.7.5.1	<i>BS type 1-C</i>	102
6.7.5.1.1	Co-location minimum requirements	102
6.7.5.1.2	Additional requirements	103
6.7.5.2	<i>BS type 1-H</i>	103
6.7.5.2.1	Co-location minimum requirements	103
6.7.5.2.2	Intra-system minimum requirements	104
6.7.5.2.3	Additional requirements	104
7	Conducted receiver characteristics	105
7.1	General	105
7.2	Reference sensitivity level	105
7.2.1	Definition and applicability	105
7.2.2	Minimum requirement	105
7.2.3	Test purpose	105
7.2.4	Method of test	106
7.2.4.1	Initial conditions	106
7.2.4.2	Procedure	106
7.2.5	Test requirements	106
7.3	Dynamic range	108

7.3.1	Definition and applicability	108
7.3.2	Minimum requirement	108
7.3.3	Test purpose.....	108
7.3.4	Method of test	108
7.3.4.1	Initial conditions	108
7.3.4.2	Procedure	108
7.3.5	Test requirements.....	109
7.4	In-band selectivity and blocking	111
7.4.1	Adjacent Channel Selectivity (ACS)	111
7.4.1.1	Definition and applicability.....	111
7.4.1.2	Minimum requirement	111
7.4.1.3	Test purpose	112
7.4.1.4	Method of test	112
7.4.1.4.1	Initial conditions.....	112
7.4.1.4.2	Procedure.....	112
7.4.1.5	Test requirements.....	112
7.4.2	In-band blocking	113
7.4.2.1	Definition and applicability.....	113
7.4.2.2	Minimum requirement	113
7.4.2.3	Test purpose	114
7.4.2.4	Method of test	114
7.4.2.4.1	Initial conditions.....	114
7.4.2.4.2	Procedure for general blocking.....	114
7.4.2.4.3	Procedure for narrowband blocking	114
7.4.2.5	Test requirements	115
7.5	Out-of-band blocking	117
7.5.1	Definition and applicability	117
7.5.2	Minimum requirement	117
7.5.3	Test purpose.....	117
7.5.4	Method of test	118
7.5.4.1	Initial conditions	118
7.5.4.2	Procedure	118
7.5.5	Test requirements.....	118
7.5.5.1	General requirements	118
7.5.5.2	Co-location requirements	119
7.6	Receiver spurious emissions.....	120
7.6.1	Definition and applicability	120
7.6.2	Minimum requirement	120
7.6.3	Test purpose.....	120
7.6.4	Method of test	120
7.6.4.1	Initial conditions	120
7.6.4.2	Procedure	120
7.6.5	Test requirements.....	121
7.6.5.1	Basic limits.....	121
7.6.5.2	BS type 1-C.....	122
7.6.5.3	BS type 1-H.....	122
7.7	Receiver intermodulation	122
7.7.1	Definition and applicability	122
7.7.2	Minimum requirement	122
7.7.3	Test purpose.....	122
7.7.4	Method of test	122
7.7.4.1	Initial conditions	122
7.7.4.2	Procedure	123
7.7.5	Test requirements.....	123
7.8	In-channel selectivity	127
7.8.1	Definition and applicability	127
7.8.2	Minimum requirement	127
7.8.3	Test purpose.....	127
7.8.4	Method of test	127
7.8.4.1	Initial conditions	127
7.8.4.2	Procedure	127
7.8.5	Test requirements.....	127

8	Conducted performance characteristics.....	131
8.1	General	131
8.1.1	Scope and definitions.....	131
8.1.2	Applicability rule	131
8.1.2.0	General	131
8.1.2.1	Applicability of PUSCH performance requirements.....	131
8.1.2.1.1	Applicability of requirements for different subcarrier spacings	131
8.1.2.1.2	Applicability of requirements for different channel bandwidths	132
8.1.2.1.3	Applicability of requirements for different configurations.....	132
8.1.2.2	Applicability of PUCCH performance requirements	132
8.1.2.2.1	Applicability of requirements for different formats.....	132
8.1.2.2.2	Applicability of requirements for different subcarrier spacings	132
8.1.2.2.3	Applicability of requirements for different channel bandwidths	132
8.1.2.2.4	Applicability of requirements for different configurations.....	132
8.1.2.2.5	Applicability of requirements for multi-slot PUCCH.....	133
8.1.2.3	Applicability of PRACH performance requirements	133
8.1.2.3.1	Applicability of requirements for different formats.....	133
8.1.2.3.2	Applicability of requirements for different subcarrier spacings	133
8.1.2.3.3	Applicability of requirements for different channel bandwidths	133
8.2	Performance requirements for PUSCH	133
8.2.1	Performance requirements for PUSCH with transform precoding disabled	133
8.2.1.1	Definition and applicability.....	133
8.2.1.2	Minimum Requirement	133
8.2.1.3	Test Purpose	133
8.2.1.4	Method of test	133
8.2.1.4.1	Initial Conditions	133
8.2.1.4.2	Procedure.....	134
8.2.1.5	Test Requirement	135
8.2.2	Performance requirements for PUSCH with transform precoding enabled	141
8.2.2.1	Definition and applicability.....	141
8.2.2.2	Minimum Requirement	141
8.2.2.3	Test Purpose	142
8.2.2.4	Method of test	142
8.2.2.4.1	Initial Conditions	142
8.2.2.4.2	Procedure.....	142
8.2.2.5	Test Requirement	143
8.2.3	Performance requirements for UCI multiplexed on PUSCH	144
8.2.3.1	Definition and applicability.....	144
8.2.3.2	Minimum Requirements.....	145
8.2.3.3	Test purpose	145
8.2.3.4	Method of test	145
8.2.3.4.1	Initial conditions.....	145
8.2.3.4.2	Procedure.....	145
8.2.3.5	Test Requirement	146
8.3	Performance requirements for PUCCH.....	147
8.3.1	Performance requirements for PUCCH format 0.....	147
8.3.1.1	Definition and applicability.....	147
8.3.1.2	Minimum Requirement	147
8.3.1.3	Test purpose	148
8.3.1.4	Method of test	148
8.3.1.4.1	Initial conditions	148
8.3.1.4.2	Procedure.....	148
8.3.1.5	Test Requirement	149
8.3.2	Performance requirements for PUCCH format 1	150
8.3.2.1	NACK to ACK detection	150
8.3.2.1.1	Definition and applicability	150
8.3.2.1.2	Minimum Requirement	150
8.3.2.1.3	Test purpose	150
8.3.2.1.4	Method of test.....	150
8.3.2.1.4.1	Initial Conditions	150
8.3.2.1.4.2	Procedure	150
8.3.2.1.5	Test Requirement.....	151

8.3.2.2	ACK missed detection.....	152
8.3.2.2.1	Definition and applicability	152
8.3.2.2.2	Minimum Requirement	152
8.3.2.2.3	Test purpose	152
8.3.2.2.4	Method of test.....	152
8.3.2.2.4.1	Initial Conditions	152
8.3.2.2.4.2	Procedure	152
8.3.2.2.5	Test Requirement.....	153
8.3.3	Performance requirements for PUCCH format 2.....	154
8.3.3.1	ACK missed detection.....	154
8.3.3.1.1	Definition and applicability	154
8.3.3.1.2	Minimum requirements	154
8.3.3.1.3	Test purpose	154
8.3.3.1.4	Method of test.....	154
8.3.3.1.4.1	Initial Condition	154
8.3.3.1.4.2	Procedure	155
8.3.3.1.5	Test requirements	155
8.3.3.2	UCI BLER performance requirements.....	156
8.3.3.2.1	Definition and applicability	156
8.3.3.2.2	Minimum Requirement	156
8.3.3.2.3	Test purpose	156
8.3.3.2.4	Method of test.....	156
8.3.3.2.4.1	Initial Condition	156
8.3.3.2.4.2	Procedure	156
8.3.3.2.5	Test requirements	157
8.3.4	Performance requirements for PUCCH format 3.....	158
8.3.4.1	Definition and applicability.....	158
8.3.4.2	Minimum requirement	158
8.3.4.3	Test purpose	158
8.3.4.4	Method of test	158
8.3.4.4.1	Initial conditions	158
8.3.4.4.2	Procedure.....	158
8.3.4.5	Test requirement	159
8.3.5	Performance requirements for PUCCH format 4.....	160
8.3.5.1	Definition and applicability.....	160
8.3.5.2	Minimum requirement	161
8.3.5.3	Test purpose	161
8.3.5.4	Method of test	161
8.3.5.4.1	Initial conditions.....	161
8.3.5.4.2	Procedure.....	161
8.3.5.5	Test requirement	162
8.3.6	Performance requirements for multi-slot PUCCH.....	163
8.3.6.1	Performance requirements for multi-slot PUCCH format 1.....	163
8.3.6.1.1	NACK to ACK detection.....	163
8.3.6.1.1.1	Definition and applicability	163
8.3.6.1.1.2	Minimum Requirement.....	163
8.3.6.1.1.3	Test purpose.....	163
8.3.6.1.1.4	Method of test	163
8.3.6.1.1.4.1	Initial conditions.....	163
8.3.6.1.1.4.2	Procedure.....	164
8.3.6.1.1.5	Test Requirement	165
8.3.6.1.2	ACK missed detection.....	165
8.3.6.1.2.1	Definition and applicability	165
8.3.6.1.2.2	Minimum Requirement.....	165
8.3.6.1.2.3	Test purpose.....	165
8.3.6.1.2.4	Method of test	165
8.3.6.1.2.4.1	Initial conditions.....	165
8.3.6.1.2.4.2	Procedure.....	165
8.3.6.1.2.5	Test Requirement.....	166
8.4	Performance requirements for PRACH.....	167
8.4.1	PRACH false alarm probability and missed detection.....	167
8.4.1.1	Definition and applicability.....	167

8.4.1.2	Minimum requirement	167
8.4.1.3	Test purpose	167
8.4.1.4	Method of test	167
8.4.1.4.1	Initial conditions	167
8.4.1.4.2	Procedure.....	168
8.4.1.5	Test requirement	169
Annex A (normative): Reference measurement channels		171
A.1	Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking, receiver intermodulation and in-channel selectivity (QPSK, R=1/3).....	171
A.2	Fixed Reference Channels for dynamic range (16QAM, R=2/3).....	171
A.3	Fixed Reference Channels for performance requirements (QPSK, R=193/1024)	172
A.4	Fixed Reference Channels for performance requirements (16QAM, R=658/1024)	174
A.5	Fixed Reference Channels for performance requirements (64QAM, R=567/1024)	176
A.6	PRACH test preambles.....	176
Annex B (normative): Environmental requirements for the BS equipment		177
B.1	General	177
B.2	Normal test environment.....	177
B.3	Extreme test environment.....	177
B.3.1	Extreme temperature	177
B.4	Vibration.....	178
B.5	Power supply	178
B.6	Measurement of test environments.....	178
Annex C (informative): Test tolerances and derivation of test requirements.....		179
C.1	Measurement of transmitter.....	179
C.2	Measurement of receiver	181
C.3	Measurement of performance requirements	182
Annex D (informative): Measurement system set-up		183
D.1	<i>BS type 1-C</i> transmitter.....	183
D.1.1	Base station output power, output power dynamics, transmitter ON/OFF power, frequency error, EVM, unwanted emissions for <i>BS type 1-C</i>	183
D.1.2	Transmitter intermodulation for <i>BS type 1-C</i>	183
D.1.3	Time alignment error for <i>BS type 1-C</i>	184
D.2	<i>BS type 1-C</i> receiver	184
D.2.1	Reference sensitivity level for <i>BS type 1-C</i>	184
D.2.2	Dynamic range for <i>BS type 1-C</i>	185
D.2.3	In-channel selectivity for <i>BS type 1-C</i>	185
D.2.4	Adjacent Channel Selectivity (ACS) and narrowband blocking for <i>BS type 1-C</i>	185
D.2.5	Blocking characteristics for <i>BS type 1-C</i>	186
D.2.6	Receiver spurious emission for <i>BS type 1-C</i>	186
D.2.7	Intermodulation characteristics for <i>BS type 1-C</i>	187
D.3	<i>BS type 1-H</i> transmitter	187
D.3.1	Base station output power, output power dynamics, transmitter ON/OFF power, frequency error, EVM, unwanted emissions for <i>BS type 1-H</i>	187
D.3.2	Transmitter intermodulation for <i>BS type 1-H</i>	188
D.3.3	Transmitter spurious emissions for <i>BS type 1-H</i>	188
D.3.4	Time alignment error for <i>BS type 1-H</i>	190

D.4	BS type 1-H receiver	190
D.4.1	Reference sensitivity level for BS type 1-H	190
D.4.2	Receiver dynamic range for BS type 1-H	191
D.4.3	Receiver adjacent channel selectivity and narrowband blocking for BS type 1-H	191
D.4.4	Receiver spurious emissions	191
D.4.5	Receiver In-channel selectivity for BS type 1-H	193
D.4.6	Receiver intermodulation for BS type 1-H	193
D.5	<i>BS type 1-C</i> performance requirements	194
D.5.1	Performance requirements for PUSCH, single user PUCCH, PRACH on single antenna port in multipath fading conditions	194
D.5.2	Performance requirements for PUSCH transmission on two antenna ports in multipath fading conditions ..	195
D.5.3	Performance requirements for PRACH in static conditions	195
D.6	BS type 1-H performance requirements	196
D.6.1	Performance requirements for PUSCH, single user PUCCH, PRACH on single antenna port in multipath fading conditions	196
D.6.2	Performance requirements for PUSCH transmission on two antenna ports in multipath fading conditions ..	197
D.6.3	Performance requirements for PRACH in static conditions	197
Annex E (normative):	Characteristics of interfering signals	198
Annex F (normative):	Void	199
Annex G (normative):	Propagation conditions	200
G.1	Static propagation condition	200
G.2	Multi-path fading propagation conditions	200
G.2.1	Delay profiles	200
G.2.1.1	Delay profiles for FR1	201
G.2.2	Combinations of channel model parameters	202
G.2.3	MIMO channel correlation matrices	203
G.2.3.1	MIMO correlation matrices using Uniform Linear Array	203
G.2.3.1.1	Definition of MIMO correlation matrices	203
G.2.3.1.2	MIMO correlation matrices at high, medium and low level	204
G.2.3.2	Multi-antenna channel models using cross polarized antennas	206
G.2.3.2.1	Definition of MIMO correlation matrices using cross polarized antennas	207
G.2.3.2.2	Spatial correlation matrices at UE and gNB sides	207
G.2.3.2.2.1	Spatial correlation matrices at UE side	207
G.2.3.2.2.2	Spatial correlation matrices at gNB side	208
G.2.3.2.3	MIMO correlation matrices using cross polarized antennas	208
Annex H (normative):	In-channel TX tests	209
H.1	General	209
H.2	Basic principles	209
H.2.1	Output signal of the TX under test	209
H.2.2	Ideal signal	209
H.2.3	Measurement results	210
H.2.4	Measurement points	210
H.3	Pre-FFT minimization process	211
H.4	Timing of the FFT window	211
H.5	Resource element TX power	212
H.6	Post-FFT equalisation	213
H.7	EVM	214
H.7.0	General	214
H.7.1	Averaged EVM (FDD)	215
H.7.2	Averaged EVM (TDD)	215

Annex I (informative): **Change history**217
History225

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 138 141-1 V15.16.0 \(2024-05\)](https://standards.iteh.ai/catalog/standards/etsi/94ca4816-e42f-4508-a8b5-10ec064313d4/etsi-ts-138-141-1-v15-16-0-2024-05)

<https://standards.iteh.ai/catalog/standards/etsi/94ca4816-e42f-4508-a8b5-10ec064313d4/etsi-ts-138-141-1-v15-16-0-2024-05>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 138 141-1 V15.16.0 \(2024-05\)](https://standards.iteh.ai/catalog/standards/etsi/94ca4816-e42f-4508-a8b5-10ec064313d4/etsi-ts-138-141-1-v15-16-0-2024-05)

<https://standards.iteh.ai/catalog/standards/etsi/94ca4816-e42f-4508-a8b5-10ec064313d4/etsi-ts-138-141-1-v15-16-0-2024-05>