
**Rubber hoses and hose assemblies —
Rubber-covered spiral-wire-
reinforced hydraulic types for
oil-based or water-based fluids —
Specification**

iT *Tuyaux et flexibles en caoutchouc — Types hydrauliques avec
armature hélicoïdale de fils métalliques pour fluides à base d'huile ou
à base d'eau — Spécifications*
[**\(https://standards.iteh.ai\)**](https://standards.iteh.ai)
Document Preview

[ISO 3862:2017](#)

<https://standards.iteh.ai/catalog/standards/iso/774c4248-6a42-4c05-9bea-719f2a97c045/iso-3862-2017>



Reference number
ISO 3862:2017(E)

© ISO 2017

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 3862:2017](#)

<https://standards.iteh.ai/catalog/standards/iso/774c4248-6a42-4c05-9bea-719f2a97c045/iso-3862-2017>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Classification	2
5 Materials and construction	2
5.1 Hoses	2
5.2 Hose assemblies	2
6 Dimensions	2
6.1 Hose diameters and hose concentricity	2
6.2 Length	5
7 Performance requirements	5
7.1 General	5
7.2 Hydrostatic requirements	5
7.3 Minimum bend radius	6
7.4 Resistance to impulse	7
7.4.1 Resistance to impulse with oil-based fluid	7
7.4.2 Resistance to impulse with water-based fluid	7
7.4.3 Optional impulse test	8
7.5 Leakage of hose assemblies	8
7.6 Cold flexibility	8
7.7 Adhesion between components	8
7.8 Fluid resistance	8
7.8.1 General	8
7.8.2 Oil resistance	8
7.8.3 Water resistance	9
7.9 Ozone resistance	9
7.10 Visual examination	9
8 Marking	9
8.1 Hoses	9
8.2 Hose assemblies	9
Annex A (normative) Type and routine testing of production hoses	11
Annex B (informative) Production acceptance testing	12
Annex C (informative) Recommendations for lengths of supplied hoses and tolerances on lengths of hose assemblies	13

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html

This document was prepared by Technical Committee ISO/TC 45, *Rubber and rubber products*, Subcommittee SC 1, *Rubber and plastics hoses and hose assemblies*.

This fourth edition cancels and replaces the third edition (ISO 3862:2009), which has been technically revised.

[ISO 3862:2017](http://www.iso.org/iso/foreword.html)

The main changes compared to the previous edition are as follows:

- [Clause 1](#) has been updated to be more precise;
- [Clause 2](#) has been updated: ISO 4672 has been deleted and replaced by ISO 10619-2, and ISO 10619-1 has been added;
- [8.1](#) has been revised: year of publication of a standard shall be included in the marking if previous edition is used.

Rubber hoses and hose assemblies — Rubber-covered spiral-wire-reinforced hydraulic types for oil-based or water-based fluids — Specification

1 Scope

This document specifies requirements for five types of spiral-wire-reinforced hydraulic hose and hose assembly of nominal size from 6,3 to 51.

They are suitable for use with:

- oil-based hydraulic fluids HH, HL, HM, HR and HV as defined in ISO 6743-4 at temperatures ranging from -40°C to $+100^{\circ}\text{C}$;
- water-based fluids HFC, HFAE, HFAS and HFB as defined in ISO 6743-4 at temperatures ranging from 0°C to $+60^{\circ}\text{C}$;
- water at temperatures ranging from 0°C to $+60^{\circ}\text{C}$.

This document does not include requirements for end fittings. It is limited to requirements for hoses and hose assemblies.

NOTE It is the responsibility of the user, in consultation with the hose manufacturer, to establish the compatibility of the hose with the fluid to be used.

Document Preview

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1307, *Rubber and plastics hoses — Hose sizes, minimum and maximum inside diameters, and tolerances on cut-to-length hoses*

ISO 1402, *Rubber and plastics hoses and hose assemblies — Hydrostatic testing*

ISO 1817, *Rubber, vulcanized or thermoplastic — Determination of the effect of liquids*

ISO 4671, *Rubber and plastics hoses and hose assemblies — Methods of measurement of the dimensions of hoses and the lengths of hose assemblies*

ISO 6605, *Hydraulic fluid power — Hoses and hose assemblies — Test methods*

ISO 6743-4, *Lubricants, industrial oils and related products (class L) — Classification — Part 4: Family H (Hydraulic systems)*

ISO 6803, *Rubber or plastics hoses and hose assemblies — Hydraulic-pressure impulse test without flexing*

ISO 7326:2016, *Rubber and plastics hoses — Assessment of ozone resistance under static conditions*

ISO 8033:2016, *Rubber and plastics hoses — Determination of adhesion between components*

ISO 8330, *Rubber and plastics hoses and hose assemblies — Vocabulary*

ISO 10619-1:2011, *Rubber and plastics hoses and tubing — Measurement of flexibility and stiffness — Part 1: Bending tests at ambient temperature*

ISO 10619-2:2011, *Rubber and plastics hoses and tubing — Measurement of flexibility and stiffness — Part 2: Bending tests at sub-ambient temperatures*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8330 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

4 Classification

Five types of hose are specified, distinguished by their construction, working pressure and oil resistance:

- Type 4SP: medium-pressure hoses with four plies of steel wire spiral.
- Type 4SH: high-pressure hoses with four plies of steel wire spiral.
- Type R12: heavy-duty high-temperature hoses with a medium-pressure rating having four plies of steel wire spiral.
- Type R13: heavy-duty high-temperature hoses with a high-pressure rating having a multiple-steel-wire spiral.
- Type R15: heavy-duty high-temperature hoses with an extra-high-pressure rating having a multiple-steel-wire spiral.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

5 Materials and construction

[ISO 3862:2017](#)

5.1 Hoses

Hoses shall consist of a rubber lining resistant to oil- or water-based hydraulic fluids, spiral plies of steel wire wrapped in alternating directions, and an oil- and weather-resistant rubber cover. Each spiral wire ply shall be separated by an insulating layer.

5.2 Hose assemblies

Hose assemblies shall be manufactured using hoses conforming to the requirements of this document.

Hose assemblies shall be manufactured only with those hose fittings whose correct functioning has been verified in accordance with [7.2](#), [7.4](#), [7.5](#) and [7.6](#). The manufacturer's instructions shall be followed for the preparation and fabrication of hose assemblies.

6 Dimensions

6.1 Hose diameters and hose concentricity

When measured in accordance with ISO 4671, the inside diameter of hoses shall conform to the values given in [Table 1](#).

When measured in accordance with ISO 4671, the diameter over reinforcement and outside diameter of hoses shall conform to the values given in [Table 2](#).