

Designation: D 4897/D 4897M - 01 (Reapproved 2009)

# Standard Specification for Asphalt-Coated Glass-Fiber Venting Base Sheet Used in Roofing<sup>1</sup>

This standard is issued under the fixed designation D 4897/D 4897M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\varepsilon$ ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

## 1. Scope

- 1.1 This specification covers asphalt-impregnated and coated glass-fiber base sheet with mineral surfacing on the top side and coarse mineral granules on the bottom side for use as the first ply of a roofing membrane. These base sheets provide for the lateral release of pressure in roofing systems because they are not solidly attached and the coarse granular surface provides an open, porous channel in the horizontal plane beneath the membrane. The base sheets shall be permitted to be with or without perforations or embossings.
  - 1.2The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.
- 1.2 The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.
- 1.3 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

#### 2. Referenced Documents

- 2.1 ASTM Standards:<sup>2</sup>
- D 146 Test Methods for Sampling and Testing Bitumen-Saturated Felts and Woven Fabrics for Roofing and Waterproofing
- D 228 Test Methods for Sampling, Testing, and Analysis of Asphalt Roll Roofing, Cap Sheets, and Shingles Used in Roofing and Waterproofing
- D 1079 Terminology Relating to Roofing, Waterproofing, and Bituminous Materials<sup>2</sup> Terminology Relating to Roofing and Waterproofing

# 3. Terminology

3.1 Definitions—For definitions of terms used in this specification, refer to Terminology D 1079.

### 4. Classification

4.1 Type II—Heavy-duty asphalt-coated glass-fiber venting base sheet.

## 5. Materials and Manufacture

- 5.1 The mat shall be a thin porous sheet of uniformly distributed glass fibers, with or without the addition of reinforcing strands, or glass yarns, which are bonded with a water-resistant resinous binder.
- 5.2 In the process of manufacture, the glass mat is impregnated and coated on both sides with a hot asphaltic coating with or without a mineral stabilizer and surfaced on the bottom side with coarse mineral granules embedded in an asphaltic coating. The top side shall be surfaced with fine mineral surfacing.
- 5.3 The product shall be permitted to be embossed or unembossed on the bottom side. The product shall be permitted to contain holes designated for attachment with mopping asphalt.

<sup>&</sup>lt;sup>1</sup> This specification is under the jurisdicton of ASTM Committee D08 on Roofing, Waterproofing, Roofing and Bituminous Materials Waterproofing and is the direct responsibility of Subcommittee D08.04 on Felts and Fabrics for Bituminous Roofing and Waterproofing.

Current edition approved November 10, 2001. Published March 2002. Originally published as D4897–89. Last previous edition D4897–98:on Felts and Fabrics. Current edition approved June 15, 2009. Published July 2009. Originally approved in 1989. Last previous edition approved in 2001 as D 4897 – 01.

<sup>&</sup>lt;sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards, Vol 04.04:volume information, refer to the standard's Document Summary page on the ASTM website.