



SLOVENSKI STANDARD
oSIST prEN 16119:2020
01-april-2020

Oprema in pribor za utekočinjeni naftni plin (UNP) - Tesnilne kape in čepi za ventile jeklenk in tlačnih posod za UNP - Specifikacija in preskušanje

LPG equipment and accessories - Sealing caps and plugs for LPG cylinder and pressure vessel valves - Specification and testing

Flüssiggas-Geräte und Ausrüstungsteile - Dichtkappen und Dichtstopfen für Flaschen und Behälter für Flüssiggas (LPG) - Spezifikation und Prüfungen

Équipements pour GPL et leurs accessoires - Bouchons d'étanchéité mâles et femelles pour robinets de bouteilles et réservoirs - Spécifications et essais

<https://standards.iteh.ai/catalog/standards/sist/37414717-5000-4e1b-856f-925747468c/osist-pr-en-16119-2020>

Ta slovenski standard je istoveten z: prEN 16119

ICS:

23.020.32	Tlačne posode	Pressure vessels
23.020.35	Plinske jeklenke	Gas cylinders
83.140.50	Tesnila	Seals

oSIST prEN 16119:2020

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 16119:2020](#)

<https://standards.iteh.ai/catalog/standards/sist/37414717-5000-4e1b-856f-ca925747468c/osist-pren-16119-2020>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

DRAFT
prEN 16119

April 2020

ICS 23.060.99

Will supersede EN 16119:2013

English Version

LPG equipment and accessories - Sealing caps and plugs for LPG cylinder and pressure vessel valves - Specification and testing

Équipements pour GPL et leurs accessoires - Bouchons
et obturateurs d'étanchéité pour robinets/vannes de
bouteilles et réservoirs - Spécifications et essais

Flüssiggas-Geräte und Ausrüstungsteile - Dichtkappen
und Dichtstopfen für Flaschen und Behälter für
Flüssiggas (LPG) - Spezifikation und Prüfungen

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 286.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	6
4 Operating temperatures	7
5 Materials	7
5.1 Environmental	7
5.2 General	7
5.3 Metallic materials	8
5.4 Non-metallic materials	8
6 Design	8
6.1 General	8
6.2 Threads	9
6.3 Leak tightness	9
7 Testing and inspection of the design	9
7.1 General	9
7.2 LPG resistance	9
7.3 Water resistance	9
7.4 Ageing	10
7.5 Hydraulic strength test	10
7.6 Endurance test	10
7.7 Torque Test	11
8 Marking	11
9 Documentation	11
10 Packaging	11
Annex A (normative) Special low temperature requirements for caps or plugs	12
Annex B (normative) Combined aging test	13
Bibliography	16

iTech STANDARD PREVIEW
(standards.itech.ai)

oSIST prEN 16119:2020

<https://standards.itech.ai/catalog/standards/sist/57414717-3000-4e16-856f-ca925747468c/osist-pr-en-16119-2020>

European foreword

This document (prEN 16119:2020) has been prepared by Technical Committee CEN/TC 286 “LPG equipment and accessories”, the secretariat of which is held by NSAI.

This document is currently submitted to the CEN Enquiry.

This document will supersede EN 16119:2013.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN 16119:2020](https://standards.iteh.ai/catalog/standards/sist/37414717-5000-4e1b-856f-ca925747468c/osist-pren-16119-2020)

<https://standards.iteh.ai/catalog/standards/sist/37414717-5000-4e1b-856f-ca925747468c/osist-pren-16119-2020>

prEN 16119:2020 (E)**Introduction**

This document calls for the use of substances and procedures that may be injurious to health and/or the environment if adequate precautions are not taken. It refers only to technical suitability and does not absolve the user from legal obligations at any stage.

Protection of the environment is a key political issue in Europe and elsewhere. Protection of the environment is taken in a very broad sense. What is meant is the total life cycle aspects of, e.g. a product on the environment, including expenditure of energy and during all phases from mining of raw materials, fabrication, packaging, distribution, use, scrapping, recycling of materials, etc.

NOTE Annex C indicates the clauses in this document that address environmental issues.

Provisions need to be restricted to a general guidance. Limit values are specified in national laws.

It is recommended that manufacturers develop an environmental management policy. For guidance, see the EN ISO 14000 series.

It has been assumed in the drafting of this document that the execution of its provisions is entrusted to appropriately qualified and experienced people.

All pressures are gauge pressures unless otherwise stated.

This document requires measurement of material properties, dimensions and pressures. All such measurements are subject to a degree of uncertainty due to tolerances in measuring equipment etc. It may be beneficial to refer to the leaflet 'Measurement uncertainty leaflet SP INFO 2000 27' [3].

ITEH STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 16119:2020](https://standards.iteh.ai/catalog/standards/sist/37414717-5000-4e1b-856f-ca925747468c/osist-pren-16119-2020)

<https://standards.iteh.ai/catalog/standards/sist/37414717-5000-4e1b-856f-ca925747468c/osist-pren-16119-2020>

1 Scope

This document specifies the design, testing and marking requirements for caps and plugs used to form a pressure tight seal with liquefied petroleum gas (LPG) cylinder valves and pressure vessel valves. Sealing caps and plugs provide an additional seal for self-closing and manually operated valves.

Dust caps or plugs and tamper evident seals that do not form an additional seal as part of their design are excluded from the scope of this document.

Cylinder valve caps and plugs can be used with valves for liquid and vapour manufactured in accordance with EN ISO 14245 and EN ISO 15995.

Pressure vessel valve caps and plugs can be used with valves for liquid and vapour manufactured in accordance with EN 13175. Occasional liquid withdrawal valve caps and plugs are excluded from the scope of this document.

Reusable and single use sealing caps and plugs are included in this document.

This document does not exclude the use of other designs that provide an equivalent level of safety.

NOTE The term “pressure vessel” does not include LPG tank vehicles, also called “road tankers”, in CEN/TC 286 standards.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 549, *Rubber materials for seals and diaphragms for gas appliances and gas equipment*

EN 751-1, *Sealing materials for metallic threaded joints in contact with 1st, 2nd and 3rd family gases and hot water — Part 1: Anaerobic jointing compounds*

EN 751-2, *Sealing materials for metallic threaded joints in contact with 1st, 2nd and 3rd family gases and hot water — Part 2: Non-hardening jointing compounds*

EN 751-3, *Sealing materials for metallic threaded joints in contact with 1st, 2nd and 3rd family gases and hot water — Part 3: Unsintered PTFE tapes*

EN 12164, *Copper and copper alloys — Rod for free machining purposes*

EN 12165, *Copper and copper alloys — Wrought and unwrought forging stock*

EN 12420, *Copper and copper alloys — Forgings*

EN 13175, *LPG equipment and accessories — Specification and testing for Liquefied Petroleum Gas (LPG) tank valves and fittings*

EN 15202, *LPG equipment and accessories — Essential operational dimensions for LPG cylinder valve outlet and associated equipment connections*

EN ISO 11114-1, *Gas cylinders — Compatibility of cylinder and valve materials with gas contents — Part 1: Metallic materials (ISO 11114-1)*

EN ISO 11114-2, *Gas cylinders — Compatibility of cylinder and valve materials with gas contents — Part 2: Non-metallic materials (ISO 11114-2)*

prEN 16119:2020 (E)

EN ISO 14021, *Environmental labels and declarations — Self-declared environmental claims (Type II environmental labelling) (ISO 14021)*

EN ISO 14024, *Environmental labels and declarations — Type I environmental labelling — Principles and procedures (ISO 14024)*

EN ISO 14025, *Environmental labels and declarations — Type III environmental declarations — Principles and procedures (ISO 14025)*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1 liquefied petroleum gas
LPG
low pressure liquefied gas composed of one or more light hydrocarbons which are assigned to UN 1011, UN 1075, UN 1965, UN 1969 or UN 1978 only and which consists mainly of propane, propene, butane, butane isomers, butene with traces of other hydrocarbon gases

Note 1 to entry: In some countries, UN numbers 1011 and 1978 may also be designated LPG.

3.2 plug
component which seals a female connection

[oSIST prEN 16119:2020](https://standards.iteh.ai/catalog/standards/sist/37414717-5000-4e1b-856f-015747468c/osist-pren-16119-2020)

<https://standards.iteh.ai/catalog/standards/sist/37414717-5000-4e1b-856f-015747468c/osist-pren-16119-2020>

3.3 cap
component which seals a male connection

3.4 cylinder valve
primary shutoff device intended for liquid filling and liquid or vapour service fitted to LPG cylinders

Note 1 to entry: The valve can also include additional devices e.g. liquid level indicator, excess flow device, pressure relief valve, sediment tube, non-return valve and eduction tube.

3.5 leak tightness
resistance to gas leakage under a specified pressure differential

3.6 sealing cap or plug
device which is intended to seal the inlet and or outlet connection of a valve

Note 1 to entry: It may also provide protection to the valve connection. The device may provide protection against the ingress of dust, dirt or other contamination. The device may also be used to provide tamper evidence.

3.7**dust cap or plug**

device which is intended to protect the inlet or outlet of a valve against the ingress of dust, dirt or other contamination

3.8**reusable sealing caps and plugs**

sealing caps and plugs that are designed for reuse and have a means of attachment to the valve

3.9**single use sealing caps and plugs**

sealing caps or plugs that are rendered incapable of reuse in their original condition by their removal from the valve

3.10**tamper evidence**

visible indication that interference has taken place with the cap or plug of the cylinder or pressure vessel

Note 1 to entry: This also includes sealing caps or plugs where a tamper evident strip is destroyed by their removal from the valve.

3.11**Standard Temperature and Pressure****STP**

15,6 °C (288,7 K), 1,013 bar absolute (0,101 3 MPa absolute)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

4 Operating temperatures

Caps and plugs designed in accordance with this document shall be suitable for the following conditions:

- a) a minimum operating temperature of -20 °C ;
- b) a minimum operating temperature of -40 °C for those parts of Europe where caps or plugs are subject to more severe temperature conditions; the material and design shall be shown to be satisfactory for operations under these conditions and shall meet the requirements of Annex A;
- c) a maximum operating temperature of 65 °C .

5 Materials**5.1 Environmental**

The manufacturer shall endeavour to acquire materials and components from suppliers who have a declared environmental policy; see EN ISO 14021, EN ISO 14024 and EN ISO 14025.

5.2 General

5.2.1 Materials in contact with LPG shall be physically and chemically compatible with LPG under all normal operating conditions for which the cap or plug is intended and shall meet the requirements for propane and butane in accordance with EN ISO 11114-1 and EN ISO 11114-2.

5.2.2 Metallic and non metallic materials used for the cap or plug shall be selected to give adequate strength in service. Material shall be selected to resist failure due to atmospheric corrosion, ultraviolet

prEN 16119:2020 (E)

rays, brass dezincification, stress corrosion or material failure. The cap or plug material shall be compatible with the valve body material.

5.3 Metallic materials

5.3.1 Metallic materials shall be stainless steel, copper alloys, aluminium alloys, zinc alloys, or other suitable materials.

5.3.2 Hot stamped brass shall be non-porous and shall be suitable for machining or other processes. Sand-cast brass shall not be used.

Leaded brass shall be CW614N or CW617N in accordance with EN 12164 or EN 12165 and forged brass in accordance with EN 12420.

Cold drawn brass rods up to 45 mm in diameter shall only be used after heat treatment and testing for internal cracking. Cold drawn brass rods greater than 45 mm in diameter shall not be used.

Components produced from stamping brass shall not exhibit cold shuts, also known as folds, or surface defects.

5.3.3 Stainless steels shall contain not less than 16 % chromium and not less than 7 % nickel.

5.3.4 Castings shall be free from inclusions and surface defects, which adversely affect the strength, leak tightness or performance of the cap or plug.

5.4 Non-metallic materials

5.4.1 All non-metallic materials for caps and plugs shall not distort, harden or adhere to the body of the valve.

5.4.2 All rubber materials shall also comply with the requirements of EN 549.

5.4.3 Where used on operating threads and seals, lubricants, sealants and adhesives shall be compatible with LPG and not interfere with the operation of the plug or cap. Sealants shall comply with EN 751-1, EN 751-2 or EN 751-3.

6 Design**6.1 General**

6.1.1 The cap or plug components shall be designed with adequate strength and adequate clearances to ensure correct operation under normal conditions of service, handling and carriage.

6.1.2 The cap or plug sealing element shall be secured to prevent it becoming lost during the intended period of service. Where a cap or plug is intended to be attached to the valve, the connection element shall be designed to ensure that it is retained for the intended period of service.

6.1.3 Reusable caps or plugs shall be designed for the strength appropriate to the maximum allowable pressure of the contents at 65 °C. This shall ensure that the caps or plugs do not permanently deform or rupture to the extent that it impairs use.

6.1.4 The cap or plug shall be designed to ensure leak tightness appropriate to the maximum allowable pressure of the contents at 50 °C.

6.1.5 The design should take account of the following: