

INTERNATIONAL
STANDARD

ISO
5295

Third edition
2017-04

**Synchronous belts — Calculation of
power rating and drive centre distance**

*Courroies synchrones — Calcul de la puissance transmissible et de
l'entraxe*

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 5295:2017](#)

<https://standards.iteh.ai/catalog/standards/iso/9716c90-8a4e-4196-a76c-7a537295ce41/iso-5295-2017>

Reference number
ISO 5295:2017(E)



© ISO 2017

iTeh Standards

(<https://standards.iteh.ai>)

Document Preview

[ISO 5295:2017](#)

<https://standards.iteh.ai/catalog/standards/iso/9716c90-8a4e-4196-a76c-7a537295ce41/iso-5295-2017>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols	2
5 Basic power rating	2
6 Power rating	2
6.1 Exact formula	2
6.2 Approximate formula	3
7 Centre distance	3
7.1 Exact formula	3
7.2 Approximate formula	4
8 Number of teeth in mesh	4
9 Factor k_z	4
10 Factor k_w	4

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 5295:2017](#)

<https://standards.iteh.ai/catalog/standards/iso/9716c90-8a4e-4196-a76c-7a537295ce41/iso-5295-2017>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html

The committee responsible for this document is ISO/TC 41, *Pulleys and belts (including veebelts)* Subcommittee SC 4, *Synchronous belt drives*.

This third edition cancels and replaces the second edition (ISO 5295:1987), which has been technically revised. The scope been revised to clarify the applicability of the document.

<https://standards.iteh.ai/catalog/standards/iso/9716c90-8a4e-4196-a76c-7a537295ce41/iso-5295-2017>

Synchronous belts — Calculation of power rating and drive centre distance

1 Scope

This document establishes formulae for the calculation of power rating and centre distance of standard synchronous belts on two pulley drives.

It is applicable to trapezoidal belts only. It does not apply to curvilinear synchronous belts.

The numerical values of certain parameters used in the calculations depend upon the pitch and the construction of the belt and are specified by the belt manufacturer.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <http://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

<http://www.iso.org/obp> ISO 5295:2017

power rating power that a specified synchronous belt can transmit under specified geometrical and ambient conditions for a satisfactory period of time, provided that the drive has been installed and is maintained in a proper manner

Note 1 to entry: The power rating depends on the following:

- the pitch of the belt and pulley teeth;
- the belt width;
- the mass of a linear metre of belt;
- the allowable working tension in the belt;
- the angular velocity of the smaller pulley;
- the number of teeth of the smaller pulley;
- the number of teeth in mesh on the smaller pulley.

4 Symbols

Symbol	Description	Units
P_b	pitch of the teeth of the belt and pulleys	mm
b_s	width of the belt to be rated	mm
b_{so}	base width of the widest standard belt of pitch P_b (see Table 2)	mm
m	linear mass of a belt having a width b_{so}	kg/m
T_a	allowable working tension of a belt having a width b_{so}	N
w	angular velocity of the smaller pulley	rad/s
v	belt velocity	m/s
z_1	number of teeth of the smaller pulley	
z_2	number of teeth of the larger pulley	
z_b	number of teeth of the belt	
Z_m	number of teeth in mesh on the smaller pulley	
c	centre distance of the pulleys	mm
P_o	power rating of a belt of base width b_{so}	kW
P	power rating of a belt of base width b_s	kW
k_w	width factor	
k_z	teeth in mesh factor	
ent []	integer part only of the expression following	

5 Basic power rating (<https://standards.iteh.ai>)

The basic power rating of a belt of base width, b_{so} , is given by the [Formula \(1\)](#):

$$P_o = \frac{(T_a - mv^2)v}{1000} \quad \text{ISO 5295:2017} \quad (1)$$

<https://standards.iteh.ai/catalog/standards/iso/9716c90-8a4e-4196-a76c-7a537295ce41/iso-5295-2017>

where the belt velocity, v , has the value given by [Formula \(2\)](#):

$$v = \frac{\omega P_b z_1 \times 10^{-3}}{2\pi} \quad (2)$$

[Formula \(1\)](#) is valid only if the number of teeth in mesh $z_m \geq 6$ (see [Clause 6](#) for $z_m < 6$).

The values of T_a and m depend upon the construction and the type of belt; these shall be supplied by the belt manufacturer.

6 Power rating

6.1 Exact formula

The power rating of a belt of width, b_s , having z_m teeth in mesh on the smaller pulley, is given by [Formula \(3\)](#):

$$P = \left(k_z k_w T_a - \frac{b_s m v^2}{b_{so}} \right) v \times 10^{-3} \quad (3)$$

See [Clauses 9](#) and [10](#) for k_z and k_w , respectively.