# INTERNATIONAL STANDARD

Third edition 2018-01

# Aerospace — Tripod jacks — Clearance dimensions

*Aéronautique — Vérins de levage tripodes — Dimensions d'encombrement* 

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 1464:2018 https://standards.iteh.ai/catalog/standards/sist/ba1426bb-ebac-4dbb-b5b1-66fff1cffdb3/iso-1464-2018



Reference number ISO 1464:2018(E)

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 1464:2018 https://standards.iteh.ai/catalog/standards/sist/ba1426bb-ebac-4dbb-b5b1-66fff1cffdb3/iso-1464-2018



### **COPYRIGHT PROTECTED DOCUMENT**

#### © ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Published in Switzerland

Page

## Contents

| Forew | ordiv                   |
|-------|-------------------------|
| 1     | Scope1                  |
| 2     | Normative references 1  |
| 3     | Terms and definitions 1 |
| 4     | Requirements 1          |

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 1464:2018 https://standards.iteh.ai/catalog/standards/sist/ba1426bb-ebac-4dbb-b5b1-66fff1cffdb3/iso-1464-2018

### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. <u>www.iso.org/directives</u>

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. <u>www.iso.org/patents</u>

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: Foreword - Supplementary information (standards.iteh.ai)

This document was prepared by Technical Committee ISO/TC 20, Aircraft and space vehicles, Subcommittee SC 9, Air cargo and ground equipment. https://standards.iteh.a/catalog/standards/sist/ba1426bb-ebac-4dbb-b5b1-

This third edition cancels and replaces the second edition (180/1464:1985), which has been technically revised.

The main changes compared to the previous edition are as follows:

<u>Clause 3</u> and <u>Table 1</u> have been technically revised by adding jacks with a load capacity between 1 112 kN and 1 600 kN for very heavy aircraft.

## Aerospace — Tripod jacks — Clearance dimensions

### 1 Scope

3

This document specifies the minimum clear space to be provided beneath the aircraft main jacking points, in order to accommodate tripod jacks and thus ensure adequate clearance between the jacks and the adjacent aircraft structure.

This document is not intended to define fully all jack clearance dimensions. In situations where clearances are critical, it is used as a design aid only. Final critical clearances are established by using actual jack dimensions.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 43, Aircraft — Jacking pads

### **iTeh STANDARD PREVIEW** Terms and definitions

(standards.iteh.ai) No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at thttp://www.electropedia.org/
- ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>

### **4** Requirements

The minimum clear space to be provided under aircraft main jacking points, to accommodate tripod jacks, shall be in the form of a truncated right pyramid having an equilateral triangular base and limiting edges at 30° to the vertical axis.

The height of the pyramid shall be sufficient to reach the airplane jacking pad at the maximum airplane height before jacking. The dimensions of the truncated top of the pyramid shall be such as to meet the dimensions of the inscribed circle given in the Table. In addition, in order to ensure adequate jack stability, the base of the pyramid shall have a minimum leg radius from the vertical centreline of 0,3 times the maximum extended jack height.

In applications where the jacking pad is embedded within the surface of the airplane, this pyramid shall have an additional clear space in the shape of a cylinder on top of the pyramid and on the vertical centreline of the pyramid. This cylinder shall be such as to meet the space requirements of the appropriate main jacking pad configuration specified in ISO 43.

The above requirements are illustrated in <u>Figures 1</u>, <u>2</u> and <u>3</u>.

| Jack capacity Diameter of apex ci         |                | apex circle |
|---|----------------|-------------|
| kN (lbf)                                  | <b>mm</b> (in) |             |
| Less than 44,5 (10 000)                   | 152,4          | (6)         |
| 44,5 to less than 500 (10 000 to 112 000) | 228,6          | (9)         |
| 500 to 1 112 (112 000 to 250 000)         | 304,8          | (12)        |
| 1 112 to 1 600 (250 000 to 359 700)       | 381            | (15)        |

Table 1 — Values of apex circle diameter



#### Key

- 1 jacking pad before jacking
- 2 floor level
- 3 truncated top of pyramid
- 4 diameter of circle from table to establish dimension of top of pyramid

### Figure 1 — Upper: side view, lower: plan view



#### Key

- 1 jacking pad
- 2 maximum jack height
- 3 floor level
- 4 0,3 times maximum jack height







#### Key

- 1 clearance cylinder
- 2 airplane structure
- 3 height as required to provide structural clearance for top of truncated pyramid
- 4 jacking pad
- 5 floor level
- 6 diameter of circle from table
- 7 diameter of cylinder to provide clearance as defined in ISO 43

Figure 3 — Upper: side view, lower: plan view

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 1464:2018 https://standards.iteh.ai/catalog/standards/sist/ba1426bb-ebac-4dbb-b5b1-66fff1cffdb3/iso-1464-2018