
Measurement of multiphase fluid flow

Mesurage des écoulements de fluides polyphasiques

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/970426fd-b404-4387-97ad-8ecf8dc56096/iso-prf-ts-21354>

PROOF / ÉPREUVE



iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/970426fd-b404-4387-97ad-8ecf8dc56096/iso-prf-ts-21354>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
3.1 Terms related to multiphase flow metering.....	1
3.2 Terms related to metrology.....	7
4 Symbols and subscripts	9
4.1 Symbols.....	9
4.2 Colours and symbols used in schematic drawings.....	10
5 Multiphase flow	11
5.1 General.....	11
5.2 Multiphase flow regime maps.....	11
5.2.1 General.....	11
5.2.2 Vertical flows.....	12
5.2.3 Horizontal flows.....	13
5.3 Slip effects.....	14
5.4 Classification of multiphase flows.....	15
6 Aims of multiphase flow measurement	16
6.1 General.....	16
6.2 Individual-well surveillance or monitoring.....	18
6.2.1 General.....	18
6.2.2 Production optimization.....	19
6.2.3 Flow assurance.....	19
6.3 Well testing.....	19
6.3.1 General.....	19
6.3.2 Conventional well testing.....	20
6.3.3 Well testing by MPFMs.....	21
6.4 Production allocation metering.....	23
6.5 Fiscal or custody transfer measurement.....	26
6.6 Summary of advantages and disadvantages of MPFMs.....	26
7 Production envelope and installation design guidelines	26
7.1 General.....	26
7.2 Production envelope.....	27
7.2.1 Plotting the production envelope in the two-phase flow map.....	27
7.2.2 Plotting the production envelope in the composition map.....	28
7.3 MPFM measuring envelope.....	29
7.3.1 Plotting the MPFM measuring envelope in the two-phase flow map.....	29
7.3.2 Plotting the MPFM measuring envelope in the composition map.....	30
7.4 Using the flow maps during testing.....	31
7.5 Cumulative performance plot.....	33
7.6 Other considerations.....	34
8 Performance specification	37
8.1 General.....	37
8.2 Technical description.....	38
8.3 Specification of individual sensors and primary devices.....	38
8.4 Specification of output data and formats.....	38
8.5 Measuring range, rated operating conditions and limiting conditions.....	39
8.6 Measurement uncertainty.....	39
8.6.1 General.....	39
8.6.2 Measurement uncertainty evaluation of MPFMs.....	40

8.6.3	Influence quantities and sensitivity coefficients.....	40
8.6.4	Repeatability.....	41
8.6.5	Stability and frequency response.....	41
8.7	Guideline on MPFM performance specification.....	41
8.7.1	General.....	41
8.7.2	Technical descriptions.....	42
8.7.3	Specification of input data.....	42
8.7.4	Specification of output data.....	42
8.7.5	Rated operating conditions and limiting conditions.....	43
8.7.6	Measurement uncertainty.....	44
8.7.7	Two-phase flow map.....	46
8.7.8	Composition map.....	46
9	Testing, calibration and adjustment.....	46
9.1	General.....	46
9.2	Factory acceptance testing (FAT).....	47
9.3	Calibration and test of MPFMs.....	48
9.3.1	General.....	48
9.3.2	Performance verification in static conditions.....	48
9.3.3	Performance verification in dynamic conditions.....	49
9.3.4	Factory test.....	51
9.3.5	Test facility.....	51
9.3.6	<i>In situ</i> test.....	53
9.3.7	Further information on performance testing.....	55
9.3.8	Test report.....	58
9.4	Adjustment of MPFMs.....	60
9.4.1	General.....	60
9.4.2	Adjustment based on static configuration.....	60
9.4.3	Adjustment based on performance verification in dynamic conditions.....	60
9.5	Blind tests.....	61
9.5.1	Scope and objective of MPFM blind test.....	61
9.5.2	Organization and implementation.....	61
9.5.3	Multiphase flow loop.....	61
9.5.4	Test matrix.....	62
9.5.5	Information to be provided by MPFM vendors.....	63
9.5.6	Information provided to MPFM vendors.....	63
9.5.7	Test completion.....	63
9.5.8	Test results and deliverables.....	64
10	Field installation and commissioning.....	64
10.1	General.....	64
10.2	Installation considerations.....	64
10.3	Installation and site integration.....	65
10.3.1	General.....	65
10.3.2	Installation requirements.....	66
10.3.3	Electrical connections and power requirements.....	66
10.3.4	Function test.....	66
10.3.5	Fluid calculation checks.....	66
10.4	Commissioning.....	66
10.4.1	General.....	66
10.4.2	Preparation.....	67
10.4.3	Documentation and equipment.....	67
10.4.4	On site authorization.....	67
10.4.5	Commissioning activities.....	67
10.5	Start-up.....	68
11	Verification during operation.....	68
11.1	General.....	68
11.2	Baseline monitoring.....	69
11.3	Self-checking / self-diagnostic capabilities / internal redundancy.....	70

11.4	Comparison with model-based multiphase flow calculations.....	70
11.5	Two meters in series.....	70
11.6	Mobile test units.....	71
11.7	Tracer technology.....	71
11.8	Injection.....	72
11.9	Sampling.....	72
	11.9.1 General.....	72
	11.9.2 Sampling for information about WLR.....	72
11.10	Imbalances and reconciliation factor.....	72
11.11	Geo-chemical fingerprinting.....	74
11.12	Subsea systems verification.....	74
Annex A (informative) Multiphase meter technologies.....		75
Annex B (informative) Fluid properties and hydrocarbon behaviour.....		87
Annex C (informative) Example of field test reference measurements.....		92
Bibliography.....		96

iTeh STANDARD PREVIEW
 (standards.iteh.ai)
 Full standard:
<https://standards.iteh.ai/catalog/standards/sist/970426fd-b404-4387-97ad-8ecf8dc56096/iso-prf-ts-21354>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 28, *Petroleum and related products, fuels and lubricants from natural or synthetic sources*, Subcommittee SC 2, *Measurement of petroleum and related products*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The need for multiphase flow measurement in the oil and gas production industry has been evident for many years. Multiphase meters have been developed since the early eighties by research organizations, meter manufacturers, oil and gas production companies and others: different technologies and various combinations of technologies have been employed. Some technologies have been abandoned, whereas other meters have become commercially available: the number of applications and users is increasing.

The first Norwegian Society for Oil and Gas Measurement (NFOGM) handbook of multiphase metering (hereafter simply called the Handbook) was published in 1995 (see Reference [9]). Since then, multiphase flow measurement has matured. New applications of multiphase flow meters (MPFMs) have emerged, from simply being a replacement for the conventional test separator shared by a number of wells, towards more compact and low-cost meters with application on a one-per-well basis and installations on shore, topside and subsea.

Since multiphase flow metering technologies and applications had developed significantly since 1995, NFOGM updated the Handbook in 2003-5 to reflect these improvements and to make it the main guide for state-of-the-art multiphase flow measurement. That work was financed by NFOGM and The Norwegian Society of Chartered Technical and Scientific Professionals (Tekna).

Following calls from industry to produce an ISO document, NFOGM very generously allowed ISO to use the Handbook as the basis for this document.

This document is intended to serve as guidance for users, designers and manufacturers of multiphase metering systems.

The document can also serve as an introduction to newcomers in the field of multiphase flow measurement, with definition of terms and a description of multiphase flow in closed conduits being included.

Even if the individual flow rates of each constituent are of primary interest, often their ratios (e.g. water liquid ratio, gas oil ratio) are useful as operational parameters. Total hydrocarbon mass flow rate can be required in particular applications. Constituents other than oil, gas and water flow rates or ratios of these are not dealt with in this document.

The performance of a multiphase flow meter in terms of uncertainty, repeatability and range is of great importance, as this enables the user to compare different meters and evaluate their suitability for use in specific applications. [Clause 8](#) covers this issue in detail and proposes standard methods to describe performance.

Testing and qualification of MPFMs are required to verify performance. Guidance is provided to help optimize the outcome of such activities. Since MPFMs measure at line conditions, the primary output is individual flow rates and fractions at actual conditions (e.g. at the operating pressure and temperature). Conversion of these actual flow rates to flow rates at standard conditions requires knowledge of composition and mass transfer between the liquid and the gas phases, which can require sampling.

The clauses logically proceed from an introduction to multiphase flow measurement, via selection of technology, design considerations and performance specifications, to field installation and commissioning, and finally the operation of MPFMs.

The definitions in [Clause 3](#) have been extended and split into definitions relating to multiphase flows in a closed conduit (see [3.1](#)) and definitions relating to metrology that can be useful in characterizing the performance of a multiphase flow meter.

[Clause 5](#) provides a general introduction to multiphase flows. This clause includes extended descriptions of flow regimes and slip effects in multiphase flows.

[Clause 6](#) covers the aims of multiphase flow measurement, giving the reasoning for selection, installation and operation of multiphase flow metering systems in various applications.

[Clause 7](#) presents guidelines for designing MPFM installations using the two-phase flow map and the composition map.

Standardized performance specification of MPFMs is essential, both for comparison of measuring ranges and measurement uncertainties, but also for more efficient selection of technology ([Clause 8](#)).

[Clause 9](#) covers all aspects of testing, calibration and adjustment of MPFMs.

[Clause 10](#) provides recommended procedures and practices for field installation and commissioning of MPFMs. Although MPFMs cannot easily be sent to a test facility for recalibration, there is a need for regular testing to verify the meter performance.

The purpose of [Clause 11](#) is to provide guidelines on how to verify meter performance in the field during operation, assuming no test separator is readily available.

[Annex A](#) includes brief descriptions of the most commonly used measurement principles in MPFMs currently available on the market. Guidance on selection of technology and maintenance requirements is also provided. [Annex B](#) gives relevant information on hydrocarbon phase behaviour.

Aspects of safety are not dealt with in this document. It is the responsibility of the user to ensure that the system meets applicable safety regulations.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/970426fd-b404-4387-97ad-8ecf8dc56096/iso-prf-ts-21354>

Measurement of multiphase fluid flow

1 Scope

This document establishes a common basis for, and assistance in, the classification of applications and multiphase meters, as well as guidance and recommendations for the implementation and use of such meters.

The so-called in-line multiphase flow meters (MPFMs) that directly measure the oil, water and gas flow rates, as well as the partial- and full-separation MPFMs are the main focus of this document. Conventional two- or three-phase separators are not included in this document. Only limited reference is made to wet-gas meters, since although wet-gas flow is a subset of multiphase flow, wet-gas measurement is covered by ISO/TR 11583 and ISO/TR 12748.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5167 (all parts), *Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full*

ISO/TR 7066-1:1997, *Assessment of uncertainty in calibration and use of flow measurement devices — Part 1: Linear calibration relationships*

ISO/TR 11583:2012, *Measurement of wet gas flow by means of pressure differential devices inserted in circular cross-section conduits*

ISO 11631:1998, *Measurement of fluid flow — Methods of specifying flowmeter performance*

ISO/TR 12748:2015, *Natural Gas — Wet gas flow measurement in natural gas operations*

ISO/IEC Guide 98-3:2008, *Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1 Terms related to multiphase flow metering

3.1.1

actual conditions

meter *in-situ* process operating conditions of pressure and temperature, at which measured flow rates are reported, without conversion to a standard or reference fluid state

3.1.2

composition map

graph with *gas volume fraction* (3.1.9) and *water liquid ratio* (3.1.42) along the x- and y-axis, respectively

Note 1 to entry: Both the GVF and WLR (3.1.42) are at *actual conditions* (3.1.1).

3.1.3

dispersed flow

flow where a particular *phase* (3.1.23) is broken up into multiple small bubbles or droplets carried within the body of another phase

Note 1 to entry: Examples of such flows are bubble flow and mist flow.

3.1.4

emulsion

colloidal mixture of two immiscible fluids, one being dispersed in the other in the form of fine droplets

Note 1 to entry: In multiphase fluids, discrimination should be made between oil-in-water emulsion and water-in-oil (3.1.21) emulsion; they respond differently to permittivity measurements.

3.1.5

flow regime

dynamic spatial and velocity distribution of flowing fluid *phases* (3.1.23) within a conduit

Note 1 to entry: This is also known as flow pattern.

Note 2 to entry: For example, in two-phase oil/water stratified flow in horizontal pipes free water occupies the bottom of the conduit with *oil* (3.1.21) or oil/water mixture flowing above.

3.1.6

gas

hydrocarbons in the gaseous state at the prevailing temperature and pressure

3.1.7

gas oil ratio

GOR

ratio of *gas* (3.1.6) *volume flow rate* (3.1.38) and *oil* (3.1.21) *volume flow rate*

Note 1 to entry: Both volume flow rates should be converted to the same pressure and temperature [generally at *standard conditions* (3.1.35)]. GOR is expressed in volume per volume, F_{GOR} , e.g. scft/bbl or m^3/m^3 .

3.1.8

gas void fraction

ratio of the cross-sectional area in a conduit occupied by the *gas* (3.1.6) *phase* (3.1.23) and the cross-sectional area of the conduit

Note 1 to entry: This is also known as gas hold-up.

3.1.9

gas volume fraction

GVF

gas (3.1.6) *volume flow rate* (3.1.38), relative to the multiphase volume flow rate, at *actual conditions* (3.1.1)

Note 1 to entry: The GVF is normally expressed as a fraction or percentage.

3.1.10

homogeneous multiphase flow

multiphase flow in which all *phases* (3.1.23) are evenly distributed over the cross section of a closed conduit

Note 1 to entry: A homogeneous multiphase flow is, therefore, one in which the composition is the same at all points in the cross section and where the liquid and *gas* (3.1.6) velocities are the same (no-slip). Note that bubbly multiphase *flow regimes* (3.1.5) are probably the best approximation to homogeneous multiphase flow.

3.1.11**intermittent flow**

flow characterized by being non-continuous in the axial direction, that is, exhibiting unsteady *phase* (3.1.23) hold-up locally

Note 1 to entry: Examples of such flows are plug, churn and slug flow (see Figures 1 and 2): the *flow regimes* (3.1.5) are all hydrodynamic (see 5.1) two-phase gas-liquid flow regimes.

3.1.12**liquid hold-up**

ratio of the cross-sectional area in a conduit occupied by the liquid *phase* (3.1.23) and the cross-sectional area of the conduit

3.1.13**liquid volume fraction****LVF**

liquid *volume flow rate* (3.1.38), relative to the multiphase volume flow rate, at *actual conditions* (3.1.1)

Note 1 to entry: The LVF is normally expressed as a fraction or percentage.

3.1.14**Lockhart-Martinelli parameter** **X**

square root of the ratio of the liquid inertia to the *gas* (3.1.6) inertia if the *phases* (3.1.23) flowed alone at *actual conditions* (3.1.1), that is

$$X = \frac{q_{v,\text{liquid}}}{q_{v,\text{gas}}} \sqrt{\frac{\rho_{\text{liquid}}}{\rho_{\text{gas}}}} = \frac{1 - F_{\text{GVF}}}{F_{\text{GVF}}} \sqrt{\frac{\rho_{\text{liquid}}}{\rho_{\text{gas}}}}$$

where

$q_{v,\text{liquid}}$ is the volume flow rate of the liquid;

$q_{v,\text{gas}}$ is the volume flow rate of the gas;

ρ_{liquid} is the density of the liquid;

ρ_{gas} is the density of the gas;

F_{GVF} is the GVF.

Note 1 to entry: The Lockhart-Martinelli parameter has a long and complicated history. There are several different definitions for this parameter, and they are not equivalent. This includes the original definition by Lockhart-Martinelli which is different from the stated definition here. The definition supplied in this document is now commonly used. Nevertheless, this issue continues to cause confusion in the industry. The different definitions are described in detail with historical context in References [23] and [3].

Note 2 to entry: In the second formula above, the relationship of the Lockhart-Martinelli number and the *GVF* (3.1.9) is a function of the density ratio.

Note 3 to entry: An increasing value of X means an increasing liquid content or wetness of the flow.

3.1.15**mass flow rate**

mass of fluid flowing through the cross section of a conduit in unit time

3.1.16**measuring envelope**

areas in the *two-phase flow map* (3.1.37) and the *composition map* (3.1.2) in which the *MPFM* (3.1.18) performs according to its specifications

3.1.17

multiphase flow

flow consisting of two or more *phases* (3.1.23) flowing simultaneously in a closed conduit

Note 1 to entry: This document deals in particular with multiphase flows of *oil* (3.1.21), water and *gas* (3.1.6) in the entire region of 0–100 % *GVF* (3.1.9) and 0–100 % *WLR* (3.1.42).

3.1.18

multiphase flow meter

MPFM

device for measuring the individual *oil* (3.1.21), water and *gas* (3.1.6) flow rates in a *multiphase flow* (3.1.17)

Note 1 to entry: The total package of measurement devices for composition and velocity, including possible conditioning unit, should be considered as an integral part of the meter.

3.1.19

multiphase mixture velocity

ratio of the *multiphase volume flow rate* (3.1.20) and the cross-sectional area of the conduit

Note 1 to entry: This is a fictitious velocity: only in *homogeneous multiphase flow* (3.1.10) does this velocity have a meaningful value. Multiphase mixture velocity is the sum of *gas* (3.1.6) superficial velocity and liquid superficial velocity.

3.1.20

total volume flow rate

multiphase volume flow rate

total volume flowing through the cross-sectional area of a conduit per unit time

3.1.21

oil

hydrocarbons in the liquid state at the prevailing temperature and pressure conditions

3.1.22

oil-continuous flow

flow in which water is distributed as droplets surrounded by *oil* (3.1.21)

Note 1 to entry: Electrically, the mixture acts as an insulator.

3.1.23

phase

one constituent in a mixture of several

Note 1 to entry: In particular, the term refers to *oil* (3.1.21), *gas* (3.1.6) or water in a mixture of any number of the three. It is recognized that the terminology of the multiphase industry is different from that in much of science.

3.1.24

phase area fraction

cross-sectional area locally occupied by one of the *phases* (3.1.23) of a *multiphase flow* (3.1.17), relative to the cross-sectional area of the conduit at the same local position

3.1.25

phase flow rate

amount of one *phase* (3.1.23) of a *multiphase flow* (3.1.17) flowing through the cross section of a conduit in unit time

Note 1 to entry: The phase flow rate may be specified as *phase volume flow rate* (3.1.38) or as *phase mass flow rate* (3.1.15).

3.1.26**phase volume fraction**

phase (3.1.23) *volume flow rate* (3.1.38) of one of the phases of a *multiphase flow* (3.1.17), relative to the *multiphase volume flow rate* (3.1.20), at *actual conditions* (3.1.1)

3.1.27**production envelope**

areas in the *two-phase flow map* (3.1.37) and the *composition map* (3.1.2) that are determined by a number of well trajectories or specified as possible flow rates and compositions that will occur in a certain application

3.1.28**proving**

set of operations that establish, under specified conditions, the relationship between the values of quantities indicated by a device and the corresponding values as determined by a traceable reference device (proving system)

3.1.29**reconciliation**

process whereby pieces of information that include some redundancy are matched together to satisfy constraint equations

Note 1 to entry: In *oil* (3.1.21) and *gas* (3.1.6) production, reconciliation is the process in which oil, water and *gas* (3.1.6) production figures that have not been measured with high *accuracy* (3.2.1) are recalculated to match production figures that have been measured with high accuracy (e.g. custody transfer measurements).

3.1.30**reference conditions**

conditions, in terms of pressure and temperature, at which fluid properties or *volume flow rates* (3.1.38) are expressed

3.1.31**salinity**

amount of dissolved salts that are present in water

Note 1 to entry: Salinity is normally expressed in units g/kg.

Note 2 to entry: Sodium and chloride are the predominant ions in seawater, and the concentrations of magnesium, calcium, and sulfate ions are also substantial.

3.1.32**slip**

flow condition that exists when the *phases* (3.1.23) have different average velocities

Note 1 to entry: The slip may be quantitatively expressed by the average phase velocity difference between the phases. See 5.3.

3.1.33**slip ratio**

ratio between two phase-average velocities

Note 1 to entry: See 5.3.

3.1.34**slip velocity**

phase (3.1.23) velocity difference between two phases

Note 1 to entry: See 5.3.