INTERNATIONAL STANDARD



First edition 2019-05

Information technology — Computer graphics, image processing and environmental data representation — Live actor and entity representation in mixed and augmented reality (MAR)

Technologies de l'information — Infographie, traitement de l'image et représentation des données environnementales — Représentation d'acteurs et d'entités réels en réalité mixte et augmentée (MAR)

Document Preview

ISO/IEC 18040:20

https://standards.iteh.ai/catalog/standards/iso/b945ed23-b4a2-494d-90d1-2b96474affe9/iso-iec-18040-2019



Reference number ISO/IEC 18040:2019(E)

ISO/IEC 18040:2019

https://standards.iteh.ai/catalog/standards/iso/b945ed23-b4a2-494d-90d1-2b96474affe9/iso-iec-18040-2019



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Page

Forev	vord		v	
Intro	ductio	n	vi	
1	Scop	e	1	
2	Norr	- native references	- 1	
2	Torre	a definitions and abhurnists descents		
3	1ern	IS, definitions and abbreviated terms	I	
	3.2	Abbreviated terms		
4	Conc	conts of LAE conceptation in MAR	3	
4	4.1 Overview			
	4.2	Components		
		4.2.1 General	6	
		4.2.2 LAE capturer and sensor	7	
		4.2.3 LAE recognizer		
		4.2.4 LAE tracker		
		4.2.5 LAE spatial mapper		
		4.2.6 LAE event mapper		
		4.2.7 Renderer		
		4.2.8 Display and user interface		
		4.2.9 Scene representation	8	
5	LAE	capturer and sensor in the standard sensor	9	
	5.1	Overview		
	5.2	Computational view	9	
		5.2.1 General		
		5.2.2 LAE capturer		
	F 0	5.2.3 LAE sensor		
	5.3	Informational view		
6	Trac	ker and spatial mapper for an LAE		
	6.1	Overview standards/150/0943ed23-04a2-494d-90d1-20904/4a11e9/150-1e	13	
	6.2	Computational view		
	6.3	Informational view		
	6.4	An example of LAE tracking and spatial mapping in MAR		
7	Reco	gnizer and event mapper for an LAE		
	7.1	Overview		
	7.2	Recognizer		
	7.3	Event mapper		
	7.4	Event execution		
	7.5	Examples of LAE recognizing and event mapping in MAR		
8	Scen	e representation for an LAE		
	8.1	Overview		
	8.2	Scene description		
9	Rend	lerer	24	
-	9.1	Overview		
	9.2	Computational view		
	9.3	Information view		
10	Disp	Display and UI		
11	Exte	nsions to virtual actor and entity		
12	Syste	em performance		
13	Safet	y		

14	Conformance	28
Annex	x A (informative) Use case examples	31
Biblio	graphy	39

ISO/IEC 18040:2019

https://standards.iteh.ai/catalog/standards/iso/b945ed23-b4a2-494d-90d1-2b96474affe9/iso-iec-18040-2019

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see http://www.iso.org/patents) or the IEC list of patent declarations received (see http://www.iso.org/patents) or the IEC list of patent declarations received (see http://www.iso.org/patents) or the IEC list of patent declarations received (see http://www.iso.org/patents) or the IEC list of patent declarations received (see http://wwww.iso.org/patents) or the IEC list of patent declarations received (see http://www.iso.org/patents) or the IEC list of patent declarations received (see http://www.iso.org/patents) or the list of patent declarations received (see http://wwww.iso.org/patents) or the IEC list of patents iso.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see <u>www.iso</u> .org/iso/foreword.html.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 24, *Computer graphics, image processing and environmental data representation*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

Introduction

This document defines the scope and key concepts of a representation model for a live actor and entity (LAE) to be included in a mixed and augmented reality (MAR) world. The relevant terms and their definitions, and a generalized system architecture, together serve as a reference model for MAR applications, components, systems, services and specifications. It defines representing and rendering an LAE in an MAR scene, and interaction interfaces between an LAE and objects in an MAR scene. It defines a set of principles, concepts and functionalities for an LAE applicable to the complete range of current and future MAR standards. This reference model establishes the set of required modules and their minimum functions, the associated information content, and the information models that shall be provided and/or be supported by a compliant MAR system. It includes (but is not limited to) the following content:

- an introduction to the mixed and augmented reality standards domain and concepts;
- a representation model for including an LAE in an MAR scene;
- 3D modelling, rendering and simulation of an LAE in an MAR scene;
- attributes of an LAE in an MAR scene;
- sensing representation of an LAE in an MAR scene;
- representation of the interfaces for controlling an LAE in an MAR scene;
- functionalities and base components for controlling an LAE in an MAR scene;
- interactive interfaces between an LAE and an MAR scene;
- interface with other MAR components;
- relationship to other standards;
- use cases.

ISO/IEC 18040:2019

The objectives of this document are as follows: b945ed23-b4a2-494d-90d1-2b96474affe9/iso-iec-18040-2019

- provide a reference model for LAE representation-based MAR applications;
- manage and control an LAE with its properties in an MAR environment;
- integrate an LAE into a 2D and/or 3D virtual scene in an MAR scene;
- achieve interaction of an LAE with a 2D and/or 3D virtual scene in an MAR scene;
- provide an exchange format necessary for transferring and storing data between LAE-based MAR applications.

This document has the following document structure:

- <u>Clause 4</u> describes the concepts of LAE-based systems represented in MAR.
- <u>Clause 5</u> illustrates how a sensor captures an LAE in a physical world and a virtual world.
- <u>Clause 6</u> describes mechanisms to track the position of an LAE and specifies the role of a spatial mapper between physical space and the MAR space.
- <u>Clause 7</u> describes mechanisms to recognize the behaviour of an LAE and specifies an association or event between an MAR event of an LAE and the condition specified by the MAR content creator.
- <u>Clause 8</u> describes a scene, which consists of a virtual scene, sensing data, a spatial scene, events, targets and so on, for an LAE.

- <u>Clause 9</u> describes how the MAR scene system renders the scene, LAE mapping, event and so on for
 presentation output on a given display device.
- <u>Clause 10</u> describes types of displays, including monitors, head mounted displays, projectors, haptic devices and sound output devices for displaying an LAE in an MAR scene.
- <u>Clause 11</u> identifies and describes virtual LAE, such as virtual 3D model (avatar) and virtual LAE, such as real human model in an MAR system.
- <u>Clause 12</u> makes statements regarding any system performance related issues of an LAE in MAR.
- <u>Clause 13</u> makes statements regarding any operational safety related issues of an LAE in MAR.
- <u>Clause 14</u> makes statements regarding any conformance related issues of an LAE in MAR.
- <u>Annex A</u> gives examples of representative LAE representation systems in MAR.

ISO/IEC 18040:2019

https://standards.iteh.ai/catalog/standards/iso/b945ed23-b4a2-494d-90d1-2b96474affe9/iso-iec-18040-2019

<u>ISO/IEC 18040:2019</u> https://standards.iteh.ai/catalog/standards/iso/b945ed23-b4a2-494d-90d1-2b96474affe9/iso-iec-18040-2019

Information technology — Computer graphics, image processing and environmental data representation — Live actor and entity representation in mixed and augmented reality (MAR)

1 Scope

This document defines a reference model and base components for representing and controlling a single LAE or multiple LAEs in an MAR scene. It defines concepts, a reference model, system framework, functions and how to integrate a 2D/3D virtual world and LAEs, and their interfaces, in order to provide MAR applications with interfaces of LAEs. It also defines an exchange format necessary for transferring and storing LAE-related data between LAE-based MAR applications.

This document specifies the following functionalities:

- a) definitions for an LAE in MAR;
- b) representation of an LAE;
- c) representation of properties of an LAE;
- d) sensing of an LAE in a physical world;
- e) integration of an LAE into a 2D/3D virtual scene;
- f) interaction between an LAE and objects in a 2D/3D virtual scene;
- g) transmission of information related to an LAE in an MAR scene.
- This document defines a reference model for LAE representation-based MAR applications to represent and to exchange data related to LAEs in a 2D/3D virtual scene in an MAR scene. It does not define specific physical interfaces necessary for manipulating LAEs, that is, it does not define how specific applications need to implement a specific LAE in an MAR scene, but rather defines common functional interfaces for representing LAEs that can be used interchangeably between MAR applications.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 18039, Information technology — Computer graphics, image processing and environmental data representation — Mixed and augmented reality (MAR) reference model

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 18039 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at http://www.electropedia.org/

3.1.1

augmented object

object with augmentation

3.1.2

geographic coordinate system

coordinate system which is provided by sensor devices for defining a location of *LAE* (3.1.4)

3.1.3

head mounted display

HMD

device which displays stereo views of virtual reality

Note 1 to entry: It has two small displays with lenses and semi-transparent mirrors which can adapt to the left and right eyes.

3.1.4

live actor and entity

LAE

representation of a living physical or real object, such as a human being, animal or bird, in the MAR content or system

Note 1 to entry: A live actor can be animated, moved and interacted with virtual objects in an MAR scene by capturing gesture from a camera. Entity refers to 3D objects and entities that exist in MAR content.

3.1.5

LAE recognizer

MAR component that recognizes the output from an *LAE capturer* (3.1.6) and an LAE sensor, then generates MAR events based on conditions indicated by the content creator

3.1.6

LAE capturer

MAR component that captures an *LAE* (3.1.4) in a virtual world and a physical world, which includes depth cameras, general cameras, 360° cameras and so on

Note 1 to entry: LAE's information can be processed by an LAE recognizer and an LAE tracker to extract background or skeleton.

3.1.7

LAE tracker

MAR component (hardware and software) that analyses signals from *LAE capturers* (3.1.6) and sensors and provides some characteristics of a tracked *LAE* (3.1.4) (for example position, orientation, amplitude, profile)

3.1.8

physical camera coordinate system

coordinate system which is provided by a camera for capturing *LAE(s)* (3.1.4) in physical world

3.1.9

physical coordinate system

coordinate system that enables locating an LAE (3.1.4) and is controlled by a geospatial coordinate system sensing device

3.1.10 virtual actor and entity VAE virtual reality representation of an *LAE* (3.1.4)

Note 1 to entry: The virtual actor and entity is obtained by a 3D capturing technique and can be reconstructed, transmitted or compressed in the MAR scene. A virtual actor and entity can be captured in one place or transmitted to another place in real time using holography technology.

3.1.11

world coordinate system

universal system in computer graphics that allows model coordinate systems to interact with each other

3.2 Abbreviated terms

For the purposes of this document, the abbreviated terms given in ISO/IEC 18039 and the following apply.

dance dance revolution
event identifier
field of view
global navigation satellite system
live actor and entity representation in mixed and augmented reality
red, green, blue
software development kit
sensor identifier
user interface <u>ISO/IEC 18040:2019</u>
universal transverse mercator

VR virtual reality

4 Concepts of LAE representation in MAR

4.1 Overview

As illustrated in ISO/IEC 18039, MAR represents a continuum which encompasses all domains or systems that use a combination of reality (for example live video) and virtuality representations (for example computer graphic objects or scene) as its main presentation medium^{[1][2]}. Figure 1 illustrates the MAR that is defined according to a mixture of reality and virtuality representations excluding pure real environment and pure virtual environment with viewpoints of an LAE representation. The real environment refers to the physical world environment where an LAE and physical objects are located. Virtual environment commonly refers to virtual reality, that is the computer-generated realistic images and hypothetical world that replicate a real environment. Augmented reality refers to the view of the real-world environment whose elements include LAE and objects that can be augmented by computer-generated sensory, and augmented virtuality is the virtual environment within which physical world elements including LAE can be mapped and interacted. In Figure 1, an LAE wears an HMD device to see the virtual world and interacts directly with virtual objects.

ISO/IEC 18040:2019(E)



Figure 1 — Mixed and augmented reality (MAR)

This clause describes the concepts of LAE representation in an MAR scene based on the MAR reference model (MAR-RM) of ISO/IEC 18039, which includes objectives, embedding, interaction and functions of the system for representing an LAE in an MAR scene. In general, an actor is an individual who portrays a character in a performance. In this case, an actor represents a human captured by a depth camera or a general camera, which can then perform actions that are embedded into an MAR scene. A 3D object that exists in an MAR scene and can interact with a live actor is called an entity. The entity can be moved or interact with an actor's motion via an event mapper. An LAE in this document is defined as a representation of a physical living actor and an object in an MAR content or system. For example, human beings, birds and animals are all represented as LAEs in an MAR scene.

Figure 2 shows the examples of LAE representation in an MAR scene which consists of 2D virtual world and 3D virtual world that can be described as the following.

Figure 2 a) shows an LAE integrated into a 2D virtual world that is a real or virtual image. The LAE can be captured from general camera and/or depth camera sensors. This subfigure shows a real-like action where a man is captured by cameras in a green screen studio and is integrated as an actor into a 2D virtual world image of the White House.

Figure 2 b) shows multiple LAEs integrated into a 3D virtual world. This scenario can be applicable in various situations, such as news studios, education services, virtual surgical operations or games^{[3][4]}. It supports an integrative combination application of 3D videoconferencing, reality-like communication features, presentation/application sharing and 3D model display within a mixed environment.

Figure 2 c) shows an MAR scene constructed by integrating a 3D virtual world and a live actor^[5]. The live actor interacts with objects in the 3D virtual world by using a joystick or by motion captured by a depth camera. An HMD device is used to display 360° 3D views, including real time and real-like action, in the virtual world^[6]. The figure shows a man in the studio wearing an HMD through which he sees the bow sling training field and handling a joystick. By handling the joystick, it appears that he is handling the arrow and bow sling. As a result, he can shoot at objects in the virtual world.

Figure 2 d) shows a virtual actor and entity with representation in the physical world^[Z]. The virtual LAE and LAE can communicate and interact with each other, for example to have a natural face-to-face conversation. When combined with MAR, this technology allows an LAE to see, hear and interact with a virtual LAE in a 3D virtual space, just like a real presentation in physical space.

Figure 2 e) describes the LAE representation as a bird and a dog from which it can be inferred that LAE can be animals, birds or humans to be represented in MAR scene.