# INTERNATIONAL STANDARD

ISO 11393-2

Second edition 2018-09

# Protective clothing for users of handheld chainsaws —

# Part 2:

# Performance requirements and test methods for leg protectors

Vêtements de protection pour utilisateurs de scies à chaîne tenues à la main —

Partie 2: Exigences de performance et méthodes d'essai pour protège-jambes

ISO 11393-2:2018



# iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 11393-2:2018

https://standards.iteh.ai/catalog/standards/iso/2a0adf99-10da-4cb6-9172-e13d47d39be8/iso-11393-2-2018



#### COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Con	tents		Page
Forev	vord		<b>v</b>
Intro	duction	n	<b>vi</b> i
1	Scone	e	1
2	_	native references	
3	Terms and definitions		
4	-	irements	
	4.1	General	
	4.2	Innocuousness	
	4.3	Sizing	ර ඉ
	4.4 4.5	Ergonomics	
	4.5	Dimensional and other changes	
		4.5.1 Dimensional change	
	4.6	Protective coverage	
	1.0	4.6.1 General designs of leg protectors	
		4.6.2 Design A	
		4.6.3 Design B (chaps)	
		4.6.4 Design C	
	4.7	Resistance to cutting by a chainsaw	
		4.7.1 Classification according to chain speed	
		4.7.2 Requirements for cut resistance	
	4.8	Requirements for strength of attachment of protective insert of trousers, chaps	
		and strap attachment for chaps	10
		4.8.1 Trousers and leggings	10
		4.8.2 Chaps	11
5	Test s	specimens for cut testing	11
6	Tost r	methods	11
s://stan	6.1		1811
	0.1	6.1.1 Cleaning	
		6.1.2 Pre-treatment for testing the effect of temperature and spinning on the	11
		structure of the protective insert	12
	6.2	Measurement of dimensional change	
	6.3	Measurement of protective coverage	
		6.3.1 General	
		6.3.2 Procedure for trousers and leggings	12
		6.3.3 Procedure for chaps	
	6.4	Testing of resistance to cutting	13
		6.4.1 Purpose of testing	
		6.4.2 Test specimens	
		6.4.3 Apparatus	
		6.4.4 Mounting of test specimens	
		6.4.5 Test procedure	
	6.5	Measurement of the strength of the protective insert attachment	
		6.5.1 General	
		6.5.2 Test specimens	
		6.5.3 Apparatus	
	6.6	6.5.4 Test procedure	
	6.6	Ergonomic testing	
		6.6.1 Ergonomic assessment 6.6.2 Procedures	
		6.6.3 Test for surface conditions	
	6.7	Test report	
	0.7		10

## ISO 11393-2:2018(E)

7	Marking	.18
8	Pictogram	.19
9	Information to be supplied by the manufacturer	.19
Annex	A (informative) Selection of design A, design B or design C	.21
Biblio	graphy	.22

# iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 11393-2:2018

### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 162, *Protective clothing including hand and arm protection and lifejackets*, in collaboration with ISO Technical Committee TC 94, *Personal safety* — *Personal protective equipment*, Subcommittee SC 13, *Protective clothing*, in accordance with the agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 11393-2:1999), which has been technically revised. The main changes compared to the previous edition are as follows:

- in the Introduction, the term "hand-held chainsaws primarily constructed for cutting wood" has been added;
- the normative references have been updated;
- the terms and definitions <u>3.1</u>, <u>3.2</u>, <u>3.3</u>, <u>3.4</u>, <u>3.5</u>, <u>3.6</u>, <u>3.7</u>, <u>3.9</u>, <u>3.10</u>, <u>3.12</u>, <u>3.14</u> and <u>3.17</u> have been added;
- in <u>Clause 4</u>, subclauses have been added, PPE for users of left-handed chainsaws has been added, the previous "design B" has been deleted, a new "design B" has been added to describe chaps, the definition for trousers has been specified and a definition valid for chaps has been added;
- in <u>Clause 5</u>, the definition has been specified;
- in <u>Clause 6</u>, the clause has been completely revised, pre-treatment regulation for testing has been changed; the definitions in <u>6.2</u>, <u>6.3</u>, <u>6.5</u> and <u>6.7</u> have been specified, a definition valid for chaps has been added, cuts of the smallest and largest sizes have been added, measuring of chaps has been added, a test method ergonomic testing has been added;
- in <u>Clause 7</u>, marking requirements have been revised;
- in <u>Clause 9</u>, information requirements have been revised;
- in <u>Clause 9</u>, the definition has been specified.

### ISO 11393-2:2018(E)

A list of all parts in the ISO 11393 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

# iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 11393-2:2018

## Introduction

This document forms part of a series concerned with personal protective equipment (PPE) designed to protect against the risks arising from the use of hand-held chainsaws primarily constructed for cutting wood.

No PPE can ensure a 100 % protection against cutting from a hand-held chainsaw. Nevertheless, experience has shown that it is possible to design PPE that offers a certain degree of protection.

Different functional principles may be applied in order to give protection. These include:

- a) chain slipping: on contact the chain does not cut the material;
- b) clogging: fibres are drawn by the chain into the drive sprocket and block chain movement;
- c) chain braking: fibres have a high resistance to cutting and absorb rotational energy, thereby reducing the chain speed.

Often more than one principle is applied.

# iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 11393-2:2018

# iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 11393-2:2018

# Protective clothing for users of hand-held chainsaws —

# Part 2:

# Performance requirements and test methods for leg protectors

## 1 Scope

This document specifies the performance requirements, test methods, design requirements, identification and marking information for leg protectors that offer protection against cutting by handheld chainsaws.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5077, Textiles — Determination of dimensional change in washing and drying

ISO 7000, Graphical symbols for use on equipment — Registered symbols

ISO 11393-1:2018, Protective clothing for users of hand-held chainsaws — Part 1: Test rig for testing resistance to cutting by a chainsaw

ISO 13688:2013, Protective clothing — General requirements

ISO 13935-2, Textiles — Seam tensile properties of fabrics and made-up textile articles — Part 2: Determination of maximum force to seam rupture using the grab method

ISO 17249, Safety footwear with resistance to chain saw cutting

ISO 20345, Personal protective equipment — Safety footwear

#### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>
- IEC Electropedia: available at <a href="http://www.electropedia.org/">http://www.electropedia.org/</a>

#### 3.1

#### attachment

connection (usually stitching) between the protective insert and the outer or lining fabric

#### 3.2

#### attachment force

force that the connection between the protective insert and any structural fabric can withstand, independent of the way the protective insert is attached to the outer fabric

### ISO 11393-2:2018(E)

#### 3.3

#### chaps

leg protectors (3.11) that cover the front of a leg and fasten around the waist and the back of the leg

#### 3.4

#### crotch

point between the legs where the two side seams (3.17), which run up the inside of each leg, meet

Note 1 to entry: In cases where the side seams do not lie along the edge of the trousers when they are flattened out, the theoretical crotch point effectively becomes the point where the two edges of the trousers converge.

#### 3.5

#### cut-through

any visible change on the underside of the innermost layer of the test sample caused by the saw chain

#### 3.6

#### damage

due to a broken ladder during the pre-treatment (3.12) cycle

Note 1 to entry: The broken ladder is often caused by a broken knitting yarn.

#### 3.7

#### fly

fastening in the *front* (3.8) of a pair of trousers

# 3.8 iTeh Standards

#### front

<leg protector> forward 50 % of the leg circumference

#### 3.9

#### joins

place or line where two or more parts of the *protective insert* (3.14) are connected or fastened together, e.g. by *seams* (3.17) or zippers

3.10 tps://standards.iteh.ai/catalog/standards/iso/2a0adf99-10da-4cb6-9172-e13d47d39be8/iso-11393-2-2018

#### leggings

seat-less trousers

#### 3.11

#### leg protectors

any type of protective garment that protects at least the *specified protective area* (3.18) to a specified level of resistance for the leg

#### 3.12

#### pre-treatment

standard way of preparing the samples before testing

Note 1 to entry: This might include a number of cleaning cycles, submitting the sample to heat, mechanical action or any other relevant exposure, and is finished by conditioning.

#### 3.13

#### protective coverage

area of the garment that is covered by protective material (3.15)

#### 3.14

#### protective insert

fabric, usually placed between the outer fabric and the lining of a garment, that is able to stop the chain by clogging, braking or repelling the chain

#### 3.15

#### protective material

material that is designed to protect the wearer against the cutting effect of a hand-held chainsaw

Note 1 to entry: The protective material may include the outer fabric of the garment.

#### 3.16

#### rear

<leg protector> backwards 50 % of the leg circumference

Note 1 to entry: Depending upon the design and construction, and due to many layers of clogging material, it can be difficult to establish the *front* (3.8) and the rear of a leg protector. It is nevertheless of great importance to establish the front and the rear before *pre-treatment* (3.12) and testing.

#### 3.17

#### seam

join where two or more layers of fabric, leather or other materials are held together with stitches

#### 3.18

#### specified protective area

minimum required *protective coverage* (3.13)

## 4 Requirements

### 4.1 General

General requirements not specifically covered in this document shall be in accordance with ISO 13688.

Tested samples shall conform to all the requirements of this document.

#### 4.2 Innocuousness

Leg protectors shall not adversely affect the health or hygiene of the user. The materials shall not release or degrade to release substances generally known to be toxic, carcinogenic, mutagenic, toxic to reproduction or otherwise harmful in the foreseeable conditions of normal use. The specific innocuousness requirements of ISO 13688:2013, 4.2, shall be met.

### 4.3 Sizing

Leg protectors shall be marked with their size in accordance with ISO 13688.

### 4.4 Ergonomics

The leg protectors shall be designed to minimize discomfort and any impediment to movement while wearing them. When tested according to <u>6.6.2</u>, the average score shall be 2 or less. The construction around the crotch shall facilitate lunges. When tested according to <u>6.6.2</u>, all adjustment systems shall not become incorrectly adjusted without the user's knowledge.

NOTE Lunges means to take a long step forward keeping the trailing foot still while bending the knee of the leading leg.

When tested according to <u>6.6.3</u>, the design shall be without any appendages below the knee region, which can become entangled in machinery or the undergrowth. The only possible exceptions to this requirement are the fastening points of chaps (design B). The leg protector shall be free of rough surfaces, sharp edges, sharp points, etc., which could cause excessive irritation or injuries.