

INTERNATIONAL STANDARD



**Information technology – Small Computer System Interface (SCSI) –
Part 454: SCSI Primary Commands – 4 (SPC-4)**

(standards.iteh.ai)

[ISO/IEC 14776-454:2018](https://standards.iteh.ai/catalog/standards/sist/c511791c-bf67-46c7-8d4b-1b6a11745f3b/iso-iec-14776-454-2018)

<https://standards.iteh.ai/catalog/standards/sist/c511791c-bf67-46c7-8d4b-1b6a11745f3b/iso-iec-14776-454-2018>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2018 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 21 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

<https://standards.iteh.ai/catalog/standards/sist/c511792c-6107-46c7-8d4b-1b6a11745f3b/iso-iec-14776-454-2018>



ISO/IEC 14776-454

Edition 1.0 2018-04

INTERNATIONAL STANDARD



Information technology – Small Computer System Interface (SCSI) –
Part 454: SCSI Primary Commands – 4 (SPC-4)

<https://standards.iteh.ai/catalog/standards/sist/c511791c-bf67-46c7-8d4b-1b6a11745f3b/iso-iec-14776-454-2018>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.200

ISBN 978-2-8322-5595-7

Warning! Make sure that you obtained this publication from an authorized distributor.

Contents

	Page
1 Scope	40
2 Normative references	40
3 Terms, definitions, symbols, abbreviations, and conventions	45
3.1 Terms and definitions	45
3.2 Abbreviations and symbols	65
3.2.1 Abbreviations	65
3.2.2 Symbols	67
3.2.3 Mathematical operators	67
3.3 Keywords	68
3.4 Conventions	69
3.5 Numeric and character conventions	70
3.5.1 Numeric conventions	70
3.5.2 Units of measure	70
3.5.3 Byte encoded character strings conventions	71
3.6 Bit and byte ordering	71
3.7 Notation conventions	73
3.7.1 Notation for procedure calls	73
3.7.2 Notation for state diagrams	74
3.7.3 Notation for flowcharts	75
3.7.4 Notation for UML figures	75
3.7.4.1 Overview	75
3.7.4.2 Class notation	77
3.7.4.3 Class association relationships notation	77
3.7.4.4 Class aggregation relationships notation	78
3.7.4.5 Class generalization relationships notation	80
3.7.4.6 Class dependency relationships notation	81
3.7.4.7 Object notation	81
3.7.5 Notation for EXTENDED COPY command segment descriptors	81
4 General concepts	82
4.1 Introduction	82
4.2 Command Descriptor Block	82
4.2.1 CDB usage and structure	82
4.2.2 Fixed length CDB formats	83
4.2.2.1 Formats for 6-byte CDBs	83
4.2.2.1.1 Generic 6-byte CDB format	83
4.2.2.1.2 Typical 6-byte CDB format	83
4.2.2.2 Formats for 10-byte CDBs	84
4.2.2.2.1 Generic 10-byte CDB format	84
4.2.2.2.2 Typical 10-byte CDB format	85
4.2.2.3 Formats for 12-byte CDBs	86
4.2.2.3.1 Generic 12-byte CDB format	86
4.2.2.3.2 Typical 12-byte CDB format	86
4.2.2.3.3 MAINTENANCE IN CDB format	87
4.2.2.3.4 MAINTENANCE OUT CDB format	88
4.2.2.3.5 SERVICE ACTION IN(12) CDB format	88
4.2.2.3.6 SERVICE ACTION OUT(12) CDB format	89
4.2.2.4 Formats for 16-byte CDBs	89
4.2.2.4.1 Generic 16-byte CDB format	89
4.2.2.4.2 Typical 16-byte CDB format, if eight-byte LBAs not supported	90
4.2.2.4.3 Typical 16-byte CDB format with eight-byte LBAs supported	91
4.2.2.4.4 SERVICE ACTION IN(16) CDB format	92

4.2.2.4.5 SERVICE ACTION OUT(16) CDB format	92
4.2.2.4.6 SERVICE ACTION BIDIRECTIONAL CDB format	93
4.2.3 Variable length CDB formats	93
4.2.3.1 Generic variable length CDB format	93
4.2.3.2 Typical 32-byte variable length CDB format	95
4.2.4 Extended CDBs	96
4.2.4.1 XCDB model	96
4.2.4.2 The XCDB format	96
4.2.5 Common CDB fields	98
4.2.5.1 Operation code	98
4.2.5.2 Service action	98
4.2.5.3 Logical block address	98
4.2.5.4 Transfer length	99
4.2.5.5 Parameter list length	99
4.2.5.6 Allocation length	99
4.3 Data field requirements	99
4.3.1 ASCII data field requirements	99
4.3.2 Null data field termination and zero padding requirements	100
4.3.3 Variable type data field requirements	100
4.3.4 Port identifier field requirements	100
4.4 Secure random numbers	101
4.5 Sense data	101
4.5.1 Sense data introduction	101
4.5.2 Descriptor format sense data	102
4.5.2.1 Descriptor format sense data overview	102
4.5.2.2 Information sense data descriptor	104
4.5.2.3 Command-specific information sense data descriptor	105
4.5.2.4 Sense key specific sense data descriptor	106
4.5.2.4.1 Sense key specific sense data descriptor overview	106
4.5.2.4.2 Field pointer sense key specific information	107
4.5.2.4.3 Actual retry count sense key specific information	108
4.5.2.4.4 Progress indication sense key specific information	108
4.5.2.4.5 Segment pointer sense key specific information	109
4.5.2.4.6 Unit attention condition queue overflow sense key specific information	109
4.5.2.5 Field replaceable unit sense data descriptor	110
4.5.2.6 Another progress indication sense data descriptor	110
4.5.2.7 Forwarded sense data	111
4.5.2.8 Vendor specific sense data descriptors	112
4.5.3 Fixed format sense data	113
4.5.4 Returning a value in the INFORMATION field in the sense data	114
4.5.5 Returning a value in the COMMAND-SPECIFIC INFORMATION field in the sense data	115
4.5.6 Current information	115
4.5.7 Deferred errors	116
4.5.8 Sense key and additional sense code definitions	117
5 Model common to all device types	136
5.1 Introduction to the model common to all device types	136
5.1.1 Overview	136
5.1.2 Important commands for all SCSI device servers	136
5.1.2.1 Commands implemented by all SCSI device servers	136
5.1.2.2 Commands recommended for all SCSI device servers	136
5.1.2.3 Using the INQUIRY command	136
5.1.2.4 Using the REPORT LUNS command	136
5.1.2.5 Using the TEST UNIT READY command	137
5.1.2.6 Using the REQUEST SENSE command	137
5.1.3 Implicit head of queue	137
5.2 Device clocks and timestamps	137

5.3 Device specific background functions	138
5.3.1 Introduction	138
5.3.2 Suspending and resuming device specific background functions	139
5.4 Downloading and activating microcode	140
5.4.1 Downloading microcode	140
5.4.2 Activating microcode	144
5.5 Error history	145
5.5.1 Error history overview	145
5.5.2 Retrieving error history with the READ BUFFER command	145
5.5.3 Adding application client error history with the WRITE BUFFER command	148
5.5.4 Clearing error history with the WRITE BUFFER command	148
5.6 Identifying information	149
5.7 Medium auxiliary memory	149
5.8 Parameter rounding	150
5.9 Parsing variable length parameter lists and parameter data	151
5.10 Pollable condition information	152
5.10.1 Information that does not represent an exception condition	152
5.10.2 REQUEST SENSE pollable sense data	152
5.10.2.1 Making information available for the REQUEST SENSE command	152
5.10.2.2 Selecting pollable sense data to return	152
5.10.2.3 Returning one or more progress indications	152
5.10.3 Log parameter pollable device condition information	153
5.11 Power management	153
5.11.1 Power management overview	153
5.11.2 Power consumption management	153
5.11.3 Power conditions management	154
5.11.4 Active power condition	155
5.11.5 Idle power conditions	155
5.11.6 Standby power conditions	156
5.11.7 Power condition pollable sense data	156
5.11.8 Power condition state machine	157
5.11.8.1 Power condition state machine overview	157
5.11.8.2 PC0:Powered_On state	158
5.11.8.2.1 PC0:Powered_On state description	158
5.11.8.2.2 Transition PC0:Powered_On to PC4:Active_Wait	159
5.11.8.3 PC1:Active state	159
5.11.8.3.1 PC1:Active state description	159
5.11.8.3.2 Transition PC1:Active to PC5:Wait_Idle	159
5.11.8.3.3 Transition PC1:Active to PC6:Wait_Standby	159
5.11.8.4 PC2:Idle state	159
5.11.8.4.1 PC2:Idle state description	159
5.11.8.4.2 Transition PC2:Idle to PC4:Active_Wait	160
5.11.8.4.3 Transition PC2:Idle to PC5:Wait_Idle	160
5.11.8.4.4 Transition PC2:Idle to PC6:Wait_Standby	160
5.11.8.5 PC3:Standby state	160
5.11.8.5.1 PC3:Standby state description	160
5.11.8.5.2 Transition PC3:Standby to PC4:Active_Wait	161
5.11.8.5.3 Transition PC3:Standby to PC6:Wait_Standby	161
5.11.8.6 PC4:Active_Wait state	161
5.11.8.6.1 PC4:Active_Wait state description	161
5.11.8.6.2 Transition PC4:Active_Wait to PC1:Active	162
5.11.8.7 PC5:Wait_Idle state	162
5.11.8.7.1 PC5:Wait_Idle state description	162
5.11.8.7.2 Transition PC5:Wait_Idle to PC2:Idle	162
5.11.8.8 PC6:Wait_Standby state	163
5.11.8.8.1 PC6:Wait_Standby state description	163
5.11.8.8.2 Transition PC6:Wait_Standby to PC3:Standby	163

5.12 Reservations.....	163
5.12.1 Persistent Reservations overview	163
5.12.2 Third party persistent reservations	168
5.12.3 Exceptions to SPC-2 RESERVE and RELEASE behavior	168
5.12.4 Persistent reservations interactions with iSCSI SA creation	169
5.12.5 Preserving persistent reservations and registrations.....	169
5.12.5.1 Requirements for preserving persistent reservations and registrations	169
5.12.5.2 Preserving persistent reservations and registrations through power loss	169
5.12.5.3 Nonvolatile memory considerations for preserving persistent reservations and registrations ..	170
5.12.5.4 Loss of persistent reservation information	170
5.12.5.4.1 Loss of persistent reservation information overview	170
5.12.5.4.2 Recoverable loss of persistent reservation information	170
5.12.5.4.3 Unrecoverable loss of persistent reservation information overview	171
5.12.6 Finding persistent reservations and reservation keys	171
5.12.6.1 Summary of commands for finding persistent reservations and reservation keys	171
5.12.6.2 Reporting reservation keys	171
5.12.6.3 Reporting the persistent reservation.....	171
5.12.6.4 Reporting full status.....	172
5.12.7 Registering	172
5.12.8 Registering and moving the reservation	176
5.12.9 Reserving	177
5.12.10 Persistent reservation holder.....	178
5.12.11 Releasing persistent reservations and removing registrations	178
5.12.11.1 Releasing persistent reservations, removing registrations, and lost reservation information ..	178
5.12.11.2 Service actions that release persistent reservations and remove registrations.....	179
5.12.11.2.1 Service actions that release persistent reservations and remove registrations overview ...	179
5.12.11.2.2 Releasing.....	180
5.12.11.2.3 Unregistering	180
5.12.11.2.4 Preempting	182
5.12.11.2.4.1 Commands that preempt reservations.....	182
5.12.11.2.4.2 Failed persistent reservation preempt.....	184
5.12.11.2.4.3 Preempting persistent reservations and registration handling.....	184
5.12.11.2.5 Removing registrations	185
5.12.11.2.6 Preempting and aborting	185
5.12.11.2.7 Clearing	186
5.12.11.3 Replacing lost reservations	187
5.13 Security features.....	188
5.13.1 Security goals and threat model	188
5.13.1.1 Introduction.....	188
5.13.1.2 Security goals	188
5.13.1.3 Threat model	189
5.13.1.4 Types of attacks	189
5.13.1.5 SCSI security considerations.....	190
5.13.2 Security associations	190
5.13.2.1 Principles of SAs	190
5.13.2.2 SA parameters	192
5.13.2.3 Creating an SA	194
5.13.3 Key derivation functions	195
5.13.3.1 KDFs overview	195
5.13.3.2 iSCSI-based iterative KDF	195
5.13.3.3 HMAC-based KDFs	196
5.13.3.4 AES-XCBC-PRF-128 iSCSI-based iterative KDF	197
5.13.4 Using iSCSI to create an SA	198
5.13.4.1 Overview.....	198
5.13.4.2 iSCSI Protocol summary	201
5.13.4.3 iSCSI Authentication.....	204
5.13.4.3.1 Overview.....	204

5.13.4.3.2 Pre-shared key authentication	205
5.13.4.3.3 Digital signature authentication	205
5.13.4.3.3.1 Overview	205
5.13.4.3.3.2 Certificates and digital signature authentication	206
5.13.4.3.3.3 Example of certificate use for digital signature authentication	206
5.13.4.3.3.4 Handling of the Certificate Request payload and the Certificate payload	207
5.13.4.3.4 Constraints on skipping the Authentication step	207
5.13.4.4 Summary of IKEv2-SCSI shared keys nomenclature and shared key sizes	209
5.13.4.5 Device Server Capabilities step	210
5.13.4.6 IKEv2-SCSI Key Exchange step	212
5.13.4.6.1 Overview	212
5.13.4.6.2 Key Exchange step SECURITY PROTOCOL OUT command	212
5.13.4.6.3 Key Exchange step SECURITY PROTOCOL IN command	213
5.13.4.6.4 Key Exchange step completion	214
5.13.4.6.5 After the Key Exchange step	214
5.13.4.7 IKEv2-SCSI Authentication step	214
5.13.4.7.1 Overview	214
5.13.4.7.2 Authentication step SECURITY PROTOCOL OUT command	215
5.13.4.7.3 Authentication step SECURITY PROTOCOL IN command	216
5.13.4.8 Generating shared keys	217
5.13.4.8.1 Overview	217
5.13.4.8.2 Generating shared keys when the Authentication step is skipped	218
5.13.4.8.3 Generating shared keys when the Authentication step is processed	218
5.13.4.8.4 Initializing shared key generation	218
5.13.4.8.4.1 Initializing for SA creation shared key generation	218
5.13.4.8.4.2 Initializing for generation of shared keys used by the created SA	219
5.13.4.8.5 Generating shared keys used for SA management	219
5.13.4.8.6 Generating shared keys for use by the created SA	220
5.13.4.9 IKEv2-SCSI SA generation	221
5.13.4.10 Abandoning an IKEv2-SCSI CCS	222
5.13.4.11 Deleting an IKEv2-SCSI SA	223
5.13.5 Security progress indication	223
5.13.6 Command security	224
5.13.6.1 Overview	224
5.13.6.2 Secure CDB Originator class	224
5.13.6.3 Secure CDB Processor class	224
5.13.6.4 Enforcement Manager class	225
5.13.6.5 Security Manager class	225
5.13.6.6 The relationship between SAs and command security	226
5.13.6.7 Capability-based command security technique	226
5.13.6.7.1 Overview	226
5.13.6.7.2 Security Manager class	229
5.13.6.7.3 CbCS Management Device Server class	230
5.13.6.7.3.1 CbCS Management Device Server class overview	230
5.13.6.7.3.2 Decision Database attribute	230
5.13.6.7.4 CbCS Management Application Client class	230
5.13.6.7.5 Secure CDB Originator class	230
5.13.6.7.6 Secure CDB Processor class	230
5.13.6.7.7 Enforcement Manager class	231
5.13.6.7.8 CbCS methods	232
5.13.6.7.8.1 Overview	232
5.13.6.7.8.2 The BASIC CbCS method	232
5.13.6.7.8.3 The CAPKEY CbCS method	233
5.13.6.7.9 CbCS trust assumptions	233
5.13.6.7.10 CbCS security tokens	234
5.13.6.7.11 CbCS shared keys	235
5.13.6.7.11.1 Overview	235

5.13.6.7.11.2 CbCS shared key identifiers	236
5.13.6.7.11.3 Specifying which CbCS shared key to change	236
5.13.6.7.11.4 Updating a CbCS master key	237
5.13.6.7.11.5 Changing a CbCS working keys	237
5.13.6.7.12 CbCS credentials	237
5.13.6.7.12.1 Overview	237
5.13.6.7.12.2 CbCS capability key computations for the secure CDB originator	238
5.13.6.7.12.3 CbCS capability key computations for general use	238
5.13.6.7.13 CbCS capability descriptors	239
5.13.6.7.13.1 Overview	239
5.13.6.7.13.2 CbCS extension descriptor validation	239
5.13.6.7.13.3 CAPKEY CbCS method capability integrity validation	240
5.13.6.7.14 Association between commands and permission bits	241
5.13.6.7.15 CbCS parameters	244
5.13.6.7.15.1 Overview	244
5.13.6.7.16 CbCS extension descriptor format	246
5.13.7 ESP-SCSI encapsulations for parameter data	247
5.13.7.1 Overview	247
5.13.7.2 ESP-SCSI required inputs	247
5.13.7.3 ESP-SCSI data format before encryption and after decryption	248
5.13.7.4 ESP-SCSI outbound data descriptors	249
5.13.7.4.1 Overview	249
5.13.7.4.2 ESP-SCSI CDBs or Data-Out Buffer parameter lists including a descriptor length	250
5.13.7.4.2.1 Initialization vector absent	250
5.13.7.4.2.2 Initialization vector present	252
5.13.7.4.3 ESP-SCSI Data-Out Buffer parameter lists for externally specified descriptor length	253
5.13.7.4.3.1 Initialization vector absent	253
5.13.7.4.3.2 Initialization vector present	254
5.13.7.5 ESP-SCSI Data-In Buffer parameter data descriptors	254
5.13.7.5.1 Overview	254
5.13.7.5.2 ESP-SCSI Data-In Buffer parameter data including a descriptor length	255
5.13.7.5.2.1 Initialization vector absent	255
5.13.7.5.2.2 Initialization vector present	257
5.13.7.5.3 ESP-SCSI Data-In Buffer parameter data for externally specified descriptor length	258
5.13.7.5.3.1 Initialization vector absent	258
5.13.7.5.3.2 Initialization vector present	259
5.13.8 Security algorithm codes	260
5.14 Self-test operations	261
5.14.1 Self-test types	261
5.14.2 Default self-test	262
5.14.3 The short self-test and extended self-test	262
5.14.4 Self-test modes	263
5.14.4.1 Self-test modes overview	263
5.14.4.2 Foreground mode	263
5.14.4.3 Background mode	263
5.14.4.4 Features common to foreground and background self-test modes	264
5.15 Target port group asymmetric access states	267
5.15.1 Target port group access overview	267
5.15.2 Asymmetric logical unit access	267
5.15.2.1 Introduction to asymmetric logical unit access	267
5.15.2.2 Explicit and implicit asymmetric logical unit access	268
5.15.2.3 Discovery of asymmetric logical unit access behavior	268
5.15.2.4 Target port asymmetric access states	269
5.15.2.4.1 Target port asymmetric access states overview	269
5.15.2.4.2 Active/optimized state	269
5.15.2.4.3 Active/non-optimized state	269
5.15.2.4.4 Standby state	269

5.15.2.4.5 Unavailable state	270
5.15.2.4.6 Offline state	271
5.15.2.4.7 Logical block dependent state	271
5.15.2.5 Transitions between target port asymmetric access states	271
5.15.2.6 Preference indicator	272
5.15.2.7 Target port asymmetric access state reporting	272
5.15.2.8 Implicit asymmetric logical units access management	273
5.15.2.9 Explicit asymmetric logical units access management	273
5.15.2.10 Behavior after power on, hard reset, logical unit reset, and I_T nexus loss	274
5.15.2.11 Behavior of target ports that are not accessible from the service delivery subsystem	274
5.15.3 Symmetric logical unit access	274
5.16 Third-party copies	274
5.16.1 General considerations for third-party copies	274
5.16.2 Copy manager model	275
5.16.3 Third-party copy commands	278
5.16.4 Third-party copy command usage	279
5.16.4.1 Prior to sending a third-party copy command	279
5.16.4.2 List identifiers for third-party copy commands	280
5.16.4.3 Third-party copy commands and operations	280
5.16.4.4 Monitoring progress of and retrieving results from third-party copy commands	281
5.16.4.5 Held data	282
5.16.4.6 Aborting third-party copy commands and copy operations	283
5.16.4.7 The COPY OPERATION ABORT command	283
5.16.5 Responses to the conditions that result from SCSI events	284
5.16.6 RODs and ROD tokens	284
5.16.6.1 RODs and ROD related tokens overview	284
5.16.6.2 ROD types	285
5.16.6.2.1 ROD types overview	285
5.16.6.2.2 Access upon reference type RODs	285
5.16.6.2.3 Point in time copy RODs	286
5.16.6.2.3.1 Point in time copy RODs overview	286
5.16.6.2.3.2 Point in time copy – default type RODs	286
5.16.6.2.3.3 Point in time copy – change vulnerable type RODs	286
5.16.6.2.3.4 Point in time copy – persistent type RODs	286
5.16.6.2.3.5 Point in time copy – any type RODs	286
5.16.6.3 Populating a ROD or ROD token	287
5.16.6.4 ROD token format	288
5.16.6.5 Generic ROD tokens	290
5.16.6.5.1 Generic ROD token format	290
5.16.6.5.2 Validating generic ROD tokens	292
5.16.6.5.2.1 Overview of validating generic ROD tokens	292
5.16.6.5.2.2 Inexact validation of generic ROD tokens	293
5.16.6.5.2.3 Validation errors for generic ROD tokens	293
5.16.6.6 ROD token usage	295
5.16.6.7 ROD token lifetime	296
5.16.7 The EXTENDED COPY command	297
5.16.7.1 EXTENDED COPY parameter list	297
5.16.7.2 EXTENDED COPY command processing	297
5.16.7.3 EXTENDED COPY command errors detected before segment descriptor processing starts ..	302
5.16.7.4 EXTENDED COPY command errors detected during processing of segment descriptors	302
5.16.7.5 EXTENDED COPY considerations for RODs and ROD tokens	304
5.16.7.5.1 EXTENDED COPY command CSCD ROD identifiers	304
5.16.7.5.2 Populating an EXTENDED COPY command ROD	305
5.16.7.6 EXTENDED COPY command use of RODs when the peripheral device type is 00h (i.e., block device)	306
5.16.7.7 EXTENDED COPY command interactions with aliases	306

6 Commands for all device types	307
6.1 Summary of commands for all device types	307
6.2 CHANGE ALIASES command	309
6.2.1 CHANGE ALIASES command introduction	309
6.2.2 Alias entry format	311
6.2.3 Alias designation validation	312
6.2.4 Alias entry protocol independent designations	312
6.2.4.1 Alias entry protocol independent designations overview	312
6.2.4.2 NULL DESIGNATION alias format	312
6.3 COPY OPERATION ABORT command	313
6.4 EXTENDED COPY(LID4) command	313
6.4.1 EXTENDED COPY(LID4) command introduction	313
6.4.2 EXTENDED COPY(LID4) parameter data	315
6.4.3 Shared EXTENDED COPY parameter list fields	317
6.4.3.1 STR bit	317
6.4.3.2 LIST IDENTIFIER field and LIST ID USAGE field	318
6.4.3.3 PRIORITY field	320
6.4.3.4 CSCD DESCRIPTOR LIST LENGTH field and CSCD descriptor list	320
6.4.3.5 SEGMENT DESCRIPTOR LIST LENGTH field and segment descriptor list	320
6.4.3.6 INLINE DATA LENGTH field and inline data	321
6.4.4 Descriptor type codes	321
6.4.5 CSCD descriptors	322
6.4.5.1 CSCD descriptors introduction	322
6.4.5.2 The CSCD descriptor extension	324
6.4.5.3 Device type specific CSCD descriptor parameters for block device types	325
6.4.5.4 Device type specific CSCD descriptor parameters for sequential-access device types	326
6.4.5.5 Device type specific CSCD descriptor parameters for processor device types	327
6.4.5.6 Identification Descriptor CSCD descriptor format	328
6.4.5.7 Alias CSCD descriptor format	329
6.4.5.8 IP Copy Service CSCD descriptor	330
6.4.5.9 ROD CSCD descriptor	332
6.4.6 Segment descriptors	337
6.4.6.1 Segment descriptors introduction	337
6.4.6.2 Block device to stream device functions	340
6.4.6.3 Stream device to block device functions	342
6.4.6.4 Block device to block device functions	343
6.4.6.5 Stream device to stream device functions	345
6.4.6.6 Inline data to stream device function	346
6.4.6.7 Embedded data to stream device function	348
6.4.6.8 Stream device to discard functions	349
6.4.6.9 Verify CSCD function	350
6.4.6.10 Block device with offset to stream device function	352
6.4.6.11 Stream device to block device with offset function	353
6.4.6.12 Block device with offset to block device with offset function	355
6.4.6.13 Write filemarks function	356
6.4.6.14 Space function	357
6.4.6.15 Locate function	358
6.4.6.16 Tape device image copy function	359
6.4.6.17 Register persistent reservation key function	360
6.4.6.18 Third party persistent reservations source I_T nexus function	361
6.4.6.19 Block device image copy function	362
6.4.6.20 Populate a ROD from one or more block ranges function	364
6.4.6.21 Populate a ROD from one block range function	366
6.5 EXTENDED COPY(LID1) command	367
6.6 INQUIRY command	370
6.6.1 INQUIRY command introduction	370
6.6.2 Standard INQUIRY data	371

6.6.3 SCSI Parallel Interface specific INQUIRY data	387
6.7 LOG SELECT command	389
6.7.1 Introduction	389
6.7.2 Processing LOG SELECT when the parameter list length is zero	391
6.8 LOG SENSE command	394
6.9 MANAGEMENT PROTOCOL IN command	396
6.9.1 MANAGEMENT PROTOCOL IN command description	396
6.9.2 Management protocol information description	397
6.9.2.1 Overview	397
6.9.2.2 CDB description	397
6.9.2.3 Supported management protocols list description	398
6.10 MANAGEMENT PROTOCOL OUT command	399
6.11 MODE SELECT(6) command	400
6.12 MODE SELECT(10) command	402
6.13 MODE SENSE(6) command	403
6.13.1 MODE SENSE(6) command introduction	403
6.13.2 Current values	404
6.13.3 Changeable values	405
6.13.4 Default values	405
6.13.5 Saved values	405
6.13.6 Initial responses	405
6.14 MODE SENSE(10) command	406
6.15 PERSISTENT RESERVE IN command	407
6.15.1 PERSISTENT RESERVE IN command introduction	407
6.15.2 READ KEYS service action	408
6.15.3 READ RESERVATION service action	408
6.15.3.1 READ RESERVATION service action operation	408
6.15.3.2 Persistent reservations scope	410
6.15.3.3 Persistent reservations type	411
6.15.4 REPORT CAPABILITIES service action	412
6.15.5 READ FULL STATUS service action	416
6.16 PERSISTENT RESERVE OUT command	418
6.16.1 PERSISTENT RESERVE OUT command introduction	418
6.16.2 PERSISTENT RESERVE OUT service actions and parameter list formats	420
6.16.3 Basic PERSISTENT RESERVE OUT parameter list	423
6.16.4 Parameter list for the PERSISTENT RESERVE OUT command with REGISTER AND MOVE service action	426
6.17 READ ATTRIBUTE command	428
6.17.1 READ ATTRIBUTE command introduction	428
6.17.2 ATTRIBUTE VALUES service action	430
6.17.3 ATTRIBUTE LIST service action	431
6.17.4 LOGICAL VOLUME LIST service action	431
6.17.5 PARTITION LIST service action	432
6.17.6 SUPPORTED ATTRIBUTES service action	432
6.18 READ BUFFER command	433
6.18.1 READ BUFFER command introduction	433
6.18.2 Vendor specific mode (01h)	434
6.18.3 Data mode (02h)	434
6.18.4 Descriptor mode (03h)	435
6.18.5 Read data from echo buffer mode (0Ah)	436
6.18.6 Echo buffer descriptor mode (0Bh)	436
6.18.7 Error history mode (1Ch)	437
6.18.7.1 Error history overview	437
6.18.7.2 Error history directory	438
6.18.7.3 Error history data buffer	441
6.18.7.4 Clear error history I_T nexus	441
6.18.7.5 Clear error history I_T nexus and release snapshot	441

6.19 READ MEDIA SERIAL NUMBER command	442
6.20 RECEIVE COPY DATA(LID4) command	443
6.21 RECEIVE COPY DATA(LID1) command	445
6.22 RECEIVE COPY OPERATING PARAMETERS command	446
6.23 RECEIVE COPY FAILURE DETAILS(LID1) command	450
6.24 RECEIVE COPY STATUS(LID4) command	452
6.25 RECEIVE COPY STATUS(LID1) command	456
6.26 RECEIVE CREDENTIAL command	458
6.26.1 RECEIVE CREDENTIAL command description	458
6.26.1.1 Overview	458
6.26.1.2 CbCS logical unit credential request descriptor	460
6.26.1.3 CbCS logical unit and volume credential request descriptor	460
6.26.2 RECEIVE CREDENTIAL parameter data	461
6.26.2.1 RECEIVE CREDENTIAL parameter data encryption	461
6.26.2.2 RECEIVE CREDENTIAL decrypted parameter data	461
6.26.2.3 CbCS capability descriptor	462
6.26.2.3.1 Overview	462
6.26.2.3.2 Logical unit designation descriptor format	465
6.26.2.3.3 Volume designation descriptors	465
6.27 RECEIVE DIAGNOSTIC RESULTS command	466
6.28 RECEIVE ROD TOKEN INFORMATION command	467
6.29 REMOVE I_T NEXUS command	470
6.30 REPORT ALIASES command	472
6.31 REPORT ALL ROD TOKENS command	474
6.32 REPORT IDENTIFYING INFORMATION command	475
6.32.1 REPORT IDENTIFYING INFORMATION command overview	475
6.32.2 Peripheral device identifying information parameter data	477
6.32.3 Identifying information supported parameter data	477
6.33 REPORT LUNS command	478
6.34 REPORT PRIORITY command	481
6.35 REPORT SUPPORTED OPERATION CODES command	483
6.35.1 REPORT SUPPORTED OPERATION CODES command introduction	483
6.35.2 All_commands parameter data format	485
6.35.3 One_command parameter data format	486
6.35.4 Command timeouts descriptor	487
6.35.4.1 Overview	487
6.35.4.2 WRITE BUFFER command timeouts descriptor COMMAND SPECIFIC field usage	488
6.36 REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS command	489
6.37 REPORT TARGET PORT GROUPS command	493
6.38 REPORT TIMESTAMP command	498
6.39 REQUEST SENSE command	499
6.40 SECURITY PROTOCOL IN command	501
6.41 SECURITY PROTOCOL OUT command	503
6.42 SEND DIAGNOSTIC command	505
6.43 SET IDENTIFYING INFORMATION command	511
6.44 SET PRIORITY command	513
6.45 SET TARGET PORT GROUPS command	515
6.46 SET TIMESTAMP command	519
6.47 TEST UNIT READY command	520
6.48 WRITE ATTRIBUTE command	522
6.49 WRITE BUFFER command	524
6.49.1 WRITE BUFFER command introduction	524
6.49.2 Vendor specific mode (01h)	525
6.49.3 Data mode (02h)	526
6.49.4 Download microcode and activate mode (04h)	526
6.49.5 Download microcode, save, and activate mode (05h)	526
6.49.6 Download microcode with offsets and activate mode (06h)	526

6.49.7 Download microcode with offsets, save, and activate mode (07h).....	527
6.49.8 Write data to echo buffer mode (0Ah)	527
6.49.9 Download microcode with offsets, select activation, save, and defer activate mode (0Dh)	527
6.49.10 Download microcode with offsets, save, and defer activate mode (0Eh)	528
6.49.11 Activate deferred microcode mode (0Fh)	528
6.49.12 Download application client error history mode (1Ch).....	529
7 Parameters for all device types.....	533
7.1 Overview.....	533
7.2 Diagnostic parameters.....	533
7.2.1 Summary of diagnostic page codes	533
7.2.2 Diagnostic page format for all device types.....	533
7.2.3 Protocol Specific diagnostic page.....	535
7.2.4 Supported Diagnostic Pages diagnostic page	535
7.3 Log parameters	537
7.3.1 Summary of log page codes.....	537
7.3.2 Log page structure and log parameter structure for all device types.....	538
7.3.2.1 Log page structure.....	538
7.3.2.2 Log parameter structure	540
7.3.2.2.1 Introduction.....	540
7.3.2.2.2 Parameter control byte	541
7.3.2.2.2.1 Introduction.....	541
7.3.2.2.2.2 Parameter control byte values for bounded data counter parameters	543
7.3.2.2.2.3 Parameter control byte values for unbounded data counter parameters	544
7.3.2.2.2.4 Parameter control byte values for ASCII format list log parameters.....	545
7.3.2.2.2.5 Parameter control byte values for binary format list log parameters	546
7.3.3 Resetting and setting log parameters.....	547
7.3.4 Application Client log page	547
7.3.4.1 Overview.....	547
7.3.4.2 General Usage Application Client log parameter.....	548
7.3.5 Buffer Over-Run/Under-Run log page	549
7.3.5.1 Overview.....	549
7.3.5.2 Buffer Over-run/Under-run log parameter	551
7.3.6 Cache Memory Statistics log page	552
7.3.6.1 Overview.....	552
7.3.6.2 Read Cache Memory Hits log parameter	553
7.3.6.3 Reads To Cache Memory log parameter	554
7.3.6.4 Write Cache Memory Hits log parameter	555
7.3.6.5 Writes From Cache Memory log parameter	556
7.3.6.6 Time From Last Hard Reset log parameter.....	557
7.3.6.7 Time Interval log parameter.....	558
7.3.7 General Statistics and Performance log pages	559
7.3.7.1 Overview.....	559
7.3.7.2 General Access Statistics and Performance log parameter	561
7.3.7.3 Idle Time log parameter.....	563
7.3.7.4 Force Unit Access Statistics and Performance log parameter	564
7.3.8 Group Statistics and Performance (n) log pages.....	565
7.3.8.1 Overview.....	565
7.3.8.2 Group n Statistics and Performance log parameter	568
7.3.8.3 Group n Force Unit Access Statistics and Performance log parameter	569
7.3.9 Informational Exceptions log page	571
7.3.9.1 Overview.....	571
7.3.9.2 Informational Exceptions General log parameter	572
7.3.10 Last n Deferred Errors or Asynchronous Events log page	573
7.3.10.1 Overview.....	573
7.3.10.2 Deferred Error or Asynchronous Event log parameters	574
7.3.11 Last n Error Events log page	575

7.3.11.1 Overview.....	575
7.3.11.2 Error Event log parameters	576
7.3.12 Non-Medium Error log page	576
7.3.12.1 Overview.....	576
7.3.12.2 Non-Medium Error Count log parameter	577
7.3.13 Power Condition Transitions log page	578
7.3.13.1 Overview.....	578
7.3.13.2 Accumulated Transitions log parameter	579
7.3.14 Protocol Specific Port log page	580
7.3.14.1 Overview.....	580
7.3.14.2 Generic protocol specific port log parameter	581
7.3.15 Read Error Counters log page.....	582
7.3.15.1 Overview.....	582
7.3.15.2 Read Error Counter log parameter	583
7.3.16 Read Reverse Error Counters log page	584
7.3.16.1 Overview.....	584
7.3.16.2 Read Reverse Error Counter log parameter	585
7.3.17 Self-Test Results log page	586
7.3.17.1 Overview.....	586
7.3.17.2 Self-Test Results log parameters	588
7.3.18 Start-Stop Cycle Counter log page	590
7.3.18.1 Overview.....	590
7.3.18.2 Date of Manufacture log parameter	591
7.3.18.3 Accounting Date log parameter	592
7.3.18.4 Specified Cycle Count Over Device Lifetime log parameter	593
7.3.18.5 Accumulated Start-Stop Cycles log parameter	593
7.3.18.6 Specified Load-Unload Count Over Device Lifetime log parameter	594
7.3.18.7 Accumulated Load-Unload Cycles log parameter	595
7.3.19 Supported Log Pages log page	596
7.3.20 Supported Log Pages and Subpages log page	597
7.3.21 Supported Subpages log page	598
7.3.22 Temperature log page	599
7.3.22.1 Overview.....	599
7.3.22.2 Temperature log parameter	600
7.3.22.3 Reference Temperature log parameter	600
7.3.23 Verify Error Counters log page	601
7.3.23.1 Overview.....	601
7.3.23.2 Verify Error Counter log parameter	602
7.3.24 Write Error Counters log page.....	603
7.3.24.1 Overview.....	603
7.3.24.2 Write Error Counter log parameter	604
7.4 Medium auxiliary memory attributes	606
7.4.1 Attribute format	606
7.4.2 Attribute identifier values	607
7.4.2.1 Attribute identifier values overview	607
7.4.2.2 Device type attributes	607
7.4.2.2.1 REMAINING CAPACITY IN PARTITION and MAXIMUM CAPACITY IN PARTITION	608
7.4.2.2.2 LOAD COUNT	608
7.4.2.2.3 MAM SPACE REMAINING	608
7.4.2.2.4 INITIALIZATION COUNT	609
7.4.2.2.5 VOLUME IDENTIFIER	609
7.4.2.2.6 DEVICE VENDOR/SERIAL NUMBER AT LAST LOAD, DEVICE VENDOR/SERIAL NUMBER AT LOAD –1, DEVICE VENDOR/SERIAL NUMBER AT LOAD –2 and DEVICE VENDOR/SERIAL NUMBER AT LOAD –3	609
7.4.2.2.7 TOTAL MEBIBYTES WRITTEN IN MEDIUM LIFE and TOTAL MEBIBYTES READ IN MEDIUM LIFE	609
7.4.2.2.8 TOTAL MEBIBYTES WRITTEN IN CURRENT/LAST LOAD and TOTAL MEBIBYTES	