

ETSI TS 138 300 V18.1.0 (2024-05)



**5G;
NR;
NR and NG-RAN Overall description;
Stage-2
(3GPP TS 38.300 version 18.1.0 Release 18)**

[ETSI TS 138 300 V18.1.0 \(2024-05\)](https://standards.iteh.ai/catalog/standards/etsi/65b6be92-ac79-42b1-8fdb-4b21a30e804f/etsi-ts-138-300-v18-1-0-2024-05)

<https://standards.iteh.ai/catalog/standards/etsi/65b6be92-ac79-42b1-8fdb-4b21a30e804f/etsi-ts-138-300-v18-1-0-2024-05>



ReferenceRTS/TSGR-0238300vi10

Keywords5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:
<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:
<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2024-05)

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	13
1 Scope	14
2 References	14
3 Abbreviations and Definitions.....	16
3.1 Abbreviations	16
3.2 Definitions.....	20
4 Overall Architecture and Functional Split.....	24
4.1 Overall Architecture	24
4.2 Functional Split	24
4.3 Network Interfaces	27
4.3.1 NG Interface	27
4.3.1.1 NG User Plane	27
4.3.1.2 NG Control Plane.....	27
4.3.2 Xn Interface	28
4.3.2.1 Xn User Plane	28
4.3.2.2 Xn Control Plane.....	28
4.4 Radio Protocol Architecture	29
4.4.1 User Plane.....	29
4.4.2 Control Plane	29
4.5 Multi-Radio Dual Connectivity	30
4.6 Radio Access Network Sharing	30
4.7 Integrated Access and Backhaul.....	30
4.7.1 Architecture	30
4.7.2 Protocol Stacks	31
4.7.3 User-plane Aspects	33
4.7.3.1 Backhaul transport	33
4.7.3.2 Flow and Congestion Control	33
4.7.3.3 Uplink Scheduling Latency	34
4.7.4 Signalling procedures	34
4.7.4.1 IAB-node Integration	34
4.7.4.2 IAB-node Migration.....	34
4.7.4.3 Topological Redundancy	34
4.7.4.4 Backhaul RLF Recovery	35
4.7.4.5 OTA timing synchronization.....	35
4.7.4.6 Inter node discovery	35
4.7.5 Mobile IAB	35
4.7.5.1 General	35
4.7.5.2 RACH-less handover	36
4.8 Non-Public Networks	36
4.9 Network-Controlled Repeaters	36
4.9.1 Architecture	36
4.9.2 Capabilities	37
4.9.3 Signalling procedures	37
4.9.4 OAM aspects	38
4.9.5 Network-controlled repeater management.....	38
5 Physical Layer	39
5.1 Waveform, numerology and frame structure	39
5.2 Downlink.....	40
5.2.1 Downlink transmission scheme	40
5.2.2 Physical-layer processing for physical downlink shared channel	40

5.2.3	Physical downlink control channels.....	40
5.2.4	Synchronization signal and PBCH block.....	41
5.2.5	Physical layer procedures	42
5.2.5.1	Link adaptation	42
5.2.5.2	Power Control	42
5.2.5.3	Cell search.....	42
5.2.5.4	HARQ	43
5.2.5.5	Reception of SIB1	43
5.2.6	Downlink Reference Signals and Measurements for Positioning.....	43
5.3	Uplink.....	43
5.3.1	Uplink transmission scheme	43
5.3.2	Physical-layer processing for physical uplink shared channel.....	44
5.3.3	Physical uplink control channel.....	44
5.3.4	Random access.....	45
5.3.5	Physical layer procedures	46
5.3.5.1	Link adaptation	46
5.3.5.2	Uplink Power control	46
5.3.5.3	Uplink timing control.....	46
5.3.5.4	HARQ	47
5.3.5.5	Prioritization of overlapping transmissions.....	47
5.3.6	Uplink Reference Signals and Measurements for Positioning.....	47
5.4	Carrier aggregation.....	47
5.4.1	Carrier aggregation	47
5.4.2	Supplementary Uplink	47
5.4.3	Uplink Tx switching	48
5.5	Transport Channels.....	48
5.6	Access to Shared Spectrum	49
5.6.1	Overview	49
5.6.2	Channel Access Priority Classes.....	49
5.7	Sidelink	50
5.7.1	General.....	50
5.7.2	Sidelink resource allocation modes	50
5.7.3	Physical sidelink channels and signals.....	50
5.7.4	Physical layer procedures for sidelink	50
5.7.4.1	HARQ feedback.....	50
5.7.4.2	Power Control	51
5.7.4.3	CSI report.....	51
5.7.5	Physical layer measurement definition	51
5.7.6	Sidelink Reference Signal and Measurements for Positioning	51
6	Layer 2.....	51
6.1	Overview	51
6.2	MAC Sublayer.....	55
6.2.1	Services and Functions	55
6.2.2	Logical Channels	56
6.2.3	Mapping to Transport Channels.....	56
6.2.4	HARQ.....	56
6.3	RLC Sublayer.....	56
6.3.1	Transmission Modes	56
6.3.2	Services and Functions	57
6.3.3	ARQ.....	57
6.4	PDCCP Sublayer.....	57
6.4.1	Services and Functions	57
6.5	SDAP Sublayer	58
6.6	L2 Data Flow.....	58
6.7	Carrier Aggregation.....	58
6.8	Dual Connectivity.....	60
6.9	Supplementary Uplink.....	60
6.10	Bandwidth Adaptation.....	60
6.11	Backhaul Adaptation Protocol Sublayer.....	61
6.11.1	Services and Functions	61
6.11.2	Traffic Mapping from Upper Layers to Layer-2.....	61

6.11.3	Routing, BAP Header Rewriting and BH-RLC-channel Mapping on BAP sublayer	62
6.12	Multiple Transmit/Receive Point Operation.....	64
7	RRC	64
7.1	Services and Functions	64
7.2	Protocol States	65
7.3	System Information Handling	66
7.3.1	Overview	66
7.3.2	Scheduling	68
7.3.3	SI Modification	68
7.4	Access Control	69
7.5	UE Capability Retrieval framework	69
7.6	Transport of NAS Messages.....	69
7.7	Carrier Aggregation.....	70
7.8	Bandwidth Adaptation.....	70
7.9	UE Assistance Information.....	70
7.10	Segmentation of RRC messages.....	71
8	NG Identities	71
8.1	UE Identities.....	71
8.2	Network Identities	72
8.3	User Data Transport on the CN-RAN Interface	73
8.4	NR sidelink communication and V2X sidelink communication related identities	73
9	Mobility and State Transitions	74
9.1	Overview	74
9.2	Intra-NR	75
9.2.1	Mobility in RRC_IDLE	75
9.2.1.1	Cell Selection	75
9.2.1.2	Cell Reselection	76
9.2.1.3	State Transitions.....	76
9.2.2	Mobility in RRC_INACTIVE.....	78
9.2.2.1	Overview	78
9.2.2.2	Cell Reselection	79
9.2.2.3	RAN-Based Notification Area	79
9.2.2.4	State Transitions.....	80
9.2.2.4.1	UE triggered transition from RRC_INACTIVE to RRC_CONNECTED	80
9.2.2.4.2	Network triggered transition from RRC_INACTIVE to RRC_CONNECTED	82
9.2.2.5	RNA update.....	82
9.2.2.6	Resume request responded with Release with Redirect, with UE context relocation	84
9.2.3	Mobility in RRC_CONNECTED	85
9.2.3.1	Overview	85
9.2.3.2	Handover	87
9.2.3.2.1	C-Plane Handling	87
9.2.3.2.2	U-Plane Handling	91
9.2.3.2.3	Data Forwarding.....	93
9.2.3.3	Re-establishment procedure	94
9.2.3.4	Conditional Handover	95
9.2.3.4.1	General	95
9.2.3.4.2	C-plane handling	96
9.2.3.4.3	U-plane handling	98
9.2.3.4.4	Data Forwarding.....	98
9.2.3.5	L1/L2 Triggered Mobility	98
9.2.3.5.1	General	98
9.2.3.5.2	C-Plane Handling	99
9.2.3.5.3	U-Plane Handling	101
9.2.4	Measurements	101
9.2.5	Paging	104
9.2.6	Random Access Procedure	107
9.2.7	Radio Link Failure	110
9.2.8	Beam failure detection and recovery	111
9.2.9	Timing Advance	112
9.2.10	Extended DRX for RRC_IDLE and RRC_INACTIVE.....	112

9.3	Inter RAT	113
9.3.1	NR-E-UTRA mobility: Intra 5GC	113
9.3.1.1	Cell Reselection	113
9.3.1.2	Handover	113
9.3.1.3	Measurements	113
9.3.2	NR-E-UTRA mobility: From 5GC to EPC	114
9.3.2.1	Cell Reselection	114
9.3.2.2	Handover and redirection	114
9.3.2.3	Measurements	114
9.3.2.4	Data Forwarding for the Control Plane	114
9.3.2.5	Data Forwarding for the User Plane	115
9.3.3	NR-E-UTRA mobility: From EPC to 5GC	115
9.3.3.1	Data Forwarding for the Control Plane	115
9.3.3.2	Data Forwarding for the User Plane	116
9.3.4	NR-UTRA mobility	117
9.3.4.1	Handover with SRVCC operation	117
9.3.4.2	Measurements	117
9.4	Roaming and Access Restrictions	117
10	Scheduling	118
10.1	Basic Scheduler Operation	118
10.2	Downlink Scheduling	118
10.3	Uplink Scheduling	119
10.4	Measurements to Support Scheduler Operation	120
10.5	Rate Control	120
10.5.1	Downlink	120
10.5.2	Uplink	121
10.6	Activation/Deactivation Mechanism	121
10.7	E-UTRA-NR Cell Resource Coordination	122
10.8	Cross Carrier Scheduling	122
10.9	IAB Resource Configuration	122
10.10	Autonomous Denial for IDC	123
10.11	Multi-cell scheduling by a single DCI	123
11	UE Power Saving	123
12	QoS	125
12.1	Overview	125
12.2	Explicit Congestion Notification	128
13	Security	128
13.1	Overview and Principles	128
13.2	Security Termination Points	130
13.3	State Transitions and Mobility	130
14	UE Capabilities	130
15	Self-Configuration and Self-Optimisation	132
15.1	Definitions	132
15.2	Void	132
15.3	Self-configuration	132
15.3.1	Dynamic configuration of the NG-C interface	132
15.3.1.1	Prerequisites	132
15.3.1.2	SCTP initialization	132
15.3.1.3	Application layer initialization	132
15.3.2	Dynamic Configuration of the Xn interface	133
15.3.2.1	Prerequisites	133
15.3.2.2	SCTP initialization	133
15.3.2.3	Application layer initialization	133
15.3.3	Automatic Neighbour Cell Relation Function	133
15.3.3.1	General	133
15.3.3.2	Intra-system Automatic Neighbour Cell Relation Function	134
15.3.3.3	Void	135
15.3.3.4	Void	135

15.3.3.5	Inter-system Automatic Neighbour Cell Relation Function.....	135
15.3.4	Xn-C TNL address discovery	136
15.4	Support for Energy Saving	137
15.4.1	General.....	137
15.4.2	Solution description	137
15.4.2.1	Intra-system energy saving	137
15.4.2.2	Inter-system energy saving	137
15.4.2.3	Cell DTX/DRX	138
15.4.2.4	Conditional Handover	138
15.4.2.5	Camping Restrictions	138
15.4.2.6	SSB-less SCell	138
15.4.2.7	Spatial and power domain adaptation	138
15.4.3	O&M requirements	139
15.5	Self-optimisation	139
15.5.1	Support for Mobility Load Balancing.....	139
15.5.1.1	General	139
15.5.1.2	Load reporting for intra-RAT and intra-system inter-RAT load balancing.....	139
15.5.1.4	Adapting handover and/or reselection configuration	140
15.5.1.5	Load reporting for inter-system load balancing	140
15.5.2	Support for Mobility Robustness Optimization	140
15.5.2.1	General	140
15.5.2.2	Connection failure	141
15.5.2.2.1	General	141
15.5.2.2.2	Connection failure due to intra-system mobility	141
15.5.2.2.3	Connection failure due to inter-system mobility	143
15.5.2.3	Inter-system Unnecessary HO.....	144
15.5.2.4	Inter-system Ping-pong	144
15.5.2.5	O&M Requirements	145
15.5.2.6	PSCell addition/change failure	145
15.5.2.7	Successful HO	145
15.5.2.8	Successful PSCell Addition/Change Report	145
15.5.3	Support for RACH Optimization	146
15.5.4	UE History Information from the UE	146
15.5.5	Support for Coverage and Capacity Optimisation	146
15.5.5.1	General	146
15.5.5.2	OAM requirements.....	146
15.5.5.3	Dynamic coverage configuration changes	147
15.5.6	Support for PCI Optimisation	147
15.5.6.1	Centralized PCI Assignment	147
15.5.6.2	Distributed PCI Assignment	147
16	Verticals Support.....	147
16.1	URLLC.....	147
16.1.1	Overview	147
16.1.2	LCP Restrictions.....	147
16.1.3	Packet Duplication.....	148
16.1.4	CQI and MCS	149
16.1.5	DCI formats	149
16.1.6	Higher layer multi-connectivity	149
16.1.6.1	Redundant user plane paths based on dual connectivity	149
16.1.6.2	Redundant data transmission via single UPF and single RAN node.....	149
16.1.7	URLLC in Unlicensed Controlled Environment.....	149
16.1.8	PUCCH cell switching for TDD cells.....	149
16.2	IMS Voice	150
16.2.0	Support for IMS voice	150
16.2.1	Support for MMTEL IMS voice and video enhancements	150
16.2.1.1	RAN-assisted codec adaptation.....	150
16.2.1.2	MMTEL voice quality/coverage enhancements.....	151
16.3	Network Slicing.....	151
16.3.1	General Principles and Requirements	151
16.3.2	AMF and NW Slice Selection.....	153
16.3.2.1	CN-RAN interaction and internal RAN aspects.....	153

16.3.2.2	Radio Interface Aspects	153
16.3.3	Resource Isolation and Management	153
16.3.3.1	General	153
16.3.3.2	Handling of Slice Resources	154
16.3.3a	Slice-based cell reselection	154
16.3.4	Signalling Aspects	154
16.3.4.1	General	154
16.3.4.2	AMF and NW Slice Selection	154
16.3.4.3	UE Context Handling	155
16.3.4.4	PDU Session Setup Handling	155
16.3.4.5	Mobility	156
16.4	Public Warning System	157
16.5	Emergency Services	158
16.5.1	Overview	158
16.5.2	IMS Emergency call	158
16.5.3	eCall over IMS	158
16.5.4	Fallback	158
16.6	Stand-Alone NPN	158
16.6.1	General	158
16.6.2	Mobility	159
16.6.2.1	General	159
16.6.2.2	Inactive Mode	159
16.6.2.3	Connected Mode	159
16.7	Public Network Integrated NPN	160
16.7.1	General	160
16.7.2	Mobility	160
16.7.2.1	General	160
16.7.2.2	Inactive Mode	161
16.7.2.3	Connected Mode	161
16.7.3	Self-Configuration for PNI-NPN	161
16.7.4	Access Control	161
16.7.5	Paging	161
16.8	Support for Time Sensitive Communications	161
16.8.1	General	161
16.8.2	Network timing synchronization status monitoring	163
16.8.2.1	General	163
16.8.2.2	Network timing synchronization status monitoring towards CN	163
16.8.2.3	Network timing synchronization status monitoring towards UE	163
16.8.3	RAN feedback for adaptation of Burst Arrival Time and Periodicity	164
16.9	Sidelink	165
16.9.1	General	165
16.9.2	Radio Protocol Architecture for NR sidelink communication	166
16.9.2.1	Overview	166
16.9.2.2	MAC	167
16.9.2.3	RLC	168
16.9.2.4	PDCCP	168
16.9.2.5	SDAP	168
16.9.2.6	RRC	168
16.9.3	Radio Resource Allocation	168
16.9.3.1	General	168
16.9.3.2	Scheduled Resource Allocation	169
16.9.3.3	UE Autonomous Resource Selection	169
16.9.3.4	LTE and NR Sidelink co-channel coexistence	169
16.9.4	Uu Control	170
16.9.4.1	General	170
16.9.4.2	Control of connected UEs	170
16.9.4.3	Control of idle/inactive UEs	170
16.9.5	Sidelink Discovery	171
16.9.6	SL DRX	171
16.9.6.1	General	171
16.9.6.2	Unicast	171
16.9.6.3	Groupcast/Broadcast	172

16.9.6.4	Alignment between Uu DRX and SL DRX	173
16.9.7	Power Savings Resource Allocation	173
16.9.8	Inter-UE Coordination (IUC).....	173
16.9.9	Sidelink in Shared Spectrum (SL-U)	174
16.9.9.1	Overview	174
16.9.9.2	Channel Access Priority Classes for Sidelink (SL-CAPC)	174
16.9.9.3	Sidelink Specific Consistent LBT Failure.....	174
16.9.9.4	COT Sharing	175
16.9.9.5	Resource Allocation	175
16.9.10	Sidelink CA	175
16.10	Multicast and Broadcast Services.....	176
16.10.1	General.....	176
16.10.2	Network Architecture	176
16.10.3	Protocol Architecture.....	176
16.10.4	Group Scheduling	178
16.10.5	Multicast Handling	179
16.10.5.1	Session Management.....	179
16.10.5.2	Configuration	179
16.10.5.3	Service Continuity.....	180
16.10.5.3.1	General	180
16.10.5.3.2	Handover between Multicast supporting cells.....	181
16.10.5.3.3	Handover between Multicast-supporting cell and Multicast non-supporting cell	181
16.10.5.3.4	MRB reconfiguration.....	182
16.10.5.3.5	Service Continuity in RRC_INACTIVE	182
16.10.5.4	Reception of MBS Multicast data	182
16.10.5.5	Support of CA	183
16.10.5.6	DRX	183
16.10.5.7	Physical Layer.....	183
16.10.6	Broadcast Handling.....	183
16.10.6.1	Session Management.....	183
16.10.6.2	Configuration	183
16.10.6.3	Support of CA	184
16.10.6.4	DRX	184
16.10.6.5	Service Continuity.....	184
16.10.6.5.0	General	184
16.10.6.5.1	Service Continuity in RRC_IDLE or RRC_INACTIVE	184
16.10.6.5.2	Service Continuity in RRC_CONNECTED	185
16.10.6.5A	Reception of MBS Broadcast data	185
16.10.6.6	Physical Layer.....	185
16.10.6.7	Shared processing for MBS broadcast and unicast reception.....	185
16.11	Minimization of Service Interruption.....	186
16.12	Sidelink Relay	186
16.12.1	General.....	186
16.12.2	Protocol Architecture.....	187
16.12.2.1	L2 UE-to-Network Relay	187
16.12.2.2	L2 UE-to-UE Relay.....	189
16.12.3	Relay Discovery.....	190
16.12.4	Relay Selection/Reselection.....	191
16.12.5	Control plane procedures for L2 U2N Relay	193
16.12.5.1	RRC Connection Management.....	193
16.12.5.2	Radio Link Failure	194
16.12.5.3	RRC Connection Re-establishment.....	194
16.12.5.4	RRC Connection Resume	194
16.12.5.5	System Information	194
16.12.5.6	Paging	195
16.12.5.7	Access Control	195
16.12.5.8	Mobility Registration Update and RAN Area Update.....	195
16.12.6	Service Continuity for L2 U2N relay.....	196
16.12.6.0	General.....	196
16.12.6.1	Switching from indirect to direct path.....	196
16.12.6.2	Switching from direct to indirect path.....	198
16.12.6.3	Switching from indirect to indirect path.....	200

16.12.7	Control plane procedures for L2 U2U Relay	203
16.13	Support of Reduced Capability (RedCap) and enhanced Reduced Capability (eRedCap) NR devices	205
16.13.1	Introduction.....	205
16.13.2	Capabilities	205
16.13.3	Identification, access and camping restrictions.....	205
16.13.4	RRM measurement relaxations.....	206
16.13.5	BWP operation.....	206
16.14	Non-Terrestrial Networks.....	206
16.14.1	Overview	206
16.14.2	Timing and Synchronization.....	208
16.14.2.1	Scheduling and Timing	208
16.14.2.2	Timing Advance and Frequency Pre-compensation.....	209
16.14.3	Mobility and State transition.....	209
16.14.3.1	Mobility in RRC_IDLE and RRC_INACTIVE	209
16.14.3.2	Mobility in RRC_CONNECTED.....	210
16.14.3.2.1	Handover	210
16.14.3.2.2	Conditional Handover	210
16.14.3.2.3	Satellite switch with re-sync.....	210
16.14.3.3	Measurements	211
16.14.4	Switchover	211
16.14.4.1	Definitions.....	211
16.14.4.2	Assumptions.....	211
16.14.4.3	Procedures.....	212
16.14.5	NG-RAN signalling	212
16.14.6	AMF (Re-)Selection	212
16.14.7	O&M Requirements.....	213
16.14.8	Coarse UE location reporting.....	213
16.14.9	Support for NR NTN coverage enhancements.....	213
16.14.10	Verification of UE location.....	214
16.15	eXtended Reality Services.....	214
16.15.1	General.....	214
16.15.2	Awareness.....	214
16.15.3	Power Saving.....	215
16.15.4	Capacity	215
16.15.4.1	Physical Layer Enhancements.....	215
16.15.4.2	Layer 2 Enhancements	215
16.15.4.2.1	Assistance Information.....	215
16.15.4.2.2	Discard.....	216
16.15.5	Non-Homogeneous support of PDU set based handling in NG-RAN	216
16.16	ECN marking for L4S and congestion information exposure	216
16.17	Support for TSN enabled Transport Network	217
16.18	Support for Aerial UE Communication.....	217
16.18.1	General.....	217
16.18.2	Subscription-based Identification of Aerial UE.....	217
16.18.3	Altitude-based Reporting for Aerial UE Communication.....	217
16.18.4	Altitude-dependent Configurations for Aerial UE Communication	218
16.18.5	Interference Detection and Mitigation for Aerial UE Communication.....	218
16.18.6	Flight Path Information Reporting for Aerial UE Communication	218
16.18.7	Location Reporting for Aerial UE Communication.....	218
16.18.8	BRID and DAA Support via A2X Communication.....	218
16.19	Support for Air to Ground Networks.....	218
16.19.1	Overview	218
16.19.2	Timing and Synchronization.....	219
16.19.2.1	Scheduling and Timing	219
16.19.2.2	Timing Advance.....	219
16.19.3	Mobility	219
16.19.3.1	Mobility in RRC_IDLE and RRC_INACTIVE	219
16.19.3.2	Mobility in RRC_CONNECTED.....	219
16.19.3.2.1	Handover	219
16.19.3.2.2	Conditional Handover	219
16.20	Support of AI/ML for NG-RAN.....	220
16.20.1	General.....	220

16.20.2	Mechanisms and Principles	220
16.21	Multi-path Relay	220
16.21.1	General.....	220
16.21.2	Protocol Architecture.....	221
16.21.2.1	L2 MP Relay using SL indirect path.....	221
16.21.2.2	L2 MP Relay using N3C indirect path.....	222
16.21.3	Control plane procedure for multi-path relaying	223
16.21.3.1	Path Management.....	223
16.21.3.2	Path Failure Report	228
16.22	Support of 2Rx XR devices.....	229
16.22.1	Introduction.....	229
16.22.2	Identification, access and camping restrictions.....	229
17	Interference Management.....	229
17.1	Remote Interference Management	229
17.2	Cross-Link Interference Management	230
18	Small Data Transmission.....	230
18.0	General	230
18.1	Support of SDT procedure over RACH	232
18.2	SDT with UE context relocation	232
18.3	SDT without UE context relocation	234
18.4	MT-SDT with/without UE context relocation.....	235
19	Support for NR coverage enhancements	236
20	Support for Multi-USIM devices	237
20.1	General	237
20.2	Paging Collision Avoidance	237
20.3	UE notification on Network Switching	237
20.4	Temporary UE capability restriction and removal of restriction.....	237
21	Application Layer Measurement Collection	238
21.1	Overview	238
21.2	QoE Measurement Configuration.....	239
21.2.1	QoE Measurement Collection Activation and Reporting	239
21.2.2	QoE Measurement Collection Deactivation	239
21.2.3	Handling of QMC during RAN Overload.....	239
21.2.4	QoE Measurement Handling in RRC_IDLE and RRC_INACTIVE States.....	240
21.2.5	Per-slice QoE Measurement	240
21.3	QoE Measurement Continuity for Mobility	241
21.4	RAN Visible QoE Measurements	241
21.5	Alignment of MDT and QoE Measurements.....	242
Annex A (informative):	QoS Handling in RAN	243
A.1	PDU Session Establishment	243
A.2	New QoS Flow with RQoS	243
A.3	New QoS Flow with Explicit RRC Signalling.....	244
A.4	New QoS Flow with Explicit NAS Signalling.....	245
A.5	Release of QoS Flow with Explicit Signalling.....	246
A.6	UE Initiated UL QoS Flow.....	246
Annex B (informative):	Deployment Scenarios	248
B.1	Supplementary Uplink.....	248
B.2	Multiple SSBs in a carrier	248
B.3	NR Operation with Shared Spectrum.....	249
B.4	Example implementation of Non-Terrestrial Networks.....	249

Annex C (informative):	I-RNTI Reference Profiles	252
Annex D (informative):	SPID ranges and mapping of SPID values to cell reselection and inter-RAT/inter frequency handover priorities	253
Annex E (informative):	NG-RAN Architecture for Radio Access Network Sharing with multiple cell ID broadcast	254
Annex F (normative):	Use and structure of the I-RNTI	255
Annex G (informative):	Components of Mobility Latency	256
Annex H (informative):	Change history	258
History		266

iTeh Standards

(<https://standards.iteh.ai>)

Document Preview

[ETSI TS 138 300 V18.1.0 \(2024-05\)](#)

<https://standards.iteh.ai/catalog/standards/etsi/65b6be92-ac79-42b1-8fdb-4b21a30e804f/etsi-ts-138-300-v18-1-0-2024-05>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 138 300 V18.1.0 \(2024-05\)](https://standards.iteh.ai/catalog/standards/etsi/65b6be92-ac79-42b1-8fdb-4b21a30e804f/etsi-ts-138-300-v18-1-0-2024-05)

<https://standards.iteh.ai/catalog/standards/etsi/65b6be92-ac79-42b1-8fdb-4b21a30e804f/etsi-ts-138-300-v18-1-0-2024-05>