ETSI TS 133 210 V18.0.0 (2024-04)



Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS);

taLTE;rds.iteh.ai)

Network Domain Security (NDS);
IP network layer security
(3GPP TS 33.210 version 18.0.0 Release 18)



Reference
RTS/TSGS-0333210vi00

Keywords
5G,GSM,LTE,SECURITY,UMTS

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from: https://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommitteeSupportStaff.aspx

If you find a security vulnerability in the present document, please report it through our Coordinated Vulnerability Disclosure Program:

https://standards.iteh.ai/catalog/s/https://www.etsi.org/standards/coordinated-vulnerability-disclosure

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024. All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECTTM, **PLUGTESTS**TM, **UMTS**TM and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP**TM and **LTE**TM are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M**TM logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM**[®] and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under https://webapp.etsi.org/key/queryform.asp.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intell	ectual Property Rights	2		
Legal	egal Notice			
Moda	Modal verbs terminology			
Foreword				
Introduction				
1	Scope	6		
2	References	6		
3	Definitions, symbols and abbreviations	8		
3.1	Definitions	8		
3.2	Symbols	9		
3.3	Abbreviations	9		
4				
4	Overview over network domain security for IP based protocols	.10		
4.1	Introduction			
4.2	Protection at the network layer			
4.3	Security for native IP based protocols			
4.4	Security domains	.10		
4.4.1	Security domains and interfaces	.10		
4.5	Security Gateways (SEGs)	.10		
_	Key management and distribution architecture for NDS/IP			
5				
5.1	Security services afforded to the protocols			
5.2	Security Associations (SAs)			
5.2.0	General	.11		
5.2.1	Security Policy Database (SPD)	.12		
5.2.2	Security Association Database (SAD)			
5.3	Profiling of IPsec.	.12		
5.3.0	General DTSLTS 122.210 V/18.0.0.(2024.04)			
5.3.1	Support of ESP			
5.3.2	Support of tunnel mode			
5.3.3	Support of ESP encryption transforms			
5.3.4	Support of ESP authentication transforms			
5.3.5	Requirements on the construction of the IV			
5.4	Profiling of IKEv2			
5.4.0	General			
5.4.1	Void			
5.4.2	Profiling of IKEv2			
5.4.3	Void			
5.5	Security policy granularity			
5.6	Network domain security key management and distribution architecture for native IP based protocols	.15		
5.6.1	Network domain security architecture outline	.15		
5.6.2	Interface description	.16		
6	Other 3GPP profiles	17		
6.1	General			
6.2				
	TLS protocol profiles			
6.2.1	General DesCline for TH C 1.2			
6.2.2	Profiling for TLS 1.3			
6.2.3	Profiling for TLS 1.2			
6.3	JWE and JWS profiles			
6.3.1	General	.19		
6.3.2	JWE profile	.19		
6.3.3	JWS profile	.20		
7	Void	20		
/	Void	.20		

Ann	ex A (informative):	Other issues	21
A.1	Network Address Tra	nslators (NATs) and Transition Gateways (TrGWs)	21
A.2	Filtering routers and f	irewalls	21
A.3	The relationship betw	een BGs and SEGs	21
Ann	ex B (normative):	Security protection for GTP	22
B.0	General		22
B.1	The need for security	protection	22
B.2	Policy discrimination	of GTP-C and GTP-U	22
B.3	Protection of GTP-C	transport protocols and interfaces	23
Ann	ex C (normative):	Security protection of IMS protocols	24
C.0	General		24
C.1	The need for security	protection	24
C.2	Protection of IMS pro	otocols and interfaces	24
Ann	ex D (normative):	Security protection of UTRAN/GERAN IP transport protocols	25
D.0	General		25
D.1	The need for security	protection	25
D.2	Protection of UTRAN	N/GERAN IP transport protocols and interfaces	25
Ann	ex E (informative):	Void	26
Ann	ex F (informative):	Change history	
		Document Preview	

ETSLTS 133 210 V18.0.0 (2024-04)

attps://standards.iteh.ai/catalog/standards/etsi/6e2df297-2dec-4bde-b685-062c52315f9a/etsi-ts-133-210-v18-0-0-2024-0

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

An identified security weakness in GPRS systems is the absence of security in the core network. This was formerly perceived not to be a problem, since the GPRS networks previously were the provinces of a small number of large institutions. This is no longer the case, and so there is now a need for security precautions. Another significant development has been the introduction of IP as the network layer in the GPRS backbone network and then later in the UMTS network domain. Furthermore, IP is not only used for signalling traffic, but also for user traffic. The introduction of IP therefore signifies not only a shift towards packet switching, which is a major change by its own accounts, but also a shift towards completely open and easily accessible protocols. The implication is that from a security point of view, a whole new set of threats and risks must be faced.

For UMTS and fixed broadband systems it is a clear goal to be able to protect the core network signalling protocols, and by implication this means that security solutions must be found for both SS7 and IP based protocols.

Starting with LTE, but especially with 5G, security of signalling protocols moves onto the application layer. The current document is the central repository of the protection mechanisms and profiles for these protocols."

Starting with LTE, but especially with 5G, security of signalling protocols moves onto the application layer. The current document is the central repository of the protection mechanisms and profiles for these protocols.

This document is the stage-2 specification for IP related security in the 3GPP and fixed broadband core networks.

The security services that have been identified as being needed are confidentiality, integrity, authentication and antireplay protection. These will be ensured by standard procedures, based on cryptographic techniques.

1 Scope

The present document defines the security architecture for network domain IP based control planes, which shall be applied to NDS/IP-networks (i.e. 3GPP and fixed broadband networks). The scope of network domain control plane security is to cover the control signalling on selected interfaces between network elements of NDS/IP networks. The present document furthermore serves as a central repository for cryptographic profiles for security above IP layer.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1]	Void.
[2]	3GPP TR 21.905: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications".
[3]	3GPP TS 23.002: "3rd Generation Partnership Project; Technical Specification Group Services and Systems Aspects; Network architecture".
[4]	Void.
[5]	Void. Document Preview
[6] ndards.iteh.ai/ca	3GPP TS 29.060: "3rd Generation Partnership Project; Technical Specification Group Core Network; General Packet Radio Service (GPRS); GPRS Tunnelling Protocol (GTP) across the Gn and Gp Interface".
[7]	Void.
[8]	Void.
[9]	Void.
[10]	3GPP TS 33.203: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Access security for IP-based services".
[11] -[25]	Void.
[26]	RFC-3554: "On the Use of Stream Control Transmission Protocol (SCTP) with IPsec".
[27]	Void.
[28]	3GPP TS 25.412: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; UTRAN Iu interface signalling transport".
[29]	Void.
[30]	3GPP TS 33.310: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; 3G Security; Network domain security; Authentication Framework".
[31]	RFC-4303: "IP Encapsulating Security Payload (ESP)"
[32]	Void.

[33]	Void
[34]	Void.
[35]	RFC-4301: "Security Architecture for the Internet Protocol".
[36]	Void.
[37]	Void.
[38]	3GPP TS 25.422: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; UTRAN Iur interface signalling transport".
[39]	3GPP TS 25.467: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; UTRAN architecture for 3G Home Node B (HNB); Stage 2".
[40]	3GPP TS 25.468: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; UTRAN Iuh Interface RANAP User Adaption (RUA) signalling".
[41]	3GPP TS 25.471: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; UTRAN Iurh Interface RNSAP User Adaption (RNA) signalling".
[42]	RFC-6311: "Protocol Support for High Availability of IKEv2/IPsec".
[43]	RFC-7296: "Internet Key Exchange Protocol Version 2 (IKEv2)".
[44]	IANA: "Internet Key Exchange Version 2 (IKEv2) Parameters".
[45]	Void.
[46]	IETF RFC 7515: "JSON Web Signature (JWS)".
[47]	IETF RFC 7516: "JSON Web Encryption (JWE)".
[48]	IETF RFC 7518: "JSON Web Algorithms (JWA)".
[49]	IETF RFC 6347: "Datagram Transport Layer Security Version 1.2".
[50]	IETF RFC 5246: "The Transport Layer Security (TLS) Protocol Version 1.2".
dards iteh.ai/cat [51]	IETF RFC 8442: "ECDHE_PSK with AES-GCM and AES-CCM Cipher Suites for TLS 1.2 and DTLS 1.2".
[52]	IETF RFC 2818: "HTTP Over TLS".
[53]	IETF RFC 2817: "Upgrading to TLS Within HTTP/1.1".
[54]	IETF RFC 5288: "AES Galois Counter Mode (GCM) Cipher Suites for TLS".
[55]	IETF RFC 5289: "TLS Elliptic Curve Cipher Suites with SHA-256/384 and AES Galois Counter Mode (GCM)".
[56]	Void.
[57]	IETF RFC 6066: "Transport Layer Security (TLS) Extensions: Extension Definitions".
[58]	Void.
[59]	IETF RFC 5077: "Transport Layer Security (TLS) Session Resumption without Server-Side State".
[60]	IETF RFC 5746: "Transport Layer Security (TLS) Renegotiation Indication Extension".
[61]	IETF RFC 7627: "Transport Layer Security (TLS) Session Hash and Extended Master Secret Extension".
[62]	IETF RFC 7919: "Negotiated Finite Field Diffie-Hellman Ephemeral Parameters for Transport Layer Security (TLS)".

[63]	Void
[64]	IETF RFC 5489: "ECDHE_PSK Cipher Suites for Transport Layer Security (TLS)".
[65]	IETF RFC 5487: "Pre-Shared Key Cipher Suites for TLS with SHA-256/384 and AES Galois Counter Mode".
[66]	IETF RFC 8446: "The Transport Layer Security (TLS) Protocol Version 1.3".
[67]	Void
[68]	Void.
[69]	IETF RFC 4086: "Randomness Recommendations for Security".
[70]	IETF RFC 8221: "Cryptographic Algorithm Implementation Requirements and Usage Guidance for Encapsulating Security Payload (ESP) and Authentication Header (AH)".
[71]	IETF RFC 8422: "Elliptic Curve Cryptography (ECC) Cipher Suites for Transport Layer Security (TLS) ".
[72]	IETF RFC 8937: "Randomness Improvements for Security Protocols".
[73]	IETF RFC-8247: "Algorithm Implementation Requirements and Usage Guidance for the Internet Key Exchange Protocol Version 2 (IKEv2)".

3 Definitions, symbols and abbreviations

3.1 Definitions trps://standards.iteh.ai

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [2] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [2].

Anti-replay protection: Anti-replay protection is a special case of integrity protection. Its main service is to protect against replay of self-contained packets that already have a cryptographical integrity mechanism in place.

Confidentiality: The property that information is not made available or disclosed to unauthorised individuals, entities or processes.

Data integrity: The property that data has not been altered in an unauthorised manner.

Data origin authentication: The corroboration that the source of data received is as claimed.

Entity authentication: The provision of assurance of the claimed identity of an entity.

Key freshness: A key is fresh if it can be guaranteed to be new, as opposed to an old key being reused through actions of either an adversary or authorised party.

NDS/IP Traffic: Traffic that requires protection according to the mechanisms defined in this specification.

NDS/IP-networks: 3GPP and fixed broadband networks.

IPsec Security Association: A unidirectional logical connection created for security purposes. All traffic traversing a SA is provided the same security protection. The SA itself is a set of parameters to define security protection between two entities. A IPsec Security Association includes the cryptographic algorithms, the keys, the duration of the keys, and other parameters.

Security Domain: Networks that are managed by a single administrative authority. Within a security domain the same level of security and usage of security services will be typical.

Transit Security Domain: A security domain, which is transmitting NDS/IP traffic between other security domains.

Transport mode: Mode of operation that primarily protects the payload of the IP packet, in effect giving protection to higher level layers.

Tunnel mode: Mode of operation that protects the whole IP packet by tunnelling it so that the whole packet is protected.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

Gi Reference point between GPRS and an external packet data network

Gn Interface between two GSNs within the same PLMN

Gp Interface between two GSNs in different PLMNs. The Gp interface allows support of GPRS

network services across areas served by the co-operating GPRS PLMNs

Mm Interface between a CSCF and an IP multimedia network

Mw Interface between a CSCF and another CSCF

Za Interface between SEGs belonging to different networks/security domains

Zb Interface between SEGs and NEs and interface between NEs within the same network/security

domain

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AAA Authentication Authorization Accounting

AES Advanced Encryption Standard

AH Authentication Header

BG Border Gateway CS Circuit Switched Standards iteh.ai)

CSCF Call Session Control Function

DES Data Encryption Standard

DoI Domain of Interpretation ESP Encapsulating Security Payload

GTP GPRS Tunnelling Protocols 133 210 V18.0.0 (2024-04)

IESG eh. ai/cata Internet Engineering Steering Group cc-4bde-b685-062c52315f9a/etsi-ts-133-210-v18-0-0-2024-04

IETF Internet Engineering Task Force

IKE Internet Key Exchange

IKEv2 Internet Key Exchange version 2

IP Internet Protocol

IPsec IP security - a collection of protocols and algorithms for IP security incl. key mngt.

ISAKMP Internet Security Association Key Management Protocol

IV Initialisation Vector

MAC Message Authentication Code NAT Network Address Translator NDS Network Domain Security NDS/IP NDS for IP based protocols

NE Network Entity
PS Packet Switched
SA Security Association

SAD Security Association Database (sometimes also referred to as SADB)

SEG Security Gateway

SIP Session Initiation Protocol

SPD Security Policy Database (sometimes also referred to as SPDB)

SPI Security Parameters Index

TISPAN Telecoms & Internet converged Services & Protocols for Advanced Networks

TrGW Transition Gateway

4 Overview over network domain security for IP based protocols

4.1 Introduction

The scope of this section is to outline the basic principles for the network domain security architecture. A central concept introduced in this specification is the notion of a security domain. The security domains are networks that are managed by a single administrative authority. Within a security domain the same level of security and usage of security services will be typical. Typically, a network operated by a single network operator or a single transit operator will constitute one security domain although an operator may at will subsection its network into separate sub-networks.

4.2 Protection at the network layer

For native IP-based protocols, security shall be provided at the network layer. The security protocols to be used at the network layer are the IETF defined IPsec security protocols as specified in RFC-4301 [35].

4.3 Security for native IP based protocols

The network domain control plane of an NDS/IP-network is sectioned into security domains and typically these coincide with operator borders. The border between the security domains is protected by Security Gateways (SEGs). The SEGs are responsible for enforcing the security policy of a security domain towards other SEGs in the destination security domain. The network operator may have more than one SEG in its network in order to avoid a single point of failure or for performance reasons. A SEG may be defined for interaction towards all reachable security domain destinations or it may be defined for only a subset of the reachable destinations.

The network domain security of an NDS/IP-network does not extend to the user plane and consequently the security domains and the associated security gateways towards other domains do not encompass the user plane Gi-interface towards other, possibly external, IP networks.

A chained-tunnel/hub-and-spoke approach is used which facilitates hop-by-hop based security protection between security domains.

<u>ETSITS 133 210 V18.0.0 (2024-04)</u>

Within a security domain the use of Transport Mode is allowed. All NDS/IP traffic shall pass through a SEG before entering or leaving the security domain.

4.4 Security domains

4.4.1 Security domains and interfaces

The network domain of an NDS/IP-network shall be logically and physically divided into security domains. These control plane security domains may closely correspond to the core network of a single operator and shall be separated by means of security gateways.

4.5 Security Gateways (SEGs)

Security Gateways (SEGs) are entities on the borders of the IP security domains and will be used for securing native IP based protocols. The SEGs are defined to handle communication over the Za-interface, which is located between SEGs from different IP security domains.

All NDS/IP traffic shall pass through a SEG before entering or leaving the security domain. Each security domain can have one or more SEGs. Each SEG will be defined to handle NDS/IP traffic in or out of the security domain towards a well-defined set of reachable IP security domains.

The number of SEGs in a security domain will depend on the need to differentiate between the externally reachable destinations, the need to balance the traffic load and to avoid single points of failure. The security gateways shall be