# INTERNATIONAL STANDARD

First edition 2018-10

# **Geographic information** — Schema for coverage geometry and functions —

Part 2: Coverage implementation schema

Information géographique — Schéma de la géométrie et des fonctions **iTeh STARD PREVIEW** Partie 2: Schéma de la mise en place de la couverture **(standards.iteh.ai)** 

<u>ISO 19123-2:2018</u> https://standards.iteh.ai/catalog/standards/sist/481071d9-6e91-4019-89bb-8efe83b34eeb/iso-19123-2-2018



Reference number ISO 19123-2:2018(E)

## iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 19123-2:2018</u> https://standards.iteh.ai/catalog/standards/sist/481071d9-6e91-4019-89bb-8efe83b34eeb/iso-19123-2-2018



#### **COPYRIGHT PROTECTED DOCUMENT**

#### © ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

## Contents

Page
------

Forev	word		iv			
Intro	ductio	n	v			
1	Scon	e	1			
2	Normativo roforoncos					
2	Torma definitions and abbreviated torms					
3	3.1	£				
	3.2	Abbreviated terms	2			
4	Conf	ormance				
5	Notation					
5	5.1	5.1 Use of the term "coverage"				
	5.2	UML notation				
	5.3	Namespace prefix conventions				
6	Coverage model					
	6.1	Coverage general				
	6.2	Overview				
	6.3	CoverageFunction	6			
	6.4					
	6.5	RangeType				
	6.6	RangeSet coherence.				
	6.7	Specific coverage types				
		6.7.1 Overview Standard Source and	ð			
		6.7.2 Discrete Coverage	ð			
		6.7.5 MultifurveCoverage (1) 1 (1) (40107110 C 01 4010				
		675 MultiSurfaceCoverage Acab / inc. 10102, 2, 2018				
		6.7.6 MultiSolidCoverage	10			
		6.7.7 GridCoverage				
		6.7.8 RectifiedGridCoverage				
		6.7.9 ReferenceableGridCoverage				
	6.8	Complete coverage example				
7	GML	representation requirements class				
8	Multipart representation requirements class					
	8.1	8.1 Coverages as multipart messages				
	8.2	First part: GML coverage				
	8.3	Second part: encoded coverage range set				
9	Special format requirements class					
Anne	<b>x A</b> (no	ormative) Abstract test suite				
Bibli	ograpł	ıy				

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www. iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html(standards.iteh.ai)

This document was prepared by ISO/TC 211, Geographic information/geomatics.

A list of all the parts in the ISO 19123 series can be found on the ISO website. 4019-89bb-8efe83b34eeb/iso-19123-2-2018

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

#### Introduction

Coverages represent digital geospatial information representing space/time-varying phenomena. Common examples include 1-D time series, 2-D imagery, 3-D x/y/t image time series and x/y/z geophysical voxel models, as well as 4-D x/y/z/t climate and ocean data.

This Coverage Implementation Schema (CIS) specifies a concrete, interoperable, conformance-testable coverage information schema. It is based on the abstract concepts of ISO 19123:2005 (which is equivalent to OGC Abstract Topic 6). ISO 19123:2005 specifies an abstract model which is not per se interoperable, i.e. many different and incompatible implementations of the abstract model are possible. CIS, on the other hand, is interoperable in the sense that coverages can be conformance tested, regardless of their data format encoding, down to the level of single "pixels" or "voxels".

Coverages can be encoded in any suitable format (such as GML, JSON[4], GeoTIFF[Z], NetCDF[9] or GMLJP2) and can be partitioned, e.g. for a time-interleaved representation. Coverages are independent from service definitions and, therefore, can be accessed through a variety of web based service types, such as the OGC Web Coverage Service (WCS) Standard. This document is a data model whereas WCS is a service model. Both are tentatively separate, thereby allowing different services to process and deliver coverages, such as WFS, WCS, WCPS, WPS, etc. WCS and WCPS are outstanding only in that they offer the most powerful coverage functionality.

Coverages are independent from service definitions and, therefore, can be accessed through a variety of standardized services types, such as the Web Coverage Service (WCS) Standard<sup>[6]</sup>, which is used in the examples in this document. The coverage structure can serve a wide range of coverage application domains, thereby contributing to harmonization and interoperability between and across these domains.

#### (standards.iteh.ai)

This document implements part of the coverage types described in ISO 19123:2005. Any extension of the coverage types addressed will be left for a future version of this document. ISO 19123:2005 is under review and will be replaced with ISO 19123-1 once the revision is published. ISO 19123-1 will be an extension of ISO 19123:2005 containing additional coverage concepts, so any references to ISO 19123:2005 in this document can be taken as references to the revised standard. The references in this document are to ISO 19123:2005 because this document is a joint standard with OGC, and the equivalent OGC standard "09-146r2 Version 1.0.1 OGC Coverage Implementation Schema (CIS 1.0)" is an existing published standard that makes references to ISO 19123:2005.

This document is a derived work based on the OGC document "Coverage Implementation Schema" OGC 09-146r2. The two documents are NOT word for word identical because each follows the document template required by each organization. However, both documents are functionally equivalent. In particular <u>Clauses 1</u> to 5 in both the ISO standard (this document) and the OGC standard (OGC 09-146r2) contain the Scope, Normative references, Terms and definitions (and Notation) and Conformance described in the manner required by each organization. Where there are minor differences, such as the definition of "coverage" and "grid", this document makes use of the terms defined in ISO standards and identifies the differences in a note.

Any extension in OGC beyond CIS 1.0 (e.g. the development of CIS 1.1) is an extension beyond this document. ISO and OGC plan to work together to ensure future synchronization of these standards.

This document is a derived work based on OGC standard 09–146r2 Version 1.0.1 OGC Coverage Implementation Schema (CIS 1.0) also known as "OGC® GML Application Schema — Coverages" published 2012–05–11 and copyrighted by the OGC ©2012 and used with permission. OGC standard 09–146r2 Version 1.0.1 is a corrigendum to existing OGC standard 09–146r1 Version 1.0.0 published 2010–10–27.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 19123-2:2018</u> https://standards.iteh.ai/catalog/standards/sist/481071d9-6e91-4019-89bb-8efe83b34eeb/iso-19123-2-2018

# Geographic information — Schema for coverage geometry and functions —

## Part 2: Coverage implementation schema

#### 1 Scope

This document specifies a concrete<sup>1)</sup> implementable, conformance-testable coverage structure based on the abstract schema for coverages defined in the ISO 19123 schema for coverage geometry. This document defines a structure that is suitable for encoding in many encoding formats.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 19103:2015, Geographic information — Conceptual schema-language

ISO 19123:2005, Geographic information Schema for coverage geometry and functions

ISO 19136:2007, Geographic information Geography Markup Language (GML)

OGC 07-011, Abstract Specification Topic 6: The Coverage Type and its Subtypes, version 7.0 (identical to 89bb-Sete83b34eeb/so-19123-2-2018

OGC 07-036, Geography Markup Language (GML) Encoding Standard, version 3.2.1

OGC 08-094, OGC® SWE Common Data Model Encoding Standard, version 2.0

#### 3 Terms, definitions, and abbreviated terms

#### 3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <u>https://www.electropedia.org/</u>
- ISO Online browsing platform: available at <a href="http://www.iso.org/obp">http://www.iso.org/obp</a>

#### 3.1.1

#### abstract test suite

abstract test module specifying all the requirements to be satisfied for conformance

[SOURCE: ISO 19105:2000, 3.4]

<sup>1) &</sup>quot;concrete" is used here as a contrast to "abstract" in the sense described in the Introduction.

#### 3.1.2

#### coverage

feature that acts as a function to return values from its range for any direct position within its spatial, temporal or spatiotemporal domain

Note 1 to entry: OGC CIS 1.0 has the definition for coverage: "feature that acts as a function to return values from its range for any direct position within its spatiotemporal domain."<sup>[13]</sup>.

[SOURCE: ISO 19123:2005, 4.1.7, modified — Note 1 to entry has been replaced and the EXAMPLE has been deleted]

#### 3.1.3

#### grid

network composed of two or more sets of curves in which the members of each set intersect the members of the other sets in an algorithmic way

Note 1 to entry: OGC Abstract Topic 6 has the definition for grid: "network composed of one or more sets of curves in which the members of each set intersect the members of the other sets in an algorithmic way". This accomplishes integration of the 1-D case, thereby enabling general n-D grids.

[SOURCE: ISO 19123:2005, 4.1.23, modified — Note 1 to entry has been replaced]

#### 3.1.4

#### implementation coverage

feature which is a subclass (specialization) of a coverage as defined in this document

Note 1 to entry: An implementation coverage is a concrete document in some concrete encoding, such as a GeoTIFF file.

(standards.iteh.ai) Note 2 to entry: The definition of implementation coverage in this standard is functionally identical to GML coverage as defined in the OGC Coverage Implementation Schema [OGC 09-146r2].

**3.2 Abbreviated terms** https://standards.iteh.ai/catalog/standards/sist/481071d9-6e91-4019-89bb-8efe83b34eeb/iso-19123-2-2018

CIS **Coverage Implementation Schema** GeoTIFF Geo Tagged Image File Format GML **Geography Markup Language** GMLCOV **GML** Application Schema for Coverages **JavaScript Object Notation** ISON netCDF network Common Data Format OGC **Open Geospatial Consortium** Sensor Web Enablement SWE TIN **Triangulated Irregular Network** UoM Unit of Measure UML Unified Modeling Language WCS Web Coverage Service

#### 4 Conformance

This document defines conformance classes that correspond to identified requirements. These conformance classes are described in <u>Annex A</u>. Any implementation claiming conformance with this document must conform to the abstract conformance class A.1: *gml-coverage* and, in addition, at least one of the concrete conformance classes A.2: *gml*, A.3: *multipart*, and A.4: *special-format*. Requirements and conformance test URIs defined in this document are relative to <<u>http://www</u>.opengis.net/spec/GMLCOV/1.0/>.

#### **5** Notation

#### 5.1 Use of the term "coverage"

The definition of "coverage" in 3.1.2 shall be the generic one provided by ISO 19123 (and equivalently shall be the one in OGC Abstract Topic 6 [OGC 07-011]). The term "implementation coverage" is coined to denote the concrete data structure defined in this document that shall rely on GML [ISO 19136:2007] and equivalently shall rely on GML 3.2.1 [OGC 07-036] and OGC SWE Common 2.0 [OGC 08-094].

For the remainder of this document, "coverage" shall be understood as a shorthand for "implementation coverage" unless explicitly stated otherwise.

#### 5.2 UML notation

The conceptual schema specified in this document is described/using the Unified Modeling Language (UML) static structure diagram, which shall follow the guidance in ISO 19103, and equivalently shall follow the guidance in OGC Web Service Common [OGC 06-121r9].

NOTE The UML and basic types used to express the diagrams in this document are equivalent to the UML and basic types used in the OGC standard even though the OGC standard is based on an earlier version of ISO 19103:2015. https://standards.iteh.ai/catalog/standards/sist/481071d9-6e91-4019-

#### 89bb-8efe83b34eeb/iso-19123-2-2018

Several model elements used in this schema are defined in other ISO geographic information standards and OGC standards. The uniqueness of objects is ensured by their namespace.

#### 5.3 Namespace prefix conventions

UML diagrams and XML code fragments adhere to the namespace conventions shown in <u>Table 1</u>. The namespace prefixes used in this document are **not** normative and are merely chosen for convenience, they may appear in examples without being formally declared, and have no semantic significance. The namespaces to which the prefixes correspond are normative.

UML prefix	GML prefix	Namespace URL	Description
GML	gml	http://www.opengis.net/gml/3.2	GML 3.2.1
SWE Common	swe	http://www.opengis.net/swe/2.0	SWE Common 2.0
CIS	cis	http://www.opengis.net/cis/1.0	Coverage Implementation Schema 1.0, formerly named GML 3.2.1 Application Schema — Coverages 1.0

#### Table 1 — Namespace mapping conventions

#### 6 Coverage model

#### 6.1 Coverage general

This document specifies the coverage structure to be used by ISO geographic information standards and jointly in OGC standards.

This document is described in terms of the Geography Markup Language (GML). This document derives from the OGC standard previously called GMLCOV which has been renamed to be Coverage Implementation Specification (CIS)  $1.0^{[5]}$ .

<u>Clause 6</u> establishes an abstract conformance class whereby "abstract" denotes that a concrete program must implement one of the concrete conformance classes in addition to claim conformance with this document. Although <u>Clause 6</u> heavily makes use of GML, it does not prescribe that a coverage instance document be encoded in GML. A GML encoding of such coverage structures is established in the conformance class *gml*.

#### 6.2 Overview

In GML (ISO 19136 and OGC GML 3.2.1<sup>[14]</sup>), all coverage types are derived from the abstract Coverage data type. This structure contains a domainSet describing the coverage's domain and a rangeSet component containing the range values ("pixels", "voxels") of the coverage. This coverage implementation schema extends (ISO 19136 and OGC GML 3.2.1<sup>[14]</sup>), class Coverage with two components, rangeType and metadata.

- The rangeType element describes the coverage's range set data structure. A range value often consists of one or more fields (in remote sensing also referred to as *bands* or *channels*), however, much more general definitions are possible. Range value structure description is based on the OGC SWE Common [OGC 08-094] DataRecord. ISO 19123-22018
- The abstract coverage definition is augmented with an extensible slot for metadata. The intended use is to define concrete metadata structures and their semantics in extensions or application profiles.

The following changes apply over the GML (ISO 19136 and OGC GML 3.2.1<sup>[14]</sup>) specification:

 The property coverageFunction, which in GML is associated with every subtype of Coverage, is moved up into Coverage in the coverage type hierarchy of this document.

NOTE 1 This way, the coverage function is available in any subtype of Coverage. This serves to prepare for continuous coverages, like in the case described by the next bullet below.

 The grid coverage types are subtypes of Coverage rather than being subtypes of DiscreteCoverage as in GML

NOTE 2 This allows representing not only discrete grid coverages, but also continuous coverages by using grids for the reference points in conjunction with a coverage function defining interpolation.

No further changes over GML (ISO 19136 and OGC GML 3.2.1<sup>[14]</sup>) are made in this document. In particular, no pre-existing component changes its semantics.



#### Figure 1 — The Coverage structure

#### iTeh STANDARD PREVIEW

In this document, Coverage shall always refer to the definition of this Application Schema and *not* to the GML definition of the same name, unless explicitly stated otherwise.

Figure 1 shows the UML diagram pertaining to this Application Schema.

#### Requirement 1 /req/gml-coverage/structural-adherence:

Any XML document instantiating a concrete subtype of Coverage **shall** conform with the UML diagram in <u>Figure 1</u>, with <u>Table 2</u>, and with the XML schema defined as part of this document.

Name	Definition	Data type	Multiplicity
coverage-Function	GML 3.2.1 coverage function to describe how range values at coverage locations can be obtained	GML:: Coverage- Function	Zero or one (optional)
metadata	Application specific metadata	Any	Zero or more (optional)
domainSet	GML 3.2.1 Definition of coverage domain	GML:: DomainSet	One (mandatory)
rangeType	Structure definition of the coverage range values	SWE:: DataRecord	One (mandatory)
rangeSet	GML 3.2.1 Coverage range values	GML:: RangeSet	One (mandatory)

#### Table 2 — The Coverage data structure

NOTE 3 UML data type Any is used here with the same meaning as XML's xsd:any, which does not have a direct equivalent in UML.

NOTE 4 Following the GML pattern described in [14] on GML level, SWE::DataRecord is linked to rangeType via an association SWE::DataRecordPropertyType.

#### 6.3 CoverageFunction

The coverageFunction component is identical in its syntax and meaning to the coverageFunction element defined in GML, 19.3.11<sup>[14]</sup>.

#### 6.4 Metadata

The metaData component is a carrier for any kind of application dependent metadata. Hence, no requirements are imposed here.

#### 6.5 RangeType

The rangeType component adds a structure description and technical metadata required for an appropriate (however, application independent) understanding of a coverage. For this structure description, the SWE Common DataRecord is used.

#### **Requirement 2 /req/gml-coverage/dataRecord:**

The range type component of a coverage **shall** conform with the DataRecord of SWE Common [OGC 08-094].

**Dependency:** [OGC 08-094] <u>Clause 7</u> (<u>http://www.opengis.net/doc/SWE/2.0/clause/7</u>), [OGC 08-094] <u>Clause 8</u> (<u>http://www.opengis.net/doc/SWE/2.0/clause/8</u>).

NOTE 1 Following GML patterns the swe:DataRecord is linked into gmlcov:AbstractCoverageType via swe:DataRecordPropertyType.

# Atomic data types available for range values are those given by the SWE Common data type AbstractSimpleComponent. As a range structure contains only structure definitions, but not the values themselves (these sit in the coverage range set component), the optional AbstractSimpleComponent component value is suppressed in coverages.

Requirement 3 /req/gml-coverage/no-value-in-rangeType:

For all SWE Common AbstractSimpleComponent subtypes in a range type structure, instance multiplicity of the value component **shall** be zero.

NOTE 2 Following [OGC 08-094], omission of the value component implies that in a DataArray there is no encoding component either.

Range values can be structured as records or arrays. Both structuring principles can be nested (and mixed) to any depth for a concrete coverage range structure definition.

#### **Requirement 4 /req/gml-coverage/record-or-dataArray:**

Wherever the SWE Common XML schema allows an AbstractDataComponent in a coverage range structure the concrete instance shall be one of the AbstractDataComponent subtypes DataRecord and DataArray.

NOTE 3 In particular, these AbstractDataComponent subtypes are not allowed in range structures: DataChoice, Vector, Matrix.

Within a DataRecord contained in a concrete range structure, each of its record components is locally uniquely identified by the record component's field attribute, in accordance with the "soft-typing" property introduced by SWE Common.

EXAMPLE The following XML fragment represents a valid range structure; it models the red, green, and blue channel of a Landsat scene. Pixels are defined as unsigned 8-bit quantities where 0 and 255 denote null values:

```
<rangeType>
<swe:DataRecord>
<swe:field name="red">
<swe:Quantity
    definition="http://opengis.net/def/property/OGC/0/Radiance">
        <gml:description>Red Channel</gml:description>
```