INTERNATIONAL STANDARD

ISO 29400

Second edition 2020-05

Ships and marine technology — Offshore wind energy — Port and marine operations

Navires et technologie maritime — Énergie éolienne offshore — Opérations portuaires et maritimes

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 29400:2020 https://standards.iteh.ai/catalog/standards/sist/72ef301d-0882-4155-8cb5-5632bb14fe0f/iso-29400-2020



iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 29400:2020 https://standards.iteh.ai/catalog/standards/sist/72ef301d-0882-4155-8cb5-5632bb14fe0f/iso-29400-2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org Published in Switzerland

Co	ntent	S	Page
Fore	eword		xi
Intr	oductio	n	xii
1	Scop	e	1
2	Norn	native references	1
3	Term	is and definitions	2
4		pols and abbreviated terms	
4	4.1	Symbols	
	4.2	Abbreviated terms	
5	Gene	ral considerations	32
	5.1	Introduction	32
		5.1.1 General	
		5.1.2 Safety requirements	
	5.2	Jurisdiction	
		5.2.1 Introduction	
		5.2.2 Safety of life at sea	
	r o	5.2.3 Environment	
	5.3 5.4	HSSE plan Risk management	
	3.4		
		5.4.1 Introduction 5.4.2 Techniques to evaluate risks	36
	5.5	lob safety analysis (stondards italy ai)	36
	5.6	Job safety analysis (standards.iteh.ai) Environmental impact study	37
	5.7	Manning, qualifications, job and safety training	37
	5.8	Daily progress and incident reporting 020 Personnel tracking hai/catalog/standards/sist/72ef301d-0882-4155-8cb5-	37
	5.9	Personnel tracking teh.a/catalog/standards/sist//2et301d-0882-4155-8cb5-	38
	5.10	Approval by national authorities is 29400-2020	38
6		nization, documentation and planning	38
	6.1	Introduction	
	6.2	Organization and communication	
		6.2.1 Project organization 6.2.2 Operational organization	
	6.3	6.2.2 Operational organization	
	6.4	Technical procedures	
	6.5	Technical documentation	
	0.0	6.5.1 Document numbering system	
		6.5.2 RAMS for port and marine operations	
		6.5.3 Operational schedule/programme	
		6.5.4 Contingency philosophy	
		6.5.5 Contingency planning and emergency procedures	
		6.5.6 Emergency response coordination plan	
		6.5.7 As-built documentation/Post construction file	
	6.6	6.5.8 Standards for data transfer to CAD systems	
	0.0	6.6.1 Introduction	
		6.6.2 Required or recommended documentation	
	6.7	Marine warranty survey	
	· · ·	6.7.1 Introduction	
		6.7.2 Role of the marine warranty surveyor	
		6.7.3 MWS scope of work	
		6.7.4 Certificate of approval	
	6.8	Systems and equipment	
		6.8.1 Introduction	51

		6.8.2 6.8.3	Marine vessels	
_	35.			
7			quirements	
	7.1		uction	
	7.2	7.2.1	er-restricted/weather-unrestricted operations	
		7.2.1 7.2.2	Weather-restricted operations	
	7.2		Weather-unrestricted operationsean conditions	
	7.3	7.3.1	Wind	
		7.3.1	Wave, wave period and swell conditions	
		7.3.2	Current	
		7.3.4	Other metocean factors	
		7.3.4	Temperature	
		7.3.6	Marine growth	
	7.4		ean criteria	
	7.1	7.4.1	Design criteria and operational limits	
		7.4.2	Return periods	
		7.4.3	Vessel response-based analysis	
		7.4.4	Probability distributions of sea state parameters	
	7.5		tional duration, contingency and weather window	55
		7.5.1	Planned operational duration	55
		7.5.2	Weather window and contingency	
		7.5.3	Point of no return	
			Forecasted and monitored operational limits, metocean reduction factor	57
	7.6	Weath	Forecasted and monitored operational limits, metocean reduction factor er forecasts	58
		7.6.1	Introduction (characteristics)	58
		7.6.2	Introduction (standards.iteh.ai) Forecast parameters	58
	7.7	On-site	e monitoring	58
8	Onsh	ore tran	ISO 29400:2020 Isport and nearshore transport lards/sist/72ef30td-0882-4t55-8cb5	59
U	8.1	Introd	uction	57 59
	8.2	Structi	ural integrity calculations	59
	8.3		port by road	
	8.4		port via inland waterways	
	8.5		port via nearshore waterways	
	8.6		port via railways	
	8.7		port frames and equipment	
0		-		
9			e storage areas	
	9.1		uction	
	9.2		tructure requirements	
		9.2.1 9.2.2	Load bearing	
	0.2		Surface	
	9.3 9.4		ge frames and equipment	
	9. 4 9.5		rements of components for storage	
	9.5 9.6		tion of components against environmental conditionsural integrity calculations	
	9.0	9.6.1	Introduction	
			Vortex shedding	
	9.7		ty measures	
10			y	
	10.1		uction	
	10.2		sembly area requirements	
	10.3		sembly activities	
	10.4		sembly equipment	
	10.5		ural integrity calculations	
	10.6		shedding	
	10.7	Securi	ty measures	64

11	Port a	ctivities	
	11.1	Introduction	64
	11.2	Accessibility of harbour areas	64
		11.2.1 Water access	64
		11.2.2 Inland access	
	11.3	Storage areas of quayside	
	11.4	Security measures	
	11.5	Quayside requirements	
	11.6	Port subsea soil requirements for jacking activities	65
12	Weigh	nt control	66
	12.1	Introduction	
	12.2	Weight control classes	
	12.3	Weight and CoG constraints	
	12.4	Weight control monitoring	
	12.5	Dimensional control	
	12.6	Serial items	68
	12.7	Weight determinations	68
13	Stabil	ity	60
13	13.1	Introduction	
	13.1	General requirements	
	13.2	Stability calculations	
	13.4	Intact stability	
	15.1	13.4.1 Introduction	
		13.4.2 Intact stability crite ia A.R.D. P.R.E.V.I.E.W.	70 71
	13.5	Damage stability	72
	10.0	Damage stability 13.5.1 Introduct of tandards.iteh.ai	72
		13.5.2 Damage stability criteria	74
	13.6	Single-barge transports. 180-29400-2020	
	13.7	Multi-barge transports catalog/standards/sist/72ef301d=0882-4155-8cb5-	75
	13.8	Classed vessels 5632bb14fc0f/iso-29400-2020	76
	13.9	Self-floating structures	76
		13.9.1 Introduction	
		13.9.2 Intact and damage stability	
		13.9.3 Upending and installation of self-floating and launched structures	
	13.10	Loadout operations	78
		Watertight integrity and temporary closures	
	13.12	Inclining tests	79
14		sting operations	
14	14.1	Introduction	
	14.1	Ballast calculations for different stages	
	14.2	In ballast system	
	17.5	14.3.1 Operational aspects	
		14.3.2 Other operational considerations	
	14.4	Protection against damage and deterioration	
	11.1	14.4.1 Introduction	
		14.4.2 Freezing	
	14.5	Prevention of progressive flooding in damage condition	
	14.6	Control and indicating systems	
	14.7	Pumps	
	- 11/	14.7.1 Introduction	
		14.7.2 Specification and layout	
		14.7.3 Pump performance curves and functional limitations	
	14.8	Valve arrangements	
	14.9	Vent systems	
		Air cushion system capacity	
		System testing	

Loado	out	
15.1	Introduction	
15.2	Categories of loadout	
	15.2.1 Introduction	
	15.2.2 Design: structural analysis during all loadout phases	87
	15.2.3 Loadout planning	87
	15.2.4 Cargo weight details and CoG information	87
	15.2.5 Deck loading plan	88
15.3	Structure being loaded	
15.4	Site and quay	
15.5	Barge	89
15.6	Link beams, skidways and skidshoes	89
15.7	Moorings	89
	15.7.1 Weather-restricted operation	89
	15.7.2 Temporary mooring system	
15.8	Grounded loadouts	
15.9	Pumping and ballasting	
	15.9.1 Pump capacity	
	15.9.2 Recommended pump capacity	
15.10	Loadouts by trailers, SPMTs or hydraulic skidshoes	92
	15.10.1 Introduction	92
	15.10.2 Structural capacity	
	15.10.3 Load equalization and stability	93
	15.10.4 Vertical alignment	93
	15.10.5 Skidshoes e.h. S. L.A.N.D.A.R.D. P.R.K.V.L.K.W.	93
15.11	Propulsion system design, redundancy and back-up 15.11.1 Propulsion system tandards.iteh.ai	93
	15.11.1 Propulsion systemstandards.iteh.al)	93
	15.11.2 Redundancy and recommendations	94
15.12	Float-on onto submersible barges or yessels 2020	95
15.13	Lifted loadoutss://standards:itch:ai/eatalog/standards/sist/72ef301d-0882-4155-8cb5	96
15.14	Horizontal loadouts5632bb14fe0fisov294400v2020	97
15.15	Barge reinstatement and sea fastenings	97
15.16	Tugs	98
	Management and organization	
15.18	Loadout manual	98
15.19	Operating manual	98
	sportation	
16.1	Introduction	
16.2	General considerations	
	16.2.1 Manned tows	
	16.2.2 Unmanned tows	
	16.2.3 Navigation lights, signals and day shapes	
	16.2.4 Contingency	
	16.2.5 Motion responses	
	16.2.6 Verification of the transported object	
	16.2.7 Structural analysis during all transport phases	
	16.2.8 Transport planning	
16.3	Weather routeing and forecasting	
16.4	Ports of shelter, shelter areas, holding areas	
16.5	Inspections during the towage or voyage	103
16.6	Responsibility	
16.7	Hazardous materials	
16.8	Ballast water	
16.9	Restricted depths, heights and manoeuvrability	104
16.10	Under-keel clearances	104
16.11	Air draught	105
16.12	Channel width	105
16.13	Survey requirements	105

	16.14	Towline pull required, fleet composition and towing arrangement	
		16.14.1 Towline pull required	
		16.14.2 Towing fleet	
		16.14.3 Towing arrangement	
		16.14.4 Towline length	108
	16.15	Tow out from dry dock	108
		16.15.1 Introduction	108
		16.15.2 Under-keel clearance	108
		16.15.3 Side clearances	108
		16.15.4 Air cushion/air pressure	
		16.15.5 Capacity of winching and towing arrangements	109
		16.15.6 Positioning systems	
		16.15.7 Survey requirements	
	16.16	Inshore tow	
		16.16.1 Tow route and towing clearances	
		16.16.2 Positioning systems	
	16.17	Transport onboard a vessel/Offshore tow	
		16.17.1 Vessel selection	
		16.17.2 Stability	
		16.17.3 Sea fastening	
		16.17.4 Vortex shedding	
		16.17.5 Navigation systems	
	16.18	Transport manual	112
		•	
17	Temp	orary mooring and stationkeeping for marine operations Introduction	113
		Introduction	113
	17.2	Environmental criteria and archaitemai Determination of mooring response	113
	17.3	Determination of mooring response	114
		17.3.1 Analysis methods	114
	1.7.4	17.3.2 General considerations on the mooring design. Sizing of mooring lines catalog/standards/sist/72ef301d-0882-4155-8cb5- 17.4.1 General considerations of the mooring design.	114
	17.4	Sizing of mooring lines catalog statistical sister / 2010/10-0002-4133-000-	115
		17.4.1 General considerations 1180-2040-2020	115
		17.4.2 Line tension limits and design safety factors	115
	455	17.4.3 Particular mooring conditions	
	17.5	Sizing of anchors	
	17.6	Sizing of attachments	
	17.7	Sizing of mooring line components	
	17.8	Clearances under extreme conditions	
	17.9	Clearances during positioning	
		Tensioning of moorings	
	17.11	Other stationkeeping means	
		17.11.1 Introduction	
		17.11.2 DP systems	
		17.11.3 Purpose-built mooring arrangements	
		17.11.4 Use of tugs	
	17.12	System for common reference stations	119
18	Offsho	ore installation operations	120
	18.1	Introduction	
		18.1.1 Foundation	
		18.1.2 Transition piece	
		18.1.3 Wind turbine generator	
		18.1.4 Offshore substation/Offshore accommodation platforms	
		18.1.5 Installation plan	
		18.1.6 Cargo weight details and CoG information	
	18.2	Installation site	
	20.2	18.2.1 Sea floor survey	
		18.2.2 Soil survey	
		18.2.3 Soil preparation	

	18.2.4	Site charts	124
	18.2.5	Unexploded ordnance (UXO)	
18.3	System	s and equipment	127
	18.3.1	Introduction	
	18.3.2	Vessels	
	18.3.3	Equipment	
	18.3.4	Position reference system	
	18.3.5	Ballast systems	
	18.3.6	Transport vessel interface with marine equipment	
18.4		ning of vessels	
18.5		erence system	
18.6		nnical site-specific assessment for jack-up operations	
	18.6.1	Introduction	
	18.6.2	Required soil investigations	129
	18.6.3	Penetration analysis, punch-through and horizontal-vertical-interaction	
18.7	Vessel o	operation manual	
18.8		preloading procedure	
18.9		ng	
18.10	Lifted in	nstallations	133
	18.10.1	Introduction	133
		Installation of liftable jackets	
		Installation of templates for piles	
		Installation of piles	
	18.10.5	Installation of transition pieces	134
	18.10.6	Installation of GBSTANDARD PREVIEW	134
		Transfer of items from a barge to the deck of a crane vessel/jack-up vessel	
	18.10.8	Installation of towersandards.iteh.ai)	135
		Installation of WTG including nacelle, hub and blades	
	18.10.1	0	
		Installation of topsides of offshore substations/accommodation platforms	135
	18.10.1	1	
		Operational aspects	135
	18.10.1	2	
		Operational control parameters	
18.11	Loweri	ng by ballasting	136
	18.11.1	Introduction	136
		Operational aspects	
	18.11.3	Operational control parameters	136
18.12	Precise	positioning on the sea floor by active and passive means	137
	18.12.1	Introduction	137
	18.12.2	Operational design aspects	137
	18.12.3	Operational control parameters	137
18.13	Skirt pe	enetration	138
	18.13.1	Introduction	138
	18.13.2	Gravity penetration	138
	18.13.3	Suction penetration	138
	18.13.4	Operational design aspects	138
	18.13.5	Operational control parameters	138
18.14	Pile ins	tallation	139
		Introduction	
	18.14.2	Operational design aspects	139
	18.14.3	Operational control parameters	140
18.15	Groutin	ıg	140
		Introduction	
		Grouting of pile/transition piece structure	
	18.15.3	Underbase grouting of pile/jacket structure	141
	18.15.4	Operational design aspects	141
	18.15.5	Preparations	141

		18.15.6 Operational control parameters	142
	18.16	Bolted connections of foundation	
		Welding of piles/foundation to topsides	
		Noise mitigation measures	
	18.19	Crew transfer to and from installation units	143
		Offshore completion	
		18.20.1 Introduction	
		18.20.2 ROV inspection	143
		18.20.3 Removal of temporary equipment	
		18.20.4 Scour protection	
		18.20.5 Final inspection	144
	18.21	Project execution manual	144
19	Design	n and operation of lifting equipment	145
	19.1	Introduction	
	19.2	Rigging geometry	147
	19.3	Actions and action effects	
	19.4	Weight contingency factors	149
	19.5	Dynamic amplification factors (DAFs)	150
		19.5.1 Introduction	150
		19.5.2 Lifts by a crane	
		19.5.3 Offshore lifts by cranes on two or more vessels	
	19.6	Representative hook load	
		19.6.1 One-hook lifts by a single crane	
		19.6.2 Two-hook lifts by two cranes Representative lift weight per lift point	152
	19.7	Representative lift weight per lift point	153
		19.7.1 One-hook lifts and ard s.iteh.ai) 19.7.2 Two-hook lifts	153
		19.7.2 Two-hook lifts	153
	19.8	Representative forces on a lift point	154
		19.8.1 Representative vertical force UZU	154
		19.8.2 Representative force in line with the sling direction 19.8.2 Representative force in line with the sling direction 19.4.1.	155
	100	19.8.3 Representative lateral force 29-400-2020	155
	19.9	Representative force for slings and grommets	
		Design values of actions and action effects	
	19.11	Strengths of slings, grommets and shackles	
		19.11.1 Steel cable slings	
		19.11.2 Fibre rope slings and fibre rope grommets	150
		19.11.3 Working load limits and design strengths of fibre slings and grommets	160
	10.12	Design verifications	
	19.12	19.12.1 Allowable hook load	
		19.12.2 Slings and grommets	
		19.12.3 Lift points and their attachment to the structure and supporting members	163
	1913	Lift point design	
	17.13	19.13.1 Introduction	
		19.13.2 Sling ovalization	
		19.13.3 Plate rolling direction and direction of loading	164
		19.13.4 Pinholes	
		19.13.5 Cast padears and welded trunnions	
		19.13.6 Cheek plates	
		19.13.7 Padeyes	
	19.14	Clearances	
	_	19.14.1 Introduction	
		19.14.2 Clearances around lifted objects	
		19.14.3 Clearances around crane vessel	
		19.14.4 Clearances around jack-up crane vessel	
		19.14.5 Clearances around mooring lines and anchors of crane vessels	
		19.14.6 Clearances around array cable zones	
		19.14.7 Clearances around spud-can positions of jack-up vessels	

	19.15	Bumpers and guides	168
		19.15.1 Introduction	168
		19.15.2 Object movements	168
		19.15.3 Position of bumpers and guides	168
		19.15.4 Bumper and guide loads	169
		19.15.5 Design considerations	169
	19.16	Heave compensated lifts	170
	19.17	Lifts using DP	170
	19.18	Practical considerations	170
		19.18.1 Access	170
		19.18.2 Design of seafastening	170
		19.18.3 Equipment	170
		19.18.4 Slings	
	19.19	Certification requirements for lifting equipment	171
		19.19.1 Standard lifting equipment	
		19.19.2 Custom-made lifting equipment	
		19.19.3 Recertification of lifting equipment	
20	Lavrin		
20		g, burial, jointing, and repair of sub-sea cables	
	20.1	Introduction	
	20.2	Planning and design	
		20.2.1 Cable dimensions and handling parameters	1/2
		20.2.2 Seafloor survey — Specifically cable route corridors between turbines	172
		and substation(s)	1/3
		 20.2.3 Vessel suitability 20.2.4 Cable storage and cable handling equipment 	1/5
		20.2.4 Cable storage and cable handling equipment	1//
	20.2	20.2.5 Navigation equipment — Positioning and control of vessel/cable interface	1//
	20.3	Cable loadout and offshore transfer	1/8
		20.3.1 Introduction 20.3.2 Handling and lifting ISO 29400:2020 20.3.3 Loadout by reeling, spooling winding and colling 82-4155-8cb5- 20.3.4 Lifted loadout and offshore transfer 400-2020	1/8
		20.3.2 Handling and lifting ISO 29400:2020	1/8
		20.3.3 Loadout by reeling, spooling winding and coiling 82-4155-8cb5-	1/8
	20.4	20.3.4 Lifted loadout and offshore transfer 9400-2020	180
	20.4	Cable laying	
		20.4.1 Introduction	
		20.4.2 Cable pull-in procedures	
	00 =	20.4.3 Laying	
	20.5	Cable protection	
		20.5.1 Introduction	
		20.5.2 Cable burial	
	20.6	20.5.3 Non-burial cable protection	
	20.6	Cable crossings	
	20.7	Landfalls	
	20.8	Cable jointing and repair	
	20.9	As-built survey	
		Cable integrity check	
	20.11	Cable installation manual	186
21	Const	ruction management	186
	21.1	Introduction	
	21.2	Marine coordination	
	21.3	Harbour coordination	
	21.4	Guard vessel	
	21.5	Reporting	
	21.6	Personnel tracking	
_			
Anne	x A (info	ormative) Additional information and guidance	189
Biblic	ography	7	203

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information/about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. (standards.iteh.ai)

This document was prepared by Technical Committee ISO/TC 8, *Ships and marine technology*. \overline{ISO} 29400:2020

This second edition cancels and replaces the first ledition (ISO-29400:2015), which has been technically revised. 5632bb14fe0f/iso-29400-2020

The main changes compared to the previous edition are as follows:

- <u>Clause 3</u>: terms and definitions revised; new entries inserted;
- Clause 7, "Metocean requirements": fully revised;
- <u>Clause 20</u>, "Cable loadout and offshore transfer": new subclause added;
- revisions made throughout most other clauses;
- Annex A: revised.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document applicable to the offshore wind industry constitutes a comprehensive and common basis covering port and marine operations of all offshore structures installed and maintained by the offshore wind industries worldwide. Through its application, the intention is to achieve reliability levels appropriate for offshore wind farm components, whatever the type of structure and the nature or combination of materials used.

It is important to recognize that during port and marine operations the structural integrity of the component is an overall concept comprising models for describing actions, structural analysis, design rules, safety elements, workmanship, quality control procedures and national requirements, all of which are mutually dependent. The modification of one aspect of design in isolation can disturb the balance of reliability inherent in the overall concept or structural system. It is necessary, therefore, to consider the implications involved in modifications in relation to the overall reliability of structures in offshore wind farms.

This document applicable to offshore wind farms is intended to provide a wide latitude in the choice of structural configuration, material and techniques without hindering innovation. Sound engineering judgment is, therefore, necessary in the use of this document.

This document was developed to provide comprehensive requirements and guidance for the planning, engineering and safe execution of port and marine operations for all types of offshore wind farm components including cable-laying and burial operations and installation and operation of floating turbines moored to the seabed.

Port operations for installation of components of offshore wind farms cover all component transport to the ports, whether marine or via inland waterways, any intermediate storage, as well as preassembly activities at the ports until placing the components close to any quayside for subsequent marine operations to start.

ISO 29400:2020

Marine operations for offshore wind farm structures cover loadout from the quayside, offshore transportation and installation phases when the structure is at risk from the marine environment including any marine logistics during offshore commissioning works, operation and maintenance, component exchange, repair operations and decommissioning or redeployment.

This document describes the principles of, and provides requirements and guidance for, port and marine operations associated with foundations, substructures, WTG, cables and topsides installed in offshore wind farms, from the point of view of planning, engineering, construction and documentation. Alternative requirements, methods and provisions can fulfil the intention of this document and may be applied, provided it can be demonstrated that they achieve at least the same level of assurance and reliability. The overall objective of this document is to ensure that port and marine operations are conducted within defined and recognized safety and reliability levels, wherever they are performed. Additional standards, codes and guidelines should also be taken into account, where applicable. Special attention should be paid to national regulations governing the area in which the port and marine operations are performed.

It is not the intent of this document to govern the design of structures, systems and components used in port and marine operations, beyond the principles given. Recognized codes and standards are normally accepted as the basis for the detailed design and the fabrication requirements of such components.

Annex A provides some background and some additional information to the main body of the document and it is intended that it be read in conjunction with the main body of the document.

This document is based on ISO 19901-6 while adapting it extensively to the specific requirements of the offshore wind industry.

NOTE Port and marine operations of offshore wind farms are covered in local, national and international regulations.

Ships and marine technology — Offshore wind energy — Port and marine operations

1 Scope

This document provides comprehensive requirements and guidance for the planning and engineering of port and marine operations of offshore wind farms, encompassing all documents and works related to such operations, e.g. the design and analysis of the components, systems, equipment and procedures required to perform port and marine operations, as well as the methods or procedures developed to carry them out safely.

This document is intended to be comprehensive, covering all relevant information related to port and marine operations necessary for loadout, offshore transport, installation, offshore commissioning works, operation and maintenance, component exchange, repair operations and decommissioning or redeployment of offshore wind farms.

This document is applicable to port and marine operations for offshore structures including:

- lattice structure foundations made from steel;
- concrete gravity base structures (GBS); ARD PREVIEW
- piled steel foundation or mixed steel and concrete foundation structures;
- subsea templates and similar temporary structures or installation aids;
- steel or mixed material towers, nacelles, and blades forming part of the wind turbine generators (WTG);

 5632bb14fe0f/iso-29400-2020
- floating turbines moored to the seabed;
- self-elevating offshore units for offshore substations or offshore accommodations platforms;
- launching systems at sea from quay side or onshore;
- array cables within the wind farms as well as export cables connecting the wind farm to the grid.

This document is also applicable to modifications of existing structures, e.g. installation of additional modules, exchange of components or decommissioning, and to marine operations during the service life of the windfarm related to the technical maintenance works.

It is not applicable to the following operations:

- construction activities, e.g. in a fabrication yard onshore, where there is no exposure to the marine environment;
- road transport onshore;
- diving.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 19901-1, Petroleum and natural gas industries — Specific requirements for offshore structures — Part 1: Metocean design and operating considerations

ISO 19901-7, Petroleum and natural gas industries — Specific requirements for offshore structures — Part 7: Stationkeeping systems for floating offshore structures and mobile offshore units)

ISO 19905-1, Petroleum and natural gas industries — Site-specific assessment of mobile offshore units — Part 1: Jack-ups

IMCA LR 008, M 179, Guidance on the Manufacture and Safe Use of Cable Laid Slings and Grommets

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/

3.1

action

external load applied to the *structure* (3.153) (direct action) or an imposed deformation or acceleration (indirect action)

Note 1 to entry: An imposed deformation can be caused by fabrication tolerances, settlement, temperature change or moisture variation.

(standards.iteh.ai)

Note 2 to entry: An earthquake typically generates imposed accelerations.

ISO 29400:2020

[SOURCE: ISO 19904-1:2006;3/5] and ards. iteh.ai/catalog/standards/sist/72ef301d-0882-4155-8cb5-

5632bb14fe0f/iso-29400-2020

3.2

action effect

effect of *actions* (3.1) on structural components

EXAMPLE Internal forces, moments, stresses, strains, rigid body motions or elastic deformations.

[SOURCE: ISO 19904-1:2006, 3.5]

3.3

adverse weather

meteorological and oceanographic conditions which can affect people, operations, equipment or facilities, to such an extent that precautionary measures must be taken to safeguard the facility to maintain a safe system of work

Note 1 to entry: Adverse weather includes, snow, ice, hail, lightning, heavy rain, high wind, low cloud base, poor visibility, severe sea states and strong *currents* (3.32). Weather conditions can change quickly and the effects of short-term variations such as wind gusts must be considered.

3.4

air cushion

air pumped into underbase compartments of the *structure* (3.153)

Note 1 to entry: An air cushion is normally applied in order to reduce the draught and increase the freeboard and/or to alter the structural loading.

[SOURCE: ISO 19903:2006, 3.10, modified - Note 1 to entry has been slightly reworded for clarity.]

3.5

alpha factor

metocean reduction factor

maximum ratio of operational criteria/design environmental condition for weather restricted marine operations (3.82) to allow for weather forecasting inaccuracies

Note 1 to entry: See also 3.91.

Note 2 to entry: [SOURCE: Reference [56], modified for clarity.]

3.6

array cable

cable between wind turbine generators (3.176) (WTG) and between a WTG and the offshore substation (3.102) connecting the WTGs with the *offshore substation* (3.102)

3.7

as-built data

as-laid data

data coming from final as built survey once every cable or structure (3.153) have been connected and tested and possibly corrected or repaired

Note 1 to entry: Final as built report includes final status of the field.

Note 2 to entry: "as-laid data" are coming from survey performed just after laying the cable or after structure installation before any test and connection. Data includes position in 3D, status, possible damages location and picture if possible, possible debris location around within target box or corridor including picture if possible. HEN STANDARD PREVIEN

assembly

(standards.iteh.ai)

designed and fabricated group of bulk and equipment items that form one unit

ISO 29400:2020

[SOURCE: ISO 19901-5:2016, 3.1.1] SOURCE: ISO 19901-5:2016, 3.1.1] https://standards.iteh.ai/catalog/standards/sist/72ef301d-0882-4155-8cb5-

5632bb14fe0f/iso-29400-2020 3.9

ballast

variable solid or fluid content in order to change the draught, stability, trim and/or heel of a *structure* (3.153) afloat

[SOURCE: ISO 19901-5:2016, 3.1.2, modified for clarity.]

3.10

ballast system

system used to change the draught, stability, trim and/or heel of a structure (3.153) afloat

3.11

barge

simple floating vessel, normally non-propelled, on which material components of an offshore wind farm (3.103), material, people and equipment can be transported

3.12

basic variable

one of a specified set of variables representing physical quantities that characterize actions (3.1), environmental influences, geometrical quantities or material properties, including soil properties

[SOURCE: ISO 19900:2013, 3.7]

3.13

bending efficiency factor

factor by which the calculated breaking strength of a rope is reduced to take account of the reduction in strength (3.152) caused by bending around a shackle, trunnion (3.165), padear (3.108) or crane hook

[SOURCE: ISO 19901-6:2009, 3.9]