
Določitev RF poljske jakosti, gostote moči in SAR v okolici radiokomunikacijskih baznih postaj za namene ocenjevanja izpostavljenosti ljudi

Determination of RF field strength, power density and SAR in the vicinity of radiocommunication base stations for the purpose of evaluating human exposure

Bestimmung der HF-Feldstärke, der Leistungsdichte und der spezifischen Absorptionsrate (SAR) in der Nachbarschaft von Funkkommunikations-Basisstationen zur Ermittlung der menschlichen Exposition

Détermination de l'intensité de champ de radiofréquences, de la densité de puissance et du DAS à proximité des stations de base de radiocommunication dans le but d'évaluer l'exposition humaine

Ta slovenski standard je istoveten z: prEN IEC 62232:2021

ICS:

13.280	Varstvo pred sevanjem	Radiation protection
17.240	Merjenje sevanja	Radiation measurements

oSIST prEN IEC 62232:2021**en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN IEC 62232:2021](#)

<https://standards.iteh.ai/catalog/standards/sist/71394d1d-d403-4e0f-aff9-faaa7c9f713b/osist-pren-iec-62232-2021>

CONTENTS

1			
2			
3	FOREWORD.....		15
4	INTRODUCTION.....		17
5	1 Scope.....		18
6	2 Normative references		19
7	3 Terms and definitions		19
8	4 Symbols and abbreviated terms.....		32
9	4.1 Physical quantities.....		32
10	4.2 Constants		33
11	4.3 Abbreviated terms.....		33
12	5 How to use this document.....		36
13	5.1 Quick start guide.....		36
14	5.2 RF evaluation purpose categories.....		37
15	5.3 Implementation case studies.....		38
16	6 Evaluation processes for product compliance, product installation compliance and in-		
17	situ RF exposure assessments		38
18	6.1 Evaluation process for product compliance		38
19	6.1.1 General		38
20	6.1.2 Establishing compliance boundaries.....		38
21	6.1.3 Iso-surface compliance boundary definition		39
22	6.1.4 Simple compliance boundaries.....		39
23	6.1.5 Methods for establishing the compliance boundary		41
24	6.1.6 Uncertainty		44
25	6.1.7 Reporting for product compliance.....		44
26	6.2 Evaluation process used for product installation compliance		45
27	6.2.1 General		45
28	6.2.2 General evaluation procedure for product installations.....		45
29	6.2.3 Product installation compliance based on the actual maximum transmitted		
30	power or EIRP		47
31	6.2.4 Product installation data collection.....		49
32	6.2.5 Simplified product installation evaluation process		50
33	6.2.6 Assessment area selection		54
34	6.2.7 Measurements		55
35	6.2.8 Computations		56
36	6.2.9 Uncertainty		57
37	6.2.10 Reporting for product installation compliance.....		57
38	6.3 In-situ RF exposure evaluation or assessment process.....		58
39	6.3.1 General		58
40	6.3.2 In-situ measurement process.....		58
41	6.3.3 Site analysis		60
42	6.3.4 Case A evaluation		60
43	6.3.5 Case B evaluation		61
44	6.3.6 Uncertainty		61
45	6.3.7 Reporting.....		61
46	6.4 Averaging procedures		62
47	6.4.1 Spatial averaging.....		62

48	6.4.2	Time averaging.....	62
49	7	Determining the evaluation method.....	62
50	7.1	Overview	62
51	7.2	Process to determine the evaluation method.....	63
52	7.2.1	General	63
53	7.2.2	Establishing the evaluation points in relation to the source-environment plane.....	63
54	7.2.3	Exposure metric selection.....	64
55	8	Evaluation methods	65
56	8.1	General.....	65
57	8.2	Measurement methods.....	66
58	8.2.1	General	66
59	8.2.2	RF field strength and power density measurements	66
60	8.2.3	SAR measurements	67
61	8.3	Computation methods	68
62	8.4	Methods for assessment based on actual maximum approach	69
63	8.4.1	General requirements	69
64	8.4.2	Actual transmitted power or EIRP monitoring.....	70
65	8.4.3	Actual transmitted power or EIRP control.....	70
66	8.5	Methods for the assessment of RF exposure to multiple sources	71
67	8.5.1	General requirements	71
68	8.5.2	Ambient fields.....	73
69	9	Uncertainty.....	73
70	10	Reporting	73
71	10.1	General requirements.....	73
72	10.2	Report format.....	74
73	10.3	Opinions and interpretations.....	75
74	Annex A (informative)	Source environment plane and guidance on the evaluation method selection.....	76
75			
76	A.1	Guidance on the source-environment plane	76
77	A.1.1	General	76
78	A.1.2	Source-environment plane example.....	76
79	A.1.3	Source regions	77
80	A.2	Select between computation or measurement approaches	84
81	A.3	Select measurement method.....	84
82	A.3.1	Selection stages	84
83	A.3.2	Selecting between RF field strength, power density and SAR measurement approaches.....	85
84			
85	A.3.3	Selecting between broadband and frequency-selective measurement.....	86
86	A.3.4	Selecting RF field strength measurement procedures	87
87	A.4	Select computation method.....	88
88	A.5	Additional considerations	89
89	A.5.1	Simplicity.....	89
90	A.5.2	Evaluation method ranking	89
91	A.5.3	Applying multiple methods for RF exposure evaluation	89
92	Annex B (normative)	Evaluation methods.....	90
93	B.1	Overview	90
94	B.2	General.....	90
95	B.2.1	Coordinate systems and reference points	90

ITeH STANDARD PREVIEW
(standards.iteh.ai)

oSIST prEN IEC 62232:2021

<https://standards.iteh.ai/catalog/standards/sist/71394d1d-d403-4e0f-af9-1aaa/c91713b/osist-pr-en-iec-62232-2021>

96	B.2.2	Variables	91
97	B.3	RF exposure evaluation principles	94
98	B.3.1	Calculation of RF field strength and power density	94
99	B.3.2	Measurement of RF field strength and power density	97
100	B.3.3	Spatial averaging	98
101	B.3.4	Time averaging	101
102	B.3.5	Comparing measured and computed values	102
103	B.3.6	Personal RF monitors	102
104	B.4	RF field strength and power density measurements	103
105	B.4.1	Applicability of RF field strength and power density measurements	103
106	B.4.2	In-situ RF exposure measurements	103
107	B.4.3	Laboratory based RF field strength and power density measurements	113
108	B.4.4	RF field strength and power density measurement uncertainty	123
109	B.5	SAR measurements	128
110	B.5.1	Overview of SAR measurements	128
111	B.5.2	SAR measurement requirements	128
112	B.5.3	SAR measurement description	130
113	B.5.4	SAR measurement uncertainty	136
114	B.6	Basic computation methods	139
115	B.6.1	General	139
116	B.6.2	Basic computation formulas for RF field strength or power density evaluation	139
117	B.6.3	Basic whole-body SAR and peak spatial-average SAR evaluation formulas	146
118	B.6.4	Basic compliance boundary assessment method for BS using parabolic dish	152
119	B.6.4	antennas	152
120	B.6.5	Basic compliance boundary assessment method for intentionally radiating	154
121	B.6.5	RF cables	154
122	B.7	Advanced computation methods	155
123	B.7.1	General	155
124	B.7.2	Synthetic model and ray tracing algorithms	155
125	B.7.3	Full wave RF exposure computation	162
126	B.7.4	Full wave SAR computation	170
127	B.8	Extrapolation from the evaluated values to the maximum or actual values	175
128	B.8.1	Extrapolation method	175
129	B.8.2	Extrapolation to maximum in-situ RF field strength or power density using	176
130	B.8.2	broadband measurements	176
131	B.8.3	Extrapolation to maximum in-situ RF field strength / power density for	176
132	B.8.3	frequency and code selective measurements	176
133	B.8.4	Influence of traffic in real operating network	177
134	B.8.5	Extrapolation for massive MIMO and beamforming BS	177
135	B.8.6	Maximum exposure extrapolation with dynamic spectrum sharing (DSS)	179
136	B.9	Guidance for implementing the actual maximum approach	179
137	B.9.1	BS actual EIRP evaluation assumptions	179
138	B.9.2	Technology duty-cycle factor description	180
139	B.9.3	CDF evaluation using modelling studies	182
140	B.9.4	CDF evaluation using measurement studies on operational BS sites	183
141	B.9.5	Actual transmitted power or EIRP monitoring counters	185
142	B.9.6	Configurations with multiple transmitters	185
143	Annex C (informative)	Guidelines for the validation of power or EIRP control features and	187
144		monitoring counter(s) related to the actual maximum approach	187
145	C.1	Overview	187

146	C.2	Guidelines for validating control feature(s) and monitoring counters.....	187
147	C.3	Validation of power or EIRP monitoring counter in laboratory conditions	188
148	C.3.1	Validation of power or EIRP monitoring counter in conducted mode.....	188
149	C.3.2	Validation of power or EIRP monitoring counter in OTA mode.....	190
150	C.3.3	Validation of control feature(s) in laboratory conditions.....	193
151	C.3.4	Validation of control features using in-situ measurements.....	196
152	C.4	Validation report	198
153	C.5	Case studies	199
154	C.5.1	Case study A – In-situ validation.....	199
155	C.5.2	Case study B – In-situ validation.....	203
156	C.5.3	Case study C – In-situ validation	205
157	Annex D (informative)	Rationale supporting simplified product installation criteria	211
158	D.1	General.....	211
159	D.2	Class E2	211
160	D.3	Class E10	212
161	D.4	Class E100	213
162	D.5	Class E+	215
163	D.6	Simplified formulas for millimetre-wave antennas using massive MIMO or beam steering	216
165	Annex E (informative)	Technology-specific guidance	218
166	E.1	Overview to guidance on specific technologies	218
167	E.2	Summary of technology-specific information.....	218
168	E.3	Guidance on spectrum analyser settings.....	220
169	E.3.1	Overview of spectrum analyser settings.....	220
170	E.3.2	Detection algorithms	220
171	E.3.3	Resolution bandwidth and channel power processing	221
172	E.3.4	Integration per service.....	223
173	E.4	Stable transmitted power signals.....	224
174	E.4.1	TDMA/FDMA technology.....	224
175	E.4.2	WCDMA/UMTS technology	225
176	E.4.3	OFDM technology	225
177	E.5	WCDMA measurement and calibration using a code domain analyser.....	225
178	E.5.1	WCDMA measurements – General	225
179	E.5.2	Requirements for the code domain analyser	226
180	E.5.3	Calibration.....	227
181	E.6	Wi-Fi measurements	228
182	E.6.1	General	228
183	E.6.2	Integration time for reproducible measurements	229
184	E.6.3	Channel occupation	229
185	E.6.4	Some considerations	230
186	E.6.5	Measurement configuration and steps	230
187	E.6.6	Influence of the application layers.....	231
188	E.6.7	Power control	231
189	E.7	LTE measurements.....	231
190	E.7.1	Overview	231
191	E.7.2	LTE transmission modes.....	232
192	E.7.3	LTE-FDD frame structure.....	233
193	E.7.4	LTE-TDD frame structure.....	234
194	E.7.5	Maximum LTE exposure evaluation	235

195	E.7.6	Instantaneous LTE exposure evaluation	240
196	E.7.7	MIMO multiplexing of LTE BS	240
197	E.8	NR BS measurements	240
198	E.8.1	General	240
199	E.8.2	Maximum NR exposure evaluation	241
200	E.9	Establishing compliance boundaries using numerical simulations of MIMO array antennas emitting correlated wave-forms	248
201			
202	E.9.1	General	248
203	E.9.2	Field combining near radio base stations for correlated exposure with the purpose of establishing compliance boundaries	249
204			
205	E.9.3	Numerical simulations of MIMO array antennas with densely packed columns	250
206	E.9.4	Numerical simulations of large MIMO array antennas	250
207	E.10	Massive MIMO antennas	251
208	E.10.1	Overview	251
209	E.10.2	Deterministic conservative approach	251
210	E.10.3	Statistical conservative approach	251
211	E.10.4	Example approaches	252
212	Annex F (informative)	Guidelines for the assessment of BS compliance with ICNIRP-2020 brief exposure limits	267
213			
214	F.1	General	267
215	F.2	Brief exposure limits	267
216	F.3	Implications of brief exposure limits on signal modulation and TDD duty cycle	268
217	F.4	Implications of brief exposure limits on the actual maximum approach	268
218	Annex G (informative)	Uncertainty	273
219	G.1	Background	273
220	G.2	Requirement to estimate uncertainty	273
221	G.3	How to estimate uncertainty	274
222	G.4	Guidance on uncertainty and assessment schemes	274
223	G.4.1	General	274
224	G.4.2	Overview of assessment schemes	274
225	G.4.3	Examples of assessment schemes	275
226	G.4.4	Assessment schemes and compliance probabilities	278
227	G.5	Guidance on uncertainty	280
228	G.5.1	Overview	280
229	G.5.2	Measurement uncertainty and confidence levels	280
230	G.6	Applying uncertainty for compliance assessments	282
231	G.7	Example influence quantities for field measurements	282
232	G.7.1	General	282
233	G.7.2	Calibration uncertainty of measurement antenna or field probe	283
234	G.7.3	Frequency response of the measurement antenna or field probe	283
235	G.7.4	Isotropy of the measurement antenna or field probe	285
236	G.7.5	Frequency response of the spectrum analyser	285
237	G.7.6	Temperature response of a broadband field probe	285
238	G.7.7	Linearity deviation of a broadband field probe	285
239	G.7.8	Mismatch uncertainty	285
240	G.7.9	Deviation of the experimental source from numerical source	286
241	G.7.10	Meter fluctuation uncertainty for time varying signals	286
242	G.7.11	Uncertainty due to power variation in the RF source	286
243	G.7.12	Uncertainty due to field gradients	286

244	G.7.13	Mutual coupling between measurement antenna or isotropic probe and object	288
245	G.7.14	Uncertainty due to field scattering from the surveyor's body	289
246	G.7.15	Measurement device.....	290
247	G.7.16	Fields out of measurement range.....	290
248	G.7.17	Noise	290
249	G.7.18	Integration time	291
250	G.7.19	Power chain.....	291
251	G.7.20	Positioning system.....	291
252	G.7.21	Matching between probe and the EUT	291
253	G.7.22	Drifts in output power of the EUT, probe, temperature, and humidity.....	291
254	G.7.23	Perturbation by the environment	291
255	G.8	Example influence quantities for RF field strength computations by ray tracing or	
256		full wave methods	292
257	G.8.1	General	292
258	G.8.2	System	292
259	G.8.3	Technique uncertainties.....	293
260	G.8.4	Environmental uncertainties.....	293
261	G.9	Influence quantities for SAR measurements	293
262	G.9.1	General	293
263	G.9.2	Post-processing.....	294
264	G.9.3	EUT holder	294
265	G.9.4	EUT positioning	295
266	G.9.5	Phantom shell uncertainty.....	296
267	G.9.6	SAR correction / target liquid permittivity and conductivity	296
268	G.9.7	Liquid permittivity and conductivity measurements.....	296
269	G.9.8	Liquid temperature.....	297
270	G.10	Influence quantities for SAR calculations.....	297
271	G.11	Spatial averaging	297
272	G.11.1	General	297
273	G.11.2	Small-scale fading variations	298
274	G.11.3	Error on the estimation of local average power density	298
275	G.11.4	Characterization of environment statistical properties	299
276	G.11.5	Characterization of different spatial averaging schemes	299
277	G.12	Influence of human body on measurements of the electric RF field strength	304
278	G.12.1	Simulations of the influence of human body on measurements based on the	
279		Method of Moments (Surface Equivalence Principle)	304
280	G.12.2	Comparison with measurements	306
281	G.12.3	Conclusions.....	306
282	Annex H (informative)	Guidance on comparing evaluated parameters with a limit value ...	308
283	H.1	Overview	308
284	H.2	Information required to compare evaluated value against limit value	308
285	H.3	Performing a limit comparison at a given confidence level	308
286	H.4	Performing a limit comparison using a process-based assessment scheme	309
287	Bibliography.....		310
288			
289	Figure 1 – Quick start guide to the evaluation process		36
290	Figure 2 – Example of iso-surface compliance boundary.....		39
291	Figure 3 – Example of circular cylindrical compliance boundaries		39

292	Figure 4 – Example of box shaped compliance boundary	40
293	Figure 5 – Example of truncated box shaped compliance boundary	41
294	Figure 6 – Example illustrating the linear scaling procedure.....	42
295	Figure 7 – Example of compliance boundary shape for BS antennas with beam steering	43
296	Figure 8 – Example of dish antenna compliance boundary.....	44
297	Figure 9 – Flowchart describing the product installation evaluation process	46
298	Figure 10 – Example of a CDF curve with normalized radiated power level with a selected	
299	95 th percentile.....	48
300	Figure 11 – Flow chart for product installation compliance based on the actual maximum	
301	transmitted power or EIRP threshold(s).....	49
302	Figure 12 – Simplified compliance assessment process using installation classes	51
303	Figure 13 – Square-shaped assessment domain boundary (ADB) with size D_{ad}	55
304	Figure 14 – In-situ RF exposure evaluation or assessment process flow chart	59
305	Figure 15 – Source-environment plane concept	64
306	Figure 16 – Flow chart of the measurement methods	66
307	Figure 17 – Flow chart of the relevant computation methods.....	68
308	Figure 18 – Example of segments used for monitoring and control of BS using mMIMO or	
309	beam steering.....	70
310	Figure A.1 – Example source-environment plane regions near a radio base station antenna	
311	on a tower.....	76
312	Figure A.2 – Example source-environment plane regions near a roof-top antenna which has	
313	a narrow vertical (elevation plane) beamwidth (not to scale)	77
314	Figure A.3 – Geometry of an antenna with largest linear dimension L_{eff} and largest end	
315	dimension L_{end}	78
316	Figure A.4 – Maximum path difference for an antenna with largest linear dimension L	82
317	Figure B.1 – Cartesian, cylindrical and spherical coordinate systems relative to the	
318	BS antenna (view from the rear panel).....	91
319	Figure B.2 – Typical RF exposure assessment case	94
320	Figure B.3 – Reflection due to the presence of a ground plane	95
321	Figure B.4 – Reflections due to the presences of internal walls of the housing and	
322	surrounding asphalts and soils configuring a base station installed underground	96
323	Figure B.5 – General representation of RF field strength or power density measurements	97
324	Figure B.6 – Practical examples of measurement equipment installation.....	97
325	Figure B.7 – Spatial averaging schemes relative to foot support level and in the vertical	
326	plane oriented to offer maximum area in the direction of the source being evaluated	99
327	Figure B.8 – Spatial averaging relative to spatial-peak field strength point height	101
328	Figure B.9 – Evaluation locations.....	111
329	Figure B.10 – Relationship of separation of remote radio source and evaluation area to	
330	separation of evaluation points	112
331	Figure B.11 – Outline of the surface scanning methodology	115
332	Figure B.12 – Block diagram of the antenna measurement system.....	116
333	Figure B.13 – Minimum radius constraint where a denotes the minimum radius of a sphere,	
334	centred at the reference point, that encompasses the EUT	117
335	Figure B.14 – Maximum angular sampling spacing constraint	117
336	Figure B.15 – Outline of the volume/surface scanning methodology.....	120
337	Figure B.16 – Block diagram of typical near-field EUT measurement system	121

338	Figure B.17 – Examples of positioning of the EUT relative to the relevant phantom	129
339	Figure B.18 – Phantom liquid volume and measurement volume used for whole-body SAR	
340	measurements with the box-shaped phantoms	135
341	Figure B.19 – Reference frame employed for cylindrical formulas for RF field strength	
342	computation at a point P (left), and on a line perpendicular to boresight (right)	140
343	Figure B.20 – Views illustrating the three valid zones for field strength computation around	
344	an antenna	141
345	Figure B.21 – Enclosed cylinder around collinear array antennas, with and without electrical	
346	downtilt	143
347	Figure B.22 – Cylindrical formulas reference results	145
348	Figure B.23 – Spherical formulas reference results	146
349	Figure B.24 – Directions for which SAR estimation expressions are provided	146
350	Figure B.25 – Description of SAR estimation formulas physical parameters	147
351	Figure B.26 – Flow chart for the simplified assessment of RF compliance boundary in the	
352	line of sight of a parabolic dish antenna	153
353	Figure B.27 – Radiating cable geometry	154
354	Figure B.28 – Synthetic model and ray tracing algorithms geometry and parameters	158
355	Figure B.29 – Line 4 far-field positions for synthetic model and ray tracing validation	
356	example	160
357	Figure B.30 – Antenna parameters for synthetic model and ray tracing algorithms validation	
358	example	161
359	Figure B.31 – Generic 900 MHz BS antenna with nine dipole radiators	167
360	Figure B.32 – Line 1, 2 and 3 near-field positions for full wave and ray tracing validation ..	168
361	Figure B.33 – Generic 1 800 MHz BS antenna with five slot radiators	169
362	Figure B.34 – BS antenna placed in front of a multi-layered lossy cylinder	174
363	Figure B.35 – Time variation over 24 h of the exposure induced by GSM 1 800 MHz and FM	
364	both normalized to the mean value	177
365	Figure B.36 – Generic structure of a base station transmitted RF signal frame	181
366	Figure C.1 – Example of set-up for the direct power level measurement for BS equipped with	
367	direct access conducted ports	188
368	Figure C.2 – Example of a laboratory test setup for validation of a time-averaged power	
369	control feature intended for use with a 5G BS	194
370	Figure C.3 – Example of a test setup for validation of a time-averaged power control feature	
371	implemented in a 5G BS	197
372	Figure C.4 – Ground based in-situ validation setup (measurement location is 90 m from the	
373	5G BS, in clear line of site and the position is approximately 14° directly below bore sight) 200	
374	Figure C.5 – In-situ validation measurement setup at the general public compliance	
375	boundary (reference level) in front of the 5G massive MIMO antenna (bore sight position).. 201	
376	Figure C.6 – Comparison between measured time-averaged EMF and power control feature	
377	(5G counter data)	201
378	Figure C.7 – Measured exposure adaptation in time expressed in percentage of ICNIRP	
379	limits [1], [2]	202
380	Figure C.8 – Overview of the measurement site	204
381	Figure C.9 – Ground view of the validation site and measurement setup, located 60 m from	
382	the 5G BS, in the line of site	204
383	Figure C.10 – Power transmitted by the massive MIMO antenna (top trace), Channel Power	
384	(ChP) measurements (middle trace) and transmitted Resource Blocks (RBs) (bottom trace) 205	
385	Figure C.11 – Overview of the test platform	206

386	Figure C.12 – Example of synthetic model simulation of the test area	206
387	Figure C.13 – Examples of traffic load profiles	207
388	Figure C.14 – Example of testing in different segments in the test area	208
389	Figure C.15 – Results of the monitoring validation and baseline test in phase 1	208
390	Figure C.16 – Example of power density measurements and power density derived from	
391	counters	209
392	Figure C.17 – Measured power density and power density derived from counters	209
393	Figure C.18 – Comparisons of both counters and measurements	210
394	Figure D.1 – Measured ER as a function of distance for a BS ($G = 5$ dBi, $f = 2\,100$ MHz)	
395	transmitting with an EIRP of 2 W (installation class E2) and 10 W (installation class E10) ..	212
396	Figure D.2 – Minimum installation height as a function of transmitting power corresponding	
397	to installation class E10	213
398	Figure D.3 – Compliance distance in the main lobe as a function of EIRP established	
399	according to the far-field formula corresponding to installation class E100	213
400	Figure D.4 – Minimum installation height as a function of transmitting power corresponding	
401	to installation class E100	214
402	Figure D.5 – Averaged power density at ground level for various installation configurations of	
403	equipment with 100 W EIRP (installation class E100)	215
404	Figure D.6 – Compliance distance in the main lobe D_m as a function of EIRP established	
405	according to the far-field formula corresponding to installation class E+	216
406	Figure D.7 – Minimum installation height H_m as a function of EIRP corresponding to	
407	installation class E+	216
408	Figure D.8 – Power density distribution in a vertical cut plane for an 8x8 antenna array at 28	
409	GHz	217
410	Figure D.9 – Power density distribution in a vertical cut plane for an 8x8 antenna array at	
411	39 GHz	217
412	Figure E.1 – Spectral occupancy for GSM	221
413	Figure E.2 – Spectral occupancy for CDMA	222
414	Figure E.3 – Channel allocation for a WCDMA signal	226
415	Figure E.4 – Example of Wi-Fi frames	228
416	Figure E.5 – Channel occupation versus the integration time for IEEE 802.11b standard ...	229
417	Figure E.6 – Channel occupation versus nominal throughput rate for IEEE 802.11b/g	
418	standards	230
419	Figure E.7 – Wi-Fi spectrum trace snapshot	230
420	Figure E.8 – Frame structure of transmission signal for LTE-FDD downlink	234
421	Figure E.9 – Frame structure LTE-TDD type 2 (for 5 ms switch-point periodicity)	234
422	Figure E.10 – Frame structure of transmission signal for LTE-TDD	235
423	Figure E.11 – LTE-TDD PBCH measurement example	237
424	Figure E.12 – Examples of received waves from LTE-FDD downlink signals using a	
425	spectrum analyser using zero span mode	239
426	Figure E.13 – LTE-TDD PBCH measurement example spectrum analyser using zero span	
427	mode	239
428	Figure E.14 – Waterfall reconstruction plot of a 1 s long measurement trace of a NR signal	
429	with subcarrier spacing (SCS) 30 kHz (along one component of the electric field)	243
430	Figure E.15 – Example of NR signal frame measured on SA with SSB signal	
431	above PDSCH (data)	244
432	Figure E.16 – Example of NR signal frame measured on SA with SSB signal below or equal	
433	to PDSCH (data)	244

434	Figure F.17 – Time gating of SS Burst signal	245
435	Figure E.18 – Representation of the channel bandwidth (CBW)	245
436	Figure E.19 – An example for one port CSI-RS beam design	247
437	Figure E.20 – MIMO array antenna with densely packed columns	249
438	Figure E.21 – Plan view representation of statistical conservative model	252
439	Figure E.22 – Binomial cumulative probability function for $N = 24$, $PR = 0,125$	260
440	Figure E.23 – Binomial cumulative probability function for $N = 18$, $PR = 2/7$	261
441	Figure E.24 – Binomial cumulative probability function for $N = 100$, $PR = 0,125$	264
442	Figure E.25 – Binomial cumulative probability function for $N = 82$, $PR = 2/7$	264
443	Figure F.1 – Limits for 'brief exposure' ($t < 360$ s), see Table F.1, divided by the	
444	corresponding time interval t and normalized with the value obtained for t up to 360 s. For	
445	visualization purposes the curve is plotted for $t > 1$ s. For shorter t , the limits for brief	
446	exposure increases (the corresponding value for $t = 1$ ms is about 18567)	268
447	Figure F.2 – F_{PR_min} as function of the pulse duration. For PRF values equal or above	
448	F_{PR_min} compliance with the whole-body time-averaged limits (over 30 min) specified by	
449	ICNIRP-2020 [1] inherently ensures compliance with the limits on brief exposure ICNIRP-	
450	2020 [1]	270
451	Figure F.3 – F_{PR_min} as function of the pulse duration. For PRF values equal or above	
452	F_{PR_min} , compliance with the whole-body time-averaged limits (assuming an averaging time	
453	of 6 min rather than the 30 min specified by ICNIRP-2020 [1] inherently ensures compliance	
454	with the limits on brief exposure ICNIRP-2020 [1]	271
455	Figure G.1 – Examples of general assessment schemes	276
456	Figure G.2 – Target uncertainty scheme overview	277
457	Figure G.3 – Probability of the true value being above (respectively below) the evaluated	
458	value depending on the confidence level assuming a normal distribution	281
459	Figure G.4 – Plot of the calibration factors for E (not E^2) provided from an example	
460	calibration report for an electric field probe	284
461	Figure G.5 – Computational model used for the variational analysis of reflected RF fields	
462	from the front of a surveyor	289
463	Figure G.6 – Positioning device and different positioning errors	295
464	Figure G.7 – Physical model of Rayleigh (a) and Rice (b) small-scale fading variations	297
465	Figure G.8 – Example of E -field variations in line of sight of an antenna operating at 2,2 GHz	297
466	Figure G.9 – Error at 95 % on average power estimation	299
467	Figure G.10 – 343 measurement positions building a cube (centre) and different templates	
468	consisting of a different number of positions	300
469	Figure G.11 – Moving a template (Line 3) through the CUBE	301
470	Figure G.12 – Standard deviations for GSM 900, DCS 1800 and UMTS	303
471	Figure G.13 – Simulation arrangement	305
472	Figure G.14 – Body influence	305
473	Figure G.15 – Simulation arrangement	306
474		
475	Table 1 – Quick start guide evaluation steps	37
476	Table 2 – Example of product installation classes where a simplified evaluation process is	
477	applicable (based on ICNIRP general public limits [1] and [2])	52
478	Table 3 – Exposure metrics validity for evaluation points in each source region	65
479	Table 4 – Requirements for RF field strength and power density measurements	67

480	Table 5 – Whole-body SAR exclusions based on RF power levels	67
481	Table 6 – Requirements for SAR measurements	68
482	Table 7 – Applicability of computation methods for source-environment regions of Figure 10	69
483	Table 8 – Requirements for computation methods.....	69
484	Table A.1 – Definition of source regions.....	79
485	Table A.2 – Default source region boundaries.....	79
486	Table A.3 – Source region boundaries for antennas with maximum dimension less than $2,5 \times \lambda$	80
487	Table A.4 – Source region boundaries for linear/planar antenna arrays with a maximum dimension greater than or equal to $2,5 \times \lambda$	80
489	Table A.5 – Source region boundaries for equiphase radiation aperture (e.g. dish) antennas with maximum reflector dimension much greater than a wavelength.....	81
490		
491	Table A.6 – Source region boundaries for radiating cables.....	81
492	Table A.7 – Far-field distance r measured in metres as a function of angle β	83
493	Table A.8 – Guidance on selecting between computation and measurement approaches	84
494	Table A.9 – Guidance on selecting between broadband and frequency-selective measurement.....	86
495		
496	Table A.10 – Guidance on selecting RF field strength measurement procedures.....	87
497	Table A.11 – Guidance on selecting computation methods.....	88
498	Table A.12 – Guidance on specific evaluation method ranking	89
499	Table B.1 – Dimension variables.....	91
500	Table B.2 – RF power variables.....	91
501	Table B.3 – Antenna variables	92
502	Table B.4 – Exposure metric variables	93
503	Table B.5 – Broadband measurement system minimum requirements	104
504	Table B.6 – Frequency-selective measurement system minimum requirements	105
505	Table B.7 – Sample template for estimating the expanded uncertainty of an in-situ RF field strength measurement that used a frequency-selective instrument.....	124
506		
507	Table B.8 – Sample template for estimating the expanded uncertainty of an in-situ RF field strength measurement that used a broadband instrument	125
508		
509	Table B.9 – Sample template for estimating the expanded uncertainty of a laboratory-based RF field strength or power density measurement using the surface scanning method.....	126
510		
511	Table B.10 – Sample template for estimating the expanded uncertainty of a laboratory-based RF field strength or power density measurement using the volume scanning method.....	127
512		
513	Table B.11 – Numerical reference SAR values for reference dipoles and flat phantom – All values are normalized to a forward power of 1 W	132
514		
515	Table B.12 – Phantom liquid volume and measurement volume used for whole-body SAR measurements [66], [53]	135
516		
517	Table B.13 – Correction factor to compensate for a possible bias in the obtained general public whole-body SAR when assessed using the large box-shaped phantom for child exposure configurations [67].....	135
518		
519		
520	Table B.14 – Measurement uncertainty evaluation template for EUT whole-body SAR test	136
521	Table B.15 – Measurement uncertainty evaluation template for whole-body SAR system validation	137
522		
523	Table B.16 – Definition of boundaries for selecting the zone of computation	141
524	Table B.17 – Input parameters for cylinder and spherical formulas validation.....	145
525	Table B.18 – Applicability of SAR estimation formulas	147

526	Table B.19 – Calculation of $A(f, d)$	149
527	Table B.20 –Antenna parameters for SAR estimation formulas verification	151
528	Table B.21– Verification data for SAR estimation formulas - front	151
529	Table B.22 – Verification data for SAR estimation formulas – axial and back	151
530	Table B.23 – Sample template for estimating the expanded uncertainty of a synthetic model	
531	and ray tracing RF field strength computation	159
532	Table B.24 – Synthetic model and ray tracing power density reference results.....	162
533	Table B.25 – Sample template for estimating the expanded uncertainty of a full wave RF field	
534	strength / power density computation	166
535	Table B.26 – Validation 1 full wave field reference results	168
536	Table B.27 – Validation 2 full wave field reference results	169
537	Table B.28 – Sample template for estimating the expanded uncertainty of a full wave SAR	
538	computation	172
539	Table B.29 – Validation reference SAR results for computation method	174
540	Table B.30 – Relevant parameters for conducting RF exposure modelling studies of a	
541	massive MIMO site or site cluster	182
542	Table B.31 – Measurement campaign parameters for conducting RF exposure assessment of	
543	a massive MIMO site or site cluster	184
544	Table B.32 – Power combination factors applicable to the normalized transmitted power CDF	
545	in case of combination of multiple independent identical transmitters.....	186
546	Table B.33 – Power combination factors applicable to two independent transmitters with a	
547	ratio p in amplitude	186
548	Table C.1 – Relative difference between the measured power and power counter value for	
549	systems that allow direct power level measurements (column headings a, b and c are for	
550	reference and the numerical values are examples)	189
551	Table C.2 – Correlation between the configured power level and the level reported by power	
552	counters for BS that allow direct power level measurements (column headings a, b and c are	
553	for reference and the numerical values are examples for the case of $P_{\max} = 100$ W and	
554	$F_{\text{TDC}} = 0,75$).....	189
555	Table C.3 – Correlation between the configured time-averaged load levels and the power	
556	counter value for systems that allow direct power level measurements (column headings a, b	
557	and c are for reference and the numerical values are examples for the case of	
558	$P_{\max} = 100$ W and $F_{\text{TDC}} = 0,75$)	190
559	Table C.4 – Relative difference between the configured power, measured power, and power	
560	counters for systems that do not allow direct power level measurements (column headings a,	
561	b and c are for reference and the numerical values are examples for the case of $P_{\max} =$	
562	100 W, 20 dBi antenna and 10 m distance).....	191
563	Table C.5 – correlation between the configured power level and the level reported by power	
564	counters for BS that do not allow direct power level measurements (column headings a, b	
565	and c are for reference and the numerical values are examples for the case of maximum	
566	configurable power $P_{\max} = 100$ W).....	192
567	Table C.6 – correlation between time linearity of the configured power level and the level	
568	reported by power counters for BS that do not allow direct power level measurements	
569	(column headings a, b and c are for reference and the numerical values are examples for the	
570	case of maximum configurable power $P_{\max} = 100$ W)	193
571	Table E.1 – Technology specific information	218
572	Table E.2 – Example of spectrum analyser settings for an integration per service.....	224
573	Table E.3 – Example constant power components for specific TDMA/FDMA technologies... 224	
574	Table E.4 – WCDMA decoder requirements	226